

Node Types

Cache	Caching station
ClassSwitch	Class switching
Delay	Infinite server
Fork	Forks jobs
Join	Joins jobs
Logger	Trace logging
Place	Petri net place
Queue	Queueing station
Router	Routing node
Sink	Job departures (open)
Source	Job arrivals (open)
Transition	Petri net transition

Job Classes

ClosedClass(model, 'name', N, refStat)
OpenClass(model, 'name')
SelfLoopingClass(model, 'name', N, ref)
DisabledClass(model, 'name')
OpenSignal, ClosedSignal (catastrophes)

Distributions

APH(α , T)	Acyclic PH
Cox2(μ , ϕ)	Two-phase Coxian
Coxian(μ , ϕ)	Coxian
Det(v)	Deterministic
Disabled	None
Erlang(λ , k)	Erlang-k
Exp(λ)	Exponential
Gamma(α , β)	Gamma
HyperExp(p, λ_1 , λ_2)	Hyper-exp
Immediate	Zero service time
Lognormal(μ , σ)	Log-normal
Normal(μ , σ)	Normal
Pareto(α , k)	Pareto
PH(α , T)	Phase-type
Uniform(a, b)	Uniform
Weibull(α , β)	Weibull

Discrete	
Bernoulli(p)	Bernoulli
Binomial(p, n)	Binomial
DiscreteUniform(a, b)	Discr. uniform
Geometric(p)	Geometric
Poisson(λ)	Poisson
Zipf(s, n)	Popularity

Correlated / trace-driven

BMAP (D0...Dk)	Batch MAP
NHPP (bp, λ , cyclic)	Non-homog. Poisson
DMAP (D0, D1)	Discrete MAP
EmpiricalCDF (F)	Empirical CDF
MAP (D0, D1)	MAP
MarkedMAP	Marked MAP
ME(α , T)	Matrix-exp.
CME (mean, order)	Concentr. matrix-exp.
MMPP2 (λ_1 , λ_2 , σ_1 , σ_2)	MMPP(2)
RAP (H0, H1)	Rational AP
RePlayer (trace)	Trace replay

Marked / time-inhomogeneous

MAPt (bp, D0, D1, cyclic)	Time-varying MAP
PHt (bp, α , S, cyclic)	Time-varying PH
MPH (α , S, { s_k })	Marked PH
MMAPt (bp, D0, D1k, cyclic)	Marked time-varying MAP
MPHT (bp, α , S, { s_k }, cyclic)	Marked time-varying PH
BMMAPt (bp, D0, D1k, cyclic)	Batch marked time-varying MAP

A mark selects the CLASS of the arriving job (setMarkedArrival); a BMMAPt epoch releases a whole batch of that class. As a service process the mark is discarded, and a

BMAP or BMMAPt service is a bulk server. Declared by LDES; MAPt/PHT also by FLD

method kp.

Scheduling Strategies

DPS	Discriminatory PS
EDD	Earliest Due Date
EDF	Earliest Deadline First
EXT	External (source)
FB	Feedback (LAS)
FCFS	First-Come First-Served
FCFSPI	FCFS Preempt. Resume-idle
FCFSPR	FCFS Preemptive Resume
FSP	Fair Sojourn Protocol
GPS	Generalized PS
HOL	Head-of-Line Priority
INF	Infinite Servers
LCFS	Last-Come First-Served
LCFSPI	LCFS Preempt. Resume-idle
LCFSPR	LCFS Preemptive Resume
LEPT	Longest Expected PT
LJF	Longest Job First
LPS	Limited PS
LRPT	Longest Remaining PT
OI	Order Independent
PAS	Pass and Swap
POLLING	Polling (switchover)
PS	Processor Sharing
PSJF	Preemptive SJF
SEPT	Shortest Expected PT
SETF	Shortest Elapsed Time First
SIRO	Random
SJF	Shortest Job First
SRPT	Shortest Remaining PT

Solvers

AUTO	Auto-select best
BA	Bound analysis (closed)
CTMC	CTMC (exact, small)
ENV	Random environments
FLD	Fluid/mean-field ODEs
LDES	Discrete Event Sim
LN	Layered networks
MAM	Matrix Analytic Methods
MVA	Mean Value Analysis
NC	Normalizing Constant Methods
SSA	Stochastic simulation

Wrappers

JMT	JMT simulator
LQNS	LQNS interface
QNS	LQNS product-form solver

Solver Options

MVA(model, method='exact')	
JMT(model, seed=123, samples=10000)	
SSA(model, samples=5000, method='para')	
LDES(model, MVA(model))	# warm start

Output Metrics

ArvR	Arrival rate
QLen	Mean queue length
ResidT	Residence time (total across visits)
RespT	Response time (per visit)
Tput	Throughput

Util	Server utilization
QLenVar	Queue-length variance
QLenSCV	Queue-length squared coeff. of variation
QLenSkew	Queue-length skewness
RespTVar	Response-time variance (FCFS only)
RespTSCV	Response-time SCV (FCFS only)
RespTSkew	Response-time skewness (FCFS only)

Moments (product form)

solver.get_moment_table()	
# per class; order 2 by default	
solver.get_moment_table(3)	
# 1=means 2+=var 3+=skew	
solver.get_moment_chain_table(3)	
# per chain	
solver.get_moment_station_table(3)	
# per station total	
solver.get_moment_station_table(3,'lin')	
# approx., for large N	

order is a set: scalar k = up to k ;
a vector, e.g. [2, 3], = exactly those.
RespT* moments are FCFS-only
(NaN elsewhere); exact methods cost
 $\prod_r (N_r + 1)$, use 'lin' beyond that.

Analysis Methods

solver.avg_table()	
solver.get_avg_qlen(), get_avg_util()	
solver.get_avg_respt(), get_avg_tput()	
solver.get_avg_sys_respt()	
solver.get_avg_sys_tput()	
solver.get_avg_qlen_chain()	

Table Methods

avg_table	per station
get_avg_chain_table	per chain
get_avg_node_table	per node
get_avg_node_chain_table	node $\times$ chain
get_avg_sys_table	system totals

Routing

model.link(Network.serial_routing(n1,n2,n3))	
n1.set_prob_routing(jobclass, n2, 0.7)	
n1.set_routing(jobclass, RoutingStrategy.RROBIN)	

Multi-Server & Finite Capacity

queue.set_number_of_servers(k)	
queue.set_capacity(bufferSize)	

Class Switching

cs = ClassSwitch(model, 'CS')	
P = [[0.3, 0.7], [0.5, 0.5]]	
cs.set_class_switching_matrix(P)	

Fork-join Networks

fork = Fork(model, 'Fork')	
join = Join(model, 'Join', fork)	

Layered Networks

lqn = LayeredNetwork('name')	
P = Processor(lqn, 'P', 1, SchedStrategy.PS)	
T = Task(lqn, 'T', 1, SchedStrategy.REF).on(P)	
E = Entry(lqn, 'E').on(T)	
A = Activity(lqn, 'A').on(T) \	
.bound_to(E).set_host_demand(Exp(1))	

Caching

cache = Cache(model, 'Cache', nItems, cap, ReplacementStrategy.LRU)	
cache.set_read(jobclass, Zipf(1.4, nItems))	# cache results
MVA(model).get_avg_cache_table()	# hit/miss
MVA(model).get_avg_item_table()	# per-item

ReplacementStrategy

CLIMB	Climb
FIFO	First-in first-out

HLRU	h-LRU
LRU	Least recently used
QLRU	q-LRU
RR	Random replacement
SFIFO	Static FIFO

Model Import/Export

model.jsimg_view()	# Open in JMT
save_model(model, 'model.json')	
model = load_model('model.json')	

Routing Strategies

JSQ	Join shortest queue
KCHOICES	Power of k choices
PROB	Probabilistic routing
RAND	Random selection
RROBIN	Round-robin
WROBIN	Weighted round-robin

Stochastic Petri Nets

p = Place(model, 'P1')	
t = Transition(model, 'T1')	
m = t.add_mode('Mode1')	
t.set_number_of_servers(m, float('inf'))	
t.set_distribution(m, Exp(4))	
t.set_enabling_conditions(m, jobclass, p, 1)	
t.set_inhibiting_conditions(m, jobclass, p, 3)	
t.set_firing_outcome(m, jobclass, sink, 1)	

Markov Chains (solved directly)

ctmc = MarkovProcess(Q)	
pi = SolverCTMC(ctmc).get_prob_sys()	
dtmc = MarkovChain(P)	
piD = SolverCTMC(dtmc).get_prob_sys()	
piT = ctmc.transient(None, 10.0)	
jump = ctmc.toEmbedded()	

Random Environments

env = Environment('R', 2)	
env.add_stage(0, 'Fast', 'operational', fastModel)	
env.add_stage(1, 'Slow', 'degraded', slowModel)	
env.add_transition(0, 1, Exp(0.5))	
env.add_transition(1, 0, Exp(1.0))	
ENV(env, lambda m: FLD(m)).avg_table()	

Finite Capacity Regions

fcr = model.add_region([queue1, queue2])	
fcr.set_global_max_jobs(10)	
fcr.set_class_max_jobs(class1, 5)	
fcr.set_drop_rule(class1, DropStrategy.DROP)	

Load-Dependent Service

queue.set_load_dependence(np.minimum(np.arange(1,N+1), c))	
queue.set_class_dependence(lambda ni: min(sum(ni), c), c)	

Impatience & Retrials

queue.set_patience(jobclass, ImpatienceType.RENEGING, Exp(0.1))	
queue.set_balking(jobclass, strategy, thresholds)	
queue.set_retry(jobclass, Exp(2), maxAttempts)	

State Probabilities

solver.get_prob(node)	# marginal
solver.get_prob_aggr(node)	# aggregate
solver.get_prob_sys()	# joint
NC(m).get_prob_sys_marg(n)	# totals
solver.get_generator()	# CTMC infin.
solver.get_state_space()	

Transient & Distributions

solver.get_tran_avg()	# transient means
solver.get_cdf_respt()	# response-time CDF
model.set_reward('Cost', lambda state: ...)	
solver.get_avg_reward()	

Symbolic Analysis

options.config['symbolic'] = 'sage'	# needs line-sage-rest
solver.getSymbolicSolution()	# pi over x1..xE
solver.getSensitivity(p, r, 'symbolic')	
SolverFLD(model, o).getJacobian()	
engine.ctmc_measures(Q, syms, W); engine.ctmc_passage(...)	