ACADEMIND

What?

Primitive Values

number
string
boolean
symbol
null
undefined
bigint

Immutable non-object values

Reference Values

Objects (i.e. plain objects, arrays, functions, ...)

Mutable object values

ACADEMIND

Reference Values in Action



ACADEMIND

How Data Is Stored



ACADEMIND

Behind the Scenes



Primitive Wrapper Objects



ACADEMIND

What about “const” Arrays & Objects?

const user = { name: ‘Max’ };

const means: “Don’t assign a new value to the ‘variable’ user”.

It does NOT mean: “Don’t change the stored value”!

Primitives: Value can’t be changed anyways (immutable)

Reference values: Underlying value CAN be changed because only a **pointer** is stored in the ‘variable’

ACADEMIND

Summary – Primitive vs Reference Values

JavaScript has various data types but two kind of data type categories: **Primitive Values** ("Primitives") and **Reference Values**

Primitives:
- Number
- String
- Boolean
- Symbol
- null & undefined
- BigInt

Reference Values:
- All Objects (incl. Arrays, Functions)

Primitive values are shared by **copy** and **immutable**. **Reference values** are shared by **reference** (i.e. NOT copied) and are **mutable**.

"**Mutable**" means that data can be edited without copying the value first.

"**Reference**" means that a pointer to the object in memory is used/ shared.