

CMSC 510 – L19

Regularization Methods for Machine Learning




Part 19b: Greedy Pretaining

Instructor:
Dr. Tom Arodz

Training deep nets


- Historically, deep networks (with many layers) were difficult to train



- A lot of effort in recent years went into making training easier
 - ReLU instead of sigmoid
 - Unsupervised pre-training
 - Normalization techniques

Pre-training


- Pre-training for dealing with depth of the network
 - Greedy layer-wise pretraining
- First, training an autoencoder unsupervised network



- Two networks: an encoder + a decoder
- Unsupervised training (no classes)
 - MSE: $(x - \text{decoder}(\text{encoder}(x)))^2$


Pre-training

- Pre-training for dealing with depth of the network
 - Greedy layer-wise pretraining
- Second:
 - eliminate the decoder
 - take the encoder part
 - add a layer or two
 - softmax on top
 - train for classification (e.g. cross-entropy)



Pre-training


- training an autoencoder unsupervised network



- If the final supervised network needs to be large (many layers) the autoencoder also needs to be large (many layers)

Pre-training



- Autoencoder with many layers
 - n layers - may be as difficult to train as a deep supervised network with n layers



Pre-training

Greedy layer-wise pretraining


- First train a shallow autoencoder (one hidden layer – green)
- Next, add another hidden layer (violet)
 - Keep the previous weights as initialization
- Repeat, adding one layer at a time
 - Actually, two: one in encoder one in decoder




Training deep nets

- Pre-training can help in training deep nets

(no pre-training)




(with pre-training)






Training deep nets

- Pre-training serves as a regularizer
 - Different runs of pre-trained nets are similar, and converge during training
 - Different runs of non-pre-trained nets progress in different directions during training (blue to green)




Training deep nets

- Pre-trained networks overtrain less
 - For the same training loss test loss is lower for pre-trained net




Pre-training

■ De-noising autoencoder:



- Can make the network more resistant to minor variations in input





Pre-training

- Pre-training for dealing with depth of the network
 - Greedy layer-wise pretraining
 - Is not as much needed these days – there are other techniques for helping with optimization of deep nets
- Pre-training (not greedy, not layer-wise)
is still very useful for dealing with limited training data
 - Transfer learning
 - Teacher-student learning