Racehall API documentation

API Specification

Base URL

`https://api.bmileisure.com`

Base Header Parameters

Parameter	Type	Suggested value	Description
Accept-Language	string	en	Language of properties
Content-Type	string	application/json	Suggested content-type for the API to consume
Bmi-Subscription-Key	string	xxxxxxxxxxxxx	Subscription key for API usage

Security

The API is secured with authentication using a bearer token. Clients should obtain an access token by sending a POST request to the `/auth/{clientkey}/publicbooking` endpoint with their username and password in the request body. The response includes a bearer access token that should be included in the Authorization header of subsequent requests. The access token has an expiration time of 3600 seconds and is included in a list of valid client keys for added security.

Note: clientkey in the example below is " `racehalltest` " - you can find the other values for clientkey and password below

Endpoint URL

`POST /auth/racehalltest/publicbooking`

Request body

```
{
  "Username": "racehalltest",
  "Password": "racehalltest"
}
```

Parameter	Type	Description	Mandatory
`username`	String	Username to login	✅

`password`	String	Password to login	✅

Response

```
{
    "TokenType": "bearer",
    "AccessToken": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJjbGllbnRrZXkiOiJ5YXNtYXJpbmEiLCJuYmYiOjE2ODIwODk0OTIsImV4cCI6MTY4MjA5MzA5MiwiaWF0IjoxNjgyMDg5NDkyfQ.xxxx",
    "ExpiresIn": "3600",
    "IncludedClientKeys": [
        "racehalltest"
    ]
}
```

Decoded token

```
{
  "alg": "HS256",
  "typ": "JWT"
}.{
  "clientkey": "racehalltest",
  "nbf": 1682089492,
  "exp": 1682093092,
  "iat": 1682089492
}.[Signature]

```

Error response(s)

400

A 400 (Bad request) response will return a `ErrorResponse` dto

```
public class ErrorResponse
{
    public ExceptionKind Kind { get; set; }
    public string Message { get; set; }
}
```

`ExceptionKind`

```
public enum ExceptionKind
{
  Unknown,
  Validation,
  Database,
  Business,
  ActionRequired,
}
```

401

A 401 (Unauthorized) response indicate either in passing a expired or wrong JWT.

Also serving a `ClientKey` in the URL parameters that is not included in the JWT claims will also results in a 401.

Endpoints

1. Retrieve all locations

Endpoint URL

`GET /public-booking/{clientKey}/locations`

Response 200 OK

```
{
    "locations": [
        {
            "clientKey": "...",
            "name": "...."
        },
        {
            "clientKey": "....",
            "name": "..."
        }
      ]
  }
```

Other possible responses: 400, 401, 500

2. Retrieve all pages available on a date

Endpoint URL

`GET /public-booking/{clientKey}/page?date={date}`

Parameter	Type	Description	Mandatory	Example
`date`	DateTime	Date on which page should be available	✅	2025-05-31T00:00:00.000Z

Response 200 OK

```
[
    {
        "id": 123,
        "name": "...",
        "kind": 0,
        "products": [
            {
                "id": 10,
                "name": "....",
                "info": "<html>\r\n\r\n<style type=\"text/css\">....
</style>\r\n\r\n<body>....</body>\r\n</html>",
                "hasPicture": true,
                "bookingMode": 0,
                "productGroup": "...",
                "minAmount": -1,
                "maxAmount": -1,
                "minAge": 0,
                "maxAge": 200,
                "resourceKind": "Race",
                "kind": 2,
                "isCombo": true,
                "isMembersOnly": false,
                "prices": [
                    {
                        "amount": 20.0,
```

```
                        "kind": 0,
                        "shortName": "m",
                        "depositKind": 0
                    },
                    {
                        "amount": 1.0,
                        "kind": 0,
                        "shortName": "c",
                        "depositKind": 2
                    }
                ],
                "resources": [
                    {
                        "id": 1,
                        "xRef": null,
                        "kind": "Race"
                    }
                ],
                "dynamicGroups": null,
                "xRef": null
            },
            {
                "id": 23,
                "name": "...",
                "info": "<html>\r\n\r\n<style type=\"text/css\">...
</style>\r\n\r\n<body>....</body>\r\n</html>",
                "hasPicture": true,
                "bookingMode": 0,
                "productGroup": "...",
                "minAmount": -1,
                "maxAmount": 12,
                "minAge": null,
                "maxAge": null,
                "resourceKind": "Race",
                "kind": 7,
                "isCombo": true,
                "isMembersOnly": false,
                "prices": [
                    {
                        "amount": 37.0,
                        "kind": 0,
                        "shortName": "m",
                        "depositKind": 0
                    },
                    {
                        "amount": 1.0,
                        "kind": 0,
                        "shortName": "c",
                        "depositKind": 2
                    }
                ],
                "resources": [
                    {
                        "id": 1,
                        "xRef": null,
                        "kind": "Race"
                    }
                ],
                "dynamicGroups": [
                    {
                        "name": "Child Drivers Aged 8-12 ",
                        "tag": "kids",
                        "minQuantity": 1.0,
                        "maxQuantity": 10.0,
                        "id": 123,
                        "quantity": 1.0
                    },
                    {
                        "name": "Adult Drivers Aged 13+",
                        "tag": "adults",
                        "minQuantity": 0.0,
```

```
                        "maxQuantity": 11.0,
                        "id": 124,
                        "quantity": 0.0
                    }
                ],
                "xRef": null
            }
        ]
    },
  {.....}
  ]

```

Other possible responses: 400, 401, 500

3. Retrieve all bookable products

Endpoint URL

`GET /public-booking/{clientKey}/products`

Response 200 OK

```
[
    {
        "id": "123",
        "name": "...",
        "info": "...",
        "hasPicture": true,
        "isCombo": true,
        "bookingMode": 0,
        "prices": [
            {
                "amount": 99.95,
                "kind": 0,
                "shortName": "m",
                "depositKind": 0
            }
        ],
        "productGroup": "...",
        "dynamicGroups": null,
        "minAmount": 14,
        "maxAmount": 18,
        "voucherMetaId": null,
        "voucherMetaKind": null,
        "isEntry": true,
        "resourceId": "123",
        "resourceKind": "Race",
        "kind": 2,
        "saleMode": 1,
        "sessionGroup": "Unknown",
        "minAge": 14,
        "maxAge": 100,
        "isMembersOnly": false
    }
]

```

Other possible responses: 400, 401, 500

4. Return image of the product

Endpoint URL

`GET /public-booking/{clientKey}/image/product?productId={productId}`

Request parameters

Parameter	Data type	Description	Mandatory
`productId`	Long	identifier of picked product	✅

Response

```
Image

```

Other possible responses: 400, 401, 404, 500

5. Return available days of a product in a given period

Endpoint URL

`GET /public-booking/{clientKey}/availability?productId={productId}&dateFrom={dateFrom}&dateTill={dateTill}`

Request parameters

Parameter	Data type	Description	Mandatory
`productId`	Long	identifier of picked product	✅
`dateFrom`	Date “2023-04-01“	beginning date to search availability e.g. beginning of the month	✅
`dateTill`	Date “2023-04-30“	ending date to search availability e.g. end of the month	✅

Response

```
{
    "activities" : [
        {
            "date": "2023-04-21",
            "status": 0 //0 available
        },
        {
            "date": "2022-04-21",
            "status": 0 // 0 available
        },
        {
            "date": "2022-04-23",
            "status": 1 //1 fully booked
        }
    ]
}

```

Status

`enum: {0: "Available", 1: "Fully Booked"}`

Other possible responses: 400, 401, 404, 500

6. Retrieve proposals for a product on the specific date

Endpoint URL

`POST /public-booking/{clientKey}/availability?date={date}`

Request parameters

Parameter	Data type	Description	Mandatory
`date`	Date “2023-04-21“	picked date to retrieve available time slots from.	✅

Request body

```
{
    "productId" : "123"
    "pageId": "123",
    "quantity": 1
}
```

Property	Data type	Description	Mandatory
`productId`	Long	identifier of picked product	✅
`pageId`	Long	identifier of picked page	❌
`quantity`	Int		✅

Response

```
{
    "proposals": [
        {
            "blocks": [
                {
                    "productLineIds": ["123"],
                    "block": {
                        "name": "...",
                        "showSessionTimes": true,
                        "capacity": 18,
                        "freeSpots": 12,
                        "resourceId": "123",
                        "prices": [
                            {
                                "amount": 99.95,
                                "kind": 0,
                                "shortName": "m",
                                "depositKind": 0
                            }
                        ],
                        "bookingMode": 0,
```

```
                        "start": "2023-04-21T14:40:00",
                        "stop": "2023-04-21T14:55:00"
                    }
                }
            ],
            "productLineId": null
        }
    ]
}

```

Other possible responses: 400, 401, 404, 500

7. Book a time slot

Endpoint URL

`POST /public-booking/{clientKey}/booking/book`

Request body

```
{
    "productId": "103983",
    "pageId": "739282",
    "quantity": 1,
    "resourceId": "19476",
    "proposal": {...},
    "contactPerson": {
       "firstName": "Nick",
       "lastName": "Test",
       "email": "nick.Test@gmail.com",
       "phone": "04500008260"
     },
     "orderId": "1234",
}

```

Property	Data type	Description	Mandatory
`productId`	String	identifier of the booked product	✅
`pageId`	String	identitier of the page, from where product was used	❌
`quantity`	Int	The amount of people to book	✅
`resourceId`	String	identifier of a specific resource in our database	❌
`proposal`	Object	proposal you want to book on	✅
`ContactPerson`	Object	information about the person who buys the ticket, if not	❌

		included we will create a booking with a no-name person	
`OrderId`	String	nullable order id to add existing products to your order	❌

Response

```
{
    "schedules": [
        {...}
    ],
    "orderId": "63000000007315961",
    "projectId": "63000000007315962",
    "parentBillLineId": "63000000007315965",
    "prices": [
        {...}
    ]
}
```

Other possible responses: 400, 401, 404, 500

8. Confirm external payment and return booking confirmation and QR code

Endpoint URL

`POST /public-booking/{clientKey}/payment/confirm`

Request body

```
{
  "id": "string",
  "paymentTime": "2023-04-20T13:31:54.135Z",
  "amount": 0,
  "orderId": 0,
  "extraData": {
    "additionalProp1": "string",
    "additionalProp2": "string",
    "additionalProp3": "string"
  }
}
```

Parameter	Date type	Description	Mandatory
`id`	String	Identifier of external payment (stored for reference)	✅
`paymentTime`	DateTime (UTC)	UTC datetime of payment confirmed	✅

`amount`	Decimal	The amount that has been payed	✅
`orderId`	Long	Identifier of the order	✅
`extraData`	Object	place to put extra properties if necessary	❌

Response

```
{
  "status": 0, //0 = payment confirmed
  "reservationCode": "r{id}", //replacement for Qr code payload
  "reservationNumber" : "123"
  "orderId": "1234"
}

```

Other possible responses: 400, 401, 404, 500

9. Cancel current bill/order

Endpoint URL

`DELETE /public-booking/{clientKey}/bill/{orderId}/cancel`

Request parameters

Parameter	Data type	Description
`orderId`	Long	identifier of the bill you want to cancel (before payment)

Other possible responses: 400, 401, 404, 500