

Master of Computer Applications
MCAC 103: Data Structures
Unique Paper Code: 223421112 / 223421103

Semester-I

December-2024

Year of admission: 2023 and 2024

Time: Three Hours


Maximum marks: 70

Note: Answer all the questions. Your code/ algorithm/ pseudocode MUST be well documented and interfaces must be clearly defined.


1. a. Determine the time complexity of the following code snippet. [4]

```
for (i = 1; i < n; i = i * 2) {  
    for (j = i; j < n; j++)  
        printf("x");  
}
```


- b. Show the resulting AVL tree after removing the node containing the value 81. [4]



- c. Show the step-by-step process of using Kruskal's algorithm with disjoint-set operations (Union-Find) to determine the Minimum Spanning Tree for the undirected graph given below. [6]



2. a. Consider the following directed, weighted graph:



Despite the presence of negative weight edges in the graph, use Dijkstra's algorithm to compute the **supposedly shortest paths** from vertex A to all other vertices. Show your steps and also list the vertices in the order which you marked them known.

- b. Consider a linear-probing hash table of size 10 with the hash function $h(x) = x \bmod 10$. After inserting six integer keys into an initially empty hash table, the array of keys is:

| 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
|---|---|----|----|----|----|----|----|---|---|
| | | 42 | 23 | 34 | 52 | 46 | 33 | | |


Which of the following choice(s) are insertion sequences resulting in the above hash table? Assume that the length of the hash table does not change during the insertions.

- 46, 42, 34, 52, 23, 33
- 34, 42, 23, 52, 33, 46
- 46, 34, 42, 23, 52, 33
- 42, 46, 33, 23, 34, 52
- 42, 23, 34, 52, 46, 33

3. a. In a complete k -ary tree, every internal node has exactly k children or no child. Find the number of leaves in such a tree with n internal nodes. [3]


$$\frac{n}{k-1}$$

- b. Consider the B+ tree shown below. Draw the updated B+ tree after inserting a data entry with key 79. [4]



- c. Write the pseudo-code for a function that takes an array of integers as input and determines the nearest smaller element for each element in the array. For an element at index i , the nearest smaller element is the closest element to the left of i that is smaller than the element at i . If no such element exist, return -1 for that position. Your solution must use a stack, ensuring that the number of *push()* operations does not exceed the number of elements in the array. [7]

4. a. Given the graph in the figure below, specify the order in which the vertices will be traversed when the edges incident on a vertex are explored in alphabetical order of the adjacent vertices, starting from node A, for both *DFS* and *BFS* traversal algorithms. [6]



- b. Give a clear description of an *efficient* algorithm for finding the k smallest elements of a very large n -element vector. Using $k=4$, show the steps of your algorithm on the following list of integers: 10, 9, 11, 14, 2, 15, 18, 7, 5, 21, 1. [8]

5. a. You are given a singly linked list where each node contains an integer value. Write an *efficient* algorithm to rearrange the list so that all odd-numbered elements (in terms of their values) appear before all even-numbered elements, maintaining the original relative order of odd and even elements. For example, given the linked list: $1 \rightarrow 4 \rightarrow 3 \rightarrow 2 \rightarrow 5 \rightarrow 6$, your algorithm should rearrange the list to: $1 \rightarrow 3 \rightarrow 5 \rightarrow 4 \rightarrow 2 \rightarrow 6$. Furthermore, the list should be scanned only once, and aside from a small amount of temporary space, no additional data structures should be used. [7]

- b. Solve the following recurrence relation using the recursion tree approach. [7]

$$T(n) = 2T(n/2) + n \log n$$

