

1

```

l,r,cnt,times,start= 0,0,0,0,0
my_list = []
my_string = input()
for x in my_string:
    if x == 'L':
        l+=1
        cnt+=1
    elif x == 'R':
        r+=1
        cnt+=1
    if l==r:
        l,r=0,0
        my_string = my_string
        end = cnt
        my_list.append(my_string[start:end:1])
        start = end
        times+=1

print(times)
for i in my_list:
    print(i)

```

2

3

a.

list	Dictionary
Works like an array having index values	It has 'key' and 'value' data; a pair value structure
[1,2,3,...] all values are same data type	[key:value,key:value,...] the key values can any data type

	<table> <tr> <th>Can access via index number</th><th>Can access via key and value relation</th></tr> <tr> <td> <p>b.</p> <p>(*args)</p> <pre>#args-> takes multiple parameter without specifying def m(*j): for num in j: print(num) m(23,56,89,6,5,54,8)</pre> </td><td> <p>(**kargs)</p> <pre># def famous(**kargs) def famous_name(first, last, **addition): name = f' {first} {last}' # print(addition['title']) for key, value in addition.items(): print(key, value) return name name = famous_name(first='Taher' , last='Ali', title="Hujur", title2="Shayokh", last2='taheri') print(name)</pre> </td></tr> <tr> <td>Takes multiple arguments. All the elements are same data type</td><td>Takes key value arguments Data type can be varied</td></tr> </table>	Can access via index number	Can access via key and value relation	<p>b.</p> <p>(*args)</p> <pre>#args-> takes multiple parameter without specifying def m(*j): for num in j: print(num) m(23,56,89,6,5,54,8)</pre>	<p>(**kargs)</p> <pre># def famous(**kargs) def famous_name(first, last, **addition): name = f' {first} {last}' # print(addition['title']) for key, value in addition.items(): print(key, value) return name name = famous_name(first='Taher' , last='Ali', title="Hujur", title2="Shayokh", last2='taheri') print(name)</pre>	Takes multiple arguments. All the elements are same data type	Takes key value arguments Data type can be varied
Can access via index number	Can access via key and value relation						
<p>b.</p> <p>(*args)</p> <pre>#args-> takes multiple parameter without specifying def m(*j): for num in j: print(num) m(23,56,89,6,5,54,8)</pre>	<p>(**kargs)</p> <pre># def famous(**kargs) def famous_name(first, last, **addition): name = f' {first} {last}' # print(addition['title']) for key, value in addition.items(): print(key, value) return name name = famous_name(first='Taher' , last='Ali', title="Hujur", title2="Shayokh", last2='taheri') print(name)</pre>						
Takes multiple arguments. All the elements are same data type	Takes key value arguments Data type can be varied						
4	<pre>n = int(input()) cnt = 0 cnt2 = 0 my_list = []</pre>						

```
my_string = input()

for x in my_string.split():
    my_list.append(int(x))

while(cnt==0):
    for i,items in enumerate(my_list):
        if items%2==0:
            my_list[i]= items//2
        else:
            cnt+=1
            break
    cnt2+=1

print(cnt2-1)
```

```
5 import pyautogui
#kindly when you run this programme please put VScode on
fullscreen. Otherwise the cursor won't be able to click
n = int(input())

pyautogui.moveTo(340,563)
pyautogui.click()
for i in range(n,0,-1):
    for j in range(0,i):
        pyautogui.write('*')

    pyautogui.write('\n')
```