

# Lecture 9-3: Selection



**Sunghyun Cho**

Professor

Division of Computer Science

chopro@hanyang.ac.kr

HANYANG UNIVERSITY

## The Selection Problem

- ◆ Given an integer  $k$  and  $n$  elements  $x_1, x_2, \dots, x_n$ , taken from a total order, find the  $k$ -th smallest element in this set.
- ◆ Of course, we can sort the set in  $O(n \log n)$  time and then index the  $k$ -th element.

$k=3$

7 4 9 6 2 → 2 4 6 7 9


- ◆ Can we solve the selection problem faster?



# Quick-Select

- ◆ Quick-select is a randomized selection algorithm based on the prune-and-search paradigm: <- devise and conquer

- **Prune:** pick a random element  $x$  (called **pivot**) and partition  $S$  into
  - ◆  $L$ : elements less than  $x$
  - ◆  $E$ : elements equal  $x$
  - ◆  $G$ : elements greater than  $x$
- **Search:** depending on  $k$ , either answer is in  $E$ , or we need to recur in either  $L$  or  $G$



## Partition

- ◆ We partition an input sequence as in the quick-sort algorithm:
  - We remove, in turn, each element  $y$  from  $S$  and
  - We insert  $y$  into  $L$ ,  $E$  or  $G$ , depending on the result of the comparison with the pivot  $x$
- ◆ Each insertion and removal is at the beginning or at the end of a sequence, and hence takes  $O(1)$  time
- ◆ Thus, the partition step of quick-select takes  $O(n)$  time

### Algorithm *partition*( $S, p$ )

**Input** sequence  $S$ , position  $p$  of pivot

**Output** subsequences  $L$ ,  $E$ ,  $G$  of the elements of  $S$  less than, equal to, or greater than the pivot, resp.

$L, E, G \leftarrow$  empty sequences

$x \leftarrow S.remove(p)$

**while**  $\neg S.isEmpty()$

$y \leftarrow S.remove(S.first())$

**if**  $y < x$

$L.addLast(y)$

**else if**  $y = x$

$E.addLast(y)$

**else**  $\{ y > x \}$


$G.addLast(y)$

**return**  $L, E, G$

# Quick-Select Visualization

- ◆ An execution of quick-select can be visualized by a recursion path

- Each node represents a recursive call of quick-select, and stores  $k$  and the remaining sequence



HANYANG UNIVERSITY

## Expected Running Time



- ◆ Consider a recursive call of quick-select on a sequence of size  $s$

- **Good call:** the sizes of  $L$  and  $G$  are each less than  $3s/4$
- **Bad call:** one of  $L$  and  $G$  has size greater than  $3s/4$




**Good call**

**Bad call**


- ◆ A call is **good** with probability  $1/2$

- $1/2$  of the possible pivots cause good calls:



HANYANG UNIVERSITY

## Expected Running Time, Part 2



- ◆ **Probabilistic Fact #1:** The expected number of coin tosses required in order to get one head is two
- ◆ **Probabilistic Fact #2:** Expectation is a linear function:
  - $E(X + Y) = E(X) + E(Y)$
  - $E(cX) = cE(X)$
- ◆ Let  $T(n)$  denote the expected running time of quick-select.
- ◆ By Fact #2,  $\rightarrow$  **Running time for L, E, or G which has a searching value. (worst case만을 고려)**
  - $T(n) \leq T(3n/4) + bn * (\text{expected \# of calls before a good call})$
- ◆ By Fact #1, **실질적인 값은 2**  $\rightarrow$  **Running time to partition n into L, E, G.**
  - $T(n) \leq T(3n/4) + 2bn$
- ◆ That is,  $T(n)$  is a geometric series:
  - $T(n) \leq 2bn + 2b(3/4)n + 2b(3/4)^2n + 2b(3/4)^3n + \dots$
- ◆ So  $T(n)$  is  **$O(n)$** .
- ◆ We can solve the selection problem in  $O(n)$  expected time.




7

HANYANG UNIVERSITY

## Deterministic Selection



- ◆ We can do **selection in  $O(n)$  worst-case time.**
- ◆ Main idea: recursively use the selection algorithm itself to find a good pivot for quick-select:
  - Divide  $S$  into  $n/5$  sets of 5 each
  - Find a median in each set
  - Recursively find the median of the "baby" medians.



8

HANYANG UNIVERSITY

# Q & A



한양대학교 ERICA 캠퍼스