

Compiler Design

Fatemeh Deldar

Isfahan University of Technology

1402-1403

LL(1) Grammars

- *LL*(1)
 - The first "L" in *LL*(1) stands for scanning the input from left to right
 - The second "L" for producing a leftmost derivation
 - The "1" for using one input symbol of lookahead at each step to make parsing action decisions
- A grammar G is *LL*(1) **if and only if** whenever $A \rightarrow \alpha | \beta$ are two distinct productions of G , the following conditions hold:
 1. $FIRST(\alpha)$ and $FIRST(\beta)$ are disjoint sets
 2. If ϵ is in $FIRST(\beta)$, then $FIRST(\alpha)$ and $FOLLOW(A)$ are disjoint sets, and likewise if ϵ is in $FIRST(\alpha)$
- Predictive parsers can be constructed for *LL*(1) grammars

LL(1) Grammars

- **Construction of a predictive parsing table**

INPUT: Grammar G .

OUTPUT: Parsing table M .

METHOD: For each production $A \rightarrow \alpha$ of the grammar, do the following:

1. For each terminal a in $\text{FIRST}(\alpha)$, add $A \rightarrow \alpha$ to $M[A, a]$.
2. If ϵ is in $\text{FIRST}(\alpha)$, then for each terminal b in $\text{FOLLOW}(A)$, add $A \rightarrow \alpha$ to $M[A, b]$. If ϵ is in $\text{FIRST}(\alpha)$ and $\$$ is in $\text{FOLLOW}(A)$, add $A \rightarrow \alpha$ to $M[A, \$]$ as well.

- If, after performing the above, there is no production at all in $M[A, a]$, then set $M[A, a]$ to error

LL(1) Grammars

- **Example**

$$\begin{aligned}
 E &\rightarrow T E' \\
 E' &\rightarrow + T E' \mid \epsilon \\
 T &\rightarrow F T' \\
 T' &\rightarrow * F T' \mid \epsilon \\
 F &\rightarrow (E) \mid \text{id}
 \end{aligned}$$

NON - TERMINAL	INPUT SYMBOL					
	id	+	*	()	\$
E	$E \rightarrow T E'$			$E \rightarrow T E'$		
E'		$E' \rightarrow + T E'$			$E' \rightarrow \epsilon$	$E' \rightarrow \epsilon$
T	$T \rightarrow F T'$			$T \rightarrow F T'$		
T'		$T' \rightarrow \epsilon$	$T' \rightarrow * F T'$		$T' \rightarrow \epsilon$	$T' \rightarrow \epsilon$
F	$F \rightarrow \text{id}$			$F \rightarrow (E)$		

LL(1) Grammars

- For every LL(1) grammar, each parsing-table entry uniquely identifies a production or an error


- Example**

$$\begin{aligned} S &\rightarrow iEtSS' \mid a \\ S' &\rightarrow eS \mid \epsilon \\ E &\rightarrow b \end{aligned}$$

NON - TERMINAL	INPUT SYMBOL					
	a	b	e	i	t	$\$$
S	$S \rightarrow a$			$S \rightarrow iEtSS'$		
S'			$S' \rightarrow \epsilon$ $S' \rightarrow eS$			$S' \rightarrow \epsilon$
E		$E \rightarrow b$				

Nonrecursive Predictive Parsing

- A nonrecursive predictive parser can be built by maintaining a stack explicitly, rather than implicitly via recursive calls



Nonrecursive Predictive Parsing

- **Table-driven predictive parsing**

- Initially, $w\$$ in the input buffer and the start symbol S of G on top of the stack, above $\$$

```
let  $a$  be the first symbol of  $w$ ;  
let  $X$  be the top stack symbol;  
while (  $X \neq \$$  ) { /* stack is not empty */  
    if (  $X = a$  ) pop the stack and let  $a$  be the next symbol of  $w$ ;  
    else if (  $X$  is a terminal ) error();  
    else if (  $M[X, a]$  is an error entry ) error();  
    else if (  $M[X, a] = X \rightarrow Y_1 Y_2 \cdots Y_k$  ) {  
        output the production  $X \rightarrow Y_1 Y_2 \cdots Y_k$ ;  
        pop the stack;  
        push  $Y_k, Y_{k-1}, \dots, Y_1$  onto the stack, with  $Y_1$  on top;  
    }  
    let  $X$  be the top stack symbol;  
}
```

- **Example**

E	\rightarrow	$T E'$
E'	\rightarrow	$+ T E' \mid \epsilon$
T	\rightarrow	$F T'$
T'	\rightarrow	$* F T' \mid \epsilon$
F	\rightarrow	$(E) \mid \text{id}$

MATCHED	STACK	INPUT	ACTION
	$E\$$	$\text{id} + \text{id} * \text{id}\$$	
	$TE'\$$	$\text{id} + \text{id} * \text{id}\$$	output $E \rightarrow TE'$
	$FT'E'\$$	$\text{id} + \text{id} * \text{id}\$$	output $T \rightarrow FT'$
	$\text{id } T'E'\$$	$\text{id} + \text{id} * \text{id}\$$	output $F \rightarrow \text{id}$
id	$T'E'\$$	$+ \text{id} * \text{id}\$$	match id
id	$E'\$$	$+ \text{id} * \text{id}\$$	output $T' \rightarrow \epsilon$
id	$+ TE'\$$	$+ \text{id} * \text{id}\$$	output $E' \rightarrow + TE'$
$\text{id} +$	$TE'\$$	$\text{id} * \text{id}\$$	match $+$
$\text{id} +$	$FT'E'\$$	$\text{id} * \text{id}\$$	output $T \rightarrow FT'$
$\text{id} +$	$\text{id } T'E'\$$	$\text{id} * \text{id}\$$	output $F \rightarrow \text{id}$
$\text{id} + \text{id}$	$T'E'\$$	$* \text{id}\$$	match id
$\text{id} + \text{id}$	$* FT'E'\$$	$* \text{id}\$$	output $T' \rightarrow * FT'$
$\text{id} + \text{id} *$	$FT'E'\$$	$\text{id}\$$	match $*$
$\text{id} + \text{id} *$	$\text{id } T'E'\$$	$\text{id}\$$	output $F \rightarrow \text{id}$
$\text{id} + \text{id} * \text{id}$	$T'E'\$$	$\$$	match id
$\text{id} + \text{id} * \text{id}$	$E'\$$	$\$$	output $T' \rightarrow \epsilon$
$\text{id} + \text{id} * \text{id}$	$\$$	$\$$	output $E' \rightarrow \epsilon$