

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000000	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:
4e	Cost = 0 Port = 0x000d					
Frame 1: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0						
IEEE 802.3 Ethernet						
Logical-Link Control						
Spanning Tree Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
2	2.002225778	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:
4e	Cost = 0 Port = 0x000d					
Frame 2: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0						
IEEE 802.3 Ethernet						
Logical-Link Control						
Spanning Tree Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
3	4.004536470	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:
4e	Cost = 0 Port = 0x000d					
Frame 3: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0						
IEEE 802.3 Ethernet						
Logical-Link Control						
Spanning Tree Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
4	6.006707928	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:
4e	Cost = 0 Port = 0x000d					
Frame 4: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0						
IEEE 802.3 Ethernet						
Logical-Link Control						
Spanning Tree Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
5	8.008973326	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:
4e	Cost = 0 Port = 0x000d					
Frame 5: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0						
IEEE 802.3 Ethernet						
Logical-Link Control						
Spanning Tree Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
6	8.810311167	8c:90:2d:fd:a6:12	Broadcast	ARP	42	Who has 172.16.30.254? Tell 172.16.30.1
Frame 6: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface if_e1, id 0						
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: Broadcast (ff:ff:ff:ff:ff:ff)						
Address Resolution Protocol (request)						
No.	Time	Source	Destination	Protocol	Length	Info
7	8.810480290	ec:75:0c:c2:26:49	8c:90:2d:fd:a6:12	ARP	60	172.16.30.254 is at ec:75:0c:c2:26:49
Frame 7: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0						
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)						
Address Resolution Protocol (reply)						
No.	Time	Source	Destination	Protocol	Length	Info
8	8.810494127	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=1/256, ttl=64 (reply in 9)
Frame 8: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0						
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)						
Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254						
Internet Control Message Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
9	8.810696553	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=1/256, ttl=64 (request in 8)
Frame 9: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0						
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)						
Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1						
Internet Control Message Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
10	9.841144424	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=2/512, ttl=64 (reply in 11)
Frame 10: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0						
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)						
Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254						
Internet Control Message Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
11	9.841333049	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=2/512, ttl=64 (request in 10)
Frame 11: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0						
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)						
Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1						
Internet Control Message Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
12	10.011202116	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:
4e	Cost = 0 Port = 0x000d					
Frame 12: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0						
IEEE 802.3 Ethernet						
Logical-Link Control						
Spanning Tree Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
13	10.865127509	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=3/768, ttl=64 (reply in 14)
Frame 13: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0						
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)						
Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254						
Internet Control Message Protocol						
No.	Time	Source	Destination	Protocol	Length	Info
14	10.865333737	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=3/768, ttl=64 (request in 13)

Frame 14: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
 Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
15	11.889135708	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=4/1024, ttl=64 (reply in 16)

Frame 15: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
 Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254
 Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
16	11.889331399	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=4/1024, ttl=64 (request in 15)

Frame 16: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
 Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
17	12.013513444	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:4e Cost = 0 Port = 0x000d

Frame 17: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet
 Logical-Link Control
 Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
18	12.913121553	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=5/1280, ttl=64 (reply in 19)

Frame 18: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
 Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254
 Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
19	12.913289566	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=5/1280, ttl=64 (request in 18)

Frame 19: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
 Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
20	13.937120281	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=6/1536, ttl=64 (reply in 21)

Frame 20: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
 Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254
 Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
21	13.937316872	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=6/1536, ttl=64 (request in 20)

Frame 21: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
 Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
22	14.015791770	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:4e Cost = 0 Port = 0x000d

Frame 22: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet
 Logical-Link Control
 Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
23	14.051295374	ec:75:0c:c2:26:49	8c:90:2d:fd:a6:12	ARP	60	Who has 172.16.30.1? Tell 172.16.30.254

Frame 23: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Address Resolution Protocol (request)

No.	Time	Source	Destination	Protocol	Length	Info
24	14.051316970	8c:90:2d:fd:a6:12	ec:75:0c:c2:26:49	ARP	42	172.16.30.1 is at 8c:90:2d:fd:a6:12

Frame 24: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
 Address Resolution Protocol (reply)

No.	Time	Source	Destination	Protocol	Length	Info
25	14.961134333	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=7/1792, ttl=64 (reply in 26)

Frame 25: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
 Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254
 Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
26	14.961330375	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=7/1792, ttl=64 (request in 25)

Frame 26: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
 Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
27	15.985135658	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=8/2048, ttl=64 (reply in 28)

Frame 27: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
 Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
28	15.985357577	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=8/2048, ttl=64 (request in 27)

Frame 28: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
29	16.017773625	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:4e Cost = 0 Port = 0x000d

Frame 29: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
 IEEE 802.3 Ethernet
 Logical-Link Control
 Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
30	17.009134334	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=9/2304, ttl=64 (reply in 31)

Frame 30: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
 Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
31	17.009331710	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=9/2304, ttl=64 (request in 30)

Frame 31: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
32	18.020143219	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:4e Cost = 0 Port = 0x000d

Frame 32: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
 IEEE 802.3 Ethernet
 Logical-Link Control
 Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
33	18.033134493	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=10/2560, ttl=64 (reply in 34)

Frame 33: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
 Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
34	18.033327771	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=10/2560, ttl=64 (request in 33)

Frame 34: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
35	19.057132897	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=11/2816, ttl=64 (reply in 36)

Frame 35: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
 Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
36	19.057287139	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=11/2816, ttl=64 (request in 35)

Frame 36: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
37	20.022416083	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:4e Cost = 0 Port = 0x000d

Frame 37: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
 IEEE 802.3 Ethernet
 Logical-Link Control
 Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
38	20.081138732	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=12/3072, ttl=64 (reply in 39)

Frame 38: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
 Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
39	20.081330855	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=12/3072, ttl=64 (request in 38)

Frame 39: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
 Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
40	21.105147534	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=13/3328, ttl=64 (reply in 41)

Frame 40: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
 Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)

```

Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254
Internet Control Message Protocol
No.    Time                Source                Destination            Protocol Length Info
  41  21.105304890         172.16.30.254         172.16.30.1            ICMP      98      Echo (ping) reply    id=0x0fcd, seq=13/3328,
ttl=64 (request in 40)
Frame 41: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
Internet Control Message Protocol
No.    Time                Source                Destination            Protocol Length Info
  42  22.024691667         Routerbo_1c:9f:5a     Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 42: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.    Time                Source                Destination            Protocol Length Info
  43  22.129141681         172.16.30.1           172.16.30.254          ICMP      98      Echo (ping) request   id=0x0fcd, seq=14/3584,
ttl=64 (reply in 44)
Frame 43: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254
Internet Control Message Protocol
No.    Time                Source                Destination            Protocol Length Info
  44  22.129332647         172.16.30.254         172.16.30.1            ICMP      98      Echo (ping) reply     id=0x0fcd, seq=14/3584,
ttl=64 (request in 43)
Frame 44: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
Internet Control Message Protocol
No.    Time                Source                Destination            Protocol Length Info
  45  23.153135421         172.16.30.1           172.16.30.254          ICMP      98      Echo (ping) request   id=0x0fcd, seq=15/3840,
ttl=64 (reply in 46)
Frame 45: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254
Internet Control Message Protocol
No.    Time                Source                Destination            Protocol Length Info
  46  23.153347095         172.16.30.254         172.16.30.1            ICMP      98      Echo (ping) reply     id=0x0fcd, seq=15/3840,
ttl=64 (request in 45)
Frame 46: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
Internet Control Message Protocol
No.    Time                Source                Destination            Protocol Length Info
  47  24.026782947         Routerbo_1c:9f:5a     Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 47: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.    Time                Source                Destination            Protocol Length Info
  48  24.177125936         172.16.30.1           172.16.30.254          ICMP      98      Echo (ping) request   id=0x0fcd, seq=16/4096,
ttl=64 (reply in 49)
Frame 48: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254
Internet Control Message Protocol
No.    Time                Source                Destination            Protocol Length Info
  49  24.177322018         172.16.30.254         172.16.30.1            ICMP      98      Echo (ping) reply     id=0x0fcd, seq=16/4096,
ttl=64 (request in 48)
Frame 49: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
Internet Control Message Protocol
No.    Time                Source                Destination            Protocol Length Info
  50  25.201128958         172.16.30.1           172.16.30.254          ICMP      98      Echo (ping) request   id=0x0fcd, seq=17/4352,
ttl=64 (reply in 51)
Frame 50: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254
Internet Control Message Protocol
No.    Time                Source                Destination            Protocol Length Info
  51  25.201321926         172.16.30.254         172.16.30.1            ICMP      98      Echo (ping) reply     id=0x0fcd, seq=17/4352,
ttl=64 (request in 50)
Frame 51: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
Internet Control Message Protocol
No.    Time                Source                Destination            Protocol Length Info
  52  26.029063846         Routerbo_1c:9f:5a     Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 52: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.    Time                Source                Destination            Protocol Length Info
  53  26.225144173         172.16.30.1           172.16.30.254          ICMP      98      Echo (ping) request   id=0x0fcd, seq=18/4608,
ttl=64 (reply in 54)
Frame 53: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

```

Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)

Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
54	26.225339824	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=18/4608, ttl=64 (request in 53)

Frame 54: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)

Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
55	27.249139977	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=19/4864, ttl=64 (reply in 56)

Frame 55: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)

Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
56	27.249345316	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=19/4864, ttl=64 (request in 55)

Frame 56: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)

Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
57	28.031322299	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:4e Cost = 0 Port = 0x000d

Frame 57: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
58	28.273137080	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=20/5120, ttl=64 (reply in 59)

Frame 58: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)

Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
59	28.273337004	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=20/5120, ttl=64 (request in 58)

Frame 59: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)

Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
60	29.297133630	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=21/5376, ttl=64 (reply in 61)

Frame 60: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)

Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
61	29.297327237	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=21/5376, ttl=64 (request in 60)

Frame 61: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)

Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
62	30.033549036	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:4e Cost = 0 Port = 0x000d

Frame 62: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
63	30.321140557	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=22/5632, ttl=64 (reply in 64)

Frame 63: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)

Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
64	30.321360629	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=22/5632, ttl=64 (request in 63)

Frame 64: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)

Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
65	31.345145594	172.16.30.1	172.16.30.254	ICMP	98	Echo (ping) request id=0x0fcd, seq=23/5888, ttl=64 (reply in 66)

Frame 65: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0

Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)

Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254

Internet Control Message Protocol

No.	Time	Source	Destination	Protocol	Length	Info
66	31.345342676	172.16.30.254	172.16.30.1	ICMP	98	Echo (ping) reply id=0x0fcd, seq=23/5888, ttl=64 (request in 65)

```

Frame 66: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
Internet Control Message Protocol
No.      Time      Source      Destination      Protocol Length Info
   67 32.035869995 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 67: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   68 32.369136008 172.16.30.1 172.16.30.254    ICMP      98      Echo (ping) request id=0x0fcd, seq=24/6144,
ttl=64 (reply in 69)
Frame 68: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
Internet Protocol Version 4, Src: 172.16.30.1, Dst: 172.16.30.254
Internet Control Message Protocol
No.      Time      Source      Destination      Protocol Length Info
   69 32.369337095 172.16.30.254 172.16.30.1    ICMP      98      Echo (ping) reply id=0x0fcd, seq=24/6144,
ttl=64 (request in 68)
Frame 69: 98 bytes on wire (784 bits), 98 bytes captured (784 bits) on interface if_e1, id 0
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
Internet Protocol Version 4, Src: 172.16.30.254, Dst: 172.16.30.1
Internet Control Message Protocol
No.      Time      Source      Destination      Protocol Length Info
   70 34.037849077 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 70: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   71 36.040158898 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 71: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   72 37.603254261 ec:75:0c:c2:26:49 8c:90:2d:fd:a6:12 ARP      60      Who has 172.16.30.1? Tell 172.16.30.254
Frame 72: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
Ethernet II, Src: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49), Dst: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12)
Address Resolution Protocol (request)
No.      Time      Source      Destination      Protocol Length Info
   73 37.603274998 8c:90:2d:fd:a6:12 ec:75:0c:c2:26:49 ARP      42      172.16.30.1 is at 8c:90:2d:fd:a6:12
Frame 73: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface if_e1, id 0
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: ec:75:0c:c2:26:49 (ec:75:0c:c2:26:49)
Address Resolution Protocol (reply)
No.      Time      Source      Destination      Protocol Length Info
   74 38.042430101 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 74: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   75 40.044671731 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 75: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   76 42.046864489 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 76: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   77 43.011410079 192.168.88.1 255.255.255.255 MNDP     189     5678 → 5678 Len=147
Frame 77: 189 bytes on wire (1512 bits), 189 bytes captured (1512 bits) on interface if_e1, id 0
Ethernet II, Src: Routerbo_1c:9f:5a (c4:ad:34:1c:9f:5a), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
Internet Protocol Version 4, Src: 192.168.88.1, Dst: 255.255.255.255
User Datagram Protocol, Src Port: 5678, Dst Port: 5678
Mikrotik Neighbor Discovery Protocol
No.      Time      Source      Destination      Protocol Length Info
   78 43.011473294 Routerbo_1c:9f:5a CDP/VTP/DTP/PAGP/UDLD CDP      132     Device ID: MikroTik Port ID: bridge/ether13
Frame 78: 132 bytes on wire (1056 bits), 132 bytes captured (1056 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Cisco Discovery Protocol
No.      Time      Source      Destination      Protocol Length Info
   79 43.011501378 Routerbo_1c:9f:5a LLDP_Multicast LLDP      146     MA/c4:ad:34:1c:9f:4e IN/bridge/ether13 120
SysN=MikroTik SysD=MikroTik RouterOS 7.2.3 (stable) May/02/2022 15:18:17 CRS326-24G-25+
Frame 79: 146 bytes on wire (1168 bits), 146 bytes captured (1168 bits) on interface if_e1, id 0
Ethernet II, Src: Routerbo_1c:9f:5a (c4:ad:34:1c:9f:5a), Dst: LLDP_Multicast (01:80:c2:00:00:0e)
Link Layer Discovery Protocol

```



```
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   119 116.127149016 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 119: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   120 118.129462267 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 120: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   121 120.131728811 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 121: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   122 122.134010528 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 122: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   123 124.136219030 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 123: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   124 126.138265393 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 124: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   125 128.140012428 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 125: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   126 130.142289151 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 126: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   127 132.144557967 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 127: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   128 134.146831536 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 128: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   129 136.148317005 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 129: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   130 138.150623401 Routerbo_1c:9f:5a Spanning-tree-(for-bridges)_00 STP      60      RST. Root = 32768/0/c4:ad:34:1c:9f:
4e Cost = 0 Port = 0x000d
Frame 130: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0
IEEE 802.3 Ethernet
Logical-Link Control
Spanning Tree Protocol
No.      Time      Source      Destination      Protocol Length Info
   131 139.887143019 172.16.30.1      224.0.0.251      MDNS      87      Standard query 0x0000 PTR _ipps._tcp.local,
"QM" question PTR _ipp._tcp.local, "QM" question
Frame 131: 87 bytes on wire (696 bits), 87 bytes captured (696 bits) on interface if_e1, id 0
Ethernet II, Src: 8c:90:2d:fd:a6:12 (8c:90:2d:fd:a6:12), Dst: IPv4mcast_fb (01:00:5e:00:00:fb)
```

Internet Protocol Version 4, Src: 172.16.30.1, Dst: 224.0.0.251

User Datagram Protocol, Src Port: 5353, Dst Port: 5353

Multicast Domain Name System (query)

No.	Time	Source	Destination	Protocol	Length	Info
132	140.152889270	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 132: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
133	142.155155454	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 133: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
134	144.157310934	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 134: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
135	146.159579868	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 135: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
136	148.161828943	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 136: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
137	150.164105351	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 137: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
138	152.166375269	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 138: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
139	154.168421786	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 139: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
140	156.170683003	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 140: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
141	158.172910406	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 141: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
142	160.175217152	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 142: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
143	162.177397508	Routerbo_1c:9f:5a	Spanning-tree-(for-bridges)_00	STP	60	RST. Root = 32768/0/c4:ad:34:1c:9f:

4e Cost = 0 Port = 0x000d

Frame 143: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface if_e1, id 0

IEEE 802.3 Ethernet

Logical-Link Control

Spanning Tree Protocol

No.	Time	Source	Destination	Protocol	Length	Info
144	163.014011238	192.168.88.1	255.255.255.255	MNDP	189	5678 → 5678 Len=147

Frame 144: 189 bytes on wire (1512 bits), 189 bytes captured (1512 bits) on interface if_e1, id 0

