

Contents

1 Misc	2		
1.1 Contest	2	5.5.1 Determinant	13
1.1.1 Makefile	2	5.5.2 Solve Linear Equation	13
1.2 How Did We Get Here?	2	5.5.3 Freivalds' algo	13
1.2.1 Macros	2	5.6 Polynomial Interpolation	13
1.2.2 constexpr	2		
1.2.3 Bump Allocator	2	6 Geometry	13
1.3 Tools	3	6.1 Point	13
1.3.1 SplitMix64	3	6.1.1 Spherical Coordinates	13
1.3.2 x86 Stack Hack	3	6.2 Segments	13
1.4 Algorithms	3	6.3 Pick's theorem	14
1.4.1 Bit Hacks	3	6.4 Convex Hull	14
1.4.2 DP opt	3	6.5 Angular Sort	14
1.4.3 Mo's Algorithm on Tree	3	6.6 Convex Polygon Minkowski Sum	14
		6.7 Point In Polygon	14
		6.7.1 Convex Version	14
		6.7.2 Offline Multiple Points Version	14
		6.8 Closest Pair	15
2 Data Structures	3		
2.1 GNU PBDS	3	7 Strings	15
2.2 Offline 2D Fenwick	4	7.1 Aho-Corasick	15
2.3 Persistent seg tree	4	7.2 Knuth-Morris-Pratt Algorithm	15
2.4 Line Container	4	7.3 Suffix Array	15
2.5 Li-Chao Tree	4	7.4 Z Value	16
2.6 Wavelet Matrix	4	7.5 Manacher's Algorithm	16
2.7 Link-Cut Tree	5	7.6 Minimum Rotation	16
2.8 Dynamic MST	5	7.7 Palindromic Tree	16
3 Graph	6	8 Debug List	16
3.1 Modeling	6		
3.2 Low link	6	9 Tech	17
3.3 Block Cut Tree	7		
3.4 Shortest paths	7		
3.4.1 Dial's Algorithm	7	1. Misc	
3.4.2 Johnson's Algorithm	7	1.1. Contest	
3.5 Matching/Flows	7	1.1.1. Makefile	
3.5.1 Bipartite Matching	7		
3.5.2 General Matching	7		
3.5.3 Dinic's Algorithm	8		
3.5.4 Minimum Cost Flow	8		
3.5.5 Gomory-Hu Tree	8		
3.5.6 Global Minimum Cut	9		
3.5.7 Bipartite Minimum Cover	9		
3.6 Strongly Connected Components	9		
3.6.1 2-Satisfiability	9		
3.7 Manhattan Distance MST	9		
3.8 Counting C3/C4	10		
3.9 Functional graph	10		
3.9.1 Loops	10		
4 Math	10		
4.1 Number Theory	10		
4.1.1 Theorems	10		
4.1.2 Euler's Totient Function	10		
4.1.3 Möbius Function	10		
4.1.4 Mod Struct	10		
4.1.5 Miller-Rabin	11		
4.1.6 Pollard's Rho	11		
4.2 Iterate $\text{floor}(n/i)$	11		
4.3 Combinatorics	11		
4.3.1 Formulas	11		
4.3.2 Stirling	11		
4.3.3 Extended Lucas	11		
4.4 Theorems	11		
4.4.1 Kirchhoff's Theorem	11		
4.4.2 Tutte's Matrix	11		
4.4.3 Cayley's Formula	12		
4.4.4 Erdős-Gallai Theorem	12		
4.4.5 Burnside's Lemma	12		
5 Numeric	12		
5.1 Fast Fourier Transform	12		
5.2 Fast Walsh-Hadamard Transform	12		
5.3 Subset Convolution	12		
5.4 Linear Recurrences	12		
5.4.1 Berlekamp-Massey Algorithm	12		
5.4.2 Linear Recurrence Calculation	12		
5.5 Matrices	13		

1. Misc

1.1. Contest

1.1.1. Makefile

```
1 .PRECIOUS: ./p%
3 %: p%
5 p%: p%.cpp
7 g++ -o %@ $< -std=c++17 -Wall -Wextra -Wshadow \
  -fsanitize=address,undefined
```

1.2. How Did We Get Here?

1.2.1. Macros

Use vectorizations and math optimizations at your own peril.
For gcc ≥ 9 , there are `[[likely]]` and `[[unlikely]]` attributes.
Call gcc with `-fopenmp` for optimization info.

```
1 #define _GLIBCXX_DEBUG 1 // for debug mode
2 #define _GLIBCXX_SANITIZE_VECTOR 1 // for asan on vectors
3 #pragma GCC optimize("O3", "unroll-loops")
4 #pragma GCC optimize("fast-math")
5 #pragma GCC target("avx,avx2,abm,bmi,bmi2") // tip: `lscpu`
6 // before a loop
7 #pragma GCC unroll 16 // 0 or 1 -> no unrolling
8 #pragma GCC ivdep
```

1.2.2. constexpr

Some default limits in gcc (7.x - trunk):

- constexpr recursion depth: 512
- constexpr loop iteration per function: 262144
- constexpr operation count per function: 33554432
- template recursion depth: 900 (gcc *might* segfault first)

1.2.3. Bump Allocator

```
1 // global bump allocator
2 char mem[256 << 20]; // 256 MB
3 size_t rsp = sizeof mem;
4 void *operator new(size_t s) {
5     assert(s < rsp); // MLE
6     return (void *)&mem[rsp -= s];
7 }
8 void operator delete(void *) {}
9
10 // bump allocator for STL / pbds containers
11 char mem[256 << 20];
12 size_t rsp = sizeof mem;
13 template <typename T> struct bump {
```

```

typedef T value_type;
bump() {}
template <typename U> bump(U, ...) {}
T *allocate(size_t n) {
    rsp -= n * sizeof(T);
    rsp &= 0 - alignof(T);
    return (T *) (mem + rsp);
}
void deallocate(T *, size_t n) {}
};

```

1.3. Tools

1.3.1. SplitMix64

```

using ull = unsigned long long;
inline ull splitmix64(ull x) {
    // change to `static ull x = SEED;` for DRBG
    ull z = (x += 0x9E3779B97F4A7C15);
    z = (z ^ (z >> 30)) * 0xBF58476D1CE4E5B9;
    z = (z ^ (z >> 27)) * 0x94D049BB133111EB;
    return z ^ (z >> 31);
}

```

1.3.2. x86 Stack Hack

```

constexpr size_t size = 200 << 20; // 200MiB
int main() {
    register long rsp asm("rsp");
    char *buf = new char[size];
    asm("movq %0, %%rsp\n" :: "r" (buf + size));
    // do stuff
    asm("movq %0, %%rsp\n" :: "r" (rsp));
    delete[] buf;
}

```

1.4. Algorithms

1.4.1. Bit Hacks

```

// next permutation of x as a bit sequence
ull next_bits_permutation(ull x) {
    ull c = __builtin_ctzll(x), r = x + (1ULL << c);
    return (r ^ x) >> (c + 2) | r;
}
// iterate over all (proper) subsets of bitset s
void subsets(ull s) {
    for (ull x = s; x;) { --x &= s; /* do stuff */ }
}

```

1.4.2. DP opt

Aliens

```

// min dp[i] value and its i (smallest one)
pll get_dp(int cost);
ll aliens(int k, int l, int r) {
    while (l != r) {
        int m = (l + r) / 2;
        auto [f, s] = get_dp(m);
        if (s == k) return f - m * k;
        if (s < k) r = m;
        else l = m + 1;
    }
    return get_dp(l).first - l * k;
}

```

DnC DP :

Given $a[i] = \min_{l_o(i) \leq k < h_i(i)} (f(i, k))$ where the (minimal) optimal k increases with i , computes $a[i]$ for $i = L..R - 1$.
Time: $O((N + (h_i - l_o)) \log N)$

```

struct DP { // Modify at will:
    int lo(int ind) { return 0; }
    int hi(int ind) { return ind; }
    ll f(int ind, int k) { return dp[ind][k]; }
    void store(int ind, int k, ll v) { res[ind] = pii(k, v); }

    void rec(int L, int R, int LO, int HI) {
        if (L >= R) return;
        int mid = (L + R) >> 1;
        pair<ll, int> best(LLONG_MAX, LO);
        rep(k, max(LO, lo(mid)), min(HI, hi(mid))) best =
            min(best, make_pair(f(mid, k), k));
        store(mid, best.second, best.first);
        rec(L, mid, LO, best.second + 1);
        rec(mid + 1, R, best.second, HI);
    }
    void solve(int L, int R) { rec(L, R, INT_MIN, INT_MAX); }
};

```

Knuth's Opt :

When doing DP on intervals:

$a[i][j] = \min_{i < k < j} (a[i][k] + a[k][j]) + f(i, j)$, where the (minimal) optimal k increases with both i and j , one can solve intervals in increasing order of length, and search $k = p[i][j]$ for $a[i][j]$ only between $p[i][j-1]$ and $p[i+1][j]$. This is known as Knuth DP. Sufficient criteria for this are if $f(b, c) \leq f(a, d)$ and $f(a, c) + f(b, d) \leq f(a, d) + f(b, c)$ for all $a \leq b \leq c \leq d$.

Consider also: LineContainer (ch. Data structures), monotone queues, ternary search.

Time: $O(N^2)$

1.4.3. Mo's Algorithm on Tree

```

void MoAlgoOnTree() {
    Dfs(0, -1);
    vector<int> euler(tk);
    for (int i = 0; i < n; ++i) {
        euler[tin[i]] = i;
        euler[tout[i]] = i;
    }
    vector<int> l(q), r(q), qr(q), sp(q, -1);
    for (int i = 0; i < q; ++i) {
        if (tin[u[i]] > tin[v[i]]) swap(u[i], v[i]);
        int z = GetLCA(u[i], v[i]);
        sp[i] = z[i];
        if (z == u) l[i] = tin[u[i]], r[i] = tin[v[i]];
        else l[i] = tout[u[i]], r[i] = tin[v[i]];
        qr[i] = i;
    }
    sort(qr.begin(), qr.end(), [&](int i, int j) {
        if (l[i] / kB == l[j] / kB) return r[i] < r[j];
        return l[i] / kB < l[j] / kB;
    });
    vector<bool> used(n);
    // Add(v): add/remove v to/from the path based on used[v]
    for (int i = 0, tl = 0, tr = -1; i < q; ++i) {
        while (tl < l[qr[i]]) Add(euler[tl++]);
        while (tl > l[qr[i]]) Add(euler[tl--]);
        while (tr > r[qr[i]]) Add(euler[tr--]);
        while (tr < r[qr[i]]) Add(euler[tr++]);
        // add/remove LCA(u, v) if necessary
    }
}

```

2. Data Structures

2.1. GNU PBDS

```

#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/priority_queue.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;

// most std::map + order_of_key, find_by_order, split, join
template <typename T, typename U = null_type>
using ordered_map = tree<T, U, std::less<>, rb_tree_tag,
    tree_order_statistics_node_update>;
// useful tags: rb_tree_tag, splay_tree_tag

template <typename T> struct myhash {
    size_t operator()(T x) const; // splitmix, bswap(x*R), ...
};
// most of std::unordered_map, but faster (needs good hash)
template <typename T, typename U = null_type>
using hash_table = gp_hash_table<T, U, myhash<T>>;

// most std::priority_queue + modify, erase, split, join
using heap = priority_queue<int, std::less<>>;
// useful tags: pairing_heap_tag, binary_heap_tag,
// (rc_)?binomial_heap_tag, thin_heap_tag

```

```

using namespace __gnu_pbds;

template <class T>
using Tree = tree<T, null_type, less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;

void example() {
    Tree<int> t, t2;
    t.insert(8);
    auto it = t.insert(10).first;
    assert(it == t.lower_bound(9));
    assert(t.order_of_key(10) == 1);
    assert(t.order_of_key(11) == 2);
    assert(*t.find_by_order(0) == 8);
    t.join(t2); // assuming T < T2 or T > T2, merge t2 into t
}

```

2.2. Offline 2D Fenwick

```

1 // 0-index, half-open interval!
2 template <class T> struct Fenwick2DOffline {
3     int n;
4     vector<vector<T>> t;
5     vector<vector<int>> val;
6
7     Fenwick2DOffline() {}
8     Fenwick2DOffline(int _n)
9         : n(_n), t(n + 1), val(n + 1, {-1}) {}
10
11     void add_upd(int x, int y) {
12         for (x++, y++; x <= n; x += x & -x) val[x].push_back(y);
13     }
14     void build() {
15         for (int i = 1; i <= n; i++) {
16             auto &v = val[i];
17             sort(begin(v), end(v));
18             v.erase(unique(begin(v), end(v)), end(v));
19             t[i].resize(v.size() + 1);
20         }
21     }
22     static int idx(const vector<int> &v, int y) {
23         return int(upper_bound(begin(v), end(v), y) - begin(v) - 1);
24     }
25     void add(int x, int y, T d) {
26         x++, y++;
27         for (int i = x; i <= n; i += i & -i)
28             for (int j = idx(val[i], y); j < t[i].size();
29                  j += j & -j)
30                 t[i][j] += d;
31     }
32     T query(int x, int y) const {
33         T sum = 0;
34         for (int i = x; i; i &= i - 1)
35             for (int j = idx(val[i], y); j &= j - 1)
36                 sum += t[i][j];
37         return sum;
38     }
39     T query(int x1, int y1, int x2, int y2) const {
40         return query(x2, y2) - query(x1, y2) - query(x2, y1) +
41             query(x1, y1);
42     }
43 };

```

2.3. Persistent seg tree

```

1 struct Node {
2     ll val;
3     Node *l, *r;
4
5     Node(ll x) : val(x), l(nullptr), r(nullptr) {}
6     Node(Node *ll, Node *rr) {
7         l = ll, r = rr;
8         val = 0;
9         if (l) val += l->val;
10        if (r) val += r->val;
11    }
12    Node(Node *cp) : val(cp->val), l(cp->l), r(cp->r) {}
13 };
14
15 int n, cnt = 1;
16 ll a[200001];
17
18 Node *roots[200001];
19 Node *build(int l = 1, int r = n) {
20     if (l == r) return new Node(a[l]);
21     int mid = (l + r) / 2;
22     return new Node(build(l, mid), build(mid + 1, r));
23 }
24
25 Node *update(Node *node, int val, int pos, int l = 1,
26             int r = n) {
27     if (l == r) return new Node(val);
28     int mid = (l + r) / 2;
29     if (pos > mid)
30         return new Node(node->l,
31                         update(node->r, val, pos, mid + 1, r));
32     else
33         return new Node(update(node->l, val, pos, l, mid),
34                         node->r);
35 }
36
37 ll query(Node *node, int a, int b, int l = 1, int r = n) {
38     if (l > b || r < a) return 0;
39     if (l >= a && r <= b) return node->val;
40     int mid = (l + r) / 2;
41     return query(node->l, a, b, l, mid) +
42         query(node->r, a, b, mid + 1, r);
43 }

```

2.4. Line Container

```

1 struct Line {
2     mutable ll k, m, p;
3     bool operator<(const Line &o) const { return k < o.k; }
4     bool operator<(ll x) const { return p < x; }
5 };
6 // add: line y=kx+m, query: maximum y of given x
7 struct LineContainer : multiset<Line, less<>> {
8     // (for doubles, use inf = 1/.0, div(a,b) = a/b)
9     static const ll inf = LLONG_MAX;
10    ll div(ll a, ll b) { // floored division
11        return a / b - ((a ^ b) < 0 && a % b);
12    }
13    bool isect(iterator x, iterator y) {
14        if (y == end()) return x->p = inf, 0;
15        if (x->k == y->k) x->p = x->m > y->m ? inf : -inf;
16        else x->p = div(y->m - x->m, x->k - y->k);
17        return x->p >= y->p;
18    }
19    void add(ll k, ll m) {
20        auto z = insert({k, m, 0}), y = z++, x = y;
21        while (isect(y, z)) z = erase(z);
22        if (x != begin() && isect(--x, y))
23            isect(x, y = erase(y));
24        while ((y = x) != begin() && (--x)->p >= y->p)
25            isect(x, erase(y));
26    }
27    ll query(ll x) {
28        assert(!empty());
29        auto l = *lower_bound(x);
30        return l.k * x + l.m;
31    }
32 };

```

2.5. Li-Chao Tree

```

1 constexpr ll MAXN = 2e5, INF = 2e18;
2 struct Line {
3     ll m, b;
4     Line() : m(0), b(-INF) {}
5     Line(ll _m, ll _b) : m(_m), b(_b) {}
6     ll operator()(ll x) const { return m * x + b; }
7 };
8 struct LiChao {
9     Line a[MAXN * 4];
10    void insert(Line seg, int l, int r, int v = 1) {
11        if (l == r) {
12            if (seg(l) > a[v](l)) a[v] = seg;
13            return;
14        }
15        int mid = (l + r) >> 1;
16        if (a[v].m > seg.m) swap(a[v], seg);
17        if (a[v](mid) < seg(mid)) {
18            swap(a[v], seg);
19            insert(seg, l, mid, v << 1);
20        } else insert(seg, mid + 1, r, v << 1 | 1);
21    }
22    ll query(int x, int l, int r, int v = 1) {
23        if (l == r) return a[v](x);
24        int mid = (l + r) >> 1;
25        if (x <= mid)
26            return max(a[v](x), query(x, l, mid, v << 1));
27        else
28            return max(a[v](x), query(x, mid + 1, r, v << 1 | 1));
29    }
30 };

```

2.6. Wavelet Matrix

```

1 #pragma GCC target("popcnt,bmi2")
2 #include <immintrin.h>
3
4 // T is unsigned. You might want to compress values first
5 template <typename T> struct wavelet_matrix {
6     static_assert(is_unsigned_v<T>, "only unsigned T");
7     struct bit_vector {
8         static constexpr uint W = 64;
9         uint n, cnt0;
10        vector<ull> bits;
11        vector<uint> sum;
12        bit_vector(uint n_)
13            : n(n_), bits(n / W + 1), sum(n / W + 1) {}
14        void build() {
15            for (uint j = 0; j != n / W; ++j)
16                sum[j + 1] = sum[j] + _mm_popcnt_u64(bits[j]);
17            cnt0 = rank0(n);
18        }
19        void set_bit(uint i) { bits[i / W] |= 1ULL << i % W; }
20        bool operator[](uint i) const {
21            return !(bits[i / W] & 1ULL << i % W);
22        }
23        uint rank1(uint i) const {

```

```

    return sum[i / W] +
        _mm_popcnt_u64(_bzhi_u64(bits[i / W], i % W));
}
uint rank0(uint i) const { return i - rank1(i); }
};
uint n, lg;
vector<bit_vector> b;
wavelet_matrix(const vector<T> &a) : n(a.size()) {
    lg =
        __lg(max(*max_element(a.begin(), a.end()), T(1))) + 1;
    b.assign(lg, n);
    vector<T> cur = a, nxt(n);
    for (int h = lg; h--;) {
        for (uint i = 0; i < n; ++i)
            if (cur[i] & T(1) << h) b[h].set_bit(i);
        b[h].build();
        int il = 0, ir = b[h].cnt0;
        for (uint i = 0; i < n; ++i)
            nxt[(b[h][i] ? ir : il)++] = cur[i];
        swap(cur, nxt);
    }
}
T operator[](uint i) const {
    T res = 0;
    for (int h = lg; h--;)
        if (b[h][i])
            i += b[h].cnt0 - b[h].rank0(i), res |= T(1) << h;
        else i = b[h].rank0(i);
    return res;
}
// query k-th smallest (0-based) in a[l, r]
T kth(uint l, uint r, uint k) const {
    T res = 0;
    for (int h = lg; h--;) {
        uint tl = b[h].rank0(l), tr = b[h].rank0(r);
        if (k >= tr - tl) {
            k -= tr - tl;
            l += b[h].cnt0 - tl;
            r += b[h].cnt0 - tr;
            res |= T(1) << h;
        } else l = tl, r = tr;
    }
    return res;
}
// count of i in [l, r] with a[i] < u
uint count(uint l, uint r, T u) const {
    if (u >= T(1) << lg) return r - l;
    uint res = 0;
    for (int h = lg; h--;) {
        uint tl = b[h].rank0(l), tr = b[h].rank0(r);
        if (u & (T(1) << h)) {
            l += b[h].cnt0 - tl;
            r += b[h].cnt0 - tr;
            res += tr - tl;
        } else l = tl, r = tr;
    }
    return res;
}
};

```

2.7. Link-Cut Tree

```

1 #define l ch[0]
2 #define r ch[1]
3 template <class M> struct LCT {
4     using T = typename M::T;
5
6     struct node;
7     using ptr = node *;
8     struct node {
9         node(int i = -1) : id(i) {}
10        static inline node nil{};
11        ptr p = &nil, ch[2]{&nil, &nil};
12        T val = M::id(), path = M::id();
13        T heavy = M::id(), light = M::id();
14        bool rev = 0;
15        int id;
16
17        T sum() { return M::op(heavy, light); }
18
19        void pull() {
20            path = M::op(M::op(l->path, val), r->path);
21            heavy = M::op(M::op(l->sum(), val), r->sum());
22        }
23        void push() {
24            if (exchange(rev, 0)) l->reverse(), r->reverse();
25        }
26        void reverse() {
27            swap(l, r), path = M::flip(path), rev ^= 1;
28        }
29    };
30    static inline ptr nil = &node::nil;
31    bool dir(ptr t) { return t == t->p->r; }

```

```

33 bool is_root(ptr t) {
34     return t->p == nil || (t != t->p->l && t != t->p->r);
35 }
36 void attach(ptr p, bool d, ptr c) {
37     if (c) c->p = p;
38     p->ch[d] = c, p->pull();
39 }
40 void rot(ptr t) {
41     bool d = dir(t);
42     ptr p = t->p;
43     t->p = p->p;
44     if (!is_root(p)) attach(p->p, dir(p), t);
45     attach(p, d, t->ch[!d]);
46     attach(t, !d, p);
47 }
48 void splay(ptr t) {
49     for (t->push(); !is_root(t); rot(t)) {
50         ptr p = t->p;
51         if (p->p != nil) p->p->push();
52         p->push(), t->push();
53         if (!is_root(p)) rot(dir(t) == dir(p) ? p : t);
54     }
55 }
56 void expose(ptr t) {
57     ptr cur = t, prv = nil;
58     for (; cur != nil; cur = cur->p) {
59         splay(cur);
60         cur->light = M::op(cur->light, cur->r->sum());
61         cur->light = M::op(cur->light, M::inv(prv->sum()));
62         attach(cur, 1, exchange(prv, cur));
63     }
64     splay(t);
65 }
66 vector<ptr> vert;
67 LCT(int n = 0) {
68     for (int i = 0; i < n; i++) vert.push_back(new node(i));
69 }
70 void expose(int v) { expose(vert[v]); }
71 void evert(int v) { expose(v), vert[v]->reverse(); }
72 void link(int v, int p) {
73     evert(v), expose(p);
74     assert(vert[p]->p == nil);
75     attach(vert[p], 1, vert[v]);
76 }
77 void cut(int v) {
78     expose(v);
79     assert(vert[v]->l != nil);
80     attach(vert[v], 0, vert[v]->l->p = nil);
81 }
82 T get(int v) { return vert[v]->val; }
83 void set(int v, const T &x) {
84     expose(v), vert[v]->val = x, vert[v]->pull();
85 }
86 void add(int v, const T &x) {
87     expose(v), vert[v]->val = M::op(vert[v]->val, x),
88         vert[v]->pull();
89 }
90 int lca(int u, int v) {
91     if (u == v) return u;
92     expose(u), expose(v);
93     if (vert[u]->p == nil) return -1;
94     splay(vert[u]);
95     return vert[u]->p != nil ? vert[u]->p->id : u;
96 }
97 T path_fold(int u, int v) {
98     evert(u), expose(v);
99     return vert[v]->path;
100 }
101 T subtree_fold(int v, int p) {
102     evert(p), cut(v);
103     T ret = vert[v]->sum();
104     link(v, p);
105     return ret;
106 }
107 };
108 #undef l
109 #undef r

```

2.8. Dynamic MST

```

1 struct Edge {
2     int l, r, u, v, w;
3     bool operator<(const Edge &o) const { return w < o.w; }
4 };
5 struct DynamicMST {
6     int n, time = 0;
7     vector<array<int, 3>> init;
8     vector<Edge> edges;
9     vector<int> lab, lst;
10    vector<int64_t> res;
11    DSU dsu1, dsu2;

```



```

13 DynamicMST(vector<array<int, 3>> es, int n)
14 : n(n), init(es, lab(n), lst(es.size()), dsu1(n),
15   dsu2(n)) {}
17 void update(int i, int nw) {
18   time++;
19   auto &[u, v, w] = init[i];
20   edges.push_back({lst[i], time, u, v, w});
21   lst[i] = time, w = nw;
22 }
23 void solve(int l, int r, vector<Edge> es, int cnt,
24   int64_t weight) {
25   auto tmp = stable_partition(all(es), [=](auto &e) {
26     return !(e.r <= l || r <= e.l);
27   });
28   es.erase(tmp, es.end());
29   dsu1.reset(cnt), dsu2.reset(cnt);
31   for (auto &e : es)
32     if (l < e.l || e.r < r) dsu1.merge(e.u, e.v);
33   for (auto &e : es)
34     if (e.l <= l && r <= e.r && dsu1.merge(e.u, e.v))
35       weight += e.w, dsu2.merge(e.u, e.v);
37   if (r - l == 1) return void(res[l] = weight);
38   int id = 0;
39   for (int i = 0; i < cnt; i++)
40     if (i == dsu2.find(i)) lab[i] = id++;
41   dsu1.reset(cnt);
42   for (auto &e : es) {
43     e.u = lab[dsu2.find(e.u)], e.v = lab[dsu2.find(e.v)];
44     if (e.l <= l && r <= e.r && !dsu1.merge(e.u, e.v))
45       e.r = -1;
46   }
47   int m = (l + r) / 2;
48   solve(l, m, es, id, weight);
49   solve(m, r, es, id, weight);
51 }
52 auto run() { // original mst weight at res[0]
53   res.resize(++time);
54   for (int i = 0; i < init.size(); i++) {
55     auto &[u, v, w] = init[i];
56     edges.push_back({lst[i], time, u, v, w});
57   }
58   sort(begin(edges), end(edges));
59   solve(0, time, edges, n, 0);
60   return res;
61 };

```

3. Graph

3.1. Modeling

- Maximum/Minimum flow with lower bound / Circulation problem
 - Construct super source S and sink T .
 - For each edge (x, y, l, u) , connect $x \rightarrow y$ with capacity $u - l$.
 - For each vertex v , denote by $in(v)$ the difference between the sum of incoming lower bounds and the sum of outgoing lower bounds.
 - If $in(v) > 0$, connect $S \rightarrow v$ with capacity $in(v)$, otherwise, connect $v \rightarrow T$ with capacity $-in(v)$.
 - To maximize, connect $t \rightarrow s$ with capacity ∞ (skip this in circulation problem), and let f be the maximum flow from S to T . If $f \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, the maximum flow from s to t is the answer.
 - To minimize, let f be the maximum flow from S to T . Connect $t \rightarrow s$ with capacity ∞ and let the flow from S to T be f' . If $f + f' \neq \sum_{v \in V, in(v) > 0} in(v)$, there's no solution. Otherwise, f' is the answer.
 - The solution of each edge e is $l_e + f_e$, where f_e corresponds to the flow of edge e on the graph.
- Construct minimum vertex cover from maximum matching M on bipartite graph (X, Y)
 - Redirect every edge: $y \rightarrow x$ if $(x, y) \in M$, $x \rightarrow y$ otherwise.
 - DFS from unmatched vertices in X .
 - $x \in X$ is chosen iff x is unvisited.
 - $y \in Y$ is chosen iff y is visited.
- Minimum cost cyclic flow
 - Construct super source S and sink T .
 - For each edge (x, y, c) , connect $x \rightarrow y$ with $(cost, cap) = (c, 1)$ if $c > 0$, otherwise connect $y \rightarrow x$ with $(cost, cap) = (-c, 1)$.
 - For each edge with $c < 0$, sum these cost as K , then increase $d(y)$ by 1, decrease $d(x)$ by 1.
 - For each vertex v with $d(v) > 0$, connect $S \rightarrow v$ with $(cost, cap) = (0, d(v))$.
 - For each vertex v with $d(v) < 0$, connect $v \rightarrow T$ with $(cost, cap) = (0, -d(v))$.
 - Flow from S to T , the answer is the cost of the flow $C + K$.
- Maximum density induced subgraph
 - Binary search on answer, suppose we're checking answer T

- Construct a max flow model, let K be the sum of all weights
- Connect source $s \rightarrow v$, $v \in G$ with capacity K
- For each edge (u, v, w) in G , connect $u \rightarrow v$ and $v \rightarrow u$ with capacity w
- For $v \in G$, connect it with sink $v \rightarrow t$ with capacity $K + 2T - (\sum_{e \in E(v)} w(e)) - 2w(v)$
- T is a valid answer if the maximum flow $f < K|V|$
- Minimum weight edge cover
 - For each $v \in V$ create a copy v' , and connect $u' \rightarrow v'$ with weight $w(u, v)$.
 - Connect $v \rightarrow v'$ with weight $2\mu(v)$, where $\mu(v)$ is the cost of the cheapest edge incident to v .
 - Find the minimum weight perfect matching on G' .
- Project selection problem
 - If $p_v > 0$, create edge (s, v) with capacity p_v ; otherwise, create edge (v, t) with capacity $-p_v$.
 - Create edge (u, v) with capacity w with w being the cost of choosing u without choosing v .
 - The mincut is equivalent to the maximum profit of a subset of projects.
- 0/1 quadratic programming

$$\sum_x c_x x + \sum_y c_y \bar{y} + \sum_{xy} c_{xy} x \bar{y} + \sum_{xyx'y'} c_{xyx'y'} (x \bar{y} + x' \bar{y}')$$

can be minimized by the mincut of the following graph:

- Create edge (x, t) with capacity c_x and create edge (s, y) with capacity c_y .
- Create edge (x, y) with capacity c_{xy} .
- Create edge (x, y) and edge (x', y') with capacity $c_{xyx'y'}$.
- Hall's Marriage Theorem
 - A bipartite graph $G = (X, Y, E)$ has a perfect matching covering X iff for all $S \subseteq X$:

$$|N(S)| \geq |S|$$
 where $N(S) = \{y \in Y \mid \exists x \in S \wedge (x, y) \in E\}$
- Equivalent flow construction:
 - Add source s , connect $s \rightarrow x$ for each $x \in X$ with capacity 1.
 - Connect $y \rightarrow t$ for each $y \in Y$ with capacity 1.
 - For each $(x, y) \in E$, connect $x \rightarrow y$ with capacity 1.
 - Run max flow; perfect matching exists iff flow = $|X|$.
- Useful for checking existence of perfect assignment or matching constraints.
- König's Theorem (Bipartite Graphs)
 - In any bipartite graph $G = (X, Y, E)$:

$$\text{Maximum Matching Size} = \text{Minimum Vertex Cover Size}$$

- Construction of minimum vertex cover from maximum matching M :
 - Redirect every edge: $y \rightarrow x$ if $(x, y) \in M$, $x \rightarrow y$ otherwise.
 - DFS from unmatched vertices in X .
 - $x \in X$ is chosen iff x is unvisited.
 - $y \in Y$ is chosen iff y is visited.
- Minimum edge cover:

$$|E_{\min_cover}| = |V| - |M|$$

3.2. Low link

```

1 void dfs(int v, int p) {
2   low[v] = ord[v] = k++;
3   bool is_articulation = false, checked = false;
4   int cnt = 0;
5   for (int c : G[v]) {
6     if (c == p && !checked) {
7       checked = true;
8       continue;
9     }
10    if (ord[c] == -1) {
11      ++cnt;
12      dfs(c, v);
13      low[v] = min(low[v], low[c]);
14      if (p != -1 && ord[v] <= low[c])
15        is_articulation = true;
16      if (ord[v] < low[c]) bridge.push_back(minmax(v, c));
17    } else {
18      low[v] = min(low[v], ord[c]);
19    }
20  }
21  if (p == -1 && cnt > 1) is_articulation = true;
22  if (is_articulation) articulation.push_back(v);
23 }
24 void build() {
25   for (int i = 0; i < G.size(); ++i)
26     if (ord[i] == -1) dfs(i, -1);
27 }
28 bool is_bridge(int u, int v) const {
29   if (ord[u] > ord[v]) swap(u, v);
30   return ord[u] < low[v];
31 }

```

3.3. Block Cut Tree

```

1 // [0;n): original vertices
2 // [n;n+k): k BCCs
3 // (v,c): has edges from v to its biconnected component
4 template <typename G> auto block_cut(G &g) {
5     int n = g.size();
6     vector<int> low(n), ord(n), st;
7     vector<bool> used(n);
8     st.reserve(n);
9     int nxt = n;
10    int k = 0;
11    vector<pair<int, int>> edges;

12
13    auto dfs = [&](auto dfs, int v, int p) -> void {
14        st.push_back(v), used[v] = 1;
15        low[v] = ord[v] = k++;
16        int child = 0;
17        for (auto u : g[v]) {
18            if (u == p) continue;
19            if (!used[u]) {
20                ++child;
21                int s = st.size();
22                dfs(dfs, u, v);
23                low[v] = min(low[v], low[u]);
24                if ((p == -1 && child > 1) ||
25                    (p != -1 && low[u] >= ord[v])) {
26                    edges.emplace_back(nxt, v);
27                    while (st.size() > s) {
28                        edges.emplace_back(nxt, st.back());
29                        st.pop_back();
30                    }
31                    ++nxt;
32                } else {
33                    low[v] = min(low[v], ord[u]);
34                }
35            }
36        }
37    };
38    for (int v = 0; v < n; v++) {
39        if (used[v]) continue;
40        dfs(dfs, v, -1);
41        for (auto &x : st) edges.emplace_back(nxt, x);
42        ++nxt, st.clear();
43    }
44    vector<vector<int>> bct(nxt);
45    for (auto &[u, v] : edges)
46        bct[u].push_back(v), bct[v].push_back(u);
47    return bct;
48 }

```

3.4. Shortest paths

3.4.1. Dial's Algorithm

```

1 template <typename Graph>
2 auto dial(Graph &graph, int src, int lim) {
3     vector<vector<int>> qs(lim);
4     vector<int> dist(graph.size(), -1);

5     dist[src] = 0;
6     qs[0].push_back(src);
7     for (int d = 0, maxd = 0; d <= maxd; ++d) {
8         for (auto &q = qs[d % lim]; q.size(); ) {
9             int node = q.back();
10            q.pop_back();
11            if (dist[node] != d) continue;
12            for (auto [vec, cost] : graph[node]) {
13                if (dist[vec] != -1 && dist[vec] <= d + cost)
14                    continue;
15                dist[vec] = d + cost;
16                qs[(d + cost) % lim].push_back(vec);
17                maxd = max(maxd, d + cost);
18            }
19        }
20    }
21    return dist;
22 }

```

3.4.2. Johnson's Algorithm

1. Add edges $\forall v : (s, v, \text{weight} = 0)$ and $p(v) = \text{dist}(s \rightarrow v)$
2. New weight: $w'(u \rightarrow v) = w(u \rightarrow v) + p(u) - p(v)$
3. All-pairs shortest path with dijkstra
4. $\text{dist}(u \rightarrow v) = \text{dist}'(u \rightarrow v) - p(u) + p(v)$

3.5. Matching/Flows

3.5.1. Bipartite Matching

```

1 // g: L->R, directed
2 // returns L[i]'s mate
3 vector<int> bip_match(int n, int m,

```

```

4     vector<vector<int>> &g) {
5     vector<int> L(n, -1), R(m, -1), d(n);
6     queue<int> que;
7     auto dfs = [&](auto &dfs, int v) -> bool {
8         int nd = exchange(d[v], 0) + 1;
9         for (auto &u : g[v]) {
10            if (R[u] == -1 || (d[R[u]] == nd && dfs(dfs, R[u]))) {
11                L[v] = u, R[u] = v;
12                return 1;
13            }
14        }
15        return 0;
16    };
17    for (;;) {
18        d.assign(n, 0);
19        queue<int> dummy;
20        swap(que, dummy);
21        bool ch = 0;
22        for (int i = 0; i < n; i++)
23            if (L[i] == -1) que.push(i), d[i] = 1;

24        while (!que.empty()) {
25            int v = que.front();
26            que.pop();
27            for (auto &u : g[v]) {
28                if (R[u] == -1) ch = 1;
29                else if (!d[R[u]]) {
30                    d[R[u]] = d[v] + 1;
31                    que.push(R[u]);
32                }
33            }
34        }
35        if (!ch) break;
36        for (int i = 0; i < n; i++)
37            if (L[i] == -1) dfs(dfs, i);
38    }
39    return L;
40 }

```

3.5.2. General Matching

```

1 struct Graph {
2     vector<int> G[MAXN];
3     int pa[MAXN], match[MAXN], st[MAXN], S[MAXN], vis[MAXN];
4     int t, n;

5     void init(int _n) {
6         n = _n;
7         for (int i = 1; i <= n; i++) G[i].clear();
8     }

9     void add_edge(int u, int v) {
10        G[u].push_back(v);
11        G[v].push_back(u);
12    }

13    int lca(int u, int v) {
14        for (++t; swap(u, v); ) {
15            if (u == 0) continue;
16            if (vis[u] == t) return u;
17            vis[u] = t;
18            u = st[pa[match[u]]];
19        }
20    }

21    void flower(int u, int v, int l, queue<int> &q) {
22        while (st[u] != l) {
23            pa[u] = v;
24            if (S[v = match[u]] == 1) {
25                q.push(v);
26                S[v] = 0;
27            }
28            st[u] = st[v] = l;
29            u = pa[v];
30        }
31    }

32    bool bfs(int u) {
33        for (int i = 1; i <= n; i++) st[i] = i;
34        memset(S, -1, sizeof(S));
35        queue<int> q;
36        q.push(u);
37        S[u] = 0;
38        while (!q.empty()) {
39            u = q.front();
40            q.pop();
41            for (int i = 0; i < (int)G[u].size(); i++) {
42                int v = G[u][i];
43                if (S[v] == -1) {
44                    pa[v] = u;
45                    S[v] = 1;
46                    if (!match[v]) {
47                        for (int lst; u; v = lst, u = pa[v]) {
48                            lst = match[u];
49                            match[u] = v;
50                            match[v] = u;
51                        }

```

```

53         return 1;
54     }
55     q.push(match[v]);
56     S[match[v]] = 0;
57     } else if (!S[v] && st[v] != st[u]) {
58         int l = lca(st[v], st[u]);
59         flower(v, u, l, q);
60         flower(u, v, l, q);
61     }
62 }
63 }
64 return 0;
65 }
66 int solve() {
67     memset(pa, 0, sizeof(pa));
68     memset(match, 0, sizeof(match));
69     int ans = 0;
70     for (int i = 1; i <= n; i++)
71         if (!match[i] && bfs(i)) ans++;
72     return ans;
73 }
74 } graph;

```

3.5.3. Dinic's Algorithm

```

1 struct Dinic {
2     struct edge {
3         int to, cap, flow, rev;
4     };
5     static constexpr int MAXN = 1000, MAXF = 1e9;
6     vector<edge> v[MAXN];
7     int top[MAXN], deep[MAXN], side[MAXN], s, t;
8     void make_edge(int s, int t, int cap, int rcap = 0) {
9         v[s].push_back({t, cap, 0, (int)v[t].size()});
10        v[t].push_back({s, rcap, 0, (int)v[s].size() - 1});
11    }
12    int dfs(int a, int flow) {
13        if (a == t || !flow) return flow;
14        for (int &i = top[a]; i < v[a].size(); i++) {
15            edge &e = v[a][i];
16            if (deep[a] + 1 == deep[e.to] && e.cap - e.flow) {
17                int x = dfs(e.to, min(e.cap - e.flow, flow));
18                if (x) {
19                    e.flow += x, v[e.to][e.rev].flow -= x;
20                    return x;
21                }
22            }
23        }
24        deep[a] = -1;
25        return 0;
26    }
27    bool bfs() {
28        queue<int> q;
29        fill_n(deep, MAXN, 0);
30        q.push(s), deep[s] = 1;
31        int tmp;
32        while (!q.empty()) {
33            tmp = q.front(), q.pop();
34            for (edge e : v[tmp])
35                if (!deep[e.to] && e.cap != e.flow)
36                    deep[e.to] = deep[tmp] + 1, q.push(e.to);
37        }
38        return deep[t];
39    }
40    int max_flow(int _s, int _t) {
41        s = _s, t = _t;
42        int flow = 0, tflow;
43        while (bfs()) {
44            fill_n(top, MAXN, 0);
45            while ((tflow = dfs(s, MAXF))) flow += tflow;
46        }
47        return flow;
48    }
49    void reset() {
50        fill_n(side, MAXN, 0);
51        for (auto &i : v) i.clear();
52    }
53 };

```

3.5.4. Minimum Cost Flow

```

1 struct MCF {
2     struct edge {
3         ll to, from, cap, flow, cost, rev;
4     } *fromE[MAXN];
5     vector<edge> v[MAXN];
6     ll n, s, t, flows[MAXN], dis[MAXN], pi[MAXN], flowlim;
7     void make_edge(int s, int t, ll cap, ll cost) {
8         if (!cap) return;
9         v[s].pb(edge{t, s, cap, 0LL, cost, v[t].size()});
10        v[t].pb(edge{s, t, 0LL, 0LL, -cost, v[s].size() - 1});
11    }

```

```

13    bitset<MAXN> vis;
14    void dijkstra() {
15        vis.reset();
16        __gnu_pbds::priority_queue<pair<ll, int>> q;
17        vector<decltype(q)::point_iterator> its(n);
18        q.push({0LL, s});
19        while (!q.empty()) {
20            int now = q.top().second;
21            q.pop();
22            if (vis[now]) continue;
23            vis[now] = 1;
24            ll ndis = dis[now] + pi[now];
25            for (edge &e : v[now]) {
26                if (e.flow == e.cap || vis[e.to]) continue;
27                if (dis[e.to] > ndis + e.cost - pi[e.to]) {
28                    dis[e.to] = ndis + e.cost - pi[e.to];
29                    flows[e.to] = min(flows[now], e.cap - e.flow);
30                    fromE[e.to] = &e;
31                    if (its[e.to] == q.end())
32                        its[e.to] = q.push({-dis[e.to], e.to});
33                    else q.modify(its[e.to], {-dis[e.to], e.to});
34                }
35            }
36        }
37    }
38    bool AP(ll &flow) {
39        fill_n(dis, n, INF);
40        fromE[s] = 0;
41        dis[s] = 0;
42        flows[s] = flowlim - flow;
43        dijkstra();
44        if (dis[t] == INF) return false;
45        flow += flows[t];
46        for (edge *e = fromE[t]; e; e = fromE[e->from]) {
47            e->flow += flows[t];
48            v[e->to][e->rev].flow -= flows[t];
49        }
50        for (int i = 0; i < n; i++)
51            pi[i] = min(pi[i] + dis[i], INF);
52        return true;
53    }
54    pll solve(int _s, int _t, ll _flowlim = INF) {
55        s = _s, t = _t, flowlim = _flowlim;
56        pll re;
57        while (re.F != flowlim && AP(re.F)) {
58            for (int i = 0; i < n; i++)
59                for (edge &e : v[i])
60                    if (e.flow != 0) re.S += e.flow * e.cost;
61            re.S /= 2;
62            return re;
63        }
64    }
65    void init(int _n) {
66        n = _n;
67        fill_n(pi, n, 0);
68        for (int i = 0; i < n; i++) v[i].clear();
69    }
70    void setpi(int s) {
71        fill_n(pi, n, INF);
72        pi[s] = 0;
73        for (ll it = 0, flag = 1, tdis; flag && it < n; it++) {
74            flag = 0;
75            for (int i = 0; i < n; i++)
76                if (pi[i] != INF)
77                    for (edge &e : v[i])
78                        if (e.cap && (tdis = pi[i] + e.cost) < pi[e.to])
79                            pi[e.to] = tdis, flag = 1;
80        }
81    }
82 };

```

3.5.5. Gomory-Hu Tree

Requires: Dinic's Algorithm

```

1 int e[MAXN][MAXN];
2 int p[MAXN];
3 Dinic D; // original graph
4 void gomory_hu() {
5     fill(p, p + n, 0);
6     fill(e[0], e[n], INF);
7     for (int s = 1; s < n; s++) {
8         int t = p[s];
9         Dinic F = D;
10        int tmp = F.max_flow(s, t);
11        for (int i = 1; i < s; i++)
12            e[s][i] = e[i][s] = min(tmp, e[t][i]);
13        for (int i = s + 1; i <= n; i++)
14            if (p[i] == t && F.side[i]) p[i] = s;
15    }

```


3.5.6. Global Minimum Cut

```

1 // weights is an adjacency matrix, undirected
  pair<int, vi> getMinCut(vector<vi> &weights) {
2   int N = sz(weights);
3   vi used(N), cut, best_cut;
4   int best_weight = -1;
5
6   for (int phase = N - 1; phase >= 0; phase--) {
7     vi w = weights[0], added = used;
8     int prev, k = 0;
9     rep(i, 0, phase) {
10      prev = k;
11      k = -1;
12      rep(j, 1, N) if (!added[j] &&
13        (k == -1 || w[j] > w[k])) k = j;
14      if (i == phase - 1) {
15        rep(j, 0, N) weights[prev][j] += weights[k][j];
16        rep(j, 0, N) weights[j][prev] = weights[prev][j];
17        used[k] = true;
18        cut.push_back(k);
19        if (best_weight == -1 || w[k] < best_weight) {
20          best_cut = cut;
21          best_weight = w[k];
22        }
23      } else {
24        rep(j, 0, N) w[j] += weights[k][j];
25        added[k] = true;
26      }
27    }
28    return {best_weight, best_cut};
29  }
30 }

```

3.5.7. Bipartite Minimum Cover

Requires: Dinic's Algorithm

```

1 // maximum independent set = all vertices not covered
  // x : [0, n), y : [0, m]
2 struct Bipartite_vertex_cover {
3   Dinic D;
4   int n, m, s, t, x[maxn], y[maxn];
5   void make_edge(int x, int y) { D.make_edge(x, y + n, 1); }
6   int matching() {
7     int re = D.max_flow(s, t);
8     for (int i = 0; i < n; i++)
9       for (Dinic::edge &e : D.v[i])
10        if (e.to != s && e.flow == 1) {
11          x[i] = e.to - n, y[e.to - n] = i;
12          break;
13        }
14     return re;
15  }
16  // init() and matching() before use
17  void solve(vector<int> &vx, vector<int> &vy) {
18    bitset<maxn * 2 + 10> vis;
19    queue<int> q;
20    for (int i = 0; i < n; i++)
21      if (x[i] == -1) q.push(i), vis[i] = 1;
22    while (!q.empty()) {
23      int now = q.front();
24      q.pop();
25      if (now < n) {
26        for (Dinic::edge &e : D.v[now])
27          if (e.to != s && e.to - n != x[now] && !vis[e.to])
28            vis[e.to] = 1, q.push(e.to);
29      } else {
30        if (!vis[y[now - n]])
31          vis[y[now - n]] = 1, q.push(y[now - n]);
32      }
33    }
34    for (int i = 0; i < n; i++)
35      if (!vis[i]) vx.pb(i);
36    for (int i = 0; i < m; i++)
37      if (vis[i + n]) vy.pb(i);
38  }
39  void init(int _n, int _m) {
40    n = _n, m = _m, s = n + m, t = s + 1;
41    for (int i = 0; i < n; i++)
42      x[i] = -1, D.make_edge(s, i, 1);
43    for (int i = 0; i < m; i++)
44      y[i] = -1, D.make_edge(i + n, t, 1);
45  }
46 }

```

3.6. Strongly Connected Components

```

1 template <class G> auto find_scc(G &g) {
2   int n = g.size();
3   vector<int> val(n), z;
4   vector<char> added(n);
5   vector<basic_string<int>> scc;

```

```

6   int time = 0;
7   auto dfs = [&](auto f, int v) -> int {
8     int low = val[v] = time++;
9     z.push_back(v);
10    for (auto u : g[v])
11      if (!added[u]) low = min(low, val[u] ? f(f, u));
12    if (low == val[v]) {
13      scc.emplace_back();
14      int x;
15      do {
16        x = z.back(), z.pop_back(), added[x] = true;
17        scc.back().push_back(x);
18      } while (x != v);
19    }
20    return val[v] = low;
21  };
22  for (int i = 0; i < n; i++)
23    if (!added[i]) dfs(dfs, i);
24  reverse(begin(scc), end(scc));
25  return scc;
26 }
27 template <class G> auto condense(G &g) {
28   auto scc = find_scc(g);
29   int n = scc.size();
30   vector<int> rep(g.size());
31   for (int i = 0; i < n; i++)
32     for (auto v : scc[i]) rep[v] = i;
33   vector<basic_string<int>> gd(n);
34   for (int v = 0; v < g.size(); v++)
35     for (auto u : g[v])
36       if (rep[v] != rep[u]) gd[rep[v]].push_back(rep[u]);
37   for (auto &v : gd) {
38     sort(begin(v), end(v));
39     v.erase(unique(begin(v), end(v)), end(v));
40   }
41   return make_tuple(move(scc), move(rep), move(gd));
42 }

```

3.6.1. 2-Satisfiability

```

1 struct TwoSAT {
2   int n;
3   vector<basic_string<int>> g;
4
5   TwoSAT(int _n) : n(_n), g(2 * n) {}
6
7   void add_if(int x, int y) { // x => y
8     g[x] += y, g[neg(y)] += neg(x);
9   }
10  void add_or(int x, int y) { add_if(neg(x), y); }
11  void add_nand(int x, int y) { add_if(x, neg(y)); }
12  void set_true(int x) { add_if(x, neg(x)); }
13  void set_false(int x) { add_if(neg(x), x); }
14
15  vector<bool> run() {
16    vector<bool> res(n);
17    auto [scc, id, gd] = condense(g);
18    for (int i = 0; i < n; i++) {
19      if (id[i] == id[neg(i)]) return {};
20      res[i] = id[i] > id[neg(i)];
21    }
22    return res;
23  }
24
25  int neg(int x) { return x < n ? x + n : x - n; }
26 };

```

3.7. Manhattan Distance MST

```

1 // returns [(dist, from, to), ...]
  // then do normal mst afterwards
2 typedef Point<int> P;
3 vector<array<int, 3>> manhattanMST(vector<P> ps) {
4   vi id(sz(ps));
5   iota(all(id), 0);
6   vector<array<int, 3>> edges;
7   rep(k, 0, 4) {
8     sort(all(id), [&](int i, int j) {
9       return (ps[i] - ps[j]).x < (ps[j] - ps[i]).y;
10     });
11     map<int, int> sweep;
12     for (int i : id) {
13       for (auto it = sweep.lower_bound(-ps[i].y);
14         it != sweep.end(); sweep.erase(it++)) {
15         int j = it->second;
16         P d = ps[i] - ps[j];
17         if (d.y > d.x) break;
18         edges.push_back({d.y + d.x, i, j});
19       }
20       sweep[-ps[i].y] = i;
21     }
22   }
23   for (P &p : ps)

```

```

    if (k & 1) p.x = -p.x;
    else swap(p.x, p.y);
}
return edges;
}

```

3.8. Counting C3/C4

```

1 long long C3(int n, const vector<pair<int, int>> &e) {
    vector<vector<int>> g(n), h(n);
    vector<int> d(n);
    for (auto [u, v] : e)
        g[u].push_back(v), g[v].push_back(u), d[u]++, d[v]++;
    for (auto [u, v] : e) {
        if (d[u] > d[v] || (d[u] == d[v] && u > v)) swap(u, v);
        h[u].push_back(v);
    }
    long long ans = 0;
    vector<int> vis(n);
    for (int u = 0; u < n; u++) {
        for (int v : h[u]) vis[v] = 1;
        for (int v : h[u])
            for (int w : h[v])
                if (vis[w]) ans++;
        for (int v : h[u]) vis[v] = 0;
    }
    return ans;
}

21 long long C4(int n, const vector<pair<int, int>> &e) {
    vector<vector<int>> g(n);
    for (auto [u, v] : e)
        g[u].push_back(v), g[v].push_back(u);
    vector<int> c(n);
    long long ans = 0;
    for (int u = 0; u < n; u++) {
        for (int v : g[u])
            if (v > u)
                for (int w : g[v])
                    if (w > u && w != u) c[w]++;
        for (int v : g[u])
            if (v > u)
                for (int w : g[v])
                    if (w > u && w != u)
                        ans += 1LL * c[w] * (c[w] - 1) / 2, c[w] = 0;
    }
    return ans;
}

```

3.9. Functional graph

3.9.1. Loops

```

1 struct Loop {
    int dist, lp_v, len;
};
template <class G> auto loops(G &f) {
    int n = f.size();
    vector<int> vis(n, n), dep(n);
    vector<Loop> res(n);
    int time = 0;
    auto dfs = [&](auto self, int v) -> int {
        vis[v] = time;
        int u = f[v];
        if (vis[u] == vis[v]) {
            int len = dep[v] - dep[u] + 1;
            res[v] = {0, v, len};
            return len - 1;
        } else if (vis[u] < vis[v]) {
            res[v] = res[u], res[v].dist++;
            return 0;
        } else {
            dep[u] = dep[v] + 1;
            int c = self(self, u);
            if (c > 0) {
                res[v] = res[u], res[v].lp_v = v;
                return c - 1;
            } else {
                res[v] = res[u], res[v].dist++;
                return 0;
            }
        }
    };
    for (int i = 0; i < n; i++, time++)
        if (vis[i] == n) dfs(dfs, i);
    return res;
}

```

4. Math

4.1. Number Theory

4.1.1. Theorems

- Euler's Totient Function $\phi(n)$

- $\phi(p) = p-1$ if p is prime.
- $\phi(p^a) = p^a - p^{a-1} = p^{a-1}(p-1)$
- If $\gcd(a, b) = 1$, $\phi(ab) = \phi(a)\phi(b)$
- $\sum_{d|n} \phi(d) = n$
- $a^{\phi(n)} \equiv 1 \pmod{n}$
- Möbius Function $\mu(n)$
 - If $\gcd(a, b) = 1$, $\mu(ab) = \mu(a)\mu(b)$
 - If $f(n) = \sum_{d|n} g(d)$ then $g(n) = \sum_{d|n} \mu(d)f(n/d)$
- Count coprime pairs
 - $\sum_{i=1}^n \sum_{j=1}^n [\gcd(i, j) = 1] = \sum_{i=1}^n \mu(d) \lfloor \frac{n}{d} \rfloor^2$

4.1.2. Euler's Totient Function

```

1 long long totient(long long n) {
    long long ret = n;
    if (n % 2 == 0) {
        ret -= ret / 2;
        while (n % 2 == 0) n /= 2;
    }
    for (long long i = 3; i * i <= n; i += 2) {
        if (n % i == 0) {
            ret -= ret / i;
            while (n % i == 0) n /= i;
        }
    }
    if (n != 1) ret -= ret / n;
    return ret;
}

17 vector<int> totient_table(int n) {
    vector<int> ret(n + 1);
    iota(ret.begin(), ret.end(), 0);
    for (int i = 2; i <= n; ++i) {
        if (ret[i] == i)
            for (int j = i; j <= n; j += i)
                ret[j] = ret[j] / i * (i - 1);
    }
    return ret;
}

```

4.1.3. Möbius Function

```

1 int mobius(long long n) {
    long long ret = 1;
    if (n % 4 == 0) return 0;
    if (n % 2 == 0) ret *= -1, n /= 2;
    for (long long i = 3; i * i <= n; i += 2) {
        if (n % (i * i) == 0) return 0;
        if (n % i == 0) ret *= -1, n /= i;
    }
    if (n != 1) ret *= -1;
    return ret;
}

11 vector<int> mobius_table(int n) {
    vector<bool> prime(n + 1, true);
    vector<int> ret(n + 1, 1);
    for (int i = 2; i <= n; ++i) {
        if (!prime[i]) continue;
        for (int j = i; j <= n; j += i) {
            if (j > i) prime[j] = false;
            if ((j / i) % i == 0) ret[j] = 0;
            else ret[j] *= -1;
        }
    }
    return ret;
}

```

4.1.4. Mod Struct

A list of safe primes: 26003, 27767, 28319, 28979, 29243, 29759, 30467, 910927547, 919012223, 947326223, 990669467, 1007939579, 1019126699, 929760389146037459, 975500632317046523, 989312547895528379

NTT prime p	$p-1$	primitive root
65537	$1 \ll 16$	3
998244353	$119 \ll 23$	3
2748779069441	$5 \ll 39$	3
1945555039024054273	$27 \ll 56$	5

```

1 array<int, 2> extgcd(int a, int b);

3 template <typename T> struct M {
    static T MOD; // change to constexpr if already known
    T v;
    M(T x = 0) {
        v = (-MOD <= x && x < MOD) ? x : x % MOD;
        if (v < 0) v += MOD;
    }
    explicit operator T() const { return v; }
    bool operator==(const M &b) const { return v == b.v; }
    bool operator!=(const M &b) const { return v != b.v; }
}

```

```

13 M operator-() { return M(-v); }
M operator+(M b) { return M(v + b.v); }
15 M operator-(M b) { return M(v - b.v); }
M operator*(M b) { return M((__int128)v * b.v % MOD); }
17 M operator/(M b) { return *this * b.inv(); }
// change above implementation to this if MOD is not prime
19 M inv() {
    auto [x, g] = extgcd(v, MOD);
    return assert(g == 1), x < 0 ? x + MOD : x;
21 }
23 friend M operator^(M a, ll b) {
    M ans(1);
    for (; b >= 1, a *= a)
        if (b & 1) ans *= a;
    return ans;
25 }
27 friend M operator+=(M &a, M b) { return a = a + b; }
friend M operator-=(M &a, M b) { return a = a - b; }
31 friend M operator*=(M &a, M b) { return a = a * b; }
friend M operator/=(M &a, M b) { return a = a / b; }
33 };
using Mod = M<int>;
35 template <> int Mod::MOD = 1'000'000'007;
int &MOD = Mod::MOD;

```

4.1.5. Miller-Rabin

Requires: Mod Struct

```

1 // checks if Mod::MOD is prime
bool is_prime() {
3     if (MOD < 2 || MOD % 2 == 0) return MOD == 2;
    Mod A[] = {2, 7, 61}; // for int values (< 2^31)
5     // ll: 2, 325, 9375, 28178, 450775, 9780504, 1795265022
    int s = __builtin_ctzll(MOD - 1), i;
7     for (Mod a : A) {
        Mod x = a ^ (MOD >> s);
9         for (i = 0; i < s && (x + 1).v > 2; i++) x *= x;
        if (i && x != -1) return 0;
11     }
    return 1;
13 }

```

4.1.6. Pollard's Rho

```

1 ll f(ll x, ll mod) { return (x * x + 1) % mod; }
// n should be composite
ll pollard_rho(ll n) {
3     if (!(n & 1)) return 2;
    while (1) {
5         ll y = 2, x = RNG() % (n - 1) + 1, res = 1;
        for (int sz = 2; res == 1; sz *= 2) {
7             for (int i = 0; i < sz && res <= 1; i++) {
                x = f(x, n);
                res = __gcd(abs(x - y), n);
9             }
            y = x;
11         }
        if (res != 0 && res != n) return res;
13     }
15 }

```

4.2. Iterate `floor(n/i)`

```

1 auto floors(ll n) {
    ll x = 1, ed;
3     vector<pair<ll, ll>> res;
    for (; x <= n; x = ed) {
5         ll val = n / x;
        ed = n / val + 1, res.emplace_back(val, ed - x);
7     }
    return res;
9 }

```

4.3. Combinatorics

4.3.1. Formulas

Derangements: $!n = (n-1)!(n-1) + (n-2)!$

4.3.2. Stirling

```

1 template <class T> auto stirling1(int n) {
    vector<T> dp(n + 1, vector<T>{});
3     for (int i = 0; i <= n; ++i) {
        dp[i].resize(i + 1);
        dp[i][0] = 0, dp[i][i] = 1;
5         for (int j = 1; j < i; ++j)
            dp[i][j] = dp[i - 1][j - 1] + (i - 1) * dp[i - 1][j];
7     }
    return dp;
9 }
11 template <class T> auto stirling2(int n) {

```

```

    vector<T> dp(n + 1, vector<T>{});
    for (int i = 0; i <= n; ++i) {
13         dp[i].resize(i + 1);
        dp[i][0] = 0, dp[i][i] = 1;
15         for (int j = 1; j < i; ++j)
            dp[i][j] = dp[i - 1][j - 1] + j * dp[i - 1][j];
17     }
    return dp;
19 }
21 template <class T> auto bell(int n) {
    vector<T> dp(n + 1, 0);
23     auto S = stirling2<T>(n);
    for (int i = 0; i <= n; ++i)
25         for (int k = 0; k <= i; ++k) dp[i] += S[i][k];
    return dp;
27 }

```

4.3.3. Extended Lucas

```

1 ll crt(vector<ll> &x, vector<ll> &mod) {
    int n = x.size();
3     ll M = 1;
    for (ll m : mod) M *= m;
5     ll res = 0;
    for (int i = 0; i < n; i++) {
7         ll out = M / mod[i];
        res += x[i] * inv(out, mod[i]) * out;
9     }
    return res;
11 }
ll f(ll n, ll k, ll p, ll q) {
13     auto fac = [](ll n, ll p, ll q) {
        ll x = 1, y = powi(p, q);
15         for (int i = 2; i <= n; i++)
            if (i % p != 0) x = x * i % y;
17         return x % y;
    };
19     ll r = n - k, x = powi(p, q);
    ll e0 = 0, eq = 0;
21     ll mul = (p == 2 && q >= 3) ? 1 : -1;
    ll cr = r, cm = k, car = 0, cnt = 0;
23     while (cr || cm || car) {
        ll rr = cr % p, rm = cm % p;
25         cnt++, car += rr + rm;
        if (car >= p) {
            e0++;
            if (cnt >= q) eq++;
27         }
        car /= p, cr /= p, cm /= p;
31     }
    mul = powi(p, e0) * powi(mul, eq);
33     ll ret = (mul % x + x) % x;
    ll tmp = 1;
35     for (; tmp != p) {
        ret = ret * fac(n / tmp % x, p, q) % x;
37         ret = ret * inv(fac(n / tmp % x, p, q), x) % x;
        ret = ret * inv(fac(n / tmp % x, p, q), x) % x;
39         if (tmp > n / p && tmp > k / p && tmp > r / p) break;
    }
41     return (ret % x + x) % x;
43 }
int comb(ll n, ll k, int m) {
    int _m = m; // can use better factorization
45     vector<ll> x, mod;
    for (int p = 2; p * p <= _m; p += 1 + (p & 1)) {
47         if (_m % p == 0) {
            int q = 0;
49             for (; _m % p == 0; _m /= p) q++;
            x.push_back(f(n, k, p, q));
            mod.push_back(powi(p, q));
51         }
    }
53     if (_m > 1)
        x.push_back(f(n, k, _m, 1)), mod.push_back(_m);
55     return crt(x, mod) % m;
57 }

```

4.4. Theorems

4.4.1. Kirchhoff's Theorem

Denote L be a $n \times n$ matrix as the Laplacian matrix of graph G , where $L_{ii} = d(i)$, $L_{ij} = -c$ where c is the number of edge (i, j) in G .

- The number of undirected spanning in G is $|\det(\tilde{L}_{11})|$.
- The number of directed spanning tree rooted at r in G is $|\det(\tilde{L}_{rr})|$.

4.4.2. Tutte's Matrix

Let D be a $n \times n$ matrix, where $d_{ij} = x_{ij}$ (x_{ij} is chosen uniformly at random) if $i < j$ and $(i, j) \in E$, otherwise $d_{ij} = -d_{ji}$. $\frac{\text{rank}(D)}{2}$ is the maximum matching on G .

4.4.3. Cayley's Formula

- Given a degree sequence d_1, d_2, \dots, d_n for each *labeled* vertices, there are

$$\frac{(n-2)!}{(d_1-1)!(d_2-1)!\cdots(d_n-1)!}$$

spanning trees.

- Let $T_{n,k}$ be the number of *labeled* forests on n vertices with k components, such that vertex $1, 2, \dots, k$ belong to different components. Then $T_{n,k} = kn^{n-k-1}$.

4.4.4. Erdős–Gallai Theorem

A sequence of non-negative integers $d_1 \geq d_2 \geq \dots \geq d_n$ can be represented as the degree sequence of a finite simple graph on n vertices if and only if $d_1 + d_2 + \dots + d_n$ is even and

$$\sum_{i=1}^k d_i \leq k(k-1) + \sum_{i=k+1}^n \min(d_i, k)$$

holds for all $1 \leq k \leq n$.

4.4.5. Burnside's Lemma

Let X be a set and G be a group that acts on X . For $g \in G$, denote by X^g the elements fixed by g :

$$X^g = \{x \in X \mid gx \in X\}$$

Then

$$|X/G| = \frac{1}{|G|} \sum_{g \in G} |X^g|.$$

5. Numeric

5.1. Fast Fourier Transform

```
1 template <typename T>
2 void fft(vector<T> &a, vector<T> &rt, bool inv) {
3     vector<int> br(n);
4     for (int i = 1; i < n; i++) {
5         br[i] = (i & 1) ? br[i - 1] + n / 2 : br[i / 2] / 2;
6         if (br[i] > i) swap(a[i], a[br[i]]);
7     }
8     for (int len = 2; len <= n; len *= 2)
9         for (int i = 0; i < n; i += len)
10            for (int j = 0; j < len / 2; j++) {
11                int pos = n / len * (inv ? len - j : j);
12                T u = a[i + j], v = a[i + j + len / 2] * rt[pos];
13                a[i + j] = u + v, a[i + j + len / 2] = u - v;
14            }
15     if (T minv = T(1) / T(n); inv)
16         for (T &x : a) x *= minv;
17 }
```

Requires: Mod Struct

```
1 void ntt(vector<Mod> &a, bool inv, Mod primitive_root) {
2     int n = a.size();
3     Mod root = primitive_root ^ (MOD - 1) / n;
4     vector<Mod> rt(n + 1, 1);
5     for (int i = 0; i < n; i++) rt[i + 1] = rt[i] * root;
6     fft(n, a, rt, inv);
7 }
8 void fft(vector<complex<double>> &a, bool inv) {
9     int n = a.size();
10    vector<complex<double>> rt(n + 1);
11    double arg = acos(-1) * 2 / n;
12    for (int i = 0; i <= n; i++)
13        rt[i] = {cos(arg * i), sin(arg * i)};
14    fft(n, a, rt, inv);
15 }
```

5.2. Fast Walsh-Hadamard Transform

Requires: Mod Struct

```
1 void fwht(vector<Mod> &a, bool inv) {
2     int n = a.size();
3     for (int d = 1; d < n; d <= 1)
4         for (int m = 0; m < n; m++)
5             if (!(m & d)) {
6                 inv ? a[m] -= a[m | d] : a[m] += a[m | d]; // AND
7                 inv ? a[m | d] -= a[m] : a[m | d] += a[m]; // OR
8                 Mod x = a[m], y = a[m | d]; // XOR
9                 a[m] = x + y, a[m | d] = x - y; // XOR
10            }
11     if (Mod iv = Mod(1) / n; inv) // XOR
12         for (Mod &i : a) i *= iv; // XOR
13 }
```

5.3. Subset Convolution

Requires: Mod Struct

```
1 #pragma GCC target("popcnt")
2 #include <immintrin.h>
3
4 void fwht(int n, vector<vector<Mod>> &a, bool inv) {
5     for (int h = 0; h < n; h++)
6         for (int i = 0; i < (1 << n); i++)
7             if (!(i & (1 << h)))
8                 for (int k = 0; k <= n; k++)
9                     inv ? a[i | (1 << h)][k] -= a[i][k]
10                        : a[i | (1 << h)][k] += a[i][k];
11 }
12 // c[k] = sum(popcnt(i & j) == sz && i | j == k) a[i] * b[j]
13 vector<Mod> subset_convolution(int n, int sz,
14                               const vector<Mod> &a_,
15                               const vector<Mod> &b_) {
16     int len = n + sz + 1, N = 1 << n;
17     vector<vector<Mod>> a(1 << n, vector<Mod>(len, 0)), b = a;
18     for (int i = 0; i < N; i++)
19         a[i][_mm_popcnt_u64(i)] = a_[i],
20         b[i][_mm_popcnt_u64(i)] = b_[i];
21     fwht(n, a, 0), fwht(n, b, 0);
22     for (int i = 0; i < N; i++) {
23         vector<Mod> tmp(len);
24         for (int j = 0; j < len; j++)
25             for (int k = 0; k <= j; k++)
26                 tmp[j] += a[i][k] * b[i][j - k];
27         a[i] = tmp;
28     }
29     fwht(n, a, 1);
30     vector<Mod> c(N);
31     for (int i = 0; i < N; i++)
32         c[i] = a[i][_mm_popcnt_u64(i) + sz];
33     return c;
34 }
```

5.4. Linear Recurrences

5.4.1. Berlekamp-Massey Algorithm

```
1 template <typename T>
2 vector<T> berlekamp_massey(const vector<T> &s) {
3     int n = s.size(), l = 0, m = 1;
4     vector<T> r(n), p(n);
5     r[0] = p[0] = 1;
6     T b = 1, d = 0;
7     for (int i = 0; i < n; i++, m++, d = 0) {
8         for (int j = 0; j <= l; j++) d += r[j] * s[i - j];
9         if ((d /= b) == 0) continue; // change if T is float
10        auto t = r;
11        for (int j = m; j < n; j++) r[j] -= d * p[j - m];
12        if (l * 2 <= i) l = i + 1 - l, b = d, m = 0, p = t;
13    }
14    return r.resize(l + 1), reverse(r.begin(), r.end()), r;
15 }
```

5.4.2. Linear Recurrence Calculation

```
1 template <typename T> struct lin_rec {
2     using poly = vector<T>;
3     poly mul(poly a, poly b, poly m) {
4         int n = m.size();
5         poly r(n);
6         for (int i = n - 1; i >= 0; i--) {
7             r.insert(r.begin(), 0), r.pop_back();
8             T c = r[n - 1] + a[n - 1] * b[i];
9             // c /= m[n - 1]; if m is not monic
10            for (int j = 0; j < n; j++)
11                r[j] += a[j] * b[i] - c * m[j];
12        }
13        return r;
14    }
15    poly pow(poly p, ll k, poly m) {
16        poly r(m.size());
17        r[0] = 1;
18        for (; k >= 1; p = mul(p, p, m))
19            if (k & 1) r = mul(r, p, m);
20        return r;
21    }
22    T calc(poly t, poly r, ll k) {
23        int n = r.size();
24        poly p(n);
25        p[1] = 1;
26        poly q = pow(p, k, r);
27        T ans = 0;
28        for (int i = 0; i < n; i++) ans += t[i] * q[i];
29        return ans;
30    }
31 }
```

5.5. Matrices

5.5.1. Determinant

Requires: Mod Struct

```
1 Mod det(vector<vector<Mod>> a) {
2     int n = a.size();
3     Mod ans = 1;
4     for (int i = 0; i < n; i++) {
5         int b = i;
6         for (int j = i + 1; j < n; j++)
7             if (a[j][i] != 0) {
8                 b = j;
9                 break;
10            }
11        if (i != b) swap(a[i], a[b]), ans = -ans;
12        ans *= a[i][i];
13        if (ans == 0) return 0;
14        for (int j = i + 1; j < n; j++) {
15            Mod v = a[j][i] / a[i][i];
16            if (v != 0)
17                for (int k = i + 1; k < n; k++)
18                    a[j][k] -= v * a[i][k];
19        }
20    }
21    return ans;
22 }
```

```
1 double det(vector<vector<double>> a) {
2     int n = a.size();
3     double ans = 1;
4     for (int i = 0; i < n; i++) {
5         int b = i;
6         for (int j = i + 1; j < n; j++)
7             if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
8         if (i != b) swap(a[i], a[b]), ans = -ans;
9         ans *= a[i][i];
10        if (ans == 0) return 0;
11        for (int j = i + 1; j < n; j++) {
12            double v = a[j][i] / a[i][i];
13            if (v != 0)
14                for (int k = i + 1; k < n; k++)
15                    a[j][k] -= v * a[i][k];
16        }
17    }
18    return ans;
19 }
```

5.5.2. Solve Linear Equation

```
1 typedef vector<double> vd;
2 const double eps = 1e-12;
3
4 // solves for x: A * x = b
5 int solveLinear(vector<vd> &A, vd &b, vd &x) {
6     int n = sz(A), m = sz(x), rank = 0, br, bc;
7     if (n) assert(sz(A[0]) == m);
8     vi col(m);
9     iota(all(col), 0);
10
11    rep(i, 0, n) {
12        double v, bv = 0;
13        rep(r, i, n) rep(c, i, m) if ((v = fabs(A[r][c])) > bv)
14            br = r, bc = c, bv = v;
15        if (bv <= eps) {
16            rep(j, i, n) if (fabs(b[j]) > eps) return -1;
17            break;
18        }
19        swap(A[i], A[br]);
20        swap(b[i], b[br]);
21        swap(col[i], col[bc]);
22        rep(j, 0, n) swap(A[j][i], A[j][bc]);
23        bv = 1 / A[i][i];
24        rep(j, i + 1, n) {
25            double fac = A[j][i] * bv;
26            b[j] -= fac * b[i];
27            rep(k, i + 1, m) A[j][k] -= fac * A[i][k];
28        }
29        rank++;
30    }
31
32    x.assign(m, 0);
33    for (int i = rank; i--;) {
34        b[i] /= A[i][i];
35        x[col[i]] = b[i];
36        rep(j, 0, i) b[j] -= A[j][i] * b[i];
37    }
38    return rank; // (multiple solutions if rank < m)
39 }
```

5.5.3. Freivalds' algo

Checks if $A \times B = C$ in $O(kn^2)$ with failure rate $\approx 2^{-k}$

Generate random $n \times 1$ 0/1 vector \vec{r} and check: $A \times (B\vec{r}) = C\vec{r}$

5.6. Polynomial Interpolation

```
1 // returns a, such that a[0]x^0 + a[1]x^1 + a[2]x^2 + ...
2 // passes through the given points
3 typedef vector<double> vd;
4 vd interpolate(vd x, vd y, int n) {
5     vd res(n), temp(n);
6     rep(k, 0, n - 1) rep(i, k + 1, n) y[i] =
7         (y[i] - y[k]) / (x[i] - x[k]);
8     double last = 0;
9     temp[0] = 1;
10    rep(k, 0, n) rep(i, 0, n) {
11        res[i] += y[k] * temp[i];
12        swap(last, temp[i]);
13        temp[i] -= last * x[k];
14    }
15    return res;
16 }
```

6. Geometry

6.1. Point

```
1 template <typename T> struct P {
2     T x, y;
3     P(T x = 0, T y = 0) : x(x), y(y) {}
4     bool operator<(const P &p) const {
5         return tie(x, y) < tie(p.x, p.y);
6     }
7     bool operator==(const P &p) const {
8         return tie(x, y) == tie(p.x, p.y);
9     }
10    P operator-() const { return {-x, -y}; }
11    P operator+(P p) const { return {x + p.x, y + p.y}; }
12    P operator-(P p) const { return {x - p.x, y - p.y}; }
13    P operator*(T d) const { return {x * d, y * d}; }
14    P operator/(T d) const { return {x / d, y / d}; }
15    T dist2() const { return x * x + y * y; }
16    double len() const { return sqrt(dist2()); }
17    P unit() const { return *this / len(); }
18    friend T dot(P a, P b) { return a.x * b.x + a.y * b.y; }
19    friend T cross(P a, P b) { return a.x * b.y - a.y * b.x; }
20    friend T cross(P a, P b, P o) {
21        return cross(a - o, b - o);
22    }
23 };
24 using pt = P<ll>;
```

6.1.1. Spherical Coordinates

```
1 struct car_p {
2     double x, y, z;
3 };
4 struct sph_p {
5     double r, theta, phi;
6 };
7
8 sph_p conv(car_p p) {
9     double r = sqrt(p.x * p.x + p.y * p.y + p.z * p.z);
10    double theta = asin(p.y / r);
11    double phi = atan2(p.y, p.x);
12    return {r, theta, phi};
13 }
14 car_p conv(sph_p p) {
15     double x = p.r * cos(p.theta) * sin(p.phi);
16     double y = p.r * cos(p.theta) * cos(p.phi);
17     double z = p.r * sin(p.theta);
18     return {x, y, z};
19 }
```

6.2. Segments

```
1 // for non-collinear ABCD, if segments AB and CD intersect
2 bool intersects(pt a, pt b, pt c, pt d) {
3     if (cross(b, c, a) * cross(b, d, a) > 0) return false;
4     if (cross(d, a, c) * cross(d, b, c) > 0) return false;
5     return true;
6 }
7 // the intersection point of lines AB and CD
8 pt intersect(pt a, pt b, pt c, pt d) {
9     auto x = cross(b, c, a), y = cross(b, d, a);
10    if (x == y) {
11        // if(fabs(x, y) < 1e-8) {
12        //     is parallel
13        // } else {
14        return d * (x / (x - y)) - c * (y / (x - y));
15    }
16 }
```


6.3. Pick's theorem

i : number of integer points inside the polygon
 b : number of integer points on the boundary

$$\text{Area} = i + \frac{b}{2} - 1$$

6.4. Convex Hull

```
1 // returns a convex hull in counterclockwise order
2 // for a non-strict one, change cross >= to >
3 vector<pt> convex_hull(vector<pt> p) {
4     sort(ALL(p));
5     if (p[0] == p.back()) return {p[0]};
6     int n = p.size(), t = 0;
7     vector<pt> h(n + 1);
8     for (int i = 2, s = 0; --i; s = --t, reverse(ALL(p)))
9         for (pt i : p) {
10             while (t > s + 1 && cross(i, h[t - 1], h[t - 2]) >= 0)
11                 t--;
12             h[t++] = i;
13         }
14     return h.resize(t), h;
15 }
```

6.5. Angular Sort

```
1 auto angle_cmp = [](const pt &a, const pt &b) {
2     auto btm = [](const pt &a) {
3         return a.y < 0 || (a.y == 0 && a.x < 0);
4     };
5     return make_tuple(btm(a), a.y * b.x, abs2(a)) <
6         make_tuple(btm(b), a.x * b.y, abs2(b));
7 };
8 void angular_sort(vector<pt> &p) {
9     sort(p.begin(), p.end(), angle_cmp);
10 }
```

6.6. Convex Polygon Minkowski Sum

```
1 // O(n) convex polygon minkowski sum
2 // must be sorted and counterclockwise
3 vector<pt> minkowski_sum(vector<pt> p, vector<pt> q) {
4     auto diff = [](vector<pt> &c) {
5         auto rcmp = [](pt a, pt b) {
6             return pt{a.y, a.x} < pt{b.y, b.x};
7         };
8         rotate(c.begin(), min_element(ALL(c), rcmp), c.end());
9         c.push_back(c[0]);
10        vector<pt> ret;
11        for (int i = 1; i < c.size(); i++)
12            ret.push_back(c[i] - c[i - 1]);
13        return ret;
14    };
15    auto dp = diff(p), dq = diff(q);
16    pt cur = p[0] + q[0];
17    vector<pt> d(dp.size() + dq.size(), ret = {cur};
18    // include angle_cmp from angular-sort.cpp
19    merge(ALL(dp), ALL(dq), d.begin(), angle_cmp);
20    // optional: make ret strictly convex (UB if degenerate)
21    int now = 0;
22    for (int i = 1; i < d.size(); i++) {
23        if (cross(d[i], d[now]) == 0) d[now] = d[now] + d[i];
24        else d[++now] = d[i];
25    }
26    d.resize(now + 1);
27    // end optional part
28    for (pt v : d) ret.push_back(cur = cur + v);
29    return ret.pop_back(), ret;
30 }
```

6.7. Point In Polygon

```
1 bool on_segment(pt a, pt b, pt p) {
2     return cross(a, b, p) == 0 && dot((p - a), (p - b)) <= 0;
3 }
4 // p can be any polygon, but this is O(n)
5 bool inside(const vector<pt> &p, pt a) {
6     int cnt = 0, n = p.size();
7     for (int i = 0; i < n; i++) {
8         pt l = p[i], r = p[(i + 1) % n];
9         // change to return 0; for strict version
10        if (on_segment(l, r, a)) return 1;
11        cnt ^= ((a.y < l.y) - (a.y < r.y)) * cross(l, r, a) > 0;
12    }
13    return cnt;
14 }
```

6.7.1. Convex Version

```
1 // no preprocessing version
2 // p must be a strict convex hull, counterclockwise
3 // if point is inside or on border
4 bool is_inside(const vector<pt> &c, pt p) {
5     int n = c.size(), l = 1, r = n - 1;
6     if (cross(c[0], c[1], p) < 0) return false;
7     if (cross(c[n - 1], c[0], p) < 0) return false;
8     while (l < r - 1) {
9         int m = (l + r) / 2;
10        T a = cross(c[0], c[m], p);
11        if (a > 0) l = m;
12        else if (a < 0) r = m;
13        else return dot(c[0] - p, c[m] - p) <= 0;
14    }
15    if (l == r) return dot(c[0] - p, c[l] - p) <= 0;
16    else return cross(c[l], c[r], p) >= 0;
17 }
18 // with preprocessing version
19 vector<pt> vecs;
20 pt center;
21 // p must be a strict convex hull, counterclockwise
22 // BEWARE OF OVERFLOWS!!
23 void preprocess(vector<pt> &p) {
24     for (auto &v : p) v = v * 3;
25     center = p[0] + p[1] + p[2];
26     center.x /= 3, center.y /= 3;
27     for (auto &v : p) v = v - center;
28     vecs = (angular_sort(p), p);
29 }
30 bool intersect_strict(pt a, pt b, pt c, pt d) {
31     if (cross(b, c, a) * cross(b, d, a) > 0) return false;
32     if (cross(d, a, c) * cross(d, b, c) >= 0) return false;
33     return true;
34 }
35 // if point is inside or on border
36 bool query(pt p) {
37     p = p * 3 - center;
38     auto pr = upper_bound(ALL(vecs), p, angle_cmp);
39     if (pr == vecs.end()) pr = vecs.begin();
40     auto pl = (pr == vecs.begin()) ? vecs.back() : *(pr - 1);
41     return !intersect_strict({0, 0}, p, pl, *pr);
42 }
43 }
```

6.7.2. Offline Multiple Points Version

Requires: GNU PBDS, Point

```
1 using Double = __float128;
2 using Point = pt<Double, Double>;
3
4 int n, m;
5 vector<Point> poly;
6 vector<Point> query;
7 vector<int> ans;
8
9 struct Segment {
10     Point a, b;
11     int id;
12 };
13 vector<Segment> segs;
14
15 Double Xnow;
16 inline Double get_y(const Segment &u, Double xnow = Xnow) {
17     const Point &a = u.a;
18     const Point &b = u.b;
19     return (a.y * (b.x - xnow) + b.y * (xnow - a.x)) /
20         (b.x - a.x);
21 }
22 bool operator<(Segment u, Segment v) {
23     Double yu = get_y(u);
24     Double yv = get_y(v);
25     if (yu != yv) return yu < yv;
26     return u.id < v.id;
27 }
28 ordered_map<Segment> st;
29
30 struct Event {
31     int type; // +1 insert seg, -1 remove seg, 0 query
32     Double x, y;
33     int id;
34 };
35 bool operator<(Event a, Event b) {
36     if (a.x != b.x) return a.x < b.x;
37     if (a.type != b.type) return a.type < b.type;
38     return a.y < b.y;
39 }
40 vector<Event> events;
41
42 void solve() {
43     set<Double> xs;
44     set<Point> ps;
45 }
```

```

45 for (int i = 0; i < n; i++) {
46     xs.insert(poly[i].x);
47     ps.insert(poly[i]);
48 }
49 for (int i = 0; i < n; i++) {
50     Segment s{poly[i], poly[(i + 1) % n], i};
51     if (s.a.x > s.b.x ||
52         (s.a.x == s.b.x && s.a.y > s.b.y)) {
53         swap(s.a, s.b);
54     }
55     segs.push_back(s);
56
57     if (s.a.x != s.b.x) {
58         events.push_back({+1, s.a.x + 0.2, s.a.y, i});
59         events.push_back({-1, s.b.x - 0.2, s.b.y, i});
60     }
61 }
62 for (int i = 0; i < m; i++) {
63     events.push_back({0, query[i].x, query[i].y, i});
64 }
65 sort(events.begin(), events.end());
66 int cnt = 0;
67 for (Event e : events) {
68     int i = e.id;
69     Xnow = e.x;
70     if (e.type == 0) {
71         Double x = e.x;
72         Double y = e.y;
73         Segment tmp = {{x - 1, y}, {x + 1, y}, -1};
74         auto it = st.lower_bound(tmp);
75
76         if (ps.count(query[i]) > 0) {
77             ans[i] = 0;
78         } else if (xs.count(x) > 0) {
79             ans[i] = -2;
80         } else if (it != st.end() &&
81             get_y(*it) == get_y(tmp)) {
82             ans[i] = 0;
83         } else if (it != st.begin() &&
84             get_y(*prev(it)) == get_y(tmp)) {
85             ans[i] = 0;
86         } else {
87             int rk = st.order_of_key(tmp);
88             if (rk % 2 == 1) {
89                 ans[i] = 1;
90             } else {
91                 ans[i] = -1;
92             }
93         }
94     } else if (e.type == 1) {
95         st.insert(segs[i]);
96         assert((int)st.size() == ++cnt);
97     } else if (e.type == -1) {
98         st.erase(segs[i]);
99         assert((int)st.size() == --cnt);
100     }
101 }

```

6.8. Closest Pair

```

1 vector<pll> p; // sort by x first!
2 bool cmpy(const pll &a, const pll &b) const {
3     return a.y < b.y;
4 }
5 ll sq(ll x) { return x * x; }
6 // returns (minimum dist)^2 in [l, r]
7 ll solve(int l, int r) {
8     if (r - l <= 1) return 1e18;
9     int m = (l + r) / 2;
10    ll mid = p[m].x, d = min(solve(l, m), solve(m, r));
11    auto pb = p.begin();
12    inplace_merge(pb + l, pb + m, pb + r, cmpy);
13    vector<pll> s;
14    for (int i = l; i < r; i++)
15        if (sq(p[i].x - mid) < d) s.push_back(p[i]);
16    for (int i = 0; i < s.size(); i++)
17        for (int j = i + 1;
18            j < s.size() && sq(s[j].y - s[i].y) < d; j++)
19            d = min(d, dis(s[i], s[j]));
20    return d;
21 }

```

7. Strings

7.1. Aho-Corasick

```

1 struct Aho {
2     static const int maxc = 26, maxn = 4e5;
3     struct NODES {
4         int Next[maxc], fail, ans;

```

```

5     };
6     NODES T[maxn];
7     int top, qtop, q[maxn];
8     int get_node(const int &fail) {
9         fill_n(T[top].Next, maxc, 0);
10        T[top].fail = fail;
11        T[top].ans = 0;
12        return top++;
13    }
14    int insert(const string &s) {
15        int ptr = 1;
16        for (char c : s) { // change char id
17            c -= 'a';
18            if (!T[ptr].Next[c]) T[ptr].Next[c] = get_node(ptr);
19            ptr = T[ptr].Next[c];
20        }
21        return ptr;
22    } // return ans_last_place
23    void build_fail(int ptr) {
24        int tmp;
25        for (int i = 0; i < maxc; i++)
26            if (T[ptr].Next[i]) {
27                tmp = T[ptr].fail;
28                while (tmp != 1 && !T[tmp].Next[i])
29                    tmp = T[tmp].fail;
30                if (T[tmp].Next[i] != T[ptr].Next[i])
31                    if (T[tmp].Next[i].fail == tmp)
32                        q[qtop++] = T[ptr].Next[i];
33            }
34    }
35    void AC_auto(const string &s) {
36        int ptr = 1;
37        for (char c : s) {
38            while (ptr != 1 && !T[ptr].Next[c]) ptr = T[ptr].fail;
39            if (T[ptr].Next[c]) {
40                ptr = T[ptr].Next[c];
41                T[ptr].ans++;
42            }
43        }
44    }
45    void Solve(string &s) {
46        for (char &c : s) // change char id
47            c -= 'a';
48        for (int i = 0; i < qtop; i++) build_fail(q[i]);
49        AC_auto(s);
50        for (int i = qtop - 1; i > -1; i--)
51            T[T[q[i]].fail].ans += T[q[i]].ans;
52    }
53    void reset() {
54        qtop = top = q[0] = 1;
55        get_node(1);
56    }
57 } AC;
58 // usage example
59 string s, S;
60 int n, t, ans_place[50000];
61 int main() {
62     Tie cin >> t;
63     while (t--) {
64         AC.reset();
65         cin >> S >> n;
66         for (int i = 0; i < n; i++) {
67             cin >> s;
68             ans_place[i] = AC.insert(s);
69         }
70         AC.Solve(S);
71         for (int i = 0; i < n; i++)
72             cout << AC.T[ans_place[i]].ans << '\n';
73     }
74 }

```

7.2. Knuth-Morris-Pratt Algorithm

```

1 vector<int> pi(const string &s) {
2     vector<int> p(s.size());
3     for (int i = 1; i < s.size(); i++) {
4         int g = p[i - 1];
5         while (g && s[i] != s[g]) g = p[g - 1];
6         p[i] = g + (s[i] == s[g]);
7     }
8     return p;
9 }
10 vector<int> match(const string &s, const string &pat) {
11     vector<int> p = pi(pat + '\0' + s), res;
12     for (int i = p.size() - s.size(); i < p.size(); i++)
13         if (p[i] == pat.size())
14             res.push_back(i - 2 * pat.size());
15     return res;
16 }

```

7.3. Suffix Array

```

1 // sa[i]: starting index of suffix at rank i

```

```

// 0-indexed, sa[0] = n (empty string)
// lcp[i]: lcp of sa[i] and sa[i - 1], lcp[0] = 0
struct SuffixArray {
    vector<int> sa, lcp;
    SuffixArray(string &s,
        int lim = 256) { // or basic_string<int>
        int n = sz(s) + 1, k = 0, a, b;
        vector<int> x(all(s) + 1), y(n), ws(max(n, lim)),
            rank(n);
        sa = lcp = y, iota(all(sa), 0);
        for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
            p = j, iota(all(y), n - j);
            for (int i = 0; i < n; i++)
                if (sa[i] >= j) y[p++] = sa[i] - j;
            fill(all(ws), 0);
            for (int i = 0; i < n; i++) ws[x[i]]++;
            for (int i = 1; i < lim; i++) ws[i] += ws[i - 1];
            for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
            swap(x, y), p = 1, x[sa[0]] = 0;
            for (int i = 1; i < n; i++)
                a = sa[i - 1], b = sa[i],
                x[b] = (y[a] == y[b] && y[a + j] == y[b + j])
                    ? p - 1 : p++;
        }
        for (int i = 1; i < n; i++) rank[sa[i]] = i;
        for (int i = 0, j; i < n - 1; lcp[rank[i++]] = k)
            for (k && k--, j = sa[rank[i] - 1];
                s[i + k] == s[j + k]; k++);
    }
};

```

7.4. Z Value

```

int z[n];
void zval(string s) {
    // z[i] => longest common prefix of s and s[i:], i > 0
    int n = s.size();
    z[0] = 0;
    for (int b = 0, i = 1; i < n; i++) {
        if (z[b] + b <= i) z[i] = 0;
        else z[i] = min(z[i - b], z[b] + b - i);
        while (s[i + z[i]] == s[z[i]]) z[i]++;
        if (i + z[i] > b + z[b]) b = i;
    }
}

```

7.5. Manacher's Algorithm

```

int z[n];
void manacher(string s) {
    // z[i] => longest odd palindrome centered at i is
    // s[i - z[i]] ... i + z[i]]
    // to get all palindromes (including even length),
    // insert a '#' between each s[i] and s[i + 1]
    int n = s.size();
    z[0] = 0;
    for (int b = 0, i = 1; i < n; i++) {
        if (z[b] + b >= i)
            z[i] = min(z[2 * b - i], b + z[b] - i);
        else z[i] = 0;
        while (i + z[i] + 1 < n && i - z[i] - 1 >= 0 &&
            s[i + z[i] + 1] == s[i - z[i] - 1])
            z[i]++;
        if (z[i] + i > z[b] + b) b = i;
    }
}

```

7.6. Minimum Rotation

```

int min_rotation(string s) {
    int a = 0, n = s.size();
    s += s;
    for (int b = 0; b < n; b++) {
        for (int k = 0; k < n; k++) {
            if (a + k == b || s[a + k] < s[b + k]) {
                b = max(0, k - 1);
                break;
            }
            if (s[a + k] > s[b + k]) {
                a = b;
                break;
            }
        }
    }
    return a;
}

```

7.7. Palindromic Tree

```

struct palindromic_tree {
    struct node {
        int next[26], fail, len;
        int cnt,
            num; // cnt: appear times, num: number of pal. suf.
        node(int l = 0) : fail(0), len(l), cnt(0), num(0) {
            for (int i = 0; i < 26; ++i) next[i] = 0;
        }
    };
    vector<node> St;
    vector<char> s;
    int last, n;
    palindromic_tree() : St(2), last(1), n(0) {
        St[0].fail = 1, St[1].len = -1, s.pb(-1);
    }
    inline void clear() {
        St.clear(), s.clear(), last = 1, n = 0;
        St.pb(0), St.pb(-1);
        St[0].fail = 1, s.pb(-1);
    }
    inline int get_fail(int x) {
        while (s[n - St[x].len - 1] != s[n]) x = St[x].fail;
        return x;
    }
    inline void add(int c) {
        s.push_back(c == 'a'), ++n;
        int cur = get_fail(last);
        if (!St[cur].next[c]) {
            int now = SZ(St);
            St.pb(St[cur].len + 2);
            St[now].fail = St[get_fail(St[cur].fail)].next[c];
            St[cur].next[c] = now;
            St[now].num = St[St[now].fail].num + 1;
        }
        last = St[cur].next[c], ++St[last].cnt;
    }
    inline void count() { // counting cnt
        auto i = St.rbegin();
        for (; i != St.rend(); ++i) {
            St[i->fail].cnt += i->cnt;
        }
    }
    inline int size() { // The number of diff. pal.
        return SZ(St) - 2;
    }
};

```

8. Debug List

- 1 - Pre-submit:
 - Did you make a typo when copying a template?
 - Test more cases if unsure.
 - Write a naive solution and check small cases.
 - Submit the correct file.
- 7 - General Debugging:
 - Read the whole problem again.
 - Have a teammate read the problem.
 - Have a teammate read your code.
 - Explain your solution to them (or a rubber duck).
 - Print the code and its output / debug output.
 - Go to the toilet.
- 15 - Wrong Answer:
 - Any possible overflows?
 - > `--int128`?
 - Try `-ftrapv` or `#pragma GCC optimize("trapv")`
 - Floating point errors?
 - > `"long double"`?
 - turn off math optimizations
 - check for `"=="`, `">="`, `"acos(1.000000001)"`, etc.
 - Did you forget to sort or unique?
 - Generate large and worst "corner" cases.
 - Check your `"m" / "n"`, `"i" / "j"` and `"x" / "y"`.
 - Are everything initialized or reset properly?
 - Are you sure about the STL thing you are using?
 - Read cppreference (should be available).
 - Print everything and run it on pen and paper.
- 31 - Time Limit Exceeded:
 - Calculate your time complexity again.
 - Does the program actually end?
 - Check for `"while(q.size())"` etc.
 - Test the largest cases locally.
 - Did you do unnecessary stuff?
 - e.g. pass vectors by value
 - e.g. `"memset"` for every test case
 - Is your constant factor reasonable?
- 41 - Runtime Error:

- Check memory usage.
- Forget to clear or destroy stuff?
- > ``vector::shrink_to_fit()``
- Stack overflow?
- Bad pointer / array access?
- Try ``-fsanitize=address``
- Division by zero? NaN's?

9. Tech

- Recursion
- Divide and conquer
 - Finding interesting points in $N \log N$
- Algorithm analysis
 - Master theorem
 - Amortized time complexity
- Greedy algorithm
 - Scheduling
 - Max contiguous subvector sum
 - Invariants
 - Huffman encoding
- Graph theory
 - Dynamic graphs (extra book-keeping)
 - Breadth first search
 - Depth first search
 - ****Normal trees / DFS trees****
 - Dijkstra's algorithm
 - MST: Prim's algorithm
 - Bellman-Ford
 - Konig's theorem and vertex cover
 - Min-cost max flow
 - Lovasz toggle
 - Matrix tree theorem
 - Maximal matching, general graphs
 - Hopcroft-Karp
 - Hall's marriage theorem
 - Graphical sequences
 - Floyd-Warshall
 - Euler cycles
 - Flow networks
 - ****Augmenting paths****
 - ****Edmonds-Karp****
 - Bipartite matching
 - Min. path cover
 - Topological sorting
 - Strongly connected components
 - 2-SAT
 - Cut vertices, cut-edges and biconnected components
 - Edge coloring
 - ****Trees****
 - Vertex coloring
 - ****Bipartite graphs (\Rightarrow trees)****
 - **** 3^n (special case of set cover)****
 - Diameter and centroid
 - K'th shortest path
 - Shortest cycle
- Dynamic programming
 - Knapsack
 - Coin change
 - Longest common subsequence
 - Longest increasing subsequence
 - Number of paths in a dag
 - Shortest path in a dag
 - Dynprog over intervals
 - Dynprog over subsets
 - Dynprog over probabilities
 - Dynprog over trees
 - 3^n set cover
 - Divide and conquer
 - Knuth optimization
 - Convex hull optimizations
 - RMQ (sparse table a.k.a 2^k -jumps)
 - Bitonic cycle
 - Log partitioning (loop over most restricted)
- Combinatorics
 - Computation of binomial coefficients
 - Pigeon-hole principle
 - Inclusion/exclusion
 - Catalan number
 - Pick's theorem
- Number theory
 - Integer parts
 - Divisibility
 - Euclidean algorithm
 - Modular arithmetic
 - ****Modular multiplication****
 - ****Modular inverses****
 - ****Modular exponentiation by squaring****
 - Chinese remainder theorem
 - Fermat's little theorem
 - Euler's theorem
 - Phi function
 - Frobenius number

- Quadratic reciprocity
- Pollard-Rho
- Miller-Rabin
- Hensel lifting
- Vieta root jumping
- Game theory
 - Combinatorial games
 - Game trees
 - Mini-max
 - Nim
 - Games on graphs
 - Games on graphs with loops
 - Grundy numbers
 - Bipartite games without repetition
 - General games without repetition
 - Alpha-beta pruning
- Probability theory
- Optimization
 - Binary search
 - Ternary search
 - Unimodality and convex functions
 - Binary search on derivative
- Numerical methods
 - Numeric integration
 - Newton's method
 - Root-finding with binary/ternary search
 - Golden section search
- Matrices
 - Gaussian elimination
 - Exponentiation by squaring
- Sorting
 - Radix sort
- Geometry
 - Coordinates and vectors
 - ****Cross product****
 - ****Scalar product****
 - Convex hull
 - Polygon cut
 - Closest pair
 - Coordinate-compression
 - Quadrees
 - KD-trees
 - All segment-segment intersection
- Sweeping
 - Discretization (convert to events and sweep)
 - Angle sweeping
 - Line sweeping
 - Discrete second derivatives
- Strings
 - Longest common substring
 - Palindrome subsequences
 - Knuth-Morris-Pratt
 - Tries
 - Rolling polynomial hashes
 - Suffix array
 - Suffix tree
 - Aho-Corasick
 - Manacher's algorithm
 - Letter position lists
- Combinatorial search
 - Meet in the middle
 - Brute-force with pruning
 - Best-first (A^*)
 - Bidirectional search
 - Iterative deepening DFS / A^*
- Data structures
 - LCA (2^k -jumps in trees in general)
 - Pull/push-technique on trees
 - Heavy-light decomposition
 - Centroid decomposition
 - Lazy propagation
 - Self-balancing trees
 - Convex hull trick (wcipeg.com/wiki/Convex_hull_trick)
 - Monotone queues / monotone stacks / sliding queues
 - Sliding queue using 2 stacks
 - Persistent segment tree