



THERMAL IMAGING CAMERA

MODEL : HD2BS



HD2BS is designed for temperature measurement to find invisible faults. It's equipped with a 256×192 resolution thermal detector. The thermography ranges from -20°C to 550°C (-4°F to 1022°F). Which meets most situation. It helps the staff to quickly find the fault according to accurate temperature measurement of high temperature targets in the environment. Meanwhile it provides assistant decision and ensure safety. The device is mainly applied to various industries, such as building, HVAC, and auto industry.



Key Features :

- Thermal resolution: 256×192 (49,152 pixels)
- NETD:< 40 mK (@ 25°C , F# = 1.0)
- Temperature measurement range : -20°C to 550°C (-4°F to 1022°F)
- Accuracy: Max. ($\pm 2^{\circ}\text{C}/3.6^{\circ}\text{F}, \pm 2\%$), for ambient temperature 15°C to 35°C (59°F to 95°F) and object temperature above 0°C (32°F)
- Measurement presets: Center spot, Hot spot, Cold spot, User Preset Point
- 25 Hz image frequency
- 3.2" LCD screen display
- Up to 8 hours continuous running

Solutions for measurement



HD[®]
ISO 9001:2015
Certified Company



Specification :

Thermal Module	
Image Sensor	Vanadium Oxide Uncooled Focal Plane Arrays
IR Resolution	256 × 192 (49,152 pixels)
Pixel Pitch	12 μm
Spectral Range	8 to 14 μm
NETD	< 40 mK (@ 25°C), F# = 1.0
Focal Length	3.6 mm
FOV (Field of View)	37.2° × 50.0°
Image Frequency	25 Hz
Focus	Fixed
IFOV (Spatial Resolution)	3.3 mrad
Aperture	F1.0
Minimum Focus Distance	0.3 m (0.98 ft)
Image Display	
Display	320 × 240 Resolution, 3.2" LCD Screen
Color Palettes	White Hot, Black Hot, Rainbow, Ironbow
Measurement and Analysis	
Object Temperature Range	-20°C to 550°C (-4°F to 1022°F)
Accuracy	Max. (± 2°C/3.6°F, ± 2%), for ambient temperature 15°C to 35°C (59°F to 95°F) and object temperature above 0°C (32°F)
Measurement Presets	Center Spot, Hot Spot, Cold Spot, Point Presets, Off
High Temperature Alarm	Audible and Visual Warning
Storage	
Storage Media	EMMC (4 GB)
Image Storage Capacity	30,000 Images
Image File Format	JPEG with Measurement Data Included
Functions	
LED Light	Yes
Wi-Fi	802.11 b/g/n (2.4GHz)
UVC Cast Screen	Yes
Level/Span	Auto/Manual
Power System	
Power Supply	3.7 VDC/0.4 A
Power Consumption	1.5 W
Battery Type	Rechargeable Li-ion Battery
Battery Operating Time	8 Hours Continuous Running
Battery Charging Time	3 Hours



HD[®]
ISO 9001:2015
Certified Company



General

	21 Languages
Menu Language	English, German, French, Spanish (Spain), Portuguese (Portugal), Italian, Czech, Slovak, Polish, Hungarian, Romanian, Dutch, Danish, Norwegian, Finnish, Swedish, Russian, Turkish, Japanese, Korean, Chinese (Traditional)
Working Temperature Range	-10°C to 50°C (14°F to 122°F)
Storage Temperature Range	-20°C to 60°C (-4°F to 140°F)
Protection Level	IP54
Drop Test Height	2 m (6.56 ft)
Interface	USB Type-C
Weight	Approx. 360 g (0.79 lb)
Dimension	221.7 mm × 73.5 mm × 80.6 mm (8.73" × 2.89" × 3.17")
Tripod Mounting	UNC 1/4"-20

Web : www.hdtnm.com

Solutions for measurement

HD ENGINEERING & SERVICES

Corporate Office : ASIDC Head Office Complex, Bamunimaidan, Near Guwahati College Bus Stop, Opp. Sani Mandir Guwahati-781021, Ph. : 0361-6774480, 9101177485, E-mail: info@hdtnm.com, hdengineering2019@gmail.com, Web : www.hdtnm.com

Manufacturing Unit: No. 55 A, Lichubagan, Nizarapur, Hengrabari, Kamrup (M), Guwahati-781036, Assam, Ph. : 0361-6774480, 9101177485, E-mail: info@hdtnm.com, hdengineering2019@gmail.com, Web : www.hdtnm.com