











2013 mm 786 mm 1115 mm

Wheel Base 1347 mm **Ground Clearance** 160 mm

Single Disc - 143 Kg, Double Disc - 144 Kg Kerb Weight

Seat Length 582 mm Seat Height 795 mm

Fuel Tank Capacity 12 L

**ENGINE** 

Width

4 Stroke, SI, BS-VI Engine

162.71 cc Displacement

10.2 kW @ 8000 rpm Max Engine Output Max Torque 14.7 N-m @ 5500 rpm

Fuel System PGM-FI

Bore x Stroke 57.300 x 63.096 mm

Compression Ratio 10.0:1 Self/Kick Starting Method

TRANSMISSION

Multiplate Wet Clutch Clutch Type

No. of Gears 5 Gears

80/100-17 M/C 46P (Tubeless) Tyre Size & Type (Front) 130/70-17 M/C 62P (Tubeless) Tyre Size & Type (Rear)

Disc - 276 mm (Single Channel ABS) Brake Type & Size (Rear) Drum - 130 mm, Disc - 220 mm

FRAME & SUSPENSION

Frame Type Diamond Type Front Suspension Telescopic

Hydraulic, Monoshock Rear Suspension

ELECTRICALS

Battery 12V, 4.0 Ah Headlamp LED





















Bharat Stage VI norms • Product shown in the picture may vary from actual product available in the market • Accessories shown in the picture are not part of standard equipment • All features may not be part of all variants • \*Figures as per internal testing • \*\*Conditions apply.



Honda Motorcycle and Scooter India Pvt. Ltd.

Registered Office: Commercial Complex II, Sector - 49-50, Golf Course Extension Road, Gurugram - 122018 (Haryana), India

Visit us at: www.honda2wheelersindia.com Customer Care: customercare@honda2wheelersindia.com

**Dealer Stamp** 

## **Kothari Honda**

Botha Road Buldhana Tel: 9422325159 Mob: 9422324157