CS 3251- Computer Networks 1: Reliable Data Transfer

Professor Patrick Traynor

Lecture 08

9/12/13

Announcements

- Project 1 is due today
  - Submit your tarball via T-Square.
  - Due by 5pm!
- Project 2 will be posted by Tuesday.
  - We will talk about the details in class on Tuesday.
  - Get started soon! This will require a significant amount of effort to get done.
- Homework 2 has been posted
  - Submission deadline pushed back to 10/1

Last Time

- Multiplexing/Demultiplexing at the Transport Layer.
  - How do TCP and UDP differ?
- UDP gives us virtually "bare-bones" access to the network layer.
  - What are the four fields in a UDP header?
- What is port scanning?
  - How can it be used to protect systems? To attack them?

Chapter 3 outline

- 3.1 Transport-layer services
- 3.2 Multiplexing and demultiplexing
- 3.3 Connectionless transport: UDP
- 3.4 Principles of reliable data transfer
- 3.5 Connection-oriented transport: TCP
  - segment structure
  - reliable data transfer
  - flow control
  - connection management
- 3.6 Principles of congestion control
- 3.7 TCP congestion control

Problem Solving

- Given all of our talk about TCP, you might assume that describing how it works is straightforward.

- The reality is that there are lots of different ways that we could have provided "reliable" delivery.
    - Here is where we will really start to see design tradeoffs.

- It's time in your CS career to be creative...
    - Let's solve some problems.

Principles of Reliable data transfer

- important in app., transport, link layers
- top-10 list of important networking topics!



- characteristics of unreliable channel will determine complexity of reliable data transfer protocol (rdt)

Reliable data transfer: getting started

rdt_send() : called from above, (e.g., by app.). Passed data to deliver to receiver upper layer

deliver_data() : called by rdt to deliver data to upper

send side



receive side

udt_send() : called by rdt, to transfer packet over unreliable channel to receiver

rdt_rcv() : called when packet arrives on rcv-side of channel

Reliable data transfer: getting started

We'll:

- incrementally develop sender, receiver sides of reliable data transfer protocol (rdt)
- consider only unidirectional data transfer
  - but control info will flow on both directions!
- use finite state machines (FSM) to specify sender, receiver

state: when in this "state" next state uniquely determined by next event



Rdt1.0: reliable transfer over a reliable channel

- underlying channel perfectly reliable
  - no bit errors
  - no loss of packets
- separate FSMs for sender, receiver:
  - sender sends data into underlying channel
  - receiver read data from underlying channel



sender



receiver

Rdt2.0: channel with bit errors

- underlying channel may flip bits in packet
  - checksum to detect bit errors
- *the* question: how to recover from errors:
  - acknowledgements (ACKs): receiver explicitly tells sender that pkt received OK
  - negative acknowledgements (NAKs): receiver explicitly tells sender that pkt had errors
  - sender retransmits pkt on receipt of NAK
- new mechanisms in **`rdt2.0`** (beyond **`rdt1.0`**):
  - error detection
  - receiver feedback: control msgs (ACK,NAK) rcvr->sender

rdt2.0: FSM specification



rdt2.0: operation with no errors



rdt2.0: error scenario



rdt2.0 has a fatal flaw!

What happens if ACK/NAK corrupted?

- sender doesn't know what happened at receiver!
- can't just retransmit: possible duplicate



Handling duplicates:

- sender retransmits current pkt if ACK/NAK garbled
- sender adds sequence number to each pkt
- receiver discards (doesn't deliver up) duplicate pkt

stop and wait

Sender sends one packet, then waits for receiver response

rdt2.1: sender, handles garbled ACK/NAKs



rdt2.1: receiver, handles garbled ACK/NAKs



rdt2.1: discussion

Sender:

- seq # added to pkt
- two seq. #'s (0,1) will suffice. Why?
- must check if received ACK/NAK corrupted
- twice as many states
  - state must "remember" whether "current" pkt has 0 or 1 seq. #

Receiver:

- must check if received packet is duplicate
  - state indicates whether 0 or 1 is expected pkt seq #
- note: receiver can not know if its last ACK/NAK received OK at sender

rdt2.2: a NAK-free protocol

- same functionality as rdt2.1, using ACKs only
- instead of NAK, receiver sends ACK for last pkt received OK
  - receiver must explicitly include seq # of pkt being ACKed
- duplicate ACK at sender results in same action as NAK: *retransmit current pkt*

rdt2.2: sender, receiver fragments



rdt3.0: channels with errors *and* loss

New assumption: underlying channel can also lose packets (data or ACKs)

- checksum, seq. #, ACKs, retransmissions will be of help, but not enough

Approach: sender waits "reasonable" amount of time for ACK

- retransmits if no ACK received in this time
- if pkt (or ACK) just delayed (not lost):
  - retransmission will be duplicate, but use of seq. #'s already handles this
  - receiver must specify seq # of pkt being ACKed
- requires countdown timer

rdt3.0 sender



rdt3.0 in action



(a) operation with no loss



(b) lost packet

rdt3.0 in action



(c) lost ACK

(d) premature timeout

Performance of rdt3.0

- rdt3.0 works, but performance stinks
- example: 1 Gbps link, 15 ms e-e prop. delay, 1KB packet:

$$T_{transmit} = \frac{L \text{ (packet length in bits)}}{R \text{ (transmission rate, bps)}} = \frac{8\text{kb/pkt}}{10^9 \text{ b/sec}} = 8 \text{ microsec}$$

- U_{sender}: utilization – fraction of time sender busy sending

$$U_{sender} = \frac{L / R}{RTT + L / R} = \frac{.008}{30.008} = 0.00027$$

- 1KB pkt every 30 msec -> 33kB/sec throughput over 1 Gbps link
- network protocol limits use of physical resources!

rdt3.0: stop-and-wait operation



$$U_{sender} = \frac{L / R}{RTT + L / R} = \frac{.008}{30.008} = 0.00027$$

Pipelined protocols

Pipelining: sender allows multiple, "in-flight", yet-to-be-acknowledged pkts

- range of sequence numbers must be increased
- buffering at sender and/or receiver



(a) a stop-and-wait protocol in operation (b) a pipelined protocol in operation

- Two generic forms of pipelined protocols:
  go-Back-N, selective repeat

Pipelining: increased utilization



Increase utilization by a factor of 3!

$$U_{sender} = \frac{3L / R}{RTT + L / R} = \frac{.0024}{30.008} = 0.00081$$

Pipelining Protocols

- Go-back-N: big picture:
  - Sender can have up to N un-ACKed packets in pipeline
  - Rcvr only sends cumulative acks
    - Doesn't ack packet if there's a gap
  - Sender has timer for oldest unacked packet
    - If timer expires, retransmit all unacked packets

Selective Repeat: Big Picture

- Sender can have up to N unacked packets in pipeline
- Rcvr acks individual packets
- Sender maintains timer for each unacked packet
  - When timer expires, retransmit only individual unacked packet.

Go-Back-N

Sender:

- k-bit seq # in pkt header
- "window" of up to N, consecutive unack'ed pkts allowed



- ACK(n): ACKs all pkts up to, including seq # n - "cumulative ACK"
  - may receive duplicate ACKs (see receiver)
- timer for each in-flight pkt
- timeout(n): retransmit pkt n and all higher seq # pkts in window

GBN: sender extended FSM



GBN: receiver extended FSM



ACK-only: always send ACK for correctly-received pkt with highest in-order seq #

- may generate duplicate ACKs
- need only remember **`expectedseqnum`**

- out-of-order pkt:
  - discard (don’t buffer) -> no receiver buffering!
  - Re-ACK pkt with highest in-order seq #

GBN in action



Selective Repeat

- receiver *individually* acknowledges all correctly received pkts
  - buffers pkts, as needed, for eventual in-order delivery to upper layer
- sender only resends pkts for which ACK not received
  - sender timer for each unACKed pkt
- sender window
  - N consecutive seq #'s
  - again limits seq #s of sent, unACKed pkts

Selective repeat: sender, receiver windows



(a) sender view of sequence numbers



(b) receiver view of sequence numbers

Selective repeat

sender

data from above :

- if next available seq # in window, send pkt

timeout(n):

- resend pkt n, restart timer

ACK(n) in [sendbase,sendbase+N]:

- mark pkt n as received
- if n smallest unACKed pkt, advance window base to next unACKed seq #

receiver

pkt n in [rcvbase, rcvbase+N-1]

- send ACK(n)
- out-of-order: buffer
- in-order: deliver (also deliver buffered, in-order pkts), advance window to next not-yet-received pkt

pkt n in [rcvbase-N,rcvbase-1]

- ACK(n)

otherwise:

- ignore

Selective repeat in action



Selective repeat: dilemma

Example:

- seq #'s: 0, 1, 2, 3
- window size=3
- receiver sees no difference in two scenarios!
- incorrectly passes duplicate data as new in (a)

Q: what relationship between seq # size and window size?



Next Time

- That was a lot of material...
  - Take time to look over the notes. Understand the differences between each of these schemes!
- Next Time
  - TCP and Congestion Control (Sections 3.5 and 3.6)
- Check the webpage for Homework 2 and (soon) Project 2!