

Party App Db Schema V1.0

1. Users Table (Core User Profile)

```
CREATE TABLE users (  
    user_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    email TEXT UNIQUE NOT NULL,  
    password_hash TEXT, -- For registered users  
    username TEXT UNIQUE,  
    is_guest BOOLEAN DEFAULT FALSE,  
    third_party_provider TEXT, -- e.g., 'google', 'apple'  
    third_party_id TEXT, -- OAuth ID  
    city TEXT,  
    age INT CHECK (age >= 0),  
    event_types TEXT[], -- e.g., ['Concert', 'Club Night']  
    budget TEXT, -- e.g., 'Low', 'Mid', 'High'  
    vibe TEXT, -- e.g., 'Chill', 'Wild'  
    genres TEXT[], -- e.g., ['EDM', 'Hip-Hop']  
    cultural_interests TEXT[], -- e.g., ['Art', 'Food', 'Dance']  
    bio TEXT,  
    social_links JSONB, -- { instagram: "", twitter: "" }  
    event_history UUID[], -- Array of attended event_ids  
    location GEOMETRY(Point, 4326), -- PostGIS point for current location  
    social_mode TEXT DEFAULT 'public', -- public, friends-only, private  
    profile_visibility TEXT DEFAULT 'public', -- public, private  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

2. Organizers Table (Event Creators)

```
CREATE TABLE organizers (  
    organizer_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    email TEXT UNIQUE NOT NULL,  
    password_hash TEXT,  
    name TEXT NOT NULL,  
    bio TEXT,  
    social_links JSONB,  
    event_history UUID[],  
    average_rating NUMERIC(2,1) DEFAULT 0.0 CHECK (average_rating >= 0 AND average_rating <= 5),  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

3. Admins Table (Platform Moderators)

```
CREATE TABLE admins (  
    admin_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    email TEXT UNIQUE NOT NULL,  
    password_hash TEXT,  
    name TEXT,  
    bio TEXT,  
    role TEXT NOT NULL, -- e.g., 'superadmin', 'moderator', 'support'  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

4. Venues Table (Physical Locations)

```
CREATE TABLE venues (  
    venue_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    name TEXT NOT NULL,  
    location GEOMETRY(Point, 4326), -- PostGIS point for venue  
    logo TEXT, -- URL or path  
    address TEXT,  
    capacity INT, -- Max attendees  
    parking_info TEXT,  
    transport_info TEXT,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

5. Events Table (Core Event Entity)

```
CREATE TABLE events (  
    event_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    organizer_id UUID REFERENCES organizers(organizer_id) ON DELETE CASCADE,  
    name TEXT NOT NULL,  
    description TEXT,  
    category TEXT, -- e.g., 'Music', 'Comedy', 'Festival'  
    vibe TEXT, -- e.g., 'Energetic', 'Relaxed'  
    genre TEXT, -- e.g., 'Techno', 'Stand-up'  
    status TEXT DEFAULT 'Draft' CHECK (status IN ('Draft', 'Published', 'Cancelled', 'Completed')),  
    date DATE NOT NULL,  
    start_time TIMESTAMPTZ,  
    end_time TIMESTAMPTZ,  
    venue_id UUID REFERENCES venues(venue_id) ON DELETE SET NULL,  
    cover_image TEXT, -- URL
```

```
region TEXT, -- e.g., 'Downtown', 'Westside'
watchlist_available BOOLEAN DEFAULT TRUE,
watching_count INT DEFAULT 0,
created_at TIMESTAMPTZ DEFAULT NOW(),
updated_at TIMESTAMPTZ DEFAULT NOW()
);
```

6. Event Categories (Many-to-Many Bridge)

```
CREATE TABLE event_categories (
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,
    category_id UUID REFERENCES categories(category_id) ON DELETE CASCADE,
    PRIMARY KEY (event_id, category_id)
);
```

7. Categories Table (Predefined Event Types)

```
CREATE TABLE categories (
    category_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),
    name TEXT UNIQUE NOT NULL,
    description TEXT,
    description_embedding VECTOR(768), -- Optional: for AI search
    created_at TIMESTAMPTZ DEFAULT NOW(),
    updated_at TIMESTAMPTZ DEFAULT NOW()
);
```

8. Performers Table (Artists/Bands/DJs)

```
CREATE TABLE performers (  
    performer_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    type TEXT NOT NULL, -- e.g., 'DJ', 'Band', 'Comedian'  
    name TEXT NOT NULL,  
    bio TEXT,  
    bio_embedding VECTOR(768), -- Optional: for AI search  
    is_group BOOLEAN DEFAULT FALSE,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

9. Event Performers (Many-to-Many Bridge)

```
CREATE TABLE event_performers (  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    performer_id UUID REFERENCES performers(performer_id) ON DELETE CASCADE,  
    is_collab BOOLEAN DEFAULT FALSE,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    PRIMARY KEY (event_id, performer_id)  
);
```

10. Vibe Tags Table (User-defined tags for events)

```
CREATE TABLE vibe_tags (  
    tag_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    name TEXT UNIQUE NOT NULL,  
    tag_embedding VECTOR(768), -- Optional: for AI search  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

11. Event Vibe Tags (Many-to-Many Bridge)

```
CREATE TABLE event_vibe_tags (  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    tag_id UUID REFERENCES vibe_tags(tag_id) ON DELETE CASCADE,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    PRIMARY KEY (event_id, tag_id)  
);
```

12. Ticket Tiers Table

```
CREATE TABLE ticket_tiers (  
    tier_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    type TEXT NOT NULL, -- e.g., 'General', 'VIP', 'Early Bird'  
    package_details TEXT,  
    price NUMERIC(10,2) NOT NULL,  
    currency TEXT DEFAULT 'USD',  
    total_quantity INT,  
    availability INT,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

13. Event Schedules Table (For multi-day or recurring events)

```
CREATE TABLE event_schedules (  
    schedule_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    start_date TIMESTAMPTZ NOT NULL,  
    end_date TIMESTAMPTZ,  
    recurrence TEXT, -- e.g., 'daily', 'weekly'  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

14. Event Policies Table (Rules for attendees)

```
CREATE TABLE event_policies (  
    policy_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    additional_policies TEXT,  
    age_restriction INT,  
    allow_pets BOOLEAN DEFAULT FALSE,  
    re_entry_allowed BOOLEAN DEFAULT FALSE,  
    refund_policy TEXT,  
    transferable_tickets BOOLEAN DEFAULT FALSE,  
    wheelchair_accessible BOOLEAN DEFAULT FALSE,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

15. Event Reservation Contacts Table

```
CREATE TABLE event_reservation_contacts (  
    contact_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    email TEXT,  
    phone TEXT,  
    website TEXT,  
    whatsapp TEXT,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

16. User Events (RSVPs / Attendances)

```
CREATE TABLE user_events (  
    user_id UUID REFERENCES users(user_id) ON DELETE CASCADE,  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    rsvp_status TEXT DEFAULT 'pending' CHECK (rsvp_status IN ('pending', 'accepted', 'declined',  
'attending')),  
    ticket_tier_id UUID REFERENCES ticket_tiers(tier_id) ON DELETE SET NULL,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW(),  
    PRIMARY KEY (user_id, event_id)  
);
```


17. Invites Table (User-to-User Event Invitations)

```
CREATE TABLE invites (  
    invite_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    sender_id UUID REFERENCES users(user_id) ON DELETE CASCADE,  
    recipient_id UUID REFERENCES users(user_id) ON DELETE CASCADE,  
    status TEXT DEFAULT 'pending' CHECK (status IN ('pending', 'accepted', 'declined')),  
    created_at TIMESTAMPTZ DEFAULT NOW()  
);
```

18. Reviews Table (User Feedback on Events/Organizers)

```
CREATE TABLE reviews (  
    review_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    user_id UUID REFERENCES users(user_id) ON DELETE CASCADE,  
    organizer_id UUID REFERENCES organizers(organizer_id) ON DELETE CASCADE,  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    rating NUMERIC(2,1) NOT NULL CHECK (rating >= 1 AND rating <= 5),  
    comment TEXT,  
    reply TEXT, -- Organizer's response  
    is_flagged BOOLEAN DEFAULT FALSE,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

19. Social Posts Table (User-generated content)

```
CREATE TABLE social_posts (  
    post_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    user_id UUID REFERENCES users(user_id) ON DELETE CASCADE,  
    media_url TEXT NOT NULL,  
    caption TEXT,  
    tags TEXT[], -- e.g., ['#SummerVibes', '#NYC']  
    location GEOMETRY(Point, 4326), -- Optional: where post was taken  
    visibility TEXT DEFAULT 'public' CHECK (visibility IN ('public', 'friends-only', 'private')),  
    is_moderated BOOLEAN DEFAULT FALSE,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

20. Post Interactions Table (Likes, Comments)

```
CREATE TABLE post_interactions (  
    interaction_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    post_id UUID REFERENCES social_posts(post_id) ON DELETE CASCADE,  
    user_id UUID REFERENCES users(user_id) ON DELETE CASCADE,  
    interaction_type TEXT NOT NULL CHECK (interaction_type IN ('like', 'comment')),  
    comment_text TEXT, -- NULL for likes  
    created_at TIMESTAMPTZ DEFAULT NOW()  
);
```

21. User Activities Table (Audit trail of user actions)

```
CREATE TABLE user_activities (  
    activity_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    user_id UUID REFERENCES users(user_id) ON DELETE CASCADE,  
    action_type TEXT NOT NULL, -- e.g., 'RSVP', 'Purchase', 'Check-In', 'Post', 'Like', 'Comment'  
    event_id UUID REFERENCES events(event_id) ON DELETE SET NULL,  
    post_id UUID REFERENCES social_posts(post_id) ON DELETE SET NULL,  
    location GEOMETRY(Point, 4326), -- Where action occurred  
    timestamp TIMESTAMPTZ DEFAULT NOW(),  
    ip_address TEXT,  
    user_agent TEXT  
);
```

22. Night Recap Media Table (User-generated event recaps)

```
CREATE TABLE night_recap_media (  
    media_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    user_id UUID REFERENCES users(user_id) ON DELETE CASCADE,  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    venue_id UUID REFERENCES venues(venue_id) ON DELETE SET NULL,  
    media_url TEXT NOT NULL,  
    timestamp TIMESTAMPTZ DEFAULT NOW(),  
    caption TEXT,  
    effects TEXT, -- e.g., 'Golden Filter', 'Neon Glow'  
    music_track TEXT, -- e.g., 'Song Title - Artist'  
    friends_tagged UUID[], -- List of tagged user_ids  
    theme TEXT, -- e.g., 'VIP Glam', 'Afterparty'  
    created_at TIMESTAMPTZ DEFAULT NOW()  
);
```

23. Night Recap Montages Table (Collections of recap media)

```
CREATE TABLE night_recap_montages (  
    montage_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    user_id UUID REFERENCES users(user_id) ON DELETE CASCADE,  
    media_ids UUID[], -- Array of media_id references  
    share_platforms TEXT[], -- e.g., ['Instagram', 'TikTok']  
    group_chat_ids UUID[], -- IDs of group chats where shared  
    is_collaborative BOOLEAN DEFAULT FALSE,  
    created_at TIMESTAMPTZ DEFAULT NOW()  
);
```

24. Live Metrics Table (Real-time event stats)

```
CREATE TABLE live_metrics (  
    metric_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    crowd_size INT,  
    music_type TEXT, -- e.g., 'EDM', 'Hip-Hop'  
    queue_time INT, -- in minutes  
    capacity INT, -- Venue capacity (denormalized for speed)  
    timestamp TIMESTAMPTZ DEFAULT NOW()  
);
```

25. Safety Alerts Table (Push notifications for users)

```
CREATE TABLE safety_alerts (  
  alert_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  user_id UUID REFERENCES users(user_id) ON DELETE CASCADE,  
  alert_type TEXT NOT NULL, -- e.g., 'queue_time', 'safety_tip', 'crowd_level'  
  alert_message TEXT NOT NULL,  
  created_at TIMESTAMPTZ DEFAULT NOW()  
);
```

26. Hosts Table (Alternative to Organizers?)

```
CREATE TABLE hosts (  
  host_id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  name TEXT NOT NULL,  
  type TEXT, -- e.g., 'Individual', 'Group', 'Brand'  
  description TEXT,  
  description_embedding VECTOR(768),  
  created_at TIMESTAMPTZ DEFAULT NOW(),  
  updated_at TIMESTAMPTZ DEFAULT NOW()  
);
```

27. Host-Venue Details (If hosts have their own venues or preferred locations)

```
CREATE TABLE host_venue_details (  
    host_id UUID REFERENCES hosts(host_id) ON DELETE CASCADE,  
    venue_id UUID REFERENCES venues(venue_id) ON DELETE CASCADE,  
    address TEXT,  
    capacity INT,  
    lat DOUBLE PRECISION,  
    lng DOUBLE PRECISION,  
    parking_info TEXT,  
    transport_info TEXT,  
    geom GEOMETRY(Point, 4326),  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    PRIMARY KEY (host_id, venue_id)  
);
```

28. Organizations Table (For large event companies)

```
CREATE TABLE organizations (  
    organizer_id UUID REFERENCES organizers(organizer_id) ON DELETE CASCADE,  
    name TEXT NOT NULL,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    updated_at TIMESTAMPTZ DEFAULT NOW(),  
    PRIMARY KEY (organizer_id)  
);
```

29. Performer Members (For groups/bands)

```
CREATE TABLE performer_members (  
    performer_id UUID REFERENCES performers(performer_id) ON DELETE CASCADE,  
    member_id UUID REFERENCES performers(performer_id) ON DELETE CASCADE,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    PRIMARY KEY (performer_id, member_id)  
);
```

30. Performer Contacts Table

```
CREATE TABLE performer_contacts (  
    performer_id UUID REFERENCES performers(performer_id) ON DELETE CASCADE,  
    email TEXT,  
    phone TEXT,  
    website TEXT,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    PRIMARY KEY (performer_id)  
);
```

-31. Event Organizations

```
CREATE TABLE event_organizations (  
    event_id UUID REFERENCES events(event_id) ON DELETE CASCADE,  
    organizer_id UUID REFERENCES organizers(organizer_id) ON DELETE CASCADE,  
    is_collab BOOLEAN DEFAULT FALSE,  
    created_at TIMESTAMPTZ DEFAULT NOW(),  
    PRIMARY KEY (event_id, organizer_id)  
);
```