

BLUEPRINT proposed data submission schemas
Draft v0.1.2

José María Fernández

September 15, 2012

Contents

1	Tabular format of input files	5
1.1	Gene Expression	5
1.1.1	Expression - Metadata File	5
1.1.2	Expression - Gene File	7
1.2	Copy Number Germline Variations	8
1.2.1	Simple Germline Variations - Metadata File	8
1.2.2	Simple Germline Variations - Primary Analysis File	9
1.3	Exon Junction	11
1.3.1	Exon Junction - Metadata File	11
1.3.2	Exon Junction - Primary Analysis File	13
1.4	DNA Methylation and Hydroxy-Methylation	15
1.4.1	Methylation - Secondary Analysis File	15
1.4.2	Methylation - Metadata File	15
1.4.3	Methylation - Primary Analysis File	16
1.5	Protein-DNA interactions	17
1.5.1	Protein-DNA interaction - Metadata File	17
1.5.2	Protein-DNA interaction - Secondary Analysis File	19
1.5.3	Protein-DNA interaction - Primary Analysis File	19
1.6	Clinical Data Submission File Specifications	20
1.6.1	Analyzed Sample Data File	20
1.6.2	Donor Data File	21
1.6.3	Specimen Data File	22
1.6.4	Donor Family History	23
1.7	Regulatory Regions	24
1.7.1	Regulatory regions - Metadata File	24
1.7.2	Regulatory regions - Primary Analysis File	25
1.7.3	Regulatory regions - Secondary Analysis File	26
A	CV Tables	27
A.1	CV Table appendix_B10.tsv	27
A.2	CV Table appendix_B5.tsv	28
A.3	CV Table appendix_B12.tsv	29
A.4	CV Table appendix_B6.tsv	30

Chapter 1

Tabular format of input files

1.1 Gene Expression

1.1.1 Expression - Metadata File

Expression [exp] – Metadata File [m]




Figure 1.1: Test

Name	Type	R/O	Description / Values
analysis_id	VARCHAR(64)	R	Unique identifier for the analysis performed for a particular set of samples
sample_id	VARCHAR(64)	R	Unique identifier for the analyzed sample
assembly_version	VARCHAR(64)	R	Version of reference genome assembly (See Table appendix.B10.tsv)
gene_build_version	INTEGER	R	Version of Ensembl gene build used for annotation
platform	VARCHAR(512)	R	Platform or technology used in detecting the expression (See Table appendix.B5.tsv)
experimental_protocol	VARCHAR(512)	0	Name of experimental protocol and URL to written protocol
base_calling_algorithm	VARCHAR(512)	R	Name of base calling algorithm and URL to written protocol
alignment_algorithm	VARCHAR(512)	R	Name of alignment algorithm and URL to written protocol
normalization_algorithm	VARCHAR(512)	R	Name of normalization algorithm and URL to written protocol
other_analysis_algorithm	VARCHAR(512)	0	Names of other analysis algorithms. Separate multiple algorithms by commas.
seq_coverage	FLOAT(5,2)	0	Sequence coverage if analyzed by sequencing platforms
raw_data_repository	VARCHAR(128)	0	Public repository where raw data is submitted (#)

1.1.2 Expression - Gene File

Expression [exp] – Gene File [g]

Name	Type	R/O	Description / Values
analysis_id	VARCHAR(64)	R	Unique identifier for the analysis performed for a particular set of samples
sample_id	VARCHAR(64)	R	Unique identifier for the analyzed sample
gene_stable_id	VARCHAR(64)	R	For annotated gene, use Ensembl gene ID. Otherwise, use assemblyBuild.chr.start.end where assemblyBuild is hg18 or hg19.
gene_chromosome	VARCHAR(64)	R	Name of the chromosome containing the expressed gene/region interrogated (See Table appendix.B6.tsv)
gene_strand	INTEGER	R	Strand of the chromosome containing the expressed gene/region <i>TBD</i>
gene_start	INTEGER	R	Start position of the gene on the chromosome
gene_end	INTEGER	R	End position of the gene on the chromosome
normalized_read_count	FLOAT(5,2)	R	Normalized count of sequencing reads if analyzed by sequencing platforms
raw_read_count	INTEGER	R	Raw count of sequencing reads if analyzed by sequencing platforms
normalized_expression_level	FLOAT(5,2)	0	Normalized value of expression level if analyzed by microarray platforms
fold_change	FLOAT(5,2)	0	Expressed fold change if differential expression is measured
reference_sample	VARCHAR(64)	0	ID of the reference analyzed sample if differential expression is measured
quality_score	INTEGER	0	Quality score for the expression call
probability	FLOAT(3,2)	0	Probability of the expression call
is_annotated	VARCHAR(64)	0	Indicate if the expressed fragment is annotated in Ensembl <i>TBD</i>
validation_status	VARCHAR(64)	R	Indicate if the expressed fragment has been validated <i>TBD</i>
validation_platform	VARCHAR(512)	0	Platform or technology used in validation (See Table appendix.B5.tsv)
probeset_id	VARCHAR(128)	0	ID of the probeset used in microarray
note	TEXT	0	Optional field to leave notes




Figure 1.2: Test

1.2 Copy Number Germline Variations

1.2.1 Simple Germline Variations - Metadata File


Simple Germline Variations [sgv] – Metadata File [m]

Name	Type	R/O	Description / Values
analysis_id	VARCHAR(64)	R	Unique identifier for the analysis performed for a particular group of samples
control_sample_id	VARCHAR(64)	R	Unique identifier for the analyzed control sample
matched_sample_id	VARCHAR(64)	R	Unique identifier for the analyzed matched sample
assembly_version	VARCHAR(64)	R	Version of reference genome assembly (See Table appendix_B10.tsv)
platform	VARCHAR(512)	R	Platform or technology used in detecting the mutation/variation (See Table appendix_B5.tsv)
experimental_protocol	VARCHAR(512)	0	Name of experimental protocol and URL to written protocol
base_calling_algorithm	VARCHAR(512)	R	Name of base calling algorithm and URL to written protocol
alignment_algorithm	VARCHAR(512)	R	Name of alignment algorithm and URL to written protocol
variation_calling_algorithm	VARCHAR(512)	R	Name of variation calling algorithm and URL to written protocol
other_analysis_algorithm	VARCHAR(512)	0	Names of other analysis algorithms. Separate multiple algorithms by commas.
seq_coverage	FLOAT(5,2)	0	Sequence coverage if analyzed by sequencing platforms
raw_data_repository	VARCHAR(512)	0	Public repository where raw data is submitted (#) (See Table appendix_B12.tsv)
raw_data_accession	VARCHAR(512)	0	Accession and URL for referencing the raw data at the public repository
note	TEXT	0	Optional field to leave notes

1.2.2 Simple Germline Variations - Primary Analysis File

Simple Germline Variations [sgv] – Primary Analysis File [p]

Name	Type	R/O	Description / Values
analysis_id	TEXT	R	Unique identifier for the analysis performed for a particular set of samples
control_sample_id	TEXT	R	Unique identifier for the analyzed control sample
variation_id	VARCHAR(128)	R	Unique identifier for the variation
variation_type	VARCHAR(64)	R	Type of variation <i>TBD</i>
chromosome	VARCHAR(64)	R	Name of the chromosome containing the mutation/variation (See Table <i>appendix.B6.tsv</i>)
chromosome_start	INTEGER	R	Start position of the mutation/variation on the chromosome
chromosome_end	INTEGER	R	End position of the mutation/variation on the chromosome
chromosome_strand	INTEGER	R	Chromosome strand <i>TBD</i>
refsnp_allele	VARCHAR(512)	R	RefSNP alleles from dbSNP (use a dash for each missing base) <i>e.g.: A/T, —/AAA</i>
refsnp_strand	INTEGER	O	Strand of RefSNP allele <i>TBD</i>
reference_genome_allele	VARCHAR(512)	R	Allele in the reference genome (use a dash for each missing base)
control_genotype	VARCHAR(512)	R	Genotype of the control sample (use a dash for each missing base)
tumour_genotype	VARCHAR(512)	R	Genotype of the tumour sample (use a dash for each missing base)
expressed_allele	VARCHAR(512)	O	The expressed allele(s) as revealed by RNA-seq, etc.
quality_score	INTEGER	O	Average quality score for the mutation/variation call
probability	FLOAT(3,2)	O	Probability of the mutation/variation call
read_count	FLOAT(5,2)	O	Average number of times the bases are covered by raw reads
is_annotated	VARCHAR(64)	O	Indicate if the mutation/variation is annotated in dbSNP <i>TBD</i>
validation_status	VARCHAR(64)	R	Indicate if the mutation/variation has been validated <i>TBD</i>
validation_platform	VARCHAR(512)	O	Platform or technology used in validation (See Table <i>appendix.B5.tsv</i>)
xref_ensembl_var_id	VARCHAR(128)	O	Cross-reference: Ensembl Variation ID in Ensembl Variation database. <i>e.g.: rs12345; ENSSNP53189</i>
note	TEXT	O	Optional field to leave notes



- junction_id is: hg19_1_100000_1_102300
- junction read count is: 3

Figure 1.3: Junction Read Count explanation

1.3 Exon Junction

The following diagram (from ICGC DCC manual) illustrates how junction_id is assigned, how junction_read_count, exon1_number_bases and exon2_number_bases are calculated:

1.3.1 Exon Junction - Metadata File

Exon Junction [jcn] – Metadata File [m]




Figure 1.4: Test

Name	Type	R/O	Description / Values
analysis_id	VARCHAR(64)	R	Unique identifier for the analysis performed for a particular set of samples
sample_id	TEXT	R	Unique identifier for the analyzed sample
assembly_version	VARCHAR(64)	R	Version of reference genome assembly (#) (See Table appendix.B10.tsv)
gene_build_version	INTEGER	R	Version of Ensembl gene build used for annotation
platform	VARCHAR(512)	R	Platform or technology used in detecting the expression (See Table appendix.B5.tsv)
experimental_protocol	VARCHAR(512)	O	Name of experimental protocol and URL to written protocol
base_calling_algorithm	VARCHAR(512)	R	Name of base calling algorithm and URL to written protocol
alignment_algorithm	VARCHAR(512)	R	Name of alignment algorithm and URL to written protocol
normalization_algorithm	VARCHAR(512)	R	Name of normalization algorithm and URL to written protocol

1.3.2 Exon Junction - Primary Analysis File

Exon Junction [jcn] – Primary Analysis File [p]

Name	Type	R/O	Description / Values
analysis_id	VARCHAR(64)	R	Unique identifier for the analysis performed for a particular group of samples
sample_id	VARCHAR(64)	R	Unique identifier for the analyzed sample
junction_id	VARCHAR(256)	R	For known exons, use exonID1_exonID2 where exonID1 and exonID2 are Ensembl IDs of the 5' and 3' exons, respectively. For novel or putative exons, use assemblyBuild_exon1chr_exon1end_exon2chr_exon2start where assemblyBuild is hg18 or hg19; exon1chr and exon2chr are the chromosomes of the 5' and 3' exons, respectively; exon1end is the end position of the 5' exon; exon2start is the start position of the 3' exon.
gene_stable_id	VARCHAR(64)	R	Stable ID of the gene containing the 5' exon at the junction. For annotated gene, use Ensembl gene ID. For putative and novel gene, use assemblyBuild_chr_start_end where assemblyBuild can be hg18 or hg19.
gene_chromosome	VARCHAR(64)	R	Name of the chromosome containing the above gene. <i>(See Table appendix.B6.tsv)</i>
gene_strand	INTEGER	R	Strand of the chromosome <i>TBD</i>
gene_start	INTEGER	R	Start position of the entire gene on the chromosome as annotated in Ensembl
gene_end	INTEGER	R	End position of the entire gene on the chromosome as annotated in Ensembl
second_gene_stable_id	VARCHAR(64)	O	In the case of a fusion gene, provide the Stable ID of the gene containing the 3' exon at the junction. For annotated genes, use Ensembl gene ID. For putative and novel genes, use assemblyBuild_chr_start_end where assemblyBuild can be hg18 or hg19.
exon1_chromosome	VARCHAR(64)	R	Name of the chromosome containing the 5' exon (#) <i>(See Table appendix.B6.tsv)</i>
exon1_number_bases	INTEGER	R	Number of bases from 5' exon
exon1_end	INTEGER	R	End position of the 5' exon on the chromosome
exon1_strand	INTEGER	O	Chromosome strand of the 5' exon <i>TBD</i>
exon2_chromosome	VARCHAR(64)	R	Name of the chromosome containing the 3' exon (#) <i>(See Table appendix.B6.tsv)</i>
exon2_number_bases	INTEGER	R	Number of bases from 3' exon
exon2_start	INTEGER	R	Start position of the 3' exon on the chromosome
exon2_strand	INTEGER	O	Chromosome strand of the 3' exon <i>TBD</i>
is_fusion_gene	VARCHAR(16)	O	Indicate if the function is the result of a fusion gene <i>TBD</i>
is_novel_splice_form	VARCHAR(16)	O	Indicate if the splice form is novel <i>TBD</i>
junction_seq	TEXT	O	Provide junction sequence if either is_fusion_gene or is_novel_splice_form is true
junction_type	VARCHAR(64)	O	Type of junction <i>TBD</i>




Figure 1.5: Test

1.4 DNA Methylation and Hydroxy-Methylation

1.4.1 Methylation - Secondary Analysis File

Methylation [meth] – Secondary Analysis File [s]

Name	Type	R/O	Description / Values
analysis_id	TEXT	R	Unique identifier for the analysis performed for a particular set of samples
analyzed_sample_id	TEXT	R	Unique identifier for the analyzed sample
methylated_fragment_id	TEXT	R	Unique identifier for the methylation
gene_affected	VARCHAR(128)	R	Gene(s) containing the methylation. Use Ensembl gene id. Separate multiple genes with vertical bars in the form of geneA—geneB—geneC. If no gene is affected, use -888 (not applicable).
gene_build_version	INTEGER	R	Version of Ensembl gene build used for annotation
note	TEXT	0	Optional field to leave notes

1.4.2 Methylation - Metadata File

Methylation [meth] – Metadata File [m]

Name	Type	R/O	Description / Values
analysis_id	VARCHAR(64)	R	Unique identifier for the analysis performed for a particular set of samples
analyzed_sample_id	VARCHAR(64)	R	Unique identifier for the analyzed sample
matched_sample_id	VARCHAR(64)	R	Unique identifier for the analyzed control sample
assembly_version	VARCHAR(64)	R	Version of reference genome assembly (See Table appendix_B10.tsv)
platform	VARCHAR(512)	R	Platform or technology used in detecting the methylation (See Table appendix_B5.tsv)
experimental_protocol	VARCHAR(512)	0	Name of experimental protocol and URL to written protocol
base_calling_algorithm	VARCHAR(512)	R	Name of base calling algorithm and URL to written protocol
alignment_algorithm	VARCHAR(512)	R	Name of alignment algorithm and URL to written protocol
variation_calling_algorithm	VARCHAR(512)	R	Name of variation calling algorithm and URL to written protocol
other_analysis_algorithm	VARCHAR(512)	0	Names of other analysis algorithms. Separate multiple algorithms by commas.
raw_data_repository	VARCHAR(128)	0	Public repository where raw data is submitted (See Table appendix_B12.tsv)
raw_data_accession	VARCHAR(128)	0	Accession and URL for referencing the raw data at the public repository
note	TEXT	0	Optional field to leave notes

1.4.3 Methylation - Primary Analysis File

Methylation [meth] – Primary Analysis File [p]

Name	Type	R/O	Description / Values
analysis_id	TEXT	R	Unique identifier for the analysis performed for a particular group of samples
analyzed_sample_id	TEXT	R	Unique identifier for the analyzed sample
methyated_fragment_id	VARCHAR(128)	R	Unique identifier for the methylated fragment
chromosome	VARCHAR(64)	R	Name of the chromosome containing the methylation (See Table appendix_B6.tsv)
chromosome_start	INTEGER	R	Start position of the methylation on the chromosome
chromosome_end	INTEGER	R	End position of the methylation on the chromosome
chromosome_strand	INTEGER	0	Chromosome strand <i>TBD</i>
beta_value_methylation	FLOAT(5,2)	0	Methylation Beta value for interrogated site
beta_value_hydroxymethylation	FLOAT(5,2)	0	Hydroxymethylation Beta value for interrogated site
quality_score_methylation	INTEGER	0	Quality score for the methylation call
quality_score_hydroxymethylation	INTEGER	0	Quality score for the hydroxymethylation call
probability_methylation	FLOAT(3,2)	0	Probability of the methylation call
probability_hydroxymethylation	FLOAT(3,2)	0	Probability of the hydroxymethylation call
validation_status	VARCHAR(64)	R	Indicate if the methylation has been validated <i>TBD</i>
validation_platform	VARCHAR(512)	0	Platform or technology used in validation (See Table appendix_B5.tsv)
note	TEXT	0	Optional field to leave notes

1.5 Protein-DNA interactions

1.5.1 Protein-DNA interaction - Metadata File

Protein-DNA [pdna] – Metadata File [m]




Figure 1.6: Test

Name	Type	R/O	Description / Values
analysis_id	VARCHAR(64)	R	Unique identifier for the analysis performed for a particular set of samples
analyzed_sample_id	VARCHAR(64)	R	Unique identifier for the analyzed sample
matched_sample_id	VARCHAR(64)	R	Unique identifier for the analyzed control sample
assembly_version	VARCHAR(64)	R	Version of reference genome assembly (See Table appendix_B10.tsv)
platform	VARCHAR(512)	R	Platform or technology used in detecting the protein-DNA interaction (See Table appendix_B5.tsv)
experimental_protocol	VARCHAR(512)	0	Name of experimental protocol and URL to written protocol
base_calling_algorithm	VARCHAR(512)	R	Name of base calling algorithm and URL to written protocol
alignment_algorithm	VARCHAR(512)	R	Name of alignment algorithm and URL to written protocol
variation_calling_algorithm	VARCHAR(512)	R	Name of variation calling algorithm and URL to written protocol
other_analysis_algorithm	VARCHAR(512)	0	Names of other analysis algorithms. Separate multiple algorithms by commas.
raw_data_repository	VARCHAR(128)	0	Public repository where raw data is submitted (See Table appendix_B12.tsv)
raw_data_accession	VARCHAR(128)	0	Accession and URL for referencing the raw data at the public repository
NSC	FLOAT(5,2)	0	Normalized strand-cross correlation of the analysis
RSC	FLOAT(5,2)	0	Relative strand-cross correlation of the analysis
note	TEXT	0	Optional field to leave notes

1.5.2 Protein-DNA interaction - Secondary Analysis File

Protein-DNA [pdna] – Secondary Analysis File [s]

Name	Type	R/O	Description / Values
analysis_id	TEXT	R	Unique identifier for the analysis performed for a particular set of samples
analyzed_sample_id	TEXT	R	Unique identifier for the analyzed sample
protein_dna_interaction_id	TEXT	R	Unique identifier for the protein-DNA interaction
gene_affected	VARCHAR(128)	R	Gene on the protein-DNA interaction area. Use Ensembl gene id. If no gene is affected, use -888 (not applicable).
transcript_affected	VARCHAR(128)	R	Transcript on the protein-DNA interaction area. Use Ensembl transcript id. Separate multiple transcripts with vertical bars in the form of transcriptA—transcriptB—transcriptC. If no transcript is affected, use -888 (not applicable).
gene_build_version	INTEGER	R	Version of Ensembl gene build used for annotation
note	TEXT	O	Optional field to leave notes

1.5.3 Protein-DNA interaction - Primary Analysis File

Protein-DNA [pdna] – Primary Analysis File [p]

Name	Type	R/O	Description / Values
analysis_id	TEXT	R	Unique identifier for the analysis performed for a particular group of samples
analyzed_sample_id	TEXT	R	Unique identifier for the analyzed sample
protein_dna_interaction_id	VARCHAR(128)	R	Unique identifier for the protein-DNA interaction
protein_stable_id	VARCHAR(128)	R	Ensembl protein stable id of the interacting protein
chromosome	VARCHAR(64)	R	Name of the chromosome where the protein-DNA interaction happened (See Table appendix.B6.tsv)
chromosome_start	INTEGER	R	Start position where the interaction happened on the chromosome
chromosome_end	INTEGER	R	End position the interaction happened on the chromosome
chromosome_strand	INTEGER	O	Chromosome strand <i>TBD</i>
idr	FLOAT(5,2)	R	Irreproducible discovery rate
fdr	FLOAT(5,2)	O	False discovery rate
rank_type	VARCHAR(64)	O	Kind of used ranking
rank_value	FLOAT(5,2)	O	Rank value
validation_status	VARCHAR(64)	R	Indicate if the detected protein-DNA interaction has been validated <i>TBD</i>
validation_platform	VARCHAR(512)	O	Platform or technology used in validation (See Table appendix.B5.tsv)
note	TEXT	O	Optional field to leave notes

1.6 Clinical Data Submission File Specifications

Overview

There are three **required** clinical and tissue annotation submission files, and one **optional** template files:

1.6.1 Analyzed Sample Data File

Analyzed Sample Data File [sample] (required)

This submission file describes an analyzed sample on which molecular characterization was performed. It includes both control samples and tumour samples.




Figure 1.7: Test

Name	Type	R/O	Description / Values
analyzed_sample_id	VARCHAR(64)	R	<i>Unique identifier</i> for the sample assigned by data provider
specimen_id	VARCHAR(64)	R	<i>Unique identifier</i> for the specimen assigned by data provider. The corresponding specimen id must appear in the specimen data submission file
analyzed_sample_type	VARCHAR(128)	R	Controlled vocabulary description of sample type <i>TBD</i>
analyzed_sample_type_other	VARCHAR(64)	0	Free text description of site of sample if "other" was specified in <i>sample_type</i> field
analyzed_sample_interval	INTEGER	0	Interval from specimen acquisition to sample use in an analytic procedure (e.g. DNA extraction), in days
analyzed_sample_notes	TEXT	0	Freertext notes about sample allowed

1.6.2 Donor Data File

Donor Data File [donor] (required)

This submission file describes a donor from which one or more specimens were obtained.

Name	Type	R/O	Description / Values
donor_id	VARCHAR(64)	R	<i>Unique identifier</i> for the donor; assigned by data provider.
donor_sex	VARCHAR(128)	R	Donor biological sex. <i>"Other" has been removed from the controlled vocabulary due to identifiability concerns. TBD</i>
donor_region_of_residence	VARCHAR(64)	R	Country, and optionally state or province code, but not city. <i>ISO3166-1-alpha-2 or ISO3166-2 codes, eg: "CA" or "CA-ON"</i>
donor_vital_status	VARCHAR(128)	R	Donor's last known vital status <i>TBD</i>
donor_age_at_diagnosis	INTEGER	R	Age at primary diagnosis <i>Use "90" for patients ≥ 90</i>
donor_diagnosis_do	VARCHAR(64)	R	Disease Ontology code <i>Disease Ontology code</i> <i>(http://diseaseontology.sourceforge.net/)</i>
donor_notes	TEXT	O	Free text notes concerning donor <i>Any additional non-identifying information can be included here.</i>

1.6.3 Specimen Data File

Specimen Data File [specimen] (required)

This submission file describes a specimen from which one or more samples were derived. Use additional rows for more than one specimen from the same patient. If more than one specimen was extracted during the same procedure, each gets a distinct ID.

Name	Type	R/O	Description / Values
donor_id	VARCHAR(64)	R	Unique identifier for the donor; assigned by data provider. It must be coded, and correspond to a donor ID listed in the donor data file.
specimen_id	VARCHAR(64)	R	Unique identifier for the specimen assigned by data provider.
specimen_type	VARCHAR(128)	R	Controlled vocabulary description of specimen type. <i>TBD</i>
specimen_type_other	VARCHAR(64)	R	Free text description of site of specimen if "normal control (other)" or "tumour (other)" was specified in specimen_type field.
specimen_processing	VARCHAR(128)	R	Description of technique used to process specimen <i>TBD</i>
specimen_processing_other	VARCHAR(64)	R	If "other" specified for specimen_processing, may indicate technique here.
specimen_storage	VARCHAR(128)	R	Description of how specimen was stored. For specimens that were extracted freshly or immediately cultured, answer (1) "NA". <i>TBD</i>
specimen_storage_other	VARCHAR(64)	R	If "other" specified for specimen_storage, may indicate technique here.
specimen_biobank	VARCHAR(64)	R	If the specimen was obtained from a biobank, provide the biobank name here
specimen_biobank_id	VARCHAR(64)	R	If the specimen was obtained from a biobank, provide the biobank accession number here.
specimen_available	VARCHAR(128)	R	Whether additional tissue is available for followup studies. <i>TBD</i>
specimen_notes	TEXT	0	Free text notes allowed <i>Any additional non-identifying information can be included here.</i>

1.6.4 Donor Family History

Donor Family History [family] (optional)

This file describes the family history of the donor.




Figure 1.8: Test

Name	Type	R/O	Description / Values
donor_id	TEXT	R	Unique identifier for the donor; assigned by data provider. It must be coded, and correspond to a donor ID listed in the donor data file.
relationship.type	VARCHAR(128)	R	Relationship to the donor <i>TBD</i>
relationship.type.other	TEXT	R	If "other" answered in previous column, specify the relationship type here
relationship.sex	VARCHAR(128)	R	Biological sex of related individual <i>TBD</i>
relationship.age	INTEGER	R	Age of relative at primary diagnosis (years) <i>Use 90 for ages ≥ 90 years.</i>
relationship.diagnosis.do	TEXT	R	Disease Ontology code for the relative's diagnosis status
relationship.diagnosis	TEXT	R	Diagnosis (disease or healthy status) <i>e.g. "breast cancer"</i>

1.7 Regulatory Regions

1.7.1 Regulatory regions - Metadata File

Regulatory regions [rreg] – Metadata File [m]

Name	Type	R/O	Description / Values
analysis_id	VARCHAR(64)	R	Unique identifier for the analysis performed for a particular set of samples
analyzed_sample_id	VARCHAR(64)	R	Unique identifier for the analyzed sample
matched_sample_id	VARCHAR(64)	R	Unique identifier for the analyzed control sample
assembly_version	VARCHAR(64)	R	Version of reference genome assembly (See Table appendix_B10.tsv)
platform	VARCHAR(512)	R	Platform or technology used in detecting the regulatory region (See Table appendix_B5.tsv)
experimental_protocol	VARCHAR(512)	O	Name of experimental protocol and URL to written protocol
base_calling_algorithm	VARCHAR(512)	R	Name of base calling algorithm and URL to written protocol
alignment_algorithm	VARCHAR(512)	R	Name of alignment algorithm and URL to written protocol
variation_calling_algorithm	VARCHAR(512)	R	Name of variation calling algorithm and URL to written protocol
other_analysis_algorithm	VARCHAR(512)	O	Names of other analysis algorithms. Separate multiple algorithms by commas.
raw_data_repository	VARCHAR(128)	O	Public repository where raw data is submitted (See Table appendix_B12.tsv)
raw_data_accession	VARCHAR(128)	O	Accession and URL for referencing the raw data at the public repository
note	TEXT	O	Optional field to leave notes

1.7.2 Regulatory regions - Primary Analysis File

Regulatory regions [rreg] – Primary Analysis File [p]

Name	Type	R/O	Description / Values
analysis_id	TEXT	R	Unique identifier for the analysis performed for a particular group of samples
analyzed_sample_id	TEXT	R	Unique identifier for the analyzed sample
regulatory_region_id	VARCHAR(128)	R	Unique identifier for the identified regulatory region
chromosome	VARCHAR(64)	R	Name of the chromosome containing the regulatory region (See Table appendix_B6.tsv)
chromosome_start	INTEGER	R	Start position of the regulatory region on the chromosome
chromosome_end	INTEGER	R	End position of the regulatory region on the chromosome
chromosome_strand	INTEGER	0	Chromosome strand <i>TBD</i>
normalized_read_count	FLOAT(5,2)	R	Normalized count of sequencing reads if analyzed by sequencing platforms
raw_read_count	INTEGER	R	Raw count of sequencing reads if analyzed by sequencing platforms
validation_status	VARCHAR(64)	R	Indicate if the regulatory region has been validated <i>TBD</i>
validation_platform	VARCHAR(512)	0	Platform or technology used in validation (See Table appendix_B5.tsv)
note	TEXT	0	Optional field to leave notes

1.7.3 Regulatory regions - Secondary Analysis File

Regulatory regions [rreg] – Secondary Analysis File [s]

Name	Type	R/O	Description / Values
analysis_id	TEXT	R	Unique identifier for the analysis performed for a particular set of samples
analyzed_sample_id	TEXT	R	Unique identifier for the analyzed sample
regulatory_region_id	TEXT	R	Unique identifier for the identified regulatory region
gene_affected	VARCHAR(128)	R	Gene(s) related to the regulatory region. Use Ensembl gene id. Separate multiple genes with vertical bars in the form of geneA—geneB—geneC. If no gene is affected, use -888 (not applicable).
gene_build_version	INTEGER	R	Version of Ensembl gene build used for annotation
note	TEXT	0	Optional field to leave notes

Appendix A

CV Tables

A.1 CV Table appendix_B10.tsv

Key	Description
1	GRCh37
2	NCBI36
3	GRCh37.p1
4	GRCh37.p2
5	GRCh37.p3
6	GRCh37.p4
7	GRCh37.p5

A.2 CV Table appendix_B5.tsv

Key	Description
1	PCR
2	qPCR
3	capillary sequencing
4	SOLiD sequencing
5	Illumina GA sequencing
6	454 sequencing
7	Helicos sequencing
8	Affymetrix Genome-Wide Human SNP Array 6.0
9	Affymetrix Genome-Wide Human SNP Array 5.0
10	Affymetrix Mapping 100K Array Set
11	Affymetrix Mapping 500K Array Set
12	Affymetrix Mapping 10K 2.0 Array Set
13	Affymetrix EMET Plus Premier Pack
14	Agilent Whole Human Genome Oligo Microarray Kit
15	Agilent Human Genome 244A
16	Agilent Human Genome 105A
17	Agilent Human CNV Association 2x105K
18	Agilent Human Genome 44K
19	Agilent Human CGH 1x1M
20	Agilent Human CGH 2x400K
21	Agilent Human CGH 4x180K
22	Agilent Human CGH 8x60K
23	Agilent Human CNV 2x400K
24	Agilent Human miRNA Microarray Kit (v2)
25	Agilent Human CpG Island Microarray Kit
26	Agilent Human Promoter ChIP-on-chip Microarray Set
27	Agilent Human SpliceArray
28	Illumina human1m-duo
29	Illumina human660w-quad
30	Illumina humancytosnp-12
31	Illumina human510s-duo
32	Illumina humanmethylation27
33	Illumina goldengate methylation
34	Illumina HumanHT-12 v4.0 beadchip
35	Illumina HumanWG-6 v3.0 beadchip
36	Illumina HumanRef-8 v3.0 beadchip
37	Illumina microRNA Expression Profiling Panel
38	Illumina humanht-16
39	Illumina humanht-17
40	Nimblegen Human CGH 3x720 Whole-Genome v3.0 Array
41	Nimblegen Human CGH 2.1M Whole-Genome v2.0D Array
42	Nimblegen Gene Expression 385K
43	Nimblegen Gene Expression 4x72K
44	Nimblegen Gene Expression 12x135K
45	Nimblegen Human Methylation 2.1M Whole-Genome sets
46	Nimblegen Human Methylation 385K Whole-Genome sets
47	Nimblegen CGS
48	Illumina Human1M OmniQuad chip
49	PCR and capillary sequencing
50	Custom-designed gene expression array
51	Affymetrix HT Human Genome U133A Array Plate Set
52	Agilent 244K Custom Gene Expression G4502A-07-1
53	Agilent 244K Custom Gene Expression G4502A-07-2
54	Agilent 244K Custom Gene Expression G4502A-07-3
55	Agilent Human Genome CGH Custom Microarray 2x415K
56	Affymetrix Human U133 Plus PM
57	Affymetrix Human U133 Plus 2.0
58	Affymetrix Human Exon 1.0 ST
59	Almac Human CRC

A.3 CV Table appendix_B12.tsv

Key	Description
1	EGA
2	dbSNP
3	TCGA
4	CGHub
5	GEO

A.4 CV Table appendix_B6.tsv

Key	Description
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	X
24	Y
25	MT
26	c5.H2
27	c6.COX
28	c6.QBL
29	NT_113870
30	NT_113871
31	NT_113872
32	NT_113874
33	NT_113878
34	NT_113880
35	NT_113881
36	NT_113884
37	NT_113885
38	NT_113886
39	NT_113888
40	NT_113889
41	NT_113890
42	NT_113898
43	NT_113899
44	NT_113901
45	NT_113902
46	NT_113903
47	NT_113906
48	NT_113908
49	NT_113909
50	NT_113910
51	NT_113911
52	NT_113912
53	NT_113915
54	NT_113916
55	NT_113917
56	NT_113923
57	NT_113924
58	NT_113925
59	NT_113926
60	NT_113927