ClickShare CSE-200+

Wireless collaboration solution for creative content-sharing fit for enterprise roll-outs



- Up to 2 users on-screen
- Share from laptop, tablet or smartphone
- Smooth switching between wired and wireless sources
- Enhanced security features
- Annotation, blackboarding and touch back support on a 4K canvas
- Central management
- Delivered with 2 Buttons

Creativity boosts businesses. Enabling creative meetings, brainstorms and discussions enhance team collaboration and business outcomes. With the wireless collaboration solution, ClickShare, you bring effortless ideation and efficient collaboration in your enterprise.

Find out what's new in the latest ClickShare update

Enriched sharing

The CSE-200+ offers interactive collaborative experiences for medium-sized meeting rooms. It allows up to 2 persons to share content simultaneously. Users simply plug a USB-powered device – the ClickShare Button – into their PC or Mac and click the button to get the content from their laptop on the large meeting room screen. With the ClickShare Apps, users can also share content from their laptops, mobile phones or tablets. Make sure to have the latest firmware installed on your Base Unit to enable the best experience with the Desktop App.

Stimulate creativity in your entire enterprise

The CSE-200+ was designed for enterprise rollouts. It offers a HDMI input for legacy equipment, easy switching between wireless and wired sources, enhanced security features, full network integration, a wide range of interactivity features - including annotation, blackboarding and touch back support on a 4K canvas and central management. Allowing up to 2 persons to share content simultaneously, the CSE-200+ encourages brainstorming and productivity in your enterprise.

The CSE-200+ is a product created with ISO 27001 certified flows and processes.



PRODUCT SPECIFICATIONS

CLICKSHARE CSE-200+

| General specifications | |
|--|--|
| Operating system | Windows 7/8/8.1/10 32 & 64 bit macOS 10.14/10.15 (Catalina) Android 9 & 10 (ClickShare app) iOS 11, 12 & 13 (ClickShare app) |
| Video outputs | 1x HDMI 1.4b |
| Video inputs | 1x HDMI 1.2 |
| Output resolution | 4K UHD (3840*2160) @ 30Hz |
| Input resolutions | 1920x1080 @60Hz |
| Audio | Via HDMI, analog via Audio Jack 3.5mm, S/PDIF |
| AirPlay Support | iOS 11, 12 & 13 / macOS 10.14, 10.15 |
| Google Cast Support | Android 9, 10 |
| Miracast support | Miracast R2 support on Windows 10 |
| Frame rate | Up to 30fps* |
| Number of sources simultaneous on screen | 2 |
| Number of simultaneous connections | 16 |
| iPad, iPhone and Android compatibility | Sharing of documents, browser, camera for both Android and iOS devices via ClickShare app |
| Extended desktop | Available for Windows, requires ClickShare Extension Pack. |
| Authentication protocol | WPA2-PSK in stand-alone mode WPA2-PSK or IEEE 802.1X using the ClickShare Button in network integration mode |
| Wireless transmission protocol | IEEE 802.11 a/b/g/n/ac and IEEE 802.15.1 |
| Reach | Adjustable with signal strength modulation; max. 30m (100 ft) between ClickShare Button and ClickShare Base Unit |
| Frequency band | 2.4 GHZ and 5 GHz (DFS channels supported in select number of countries) |
| Connections | 1x Ethernet LAN 1Gbit 1x USB Type-C 2.0 (back); 2x USB Type A 2.0 (back); 1x USB Type A 2.0 (front) Audio analog line out on mini jack socket (3.5mm), digital S/PDIF |
| Noise Level | Max. 25dBA @ 0-30°C Max. 30dBA @ 30-40°C |
| Temperature range | Operating: 0°C to +40°C (+32°F to +104°F) Max: 35°C (95°F) at 3000m Storage: -20°C to +60°C (-4°F to +140°F) |
| Humidity | Storage: 0 to 90% relative humidity, non-condensing Operation: 0 to 85% relative humidity, non-condensing |
| Anti-theft system | Kensington lock |
| Certifications | FCC/CE |
| Warranty | 3 years standard |
| *Note | *In optimal WiFi conditions with minimal WiFi interference and as measured during our quality validation. Check Network Deployment Guide for more info on WiFi optimisation and ideal configuration depending on your network environment. |
| ClickShare Base Unit dimensions | |
| Dimensions (HxWxD) | 39mm x 200mm x 202mm |
| Power supply | Standard 110/220 V AC plug |
| Power consumption | Operational: 50W (max) Standby: |
| Weight | 900 gr |

Last updated: 03 Dec 2020

 $Technical \ specifications \ are \ subject \ to \ change \ without \ prior \ notice. \ Please \ check \ www.barco.com \ for \ the \ latest \ information.$

