

**Q**

QAM16 modulation, 521  
 Q2931b protocol, 654  
 QoS (Quality-of-Service), 329, 653–654  
 QQ, 592, 623  
 Quality-of-Service. *See* QoS  
 quantization, 590  
 query  
   ARP message, 467  
   information about, 141  
 query messages, 140–142  
 queues  
   FIFO (first-in-first-out), 641–642  
   packet-discarding policy, 641  
   priority queuing, 642–643  
   provable maximum delay, 647–648  
   round robin queuing discipline,  
     643–644  
   WFQ (weighted fair queuing),  
     644–645  
   work-conserving round robin  
     discipline, 644  
 queuing, 327–331  
 queuing delays, 25, 36–37, 39–42, 60

**R**

radio channels, 21  
 Radio Network Controller. *See* RNC  
 RADIUS protocol, 530, 730  
 random access protocols, 447, 473  
   Aloha protocol, 452–453  
   CSMA (carrier sense multiple access)  
     protocol, 453–456  
   CSMA/CD (carrier sense multiple  
     access with collision detection),  
     455–459  
   slotted ALOHA protocol, 450–452  
 Random Early Detection algorithm. *See*  
   RED algorithm  
 rarest first, 149  
 rate adaptation, 542–543  
 RC4 algorithm, 727–728  
 RCP (Routing Control Platform), 786  
 rdt (reliable data transfer protocol), 204  
   building, 206–215

  packet reordering, 229–230  
   pipelined, 215–218  
   TCP (Transmission Control Protocol),  
     204  
   unreliable layer below, 204  
 real-time applications  
   timing, 92  
   UDP (User Datagram Protocol), 200  
 real-time interactive applications  
   protocols, 623–632  
   RTP (Real-Time Transport Protocol),  
     623–626  
   SIP, 626–632  
 real-time measurements of delay and loss  
   performance, 606  
 Real-Time Streaming Protocol. *See* RTSP  
 Real-Time Transport Protocol. *See* RTP  
 receive buffer, 233  
 receiver authentication, 706  
 receiver-based recovery, 621  
 receiver feedback, 208  
 receivers  
   ACK generation policy, 247  
   defining operation, 206  
   sequence number of packet acknowl-  
     edged by ACK message, 212  
 receiver-side transport layer, 54  
 receive window, 250–252  
 receive window field, 234  
 receiving adapter, 472  
 receiving processes addresses, 90  
 records, inserting in DNS database, 142,  
   144  
 recursive queries and DNS servers,  
   137–138, 140  
 RED (Random Early Detection)  
   algorithm, 329  
 regional ISPs, 33  
 registrars, 142  
 registration with home agent, 568–569  
 relays, 622–623  
 reliable channel, 204  
 reliable data transfer, 91, 190  
   application layer, 204  
   channel with bit errors, 207–212

- link layer, 204
- lossy channel with bit errors, 212–215
- perfectly reliable channel, 206–207
- principles, 204–230
- reliable channel, 204
- TCP (Transmission Control Protocol), 230–231, 240, 242–250
- transport layer, 204
- transport-layer protocols, 91
- reliable data transfer protocol. *See* rdt
- reliable data transfer service, 235
- reliable delivery, 436
- reliable transport service, 269
- remote host, transferring files, 116–118
- rendezvous point, 404
- repeater, 474
- replicated servers, 132
- reply messages and DNS (domain name system), 140–142
- repositioning video, 600
- request messages and HTTP, 103–105
- request-response mode, 772
- requests for comments. *See* RFCs
- Request to Send control frame. *See* RTS control frame
- residential ISPs, 87
- resource-management cells. *See* RM cells
- resource records. *See* RRs
- resource reservation protocols, 362
- resources
  - admitting or blocking flows, 653
  - efficient use of, 640
  - reservations, 653–654
- response ARP, 467
- response messages and HTTP, 105–108
- retransmission, 208, 212
- retransmitting data, 241, 262
- retransmitting packets, 259, 261–263
- reverse path broadcast. *See* RPB
- reverse path forwarding. *See* RPF
- Rexford, Jennifer, 786–787
- RFCs (requests for comments), 5
- RIP advertisements, 384–385
- RIP request message, 387
- RIP response message, 384
- RIP routers, 386–387
- RIP (Routing Information Protocol), 384, 498
  - hops, 384
  - implementation aspects, 386–388
  - IP network-layer protocol, 387
  - lower-tier ISPs, 388
  - modifying local routing table and propagating information, 387
  - RIP messages, 384–385
  - RIP table, 385–386
  - routing updates, 384
  - UDP transport-layer protocol, 387
  - UNIX implementation, 387–388
- Rivest, Ron, 684, 690
- RM (resource-management cells), 267–269
- RNC (Radio Network Controller), 552
- roaming number, 572
- Roberts, Larry, 61, 511
- root DNS servers, 134–136
- round robin queuing discipline, 643–644
- round-trip delays, 43
- round-trip time. *See* RTT
- route aggregation, 342
- route attributes, 395
- router control plane functions, 322
- router discovery message, 566–567
- router forwarding plane, 321
- routers, 4, 12, 22, 53, 303, 310
  - access control lists, 734
  - adapters, 468
  - address of, 43
  - administrative autonomy, 380
  - area border, 389
  - ARP modules, 468
  - AS-PATH attribute, 394
  - ASs (autonomous systems), 380
  - authenticated and encrypted channel
    - between, 725
  - buffering packet bits, 24
  - buffer sizing, 328–329
  - connected into network, 338
  - connection state information, 315
  - control functions, 321–322

routers (*continued*)

- control plane implemented in, 331
- data center hierarchy, 492–493
- default, 364
- destination, 364
- finite buffers, 261–265
- firewalls, 355, 481
- first-hop, 364
- fixed-length labels, 487
- forwarding function, 320–322
- forwarding table, 26, 308–309, 317–318, 322–323, 394, 396–397, 469
- gateway, 380–381
- implementing layers 1 through 3, 53
- incident links, 22
- input ports, 320
- input processing, 322–324
- interfaces, 338, 468
- intra-AS routing protocols, 397
- IP addresses, 394, 465, 468
- IP protocol, 53
- label-switched, 488
- layer-2 packet switch, 480
- link-layer and MAC addresses, 462–463, 465
- longest prefix matching rule, 318–319
- lookup, 323–324
- looping advertisements, 394
- memory access times, 324
- network core, 4
- network-layer addresses, 462, 465
- output ports, 320–321
- output processing, 326
- packet-forwarding decisions, 364
- packet loss, 327
- packets not cycling through, 481
- physical links between, 364
- plug-and-play, 481
- primary role, 306
- processing datagrams, 480
- processing packets, 351
- protocols, 9
- queuing, 327–331
- routing control plane, 331

- routing packets, 380–382

- routing processor, 321

- routing tables, 385–386

- scale, 379–380

- self-synchronizing, 371

- source, 364

- spanning tree, 481

- store-and-forward, 22, 24

- store-and-forward packet switches, 480

- versus* switches, 480–482

- switching, 320, 324–326

- terminating incoming physical link, 320

- VC setup, 316

- routes, 4, 394–396

- route summarization, 342

- routing, 305–306, 308–310

- advertising information, 382–383

- broadcast, 399–405

- calls to mobile user, 571–572

- distance vector, 384

- hierarchical, 379–383

- hot-potato, 382

- to mobile node, 559–564

- multicast, 399, 405–412

- storing information, 379–380

- routing algorithms, 309, 363–383

- ARPAnet, 366

- circuit-switched, 379

- decentralized, 366

- DV (distance-vector) algorithm, 366, 371–379

- dynamic, 366

- forwarding tables, 364

- global, 365–366

- hierarchical routing, 379–383

- least costly paths, 365

- load-sensitive, 366

- LS (link-state) algorithms, 366–371

- path from source to destination router, 364

- scale of routers, 379–380

- static, 366

- switches, 494–495

- viewing packet traffic flows, 379

- routing control plane, 331