



# Silhouette Analysis (Silhouette Clustering)

## 1 WHY SILHOUETTE EXISTS

After clustering, we always ask:

**“Are these clusters actually good?”**

Problems:

- K-Means needs **k** → how to choose it?
- DBSCAN gives clusters → how to **evaluate** them?
- Labels exist, but **no ground truth**

👉 Silhouette score measures how well each point fits in its cluster compared to others.

---

## 2 CORE IDEA (ONE LINE)

A point is good if it is close to its own cluster and far from other clusters.

Silhouette captures exactly this.

---

## 3 TWO DISTANCES YOU MUST UNDERSTAND

For each data point **i**:

- ◆ **a(i) — Intra-cluster distance**
  - Average distance from point **i** to all other points in **its own cluster**
  - Measures **compactness**

👉 Smaller = better

---

♦ **b(i) — Nearest-cluster distance**

- Average distance from point **i** to points in the **nearest neighboring cluster**
- Measures **separation**

👉 Larger = better

---

## 4 SILHOUETTE FORMULA (VERY IMPORTANT)

✓ Silhouette value for a single point (PLAIN TEXT)

$$s(i) = (b(i) - a(i)) / \max(a(i), b(i))$$

---

✓ Range (PLAIN TEXT)



$$-1 \leq s(i) \leq 1$$

---

## 5 HOW TO INTERPRET THE VALUE

Silhouette value	Meaning
$\approx +1$	Perfectly clustered
$\approx 0$	On decision boundary
$< 0$	Probably misclustered

Visual intuition 👇



---

## 6 OVERALL SILHOUETTE SCORE

- Compute  $s(i)$  for every point
- Take the **mean**

Silhouette Score =  $\frac{1}{n} \sum s(i)$  Silhouette Score =  $\frac{1}{n} \sum s(i)$

📌 Used to:


- Compare different **k**
- Compare different clustering algorithms

---

## 7 USING SILHOUETTE TO CHOOSE k (VERY COMMON)

# Optimal number of clusters

## Silhouette method




### Steps:


1. Try  $k = 2, 3, 4, \dots$
2. Compute silhouette score for each
3. Choose **k with highest score**

👉 Unlike elbow method, silhouette has a **clear numeric meaning**

---

## 8 SILHOUETTE PLOT (INTERVIEW FAVORITE)





What it shows:

- Each bar = one point
- Width = silhouette value
- Grouped by cluster

Good plot:

- Mostly positive bars
- Similar heights across clusters

## **9 WHEN SILHOUETTE WORKS BEST**

- 
- ✓ Convex / well-separated clusters
  - ✓ K-Means, Agglomerative clustering
  - ✓ Low–medium dimensional data
- 

## 10 WHEN SILHOUETTE FAILS (IMPORTANT)

- ✗ Non-convex clusters (DBSCAN shapes)
  - ✗ Varying densities
  - ✗ High-dimensional data (distance meaningless)
  - ✗ Single cluster ( $k = 1 \rightarrow$  undefined)
- 

## 11 SILHOUETTE WITH DBSCAN

⚠ Careful here:

- DBSCAN labels **noise as -1**
- Silhouette **cannot handle noise directly**

**Correct approach:**

```
mask = labels != -1  
silhouette_score(X[mask], labels[mask])
```

📌 Even then:

- DBSCAN clusters are **shape-based**
  - Silhouette may **underestimate quality**
- 

## 12 SILHOUETTE vs ELBOW (VERY COMMON)

Feature	Silhouette	Elbow
Metric meaning	Clear (-1 to 1)	Heuristic

Works without k	✗	✗
Cluster separation	✓	✗
Interpretability	High	Medium

---

## 13 SKLEARN CODE (MINIMAL)

```
from sklearn.metrics import silhouette_score  
  
score = silhouette_score(X, labels)  
print(score)
```

For plotting:

```
from sklearn.metrics import silhouette_samples
```

---

## 14 EXAM / INTERVIEW ANSWER (PERFECT)

Silhouette score evaluates clustering quality by comparing intra-cluster compactness and inter-cluster separation. Values close to +1 indicate well-separated clusters, while negative values suggest misclassification.

---

## 15 ONE-LINE MEMORY TRICK 🧠

Silhouette asks: “Am I closer to my own group than to others?”

---

## 🔑 FINAL SUMMARY

- Uses `distance`
- No ground truth needed

- Range **-1 to +1**
- Best for **choosing k**
- Weak for **DBSCAN & complex shapes**