

# Situated Display in Hospital Ward

Ivan Naumovski  
ITU

Rued Langaardsvej 7, 2300  
Copenhagen  
inau@itu.dk

Martino Secchi  
ITU

Rued Langaardsvej 7, 2300  
Copenhagen  
msec@itu.dk

Diem Hong  
Affiliation

Rued Langaardsvej 7, 2300  
Copenhagen  
hong@itu.dk

## ABSTRACT

### Author Keywords

Guides; instructions; author's kit; conference publications; keywords should be separated by a semi-colon. **Mandatory section to be included in your final version.**

### ACM Classification Keywords

H.5.2. Information Interfaces and Presentation: Input devices and strategies; I.2.6. Artificial Intelligence: Learning

See: <http://www.acm.org/about/class/1998/> for more information and the full list of ACM classifiers and descriptors.

## INTRODUCTION

Since the dawn of the computer age modalities have been an important aspect to consider when interfacing with the machines, whether it has been done using keystrokes, audio-control or gestures.

It has always been of high relevance to push the limits for how we interact with technology, mainly to empower the individual.

Technology is supposed to make common tasks even easier to achieve. Consider the case of a physically disabled person being empowered by using an alternative modality such as voice control.

In our case the focus is to improve on how people in the healthcare sector interact with technology. In the healthcare sector interaction can actually prove to have negative effects, particularly bacteria can be transferred.

One way to avoid spreading bacteria is by avoiding physical interaction with input devices.

This can result in less time spent scrubbing or rinsing as the likelihood for microbacteria being transferred via input devices is reduced.

Ultimately alternative modalities could provide employees within the sector a way to use native hand gestures to perform tasks such as interacting with x-ray images.

## PREVIOUS WORK

There exist a lot of prior work within the field of HCI which is relevant to our solution. The papers which influenced this project the most will be mentioned in following section.

### Alternative Modalities

Prior work in regards to pattern recognition has been of high relevance to our solution. bla bla bla bla

### Smart Machines

Prior work in regards to pattern recognition has been of high relevance to our solution. bla bla bla bla

## OUR SOLUTION - BETTER HEADING

The system we have designed consists of two parts, one being an input device and the other being an application able to recognize the patterns from the device and forward predefined commands.

### Building the input device

Our motion tracking device has been built in such a fashion that it resembles a wrist watch. This form factor makes it rather compact. Additionally a lot of people wear watches on a daily basis which makes it recognizable and barely noticeable for people.

The specific device contains a list of components, the most important are 6DoF Sensor, Bluetooth and Arduino micro-controller.

### 6DoF Sensor:

This is the heart of the device. It contains an accelerometer and a gyroscope. This means we can measure movement and rotation of the wrist of anyone wearing the device.

### Arduino Pro Mini:


This is the brain of the device, it handles all communication between the 6DoF chip and forwards the data over bluetooth to any consumers of the data.

The others are not that important to spend a lot of time on, they provide means of communicating, charging and toggling the device on and off.

### Big Data, slightly larger challenge

Since the input device we have built is quite lightweight, data processing needs to be done elsewhere. This provided us with the challenge of transferring data from one bluetooth capable device to another. To

*Raw Data and purifying*



We thank CHI, PDC and CSCW volunteers, and all publications support and staff, who wrote and provided helpful comments on previous versions of this document. Some of the references cited in this paper are included for illustrative purposes only. **Don't forget to acknowledge funding sources as well**, so you don't wind up having to correct it later.