

## 0.1 Inconsolata

The easiest way to combine the different Rmd files in the correct order is as follows: call the first file `index.Rmd`. All other Rmd files will be appended based on the alphabetical order of their filename. Therefore it is handy to add the desired order number as a prefix to the filenames. See <https://bookdown.org/yihui/bookdown/usage.html> for an example.

```
model <- lm(log(pressure) ~ poly(temperature, 2), data = pressure)
summary(model)

## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      1.09440    0.05917   18.50 3.18e-12
## poly(temperature, 2)1 19.00036    0.25791   73.67 < 2e-16
## poly(temperature, 2)2 -4.40129    0.25791  -17.07 1.09e-11
##
## Residual standard error: 0.2579 on 16 degrees of freedom
## Multiple R-squared:  0.9972, Adjusted R-squared:  0.9969
## F-statistic: 2859 on 2 and 16 DF,  p-value: < 2.2e-16
```

## 0.2 Latin Modern Mono

The easiest way to combine the different Rmd files in the correct order is as follows: call the first file `index.Rmd`. All other Rmd files will be appended based on the alphabetical order of their filename. Therefore it is handy to add the desired order number as a prefix to the filenames. See <https://bookdown.org/yihui/bookdown/usage.html> for an example.

```
model <- lm(log(pressure) ~ poly(temperature, 2), data = pressure)
summary(model)

## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      1.09440    0.05917   18.50 3.18e-12
## poly(temperature, 2)1 19.00036    0.25791   73.67 < 2e-16
## poly(temperature, 2)2 -4.40129    0.25791  -17.07 1.09e-11
##
## Residual standard error: 0.2579 on 16 degrees of freedom
## Multiple R-squared:  0.9972, Adjusted R-squared:  0.9969
## F-statistic: 2859 on 2 and 16 DF,  p-value: < 2.2e-16
```

## 0.3 Consolas

The easiest way to combine the different Rmd files in the correct order is as follows: call the first file `index.Rmd`. All other Rmd files will be appended based on the alphabetical order of their filename. Therefore it is handy to add the desired order number as a prefix to the filenames. See <https://bookdown.org/yihui/bookdown/usage.html> for an example.

```
model <- lm(log(pressure) ~ poly(temperature, 2), data = pressure)
summary(model)

## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      1.09440    0.05917   18.50 3.18e-12
```

```
## poly(temperature, 2)1 19.00036    0.25791   73.67 < 2e-16
## poly(temperature, 2)2 -4.40129    0.25791  -17.07 1.09e-11
##
## Residual standard error: 0.2579 on 16 degrees of freedom
## Multiple R-squared:  0.9972, Adjusted R-squared:  0.9969
## F-statistic: 2859 on 2 and 16 DF,  p-value: < 2.2e-16
```

## 0.4 Nimbus 15 Mono

The easiest way to combine the different Rmd files in the correct order is as follows: call the first file `index.Rmd`. All other Rmd files will be appended based on the alphabetical order of their filename. Therefore it is handy to add the desired order number as a prefix to the filenames. See <https://bookdown.org/yihui/bookdown/usage.html> for an example.

```
model <- lm(log(pressure) ~ poly(temperature, 2), data = pressure)
summary(model)

## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      1.09440    0.05917   18.50 3.18e-12
## poly(temperature, 2)1 19.00036    0.25791   73.67 < 2e-16
## poly(temperature, 2)2 -4.40129    0.25791  -17.07 1.09e-11
##
## Residual standard error: 0.2579 on 16 degrees of freedom
## Multiple R-squared:  0.9972, Adjusted R-squared:  0.9969
## F-statistic: 2859 on 2 and 16 DF,  p-value: < 2.2e-16
```

## 0.5 Droid Sans Mono

The easiest way to combine the different Rmd files in the correct order is as follows: call the first file `index.Rmd`. All other Rmd files will be appended based on the alphabetical order of their filename. Therefore it is handy to add the desired order number as a prefix to the filenames. See <https://bookdown.org/yihui/bookdown/usage.html> for an example.

```
model <- lm(log(pressure) ~ poly(temperature, 2), data = pressure)
summary(model)

## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      1.09440    0.05917   18.50 3.18e-12
## poly(temperature, 2)1 19.00036    0.25791   73.67 < 2e-16
## poly(temperature, 2)2 -4.40129    0.25791  -17.07 1.09e-11
##
## Residual standard error: 0.2579 on 16 degrees of freedom
## Multiple R-squared:  0.9972, Adjusted R-squared:  0.9969
## F-statistic: 2859 on 2 and 16 DF,  p-value: < 2.2e-16
```

## 0.6 Courier New

The easiest way to combine the different Rmd files in the correct order is as follows: call the first file `index.Rmd`. All other Rmd files will be appended based on the alphabetical order of their filename. Therefore it is handy to add the desired order number as a prefix to the filenames. See <https://bookdown.org/yihui/bookdown/usage.html> for an example.

```
model <- lm(log(pressure) ~ poly(temperature, 2), data = pressure)
summary(model)

## Coefficients:
##              Estimate Std. Error t value Pr(>|t|)
## (Intercept)      1.09440    0.05917   18.50 3.18e-12
## poly(temperature, 2)1 19.00036    0.25791   73.67 < 2e-16
## poly(temperature, 2)2 -4.40129    0.25791  -17.07 1.09e-11
##
## Residual standard error: 0.2579 on 16 degrees of freedom
## Multiple R-squared:  0.9972, Adjusted R-squared:  0.9969
## F-statistic: 2859 on 2 and 16 DF, p-value: < 2.2e-16
```