

# Meridian Platform REST API Reference

Meridian Global Corp — Confidential Internal Document

## Meridian Platform REST API Reference

**Version 2.4.1**

**Effective Date: 15 January 2025**

This document provides the authoritative specification for the Meridian Platform REST API. All requests must adhere to the authentication, rate limiting, and pagination rules outlined below. The base URL for all endpoints is `https://api.meridianglobal.com`.

---

## Authentication

The Meridian API supports two authentication methods. All requests must include one of the following credentials.

**OAuth 2.0 Bearer Tokens**

Obtain a bearer token via the OAuth 2.0 authorization code flow. Include the token in the `Authorization` header:

`Authorization: Bearer <token>`

Tokens expire 24 hours after issuance. A 401 Unauthorized response is returned for expired or invalid tokens. Refresh tokens are available for server-to-server integrations; contact your Meridian account manager for details.

**API Keys**

For server-side applications, use an API key passed in the `X-API-Key` header:

`X-API-Key: mg_<32 character key>`

API keys do not expire but can be revoked at any time via the Meridian Admin Console. Use of an API key in conjunction with a bearer token is not permitted; only one authentication method per request is allowed.

---

## Core Endpoints

All endpoints accept JSON request bodies and return JSON responses. Dates and timestamps follow ISO 8601 format (e.g., `2025-01-15T14:30:00Z`).

#### **\*\*POST /v2/query\*\***

Submit a natural language query against your Meridian data lake. The request body must contain a `query` field (string, max 2,000 characters) and an optional `language` field (default `en`).

*\*Example request:\**

```
```json
```

```
{ "query": "Show total revenue by region for Q4 2024", "language": "en" }
```

```
```
```

*\*Response:\** Returns a `query\_id` (UUID) and a `status` field. For synchronous queries, the result is embedded in the response. For long-running queries, a `202 Accepted` is returned and results are delivered via webhook (see Webhook Support below).

#### **\*\*POST /v2/ingest\*\***

Upload a data file (CSV, JSON, or Parquet) to a specified dataset. Send the file as `multipart/form-data` with the following fields:

- `file` – the data file (max 500 MB)
- `dataset\_id` – the target dataset identifier (string)
- `mode` – `append` or `replace` (default `append`)

*\*Response:\** Returns an `ingest\_id` and a `status` of `processing`. Final status is sent via webhook.

#### **\*\*GET /v2/reports/{id}\*\***

Retrieve a previously generated report by its report ID. The report is returned as a JSON object containing metadata (title, created date, parameters) and a `data\_url` field that provides a direct download link to the report file (CSV or PDF). The download link expires 60 minutes after issuance.

#### **\*\*DELETE /v2/data/{dataset\_id}\*\***

Permanently delete a dataset and all its associated data. This action cannot be undone. The request must include an `X-Confirm-Delete: true` header.

*\*Response:\** Returns `204 No Content` on success. If the dataset does not exist, a `404 Not Found` is returned.

---

## Rate Limits

API keys are subject to the following rate limits, applied per key on a rolling one-minute window:

- **Standard Tier**: 1,000 requests per minute
- **Enterprise Tier**: 10,000 requests per minute

Exceeding the limit returns a `429 Too Many Requests` response. The `Retry-After` header indicates the number of seconds to wait before retrying. Rate limits are enforced per endpoint; a query request and an ingest request consume separate allowances. Contact [support@meridianglobal.com](mailto:support@meridianglobal.com) to upgrade your tier.

---

## Error Codes

The API returns standard HTTP status codes with a JSON error body containing an `error` object with `code` and `message` fields.

| Code | Meaning | Typical Cause |
|------|---------|---------------|
|------|---------|---------------|

| ----- | ----- | ----- |
|-------|-------|-------|
|-------|-------|-------|

|     |             |                                                                       |
|-----|-------------|-----------------------------------------------------------------------|
| 400 | Bad Request | Malformed JSON, missing required fields, or invalid parameter values. |
|-----|-------------|-----------------------------------------------------------------------|

|     |              |                                                                                     |
|-----|--------------|-------------------------------------------------------------------------------------|
| 401 | Unauthorized | Missing or expired bearer token, invalid API key, or token without required scopes. |
|-----|--------------|-------------------------------------------------------------------------------------|

|     |           |                                                                |
|-----|-----------|----------------------------------------------------------------|
| 404 | Not Found | The requested resource (report, dataset, etc.) does not exist. |
|-----|-----------|----------------------------------------------------------------|

|     |              |                                                                   |
|-----|--------------|-------------------------------------------------------------------|
| 429 | Rate Limited | Request count exceeded the per-minute limit for the current tier. |
|-----|--------------|-------------------------------------------------------------------|

|     |              |                                                                                        |
|-----|--------------|----------------------------------------------------------------------------------------|
| 500 | Server Error | An internal error occurred. Retry after a brief delay; if persistent, contact support. |
|-----|--------------|----------------------------------------------------------------------------------------|

Example error response:

```
```json
```

```
{ "error": { "code": 400, "message": "Field 'query' is required." } }
```

```
```
```

---

## Pagination

Endpoints that return