

Incode Parent

# Table of Contents

Contents .....	2
How to Configure .....	4
Dependencies .....	6

This module defines a standard parent POM that can be used as a parent for applications that use the Incode Platform modules.

Its primary purpose is to make it easy to use a set up [maven mixins](#) within child POMs; specifically to hold the required `<pluginManagement>` so that versions of plugins are locked down. The [quickstart app](#) inherits from this module.

See below for details of the maven mixins so configured.

# Contents

This parent POM defines `<properties>` and `<pluginManagement>` for the plugins defined in the following maven mixins:

Module	Ver.	Description	Mixin to add
<a href="#">cucumber reporting</a>	0.0.2	Configures cucumber reporting plugin for BDD specs.	<pre>&lt;mixIn&gt;   &lt;groupId&gt;com.danhaywood.mavenmixin&lt;/groupId&gt;   &lt;artifactId&gt;cucumberreporting&lt;/artifactId&gt; &lt;/mixIn&gt;</pre>
<a href="#">datanucleus enhance</a>	0.0.4	Configures datanucleus:enhance (for JDO entities of DN modules) for production and test code	<pre>&lt;mixIn&gt;   &lt;groupId&gt;com.danhaywood.mavenmixin&lt;/groupId&gt;   &lt;artifactId&gt;datanucleusenhanace&lt;/artifactId&gt; &lt;/mixIn&gt;</pre>
<a href="#">docker</a>	0.0.3	Configures docker to package images and upload to a docker registry (docker hub by default)	<pre>&lt;mixIn&gt;   &lt;groupId&gt;com.danhaywood.mavenmixin&lt;/groupId&gt;   &lt;artifactId&gt;docker&lt;/artifactId&gt; &lt;/mixIn&gt;</pre>
<a href="#">enforcer relaxed</a>	0.0.2	Applies the maven enforcer plugin (but with relaxed dependency convergence)	<pre>&lt;mixIn&gt;   &lt;groupId&gt;com.danhaywood.mavenmixin&lt;/groupId&gt;   &lt;artifactId&gt;enforcerrelaxed&lt;/artifactId&gt; &lt;/mixIn&gt;</pre>
<a href="#">jetty console</a>	0.0.2	Configure jetty-console plugin (to create a standalone version of a webapp)	<pre>&lt;mixIn&gt;   &lt;groupId&gt;com.danhaywood.mavenmixin&lt;/groupId&gt;   &lt;artifactId&gt;jettyconsole&lt;/artifactId&gt; &lt;/mixIn&gt;</pre>
<a href="#">jetty war</a>	0.0.2	Package up a webapp as a WAR file, and to allow the webapp to be run using the jetty maven plugin	<pre>&lt;mixIn&gt;   &lt;groupId&gt;com.danhaywood.mavenmixin&lt;/groupId&gt;   &lt;artifactId&gt;jettywar&lt;/artifactId&gt; &lt;/mixIn&gt;</pre>
<a href="#">source and javadoc</a>	0.0.2	Provides the ability to run source, javadoc and jxr plugins (packaged as JAR files or report using <code>mvn site</code> )	<pre>&lt;mixIn&gt;   &lt;groupId&gt;com.danhaywood.mavenmixin&lt;/groupId&gt;   &lt;artifactId&gt;sourceandjavadoc&lt;/artifactId&gt; &lt;/mixIn&gt;</pre>
<a href="#">standard</a>	0.0.3	Defines the "standard" set of plugins (clean, compile, jar, install, site etc)	<pre>&lt;mixIn&gt;   &lt;groupId&gt;com.danhaywood.mavenmixin&lt;/groupId&gt;   &lt;artifactId&gt;standard&lt;/artifactId&gt; &lt;/mixIn&gt;</pre>
<a href="#">surefire</a>	0.0.4	Run surefire plugin for unit, integration and/or ( <a href="#">Cucumber</a> ) BDD specs.	<pre>&lt;mixIn&gt;   &lt;groupId&gt;com.danhaywood.mavenmixin&lt;/groupId&gt;   &lt;artifactId&gt;surefire&lt;/artifactId&gt; &lt;/mixIn&gt;</pre>

Module	Ver.	Description	Mixin to add
static analysis	0.0.2	Ability to run various static analysis plugins (checkstyle, pmd, findbugs, javancss, jdepend) as report <code>mvn site</code>	<pre> &lt;mixin&gt;   &lt;groupId&gt;com.danhaywood.mavenmixin&lt;/groupId&gt;   &lt;artifactId&gt;staticanalysis&lt;/artifactId&gt; &lt;/mixin&gt; </pre>

# How to Configure

To configure:

- inherit from this pom:

```
<parent>
  <groupId>org.incode</groupId>
  <artifactId>incode-parent</artifactId>
  <version>1.15.1.1</version>
</parent>
```

This has the effect of defining a number of `<properties>` (eg `${mavenmixin-surefire.version}`) and also the setting up the `<pluginManagement>` of all of the plugins referenced by the above maven mixins.

- optionally, override the `isis.version` :

```
<properties>
  <isis.version>1.15.1</isis.version>
  ...
</properties>
```

- for each maven mixin required in the consuming module, just add the corresponding `<mixin>` to:

```
<build>
  <plugins>
    <plugin>
      <groupId>com.github.odavid.maven.plugins</groupId>
      <artifactId>mixin-maven-plugin</artifactId>
      <version>0.1-alpha-39</version>
      <extensions>true</extensions>
      <configuration>
        <mixins>
          ...
        </mixins>
      </configuration>
    </plugin>
  </plugins>
</build>
```

①

① add in mixin reference here - just copy-n-paste from the fourth column of the above table,

For example, to enable the [surefire](#) mixin, just add:

```
<mixin>  
  <groupId>com.danhaywood.mavenmixin</groupId>  
  <artifactId>surefire</artifactId>  
</mixin>
```

# Dependencies

This mixin module relies on the [com.github.odavid.maven.plugins:mixin-maven-plugin](#), released under Apache License v2.0.