

# Committers Guide

# Table of Contents

Build process .....	2
Release process .....	3
Prereqs .....	3
Release Maven Mixins .....	3
Release Modules .....	4
Recreating the archetype .....	5
Releasing the archetype .....	6
Release an Interim Build .....	8
Release Snapshot .....	9
Docs & website .....	10
Prerequisites .....	10
Previewing the website .....	10
Publishing the website .....	11

This guide contains procedures to be performed by committers/maintainers of this codebase.

# Build process

To build the platform, see the [contributors' guide](#).

# Release process

This section describes the steps to release the platform to Maven central. There are four stages:

- release the maven mixins
- release the modules
- recreate the quickstart archetype (referencing the just-released modules)
- release the quickstart archetype

The release process uses Sonatype's OSS support (see [user guide](#)); our thanks to them for providing this service.

## Prereqs

First, set the `$INCODEREL` environment variable to the release. Generally speaking this should correspond to the version of Apache Isis.

```
export INCODEREL=1.15.0
export INCODENEXT=1.16.0-SNAPSHOT

env | grep ^INCODE
```

## Release Maven Mixins

The `release.sh` script automates the release process. It performs the following:

- performs a sanity check (`mvn clean install -o`) that everything builds ok
- bumps the `pom.xml` to a specified release version, and tag
- performs a double check (`mvn clean install -o`) that everything still builds ok
- releases the code using `mvn clean deploy`
- bumps the `pom.xml` to a specified release version

For example:

```
pushd mavenmixins
sh release.sh $INCODEREL \
              $INCODENEXT \
              dan@haywood-associates.co.uk \
              "this is not really my passphrase"
popd
```

where

- `$1` is the release version

- `$2` is the snapshot version
- `$3` is the email of the secret key (`~/ .gnupg/secring.gpg`) to use for signing
- `$4` is the corresponding passphrase for that secret key.

Other ways of specifying the key and passphrase are available, see the [`pgp-maven-plugin's documentation](#)).

If the script completes successfully, then push changes:

```
git push origin master
```



The mavenmixins' `release.sh` does *not* tag the repo; this is left until the modules have also been released.

If the script fails to complete, then identify the cause, perform a `git reset --hard` to start over and fix the issue before trying again. Note that in the parent `pom.xml`, the `nexus-staging-maven-plugin` has the `autoReleaseAfterClose` setting set to `true` (to automatically stage, close and the release the repo). You may want to set this to `false` if debugging an issue.

According to Sonatype's guide, it takes about 10 minutes to sync, but up to 2 hours to update [search](#).

## Release Modules

The modules are released using their own `release.sh` script. This is very similar to that of the mavenmixins; the only substantive difference is that it also tags the repo with the release version.

```
pushd modules
```

Before doing so, update the `incode-parent` module's `pom.xml`, so that it references the (just released) non-SNAPSHOT version of the mavenmixins.



TODO: should automate this editing, put into the `release.sh` script instead.

Commit the changes.

Then, release using:

```
sh release.sh $INCODEREL \
              $INCODENEXT \
              dan@haywood-associates.co.uk \
              "this is not really my passphrase"
```

If the script completes successfully, then push changes and the tag:

```
git push origin master && git push origin $INCODEREL
popd
```

## Recreating the archetype

The quickstart archetype is re-created for each release from the current quickstart application. The generated archetype is then released by deploying up to Maven Central.

Switch to the quickstart *application*:

```
pushd ex/app/quickstart
```

Now check the application source code:

- Confirm that the parent `pom.xml` of the quickstart application inherits from the release version of `org.incode:incode-parent`. For example:

```
<parent>
  <groupId>org.incode</groupId>
  <artifactId>incode-parent</artifactId>
  <version>1.15.0</version>
  <relativePath/>
</parent>
```

- Also check that the parent `pom.xml` references the release (non-SNAPSHOT) versions of `isis.version`:

```
<properties>
  <isis.version>1.15.0</isis.version>
  ...
</properties>
```

- Finally, ensure that the optional modules are **commented in**.

Search for the phrase *"Comment in to include example modules"*

Staying in the same directory, recreate using:

```
sh ../../arch/recreate-archetype.sh $INCODEREL
```

And then:

```
popd
```

# Releasing the archetype

We release in three steps:

- build the archetype locally (analogous to `mvn release:prepare`)
- check that an application can be built from the archetype
- deploy the archetype (using `mvn deploy`).

## Prepare the archetype

The archetype is prepared using:

```
pushd ex/arch/quickstart
sh ../release-prepare.sh $INCODEREL
popd
```

## Testing the archetype

In a *different session*:

```
export INCODETMP=/c/tmp    # or as required
export INCODEART=quickstart
env | grep INCODE | sort
```

then:

```
rm -rf $INCODETMP/test-$INCODEART

mkdir $INCODETMP/test-$INCODEART
cd $INCODETMP/test-$INCODEART
```

then:

```
mvn archetype:generate \
  -D archetypeGroupId=org.incode.platform.archetype \
  -D archetypeArtifactId=quickstart-archetype \
  -D archetypeVersion=1.15.0 \
  -D groupId=com.mycompany \
  -D artifactId=myapp \
  -D version=1.0-SNAPSHOT \
  -D archetypeCatalog=local \
  -B
```

and build and run using:



```
cd myapp
mvn clean install

mvn -pl webapp jetty:run \
    -Disis.appManifest=domainapp.appdefn.DomainAppAppManifestWithFixtures
```

Login using sven/pass. The application generated should be the [Quickstart app](#).

## Deploying the archetype

Back in the original session (in the `ex/arch/quickstart` directory), the archetype is released (deployed to Maven Central) using:

```
sh ../release-deploy.sh \
    $INCODENEXT \
    dan@haywood-associates.co.uk \
    "this is not really my passphrase"
```

Once done:

```
popd
```

# Release an Interim Build

If you have commit access to this project (or a fork of your own) then you can create interim releases using the `interim-release.sh` script.

The idea is that this will - in a new branch - update the artifacts with a timestamped version (eg `1.15.0.20170927-0738`). It then pushes the branch (and a tag) to the specified remote.

A CI server such as Jenkins can monitor the branches matching the wildcard `origin/interim/*` and create a build. These artifacts can then be published to a snapshot repository.

For example:

```
pushd modules
sh interim-release.sh $INCODEREL origin
popd
```

where

- `origin` is the name of the remote to which you have permissions to write to.

# Release Snapshot

To deploy a snapshot (to Sonatype's snapshot repo), use:

```
pushd modules  
mvn clean deploy  
popd
```

The artifacts should be available in Sonatype's [Snapshot Repo](#).

# Docs & website

The website resides in the `adocs` directory:

- `documentation/` is the source for website itself (Asciidoctor)
- `template/` is the HTML template
- `search/` holds node.js Javascript files to index the built site so that it is searchable

The website is published to the [incodehq/incodehq.github.io](https://github.com/incodehq/incodehq.github.io) github repository; a `CNAME` file (in the root directory) maps this to <http://platform.catalog.org>.

To publish, this repository must also be cloned to your local computer. The scripts assume that the `incode-platform` repository (ie this repo) and the `incodehq.github.io` repository cloned at the same level, eg:

```
├── incodehq
│   ├── incode-platform
│   └── incodehq.github.io
```

## Prerequisites

Make sure that you've checked out the `incodehq/incodehq.github.io` repository alongside this one (see discussion above).

You'll also need to install:

- node (v7.10.0 or later) ... used to build the search index
- python 3 ... used to preview

The actual website generation uses AsciidoctorJ, which is called by Maven plugin. There are no other software prereqs.

Normally you'll want to work in the `adocs/documentation` directory:

```
pushd adocs/documentation
```

## Previewing the website

To do a quick build the website and preview locally, use:

```
sh preview-html.sh
```

This builds the HTML and the search index, but omits building the PDFs. To enable you to preview the generated site, it starts a (python) webserver to browse.

To also build the PDFs, use:

```
sh preview-html.sh
```

## Publishing the website

When you are ready to publish the website, use:

```
sh publish.sh
```

This will remove all files in the `incodeh.github.io` directory and replace with the latest build.

To check everything is ok:

```
pushd ../../../../incodehq.github.io  
sh preview.sh
```

If all looks ok, then just push the changes:

```
git push
```