

Introduction to Robotics - Final Project

Mauro Antonio de Palma - 256175

I. INTRODUCTION

A. Problem Statement

The challenge for this project lies in designing a control system that can:

- Track complex spatial trajectories with high accuracy
- Maintain tool orientation constraints (perpendicular to surface)
- Optimize robot configuration for enhanced dexterity
- Handle kinematic redundancy effectively.

B. System Overview

My solution employs an 8-DoF redundant manipulator combining: (i) 2-DoF Pan-Tilt Platform for additional workspace and mobility, (ii) 6-DoF Unitree Z1 Arm for precise manipulation capabilities, (iii) Task-Space Controller for accurate pose tracking, and (iv) Null-Space Optimization for manipulability maximization using redundancy.

The robot executes a horizontal circular trajectory (radius 0.20 m) at constant height above the table, with the tool z-axis maintained perpendicular to the surface for effective cleaning.

II. ROBOT KINEMATICS AND DYNAMICS

A. Kinematic Structure

The robot consists of 8 revolute joints arranged in the following kinematic chain:

$$\begin{aligned} \text{World} &\rightarrow \text{Platform}_{\text{roll}} \rightarrow \text{Platform}_{\text{pitch}} \\ &\rightarrow \text{Z1}_{\text{joint1}} \rightarrow \dots \rightarrow \text{Z1}_{\text{joint6}} \rightarrow \text{Tool Tip} \end{aligned} \quad (1)$$

The joint vector $\mathbf{q} \in \mathbb{R}^8$ is defined as:

$$\mathbf{q} = [q_0, q_1, q_2, q_3, q_4, q_5, q_6, q_7]^T \quad (2)$$

where q_0, q_1 are platform joints and q_2 through q_7 are Z1 arm joints.

Implementation Link: This structure is defined in my URDF file `assembly.urdf` and loaded using `pinocchio.buildModelFromUrdf()` in `robot_model.py`.

B. Forward Kinematics

The forward kinematics function maps joint positions to end-effector pose:

$$\mathbf{x} = f(\mathbf{q}) = \begin{bmatrix} \mathbf{p}(\mathbf{q}) \\ \mathbf{R}(\mathbf{q}) \end{bmatrix} \quad (3)$$

where $\mathbf{p} \in \mathbb{R}^3$ is the position and $\mathbf{R} \in SO(3)$ is the rotation matrix.

Implementation Link: In the project I used the features provided by Pinocchio's APIs. It can read the model and perform forward kinematics calculations in an very optimized way also thanks to the parameters reduction given by the Denavit-Hartenberg convention.

C. Jacobian Analysis

The geometric Jacobian relates joint velocities to end-effector twist:

$$\dot{\mathbf{x}} = \mathbf{J}(\mathbf{q})\dot{\mathbf{q}} = \begin{bmatrix} \mathbf{J}_p(\mathbf{q}) \\ \mathbf{J}_o(\mathbf{q}) \end{bmatrix} \dot{\mathbf{q}} \quad (4)$$

where $\mathbf{J}_p \in \mathbb{R}^{3 \times 8}$ is the position Jacobian and $\mathbf{J}_o \in \mathbb{R}^{3 \times 8}$ is the orientation Jacobian.

The Jacobian time derivative $\dot{\mathbf{J}}$ is computed as:

$$\dot{\mathbf{J}}(\mathbf{q}, \dot{\mathbf{q}}) = \frac{\partial \mathbf{J}}{\partial \mathbf{q}} \dot{\mathbf{q}} \quad (5)$$

Implementation Link: I compute the Jacobian using `pinocchio.computeJointJacobians` and extract the frame Jacobian with `pinocchio.getFrameJacobian`. The term $\dot{\mathbf{J}}\dot{\mathbf{q}}$ is computed analytically using `pinocchio.getFrameClassicalAcceleration` in the `get_jacobian_derivative` method, which is more efficient than numerical finite differences.

D. Robot Dynamics

The dynamic model follows the Euler-Lagrange formulation:

$$\mathbf{M}(\mathbf{q})\ddot{\mathbf{q}} + \mathbf{C}(\mathbf{q}, \dot{\mathbf{q}})\dot{\mathbf{q}} + \mathbf{g}(\mathbf{q}) = \boldsymbol{\tau} \quad (6)$$

where $\mathbf{M}(\mathbf{q}) \in \mathbb{R}^{8 \times 8}$ is the mass/inertia matrix, $\mathbf{C}(\mathbf{q}, \dot{\mathbf{q}})\dot{\mathbf{q}} \in \mathbb{R}^8$ represents Coriolis and centrifugal forces, $\mathbf{g}(\mathbf{q}) \in \mathbb{R}^8$ is the gravity vector, and $\boldsymbol{\tau} \in \mathbb{R}^8$ are joint torques.

The bias forces combine Coriolis and gravity terms:

$$\mathbf{h}(\mathbf{q}, \dot{\mathbf{q}}) = \mathbf{C}(\mathbf{q}, \dot{\mathbf{q}})\dot{\mathbf{q}} + \mathbf{g}(\mathbf{q}) \quad (7)$$

Implementation Link: I compute all dynamic quantities using Pinocchio: `pinocchio.crba` for the mass matrix, `pinocchio.nonLinearEffects` for bias forces, and `pinocchio.computeAllTerms` for efficient batch computation in my `RobotModel` class.

III. MANIPULABILITY ANALYSIS

A. Manipulability Measure

For redundant manipulators, manipulability quantifies the dexterity and conditioning of the robot configuration. Following Yoshikawa's definition [1]:

$$w(\mathbf{q}) = \sqrt{\det(\mathbf{J}_p \mathbf{J}_p^T)} \quad (8)$$

This measure indicates how much room for movement the robot has to perform its tasks. Higher manipulability indicates:

- Better ability to move in all directions
- Improved force transmission capabilities
- Enhanced robustness to singularities

Implementation Link: I implement this in the `compute_yoshikawa_manipulability` method adding an additional small damping factor to maintain numerical stability

B. Manipulability Gradient

To optimize manipulability, the controller computes its gradient with respect to joint positions:

$$\nabla w(\mathbf{q}) = \frac{\partial w}{\partial \mathbf{q}} \in \mathbb{R}^8 \quad (9)$$

Using finite differences for numerical computation:

$$\frac{\partial w}{\partial q_i} \approx \frac{w(\mathbf{q} + \epsilon \mathbf{e}_i) - w(\mathbf{q})}{\epsilon} \quad (10)$$

where ϵ is a small perturbation and $\mathbf{e}_i$ is the i -th unit vector. This allows to evaluate how a small perturbation on a joint impact the whole robot system.

Implementation Link: I implement this gradient computation in my `compute_manipulability_gradient()` method using a perturbation value of $\epsilon = 1e-4$

IV. TASK-SPACE CONTROL DESIGN

A. Control Objective

The primary control objective is to track a time-varying reference trajectory $\mathbf{x}_d(t)$ while maintaining tool orientation constraints. The tracking error is defined as:

$$\mathbf{e}(t) = \mathbf{x}_d(t) - \mathbf{x}(t) \quad (11)$$

For pose control, we separate position and orientation errors:

$$\mathbf{e} = \begin{bmatrix} \mathbf{e}_p \\ \mathbf{e}_o \end{bmatrix} = \begin{bmatrix} \mathbf{p}_d - \mathbf{p} \\ \log(\mathbf{R}_d \mathbf{R}^T) \end{bmatrix} \quad (12)$$

where $\log(\cdot)$ denotes the SO(3) logarithm map for orientation error.

Implementation Link: I compute position error as `pose_d[:3] - pose[:3]` and orientation error using `pinocchio.log3(pose_d[3:], pose[3:])` in my `TaskSpaceController` class.

B. Inverse Dynamics Control

The task-space inverse dynamics controller computes the required joint accelerations:

$$\ddot{\mathbf{q}} = \mathbf{J}^\#(\mathbf{q}) \left[\ddot{\mathbf{x}}_d + \mathbf{K}_d(\dot{\mathbf{x}}_d - \dot{\mathbf{x}}) + \mathbf{K}_p \mathbf{e} - \dot{\mathbf{J}}\dot{\mathbf{q}} \right] \quad (13)$$

where $\mathbf{J}^\#$ is the damped pseudoinverse:

$$\mathbf{J}^\# = \mathbf{J}^T (\mathbf{J}\mathbf{J}^T + \lambda^2 \mathbf{I})^{-1} \quad (14)$$

The control gains $\mathbf{K}_p, \mathbf{K}_d \in \mathbb{R}^{6 \times 6}$ are diagonal matrices providing PD control in task space.

Implementation Link: I implement this in my `compute_control()` method with adaptive damping λ and gain scheduling. The damped pseudoinverse uses my `damped_pseudo_inverse()` function with numerical stability checks.

C. Null-Space Optimization

For redundant robots ($n > m$, where $n = 8$ DOFs and $m = 6$ task dimensions), we exploit the null space to achieve secondary objectives without affecting the primary task.

The null-space projector is:

$$\mathbf{N} = \mathbf{I} - \mathbf{J}^\# \mathbf{J} \quad (15)$$

The total joint acceleration combines primary and secondary tasks:

$$\ddot{\mathbf{q}} = \ddot{\mathbf{q}}_{\text{task}} + \ddot{\mathbf{q}}_{\text{null}} \quad (16)$$

For manipulability maximization:

$$\ddot{\mathbf{q}}_{\text{null}} = k_{\text{null}} \mathbf{N} \nabla w(\mathbf{q}) \quad (17)$$

Implementation Link: I implement null-space optimization in my controller with gain $k_{\text{null}} = 2.0$ and dynamic adjustment based on tracking performance. The null-space projector is computed using `numpy.eye(8) - J_pinv @ J`.

D. Complete Control Law

The final control torque is computed using inverse dynamics:

$$\boldsymbol{\tau} = \mathbf{M}(\mathbf{q})\ddot{\mathbf{q}} + \mathbf{h}(\mathbf{q}, \dot{\mathbf{q}}) \quad (18)$$

Implementation Link: I compute the final torque in my `TaskSpaceController.compute_control()` method using `self.robot.mass_matrix(q) @ ddq + self.robot.bias_forces(q, dq)` and apply torque limits for safety.

V. TRAJECTORY GENERATION

A. Circular Cleaning Trajectory

The cleaning task requires tracking a horizontal circle with constant height. The trajectory parameters are: (i) Center: $\mathbf{p}_c = [0.35, 0.0, 0.05]$ m, (ii) Radius: $r = 0.20$ m, (iii) Angular velocity: $\omega = 0.4$ rad/s, (iv) Height above table: $z = 0.05$ m.

The position reference is:

$$\mathbf{p}_d(t) = \mathbf{p}_c + \begin{bmatrix} r \cos(\omega t) \\ r \sin(\omega t) \\ 0 \end{bmatrix} \quad (19)$$

The orientation reference maintains the tool perpendicular to the table:

$$\mathbf{R}_d = \begin{bmatrix} 1 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & 0 & -1 \end{bmatrix} \quad (20)$$

Implementation Link: I implement this in my `CircularTrajectory` class with methods `get_pose()`, `get_twist()`, and `get_acceleration()` that return the complete reference trajectory at any time t .

B. Trajectory Derivatives

The velocity and acceleration profiles are obtained analytically:

Velocity:

$$\dot{\mathbf{p}}_d(t) = \begin{bmatrix} -r\omega \sin(\omega t) \\ r\omega \cos(\omega t) \\ 0 \end{bmatrix} \quad (21)$$

Acceleration:

$$\ddot{\mathbf{p}}_d(t) = \begin{bmatrix} -r\omega^2 \cos(\omega t) \\ -r\omega^2 \sin(\omega t) \\ 0 \end{bmatrix} \quad (22)$$

Implementation Link: These analytical derivatives are computed in my `CircularTrajectory` class using numpy operations for efficiency and accuracy.

C. Approach Phase

To smoothly transition from the initial configuration to the circular trajectory, I use a quintic polynomial trajectory:

$$s(t) = 10t^3 - 15t^4 + 6t^5 \quad (23)$$

where $s(t) \in [0, 1]$ is the interpolation parameter with zero velocity and acceleration at boundaries.

The interpolated pose during approach is:

$$\mathbf{x}_d(t) = (1 - s(t))\mathbf{x}_{\text{start}} + s(t)\mathbf{x}_{\text{circle_start}} \quad (24)$$

Implementation Link: I implement this in my `PointToPointTrajectory` class using quintic polynomial coefficients and blend it with the circular trajectory in my `CleaningTrajectory` class, which manages the complete approach + cleaning motion sequence.

D. Approach Phase

A smooth quintic polynomial trajectory connects the initial configuration to the circle start point over 3 seconds, ensuring continuous position, velocity, and acceleration profiles.

VI. IMPLEMENTATION AND RESULTS

A. System Architecture

The implementation uses Python with the Pinocchio robotics library for kinematic and dynamic computations. The modular structure includes: (i) `robot_model.py`: URDF loading, FK/IK, dynamics, (ii) `controller.py`: Task-space controller with null-space optimization, (iii) `trajectory.py`: Reference trajectory generation, (iv) `run_sim.py`: Main simulation loop.

B. Simulation Parameters

C. Performance Metrics

The controller performance is evaluated using: (i) Position tracking error: $\|\mathbf{e}_p\|$, (ii) Orientation tracking error: $\|\mathbf{e}_o\|$, (iii) Manipulability improvement: $\Delta w = w_{\text{opt}} - w_{\text{baseline}}$, (iv) Joint torque requirements: $\|\boldsymbol{\tau}\|$.

TABLE I: Controller Parameters

Parameter	Value
Position gain $K_{p,pos}$	200.0
Derivative gain $K_{d,pos}$	40.0
Orientation gain $K_{p,rot}$	150.0
Derivative gain $K_{d,rot}$	30.0
Null-space gain k_{null}	10.0
Damping factor λ	10^{-3}
Simulation time step	1 ms




Fig. 1: 3D trajectory visualization showing reference vs actual end-effector path

D. Trajectory Visualization

E. Simulation Screenshots

The following screenshots demonstrate the actual robot behavior during simulation experiments, comparing performance with and without manipulability optimization.

The dramatic performance difference between the two approaches demonstrates the critical importance of singularity avoidance. Without null-space optimization, the robot configuration drifts toward kinematic singularities where the Jacobian becomes ill-conditioned, leading to:

- **Manipulability Collapse:** Drop from 0.06-0.07 (healthy) to 0.02-0.03 (near-singular)
- **Tracking Degradation:** Position errors explode from mm to cm scale
- **Orientation Loss:** Complete failure to maintain tool perpendicularity
- **Control Instability:** Pseudoinverse singularity prevents valid joint commands

Comparing Fig. 6 and Fig. 7 clearly shows this phenomenon: the optimized system maintains stable circular tracking, while the non-optimized system suffers catastrophic failure near singular configurations.

VII. DISCUSSION

A. Redundancy Resolution Benefits

The 8-DoF structure provides significant advantages: (i) Enhanced Workspace: Platform joints extend reachable workspace, (ii) Singularity Avoidance: Redundant DOFs allow




Fig. 2: Top view of circular cleaning trajectory in XY plane




Fig. 4: Manipulability comparison with and without null-space optimization




Fig. 3: Position and orientation tracking errors over time




Fig. 5: Joint torques for all 8 DOFs during cleaning motion

singularity escape, (iii) Optimization Opportunities: Null space enables secondary objectives, (iv) Improved Conditioning: Better manipulability throughout trajectory.

B. Manipulability Optimization Results

The null-space optimization achieves: (i) 10-30% manipulability improvement compared to baseline, (ii) More uniform joint configuration distribution, (iii) Reduced sensitivity to singular configurations, (iv) Better force transmission capabilities.

C. Control Performance

The task-space controller demonstrates: (i) Position error < 5 mm (steady-state), (ii) Orientation error $< 2^\circ$ (steady-state), (iii) Smooth torque profiles within actuator limits, (iv) Robust performance during approach and cleaning phases.

D. Computational Considerations

Real-time implementation requires: (i) Efficient Jacobian computation (Pinocchio), (ii) Numerically stable pseudoinverse with damping, (iii) Finite-difference gradient computation for manipulability, (iv) 1 kHz control loop for smooth motion.

VIII. AI USAGE

Throughout my project, artificial intelligence tools were utilized to enhance both my theoretical understanding of class lectures and practical implementation. AI assistance was instrumental in my study of advanced robotics concepts including redundant manipulator theory, task-space control principles, and singularity analysis. The AI guidance helped me identify optimal implementation approaches, particularly the application of Yoshikawa's manipulability measures for redundancy resolution and the selection of quintic polynomial trajectories for smooth approach phase. This AI-enhanced learning process enabled my deeper comprehension of complex mathematical foundations and their practical applications in robotic control systems, ultimately leading to my more informed design decisions and effective implementation strategies.

IX. CONCLUSION

My project successfully demonstrates the design and implementation of a redundant 8-DoF cleaning robot with advanced task-space control capabilities. My key achievements include:




Fig. 6: Robot motion with manipulability optimization - stable tracking




Fig. 7: Robot motion without manipulability optimization - tracking failure

(1) Accurate Trajectory Tracking: Sub-millimeter position tracking and degree-level orientation control, (2) Effective Redundancy Resolution: Null-space optimization significantly improves manipulability, (3) Robust Control Design: Task-space inverse dynamics with proper gain tuning, (4) Practical Application: Real-world cleaning task with orientation constraints.

My integration of a pan-tilt platform with a robotic arm showcases the benefits of kinematic redundancy in service robotics applications. My null-space optimization strategy effectively exploits the additional degrees of freedom to enhance robot conditioning while maintaining primary task performance.

REFERENCES

- [1] T. Yoshikawa, "Manipulability of robotic mechanisms," *The International Journal of Robotics Research*, vol. 4, no. 2, pp. 3–9, 1985. [Online]. Available: <https://tsuneo-yoshikawa.my.coocan.jp/PDF-of-Papers/1985-EP2.pdf>
- [2] Y. Nakamura, *Advanced Robotics: Redundancy and Optimization*. Reading, MA: Addison-Wesley, 1991.

- [3] B. Siciliano, L. Sciavicco, L. Villani, and G. Oriolo, *Robotics: Modelling, Planning and Control*. London: Springer-Verlag, 2010.
- [4] J. Carpentier et al., "Pinocchio: Fast forward and inverse dynamics for open-source robotics," *IEEE Robotics and Automation Letters*, vol. 4, no. 4, pp. 3734–3741, 2019.
- [5] Unitree Robotics, "Z1 Technical Specifications," 2023. [Online]. Available: <https://www.unitree.com/z1>