

ABSTRACT

The increasing pollution of water bodies due to floating waste has created a need for efficient and automated cleaning solutions. Manual cleaning methods are time-consuming, unsafe, and inefficient in hazardous environments. This project presents the design and development of a hybrid amphibious waste collection rover capable of operating on both land and water for effective waste management.

The proposed system integrates mechanical design, embedded systems, and IoT-based communication to achieve real-time control and monitoring. The robot is powered by four geared DC motors driven through an L298N motor driver, enabling smooth navigation across different terrains. An Arduino UNO is used as the low-level controller to manage motor operations, control the servo-based manipulator, and process data from IR sensors for obstacle detection.

The system incorporates an ESP32-CAM module, which provides wireless communication, live video streaming, and a web-based control interface. Users can remotely control the robot using directional commands and monitor its operation through real-time camera feedback. The interface also displays IR sensor status, where obstacle detection is visually indicated, improving operational safety and usability.

A robotic manipulator with shoulder, elbow, and gripper mechanisms is integrated into the system to perform automated waste pickup and placement into an onboard container. The shoulder is designed to rotate backward, eliminating the need for a rotating base and simplifying the mechanical structure.

The system demonstrates reliable performance in navigation, obstacle detection, and waste collection under normal operating conditions. It provides a cost-effective and practical solution for cleaning water bodies and inaccessible environments. The modular architecture allows future enhancements such as autonomous navigation, AI-based waste detection, and long-range communication.

Keywords:

Hybrid Amphibious Robot, IoT Control, ESP32-CAM, Waste Collection, Robotic Arm, Obstacle Detection, Web Dashboard, Environmental Cleaning

LIST OF CONTENTS

TOPIC	PAGE NO
COVER PAGE	i
CERTIFICATE.....	ii
DECLARATION.....	iii
ACKNOWLEDGEMENT.....	iv
COLLEGE VISION & MISSION.....	v
DEPARTMENT VISION & MISSION.....	vi
DEPARTMENT Pos.....	vii
DEPARTMENT PSOs.....	viii
ABSTRACT.....	ix
TABLE OF CONTENTS.....	x-xii
LIST OF FIGURES.....	xiii
1. INTRODUCTION.....	1-4
1.1 Purpose of the System.....	1
1.2 Scope of the System.....	2
1.3 Existing System.....	3
1.4 Proposed System.....	3
2. LITERATURE SURVEY.....	5-7
2.1 Review of Literature.....	5
2.2 Gaps Identified.....	6
2.3 Objectives.....	7
3. REQUIREMENT & SYSTEM ANALYSIS.....	8-20
3.1 Functional Requirements.....	8-13
3.2 Non-Functional Requirements.....	13-15
3.3 System Analysis.....	15
3.4 Use Case Analysis.....	16-20
4. MATERIALS AND METHODOLOGY.....	21-24
4.1 Introduction.....	21
4.2 Material Selection.....	21-22
4.3 Methodology.....	22-24
4.4 Summary.....	24
5. SYSTEM DESIGN.....	25-35
5.1 Introduction.....	25
5.2 System Architecture.....	25
5.3 Output Layer.....	26
5.4 Communication & Processing Layer.....	26
5.5 Control Logic Layer.....	27-28
5.6 System Components.....	29-30
5.7 Control Logic & Software Design.....	31-33

5.8 Autonomous Agent & Future Enhancements.....	33-35
5.9 Conclusion.....	35
6. IMPLEMENTATION,	36-55
6.1 Introduction.....	36
6.2 Software Used.....	36-37
6.3 System Requirements.....	37-38
6.4 Data Input & Sensor Description.....	38-41
6.5 Frontend (ESP32-CAM Web Interface).....	41
6.6 Control System Implementation.....	42
6.7 Obstacle Detection Implementation.....	43
6.8 Manipulator Control Implementation.....	43
6.9 Multi-Component Handling.....	44
6.10 Output Generation.....	45
6.11 Data Logging.....	45
6.12 Control Code Implementation.....	46
6.13 Control Logic Code (Robot Implementation).....	47
6.14 Command Processing & Response Implementation.....	48-50
6.15 System Testing and Validation.....	50
6.16 Results and Discussion.....	51
6.17 Limitations of the System.....	52
6.18 Advantages of the System.....	52
6.19 Applications of the System.....	53
6.20 Summary.....	53
6.21 Performance Evaluation.....	53-54
6.22 Power Management Analysis.....	54
6.23 Conclusion.....	55
7. TESTING	56-68
7.1 Introduction.....	56
7.2 Testing Methodology.....	57
7.3 Types of Testing Performed.....	58
7.4 System Calibration and Tuning.....	59
7.5 System Execution and Validation.....	60-62
7.6 System Optimization and Stability Control.....	62
7.7 Integration Testing.....	63
7.8 Test Case Identification.....	64-67
7.9 Test Results Analysis.....	67
7.10 Limitations Identified During Testing.....	68
7.11 Conclusion of Testing.....	68

8. RESULT ANALYSIS.....	69-76
8.1 Introduction.....	69
8.2 Analysis of Robot Movement and Navigation.....	69
8.3 Analysis of Obstacle Detection.....	70
8.4 Analysis of Pickup Operation.....	70
8.5 Analysis of Communication and Control.....	71-72
8.6 Accuracy Analysis.....	73
8.7 Error Analysis.....	74-75
8.8 Overall Analysis.....	76
8.9 Conclusion of Result Analysis.....	76
9. CONCLUSION & FUTURE SCOPE.....	77-79
9.1 Conclusion.....	77
9.2 Future Scope.....	78-79
10. REFERENCES.....	80

LIST OF FIGURES

FIGURE NO	FIGURE NAME	PAGE NO
Figure 3.1	System Architecture of Hybrid Amphibious Waste Collection Rover	20
Figure 5.1	Flowchart of Robot Operation	28
Figure 5.2	Embedded control Logic and Operation Implementation	30
Figure 5.3	Embedded Control Logic and Operational Flow of Hybrid Amphibious Waste Collection Rover	32
Figure 5.4	Embedded Autonomus Robot Functionality	34
Figure 6.1	Robot Hardware Components Diagram	38
Figure 6.2	System Controlling System Sample	42
Figure 6.3	Manipulator Control Implementation	44
Figure 6.4	Manipulator Control Features	45
Figure 7.1	Working Flow of Amphibious Robot System	57
Figure 7.2	Testing Pipelines of Hybrid Amphibious Waste Collection Rover	63
Figure 7.3	Live Robot Operation and Waste Collection	65
Figure 7.4	Obstacle Detection in Amphibious Robot	65
Figure 7.5	Live Camera-Based Obstacle Detection in Hybrid Amphibious Waste Collection Rover	66
Figure 7.6	Waste Pickup and Drop Operation	67
Figure 7.7	Testing and Performance Analysis of Robot	68
Figure 8.1	Performace of the Robot	70
Figure 8.2	Pick up the Trash	71
Figure 8.3	Final Result Output	72

CHAPTER-1

INTRODUCTION

In today's rapidly evolving technological landscape, robotics and automation are playing a crucial role in solving real-world environmental and safety challenges. One of the major concerns faced globally is the accumulation of waste in water bodies and hazardous environments, including toxic and radioactive zones. Manual intervention in such areas is not only inefficient but also poses serious health risks to humans. To address these challenges, the development of amphibious robotic systems has gained significant importance. These systems are capable of operating across multiple terrains, including land and water, making them ideal for applications such as waste collection, environmental monitoring, and disaster response. However, designing a compact, cost-effective, and efficient amphibious robot with manipulation capabilities remains a complex engineering problem. This project focuses on the design and development of a hybrid amphibious waste collection rover equipped with a robotic manipulator. The system integrates both mechanical innovation and embedded system design to achieve seamless operation in dual environments. A custom-designed hybrid wheel mechanism enables smooth movement on land using an outer ring structure, while internal fins provide propulsion in water. This eliminates the need for separate locomotion systems and enhances overall efficiency. The robot utilizes an ESP32-CAM module for wireless communication, live video streaming, and user interface control, allowing remote monitoring and operation. An Arduino UNO is employed as the main control unit for handling motor drivers, sensor inputs, and manipulator control. The system is equipped with infrared (IR) sensors for obstacle detection and a high-torque robotic arm capable of performing automated pickup and disposal of waste materials through a predefined sequence.

1.1 PURPOSE OF THE SYSTEM

The primary purpose of this system is to develop an efficient, reliable, and cost-effective hybrid amphibious robotic platform capable of operating in both land and water environments for waste collection in hazardous areas. The system is designed to remotely navigate through difficult terrains, detect obstacles, and safely collect waste materials using an integrated robotic manipulator. This project aims to provide a user-friendly web-based control interface, allowing users to operate the robot in real time

through wireless communication. The ESP32-CAM module enables live video streaming, giving the user visual feedback for precise navigation and operation. The system processes user commands and executes them through an Arduino UNO, which controls motors, sensors, and the manipulator mechanism. The robot is equipped with infrared (IR) sensors for obstacle detection and a predefined automated pickup sequence for efficient waste collection and disposal.

The robot is equipped with infrared (IR) sensors for obstacle detection and a predefined automated pickup sequence for efficient waste collection and disposal. The hybrid wheel design ensures smooth movement on land and effective propulsion in water, enabling seamless transition between different environments.

The overall goal of this system is to minimize human intervention in toxic, polluted, and inaccessible areas by providing a practical robotic solution that enhances safety, efficiency, and environmental cleanliness.

1.2 SCOPE OF THE SYSTEM

The scope of this project covers the design, development, and implementation of a hybrid amphibious robotic system capable of operating efficiently in both land and water environments for waste collection in hazardous areas. The system is designed to be remotely controlled using a web-based interface, enabling users to monitor and operate the robot in real time without direct physical interaction.

The project includes several key functionalities such as amphibious mobility using custom hybrid wheels, real-time video streaming through the ESP32-CAM, wireless communication, obstacle detection using infrared (IR) sensors, and automated waste collection using a robotic manipulator. The system supports navigation across uneven terrains and water surfaces, making it suitable for practical environmental applications.

Users can interact with the system through a simple and intuitive interface, allowing control of movement, monitoring of sensor data, and execution of automated pickup sequences. The integration of camera streaming ensures visual feedback, improving accuracy and control during operation.

This project is applicable in various domains including:

- Water body cleaning and waste management
- Toxic and hazardous environment handling

- Industrial waste collection
- Disaster response and rescue operations
- Remote environmental monitoring

1.3 EXISTING SYSTEM

In the current scenario, waste collection in water bodies and hazardous environments is primarily carried out using manual methods or semi-mechanized systems. These approaches often involve human intervention, which exposes workers to toxic substances, polluted water, and unsafe conditions.

Traditional methods rely on manual labor using tools such as nets, boats, and protective equipment. While these methods are simple, they are time-consuming, inefficient, and pose serious health risks. In hazardous or radioactive environments, human involvement becomes highly dangerous and sometimes impossible.

Some existing robotic systems and cleaning machines are available; however, they are often:

- Expensive and not cost-effective for small-scale applications
- Limited to either land or water, but not both
- Lacking manipulation capabilities for picking and placing waste
- Complex to operate and maintain

Additionally, many systems do not provide real-time monitoring or user-friendly remote control interfaces, limiting their usability in practical scenarios. These limitations highlight the need for a compact, affordable, and multifunctional robotic system capable of operating in both land and water environments

1.4 PROPOSED SYSTEM

The proposed system introduces a hybrid amphibious robotic rover designed to overcome the limitations of existing waste collection methods in hazardous environments. The system combines mechanical innovation with embedded control systems to enable efficient operation on both land and water, along with automated waste collection capabilities. The robot utilizes a custom-designed hybrid wheel mechanism that integrates an outer ring for smooth movement on land and internal fins for propulsion in water. This design allows seamless transition between terrains without requiring separate locomotion systems, improving efficiency and reducing

mechanical complexity.

The system is built using a dual-controller architecture:

- The ESP32-CAM module handles wireless communication, live video streaming, and web-based user interface
- The Arduino UNO manages motor control, sensor data processing, and robotic manipulator operations

A major advantage of the proposed system is its web-based control interface, which allows users to:

- Remotely control robot movement (forward, backward, left, right, stop)
- View live camera feed for real-time monitoring
- Observe IR sensor status for obstacle detection
- Trigger an automated pickup sequence using a single command

The robotic manipulator is designed with high-torque servo motors and performs a predefined sequence to pick and place waste efficiently. This reduces the need for manual control during critical operations and improves consistency. The system incorporates infrared (IR) sensors to detect obstacles and assist in navigation. Communication between the ESP32-CAM and Arduino UNO is achieved through serial communication, ensuring synchronized operation between user commands, sensor feedback, and actuator control.

CHAPTER-2

LITERATURE SURVEY

2.1 REVIEW OF LITERATURE

Several studies have been carried out in the field of cleaning robots, amphibious robotic systems, IoT-based monitoring, and waste collection technologies. These works focus on improving efficiency, automation, and environmental sustainability.

[1] IoT Based River Cleaning Robot

Koli, S. S. [1] developed an IoT-based river cleaning robot designed to collect floating waste from water bodies. The system used sensors, microcontrollers, and wireless communication for remote monitoring and control. The robot was capable of detecting waste and collecting it using a conveyor or mechanical system. The study highlighted the importance of automation in reducing human effort and improving cleaning efficiency. It was observed that IoT integration allows real-time monitoring and control of the robot. The author concluded that such systems are effective for environmental protection and water pollution control.

[2] Floor Cleaning Robot for Domestic Environments

Bordoloi, A. K. et al. [2] designed a floor cleaning robot for domestic use. The robot used motors, sensors, and a microcontroller to perform cleaning operations automatically. Different navigation strategies and sensor-based obstacle detection methods were implemented. The study observed that the robot could move efficiently in indoor environments and avoid obstacles using sensor feedback. The authors concluded that automated cleaning systems reduce manual effort and improve operational efficiency.

[3] Amphibious Robot Design and Applications

Various studies on amphibious robots show that such systems can operate in both land and water environments. These robots use specialized mechanical structures and propulsion systems to achieve mobility across different terrains. Researchers observed that amphibious robots are highly useful in environmental monitoring,

rescue operations, and waste collection. It was concluded that combining land and water mobility significantly enhances the operational range of robotic systems.

[4] ESP32-CAM Based Surveillance and IoT Systems

ESP32-CAM-based systems have been widely used for real-time monitoring and IoT applications. These systems provide live video streaming and wireless communication through web interfaces. Studies show that ESP32-CAM enables low-cost and efficient remote monitoring solutions. It was observed that real-time video feedback improves user control and system reliability. The researchers concluded that ESP32-CAM is suitable for robotics applications requiring visual monitoring.

[5] Robotic Manipulator for Object Handling

Research on robotic manipulators focuses on object pickup, handling, and placement using servo motors. Different configurations of robotic arms have been studied for improving precision and flexibility. It was observed that multi-joint manipulators provide better control and adaptability. The authors concluded that robotic arms are essential for automation in waste collection and industrial applications.

[6] Obstacle Detection Using IR Sensors

IR sensor-based obstacle detection systems are commonly used in mobile robots. These sensors detect objects based on reflected infrared signals. Studies show that IR sensors are cost-effective and suitable for short-range detection. It was observed that sensor accuracy depends on surface properties and environmental conditions. Researchers concluded that IR sensors are effective for basic obstacle avoidance in robotic systems.

[7] Motor Control Using L298N Driver

The L298N motor driver is widely used for controlling DC motors in robotic applications. It allows bidirectional control and speed variation of motors. Studies show that it is suitable for low-cost robotic systems. It was observed that motor performance depends on power supply and load conditions. The authors concluded that L298N is effective for small-scale robotic control systems.

2.2 GAPS IDENTIFIED

From the literature survey, the following gaps are identified:

- Most systems focus on either land robots or water robots, but not both together
- Limited work is available on hybrid amphibious waste collection robots
- Very few systems integrate live video streaming with robot control
- Existing robots lack efficient waste pickup mechanisms using manipulators
- Existing robots lack efficient waste pickup mechanisms using manipulators
- Limited focus on real-time user interaction through web-based dashboards
- Obstacle detection is often basic and not integrated with control feedback
- Less emphasis on cost-effective and compact robotic solutions

2.3 OBJECTIVES

Based on the identified gaps, the objectives of this project are:

- To design and develop a hybrid amphibious robot capable of operating on both land and water
- To implement a robotic manipulator for waste pickup and disposal
- To develop a web-based control system using ESP32-CAM
- To provide real-time video streaming for monitoring and navigation
- To integrate IR sensors for obstacle detection and feedback
- To ensure efficient movement using DC motors and motor driver
- To create a cost-effective and practical solution for environmental waste management
- To improve system usability through a user-friendly control interface

CHAPTER-3

REQUIREMENT & SYSTEM ANALYSIS

Requirement analysis is a crucial phase in system design that involves identifying, analyzing, and defining the needs and expectations of users for a system. It serves as the foundation for developing an efficient, reliable, and user-friendly robotic solution. In this project, requirement analysis helps in understanding how the hybrid amphibious waste collection rover should function, what features it must provide, and how it should perform under different environmental conditions such as land, water, and hazardous areas. It ensures that the system meets both operational requirements (movement, control, manipulation) and user requirements (remote access, monitoring, ease of use).

The requirements of this system are broadly categorized into:

- Functional Requirements
- Non-Functional Requirements

3.1 FUNCTIONAL REQUIREMENTS

Functional requirements define the core functionalities and operations that the system must perform.

The functional requirements of the proposed system are as follows:

Web-Based Control Interface The system should provide a web-based user interface hosted on the ESP32-CAM that allows users to remotely control the robot using a mobile phone or computer.

Live Video Streaming The system should stream real-time video from the ESP32-CAM to the user interface, enabling visual monitoring and precise navigation.

Manual Movement Control

The system should allow users to control the robot's movement in different directions:

- Forward
- Backward
- Left
- Right
- Stop

Automated Pickup Operation

The system should provide a dedicated control (button) to trigger a predefined pickup sequence using the robotic manipulator.

Manipulator Control

The system should control the robotic arm consisting of:

- Shoulder rotation (0°–180°)
- Elbow movement (up and down)

3.1.1 USER INTERFACE & INTERACTION

The user interface and interaction requirements define how users will interact with the hybrid amphibious robotic system. The interface is designed to be intuitive, responsive, and easy to operate, allowing users to control the robot without requiring technical expertise.

The system shall provide a clean and visually organized web-based interface hosted on the ESP32-CAM, accessible through modern web browsers on both desktop and mobile devices.

The interface shall include the following features:

- A live video streaming window displaying real-time camera feed from the robot for monitoring and navigation
- A control panel with clearly labeled buttons for movement:
 - Forward
 - Backward
 - Left
 - Right
 - Stop
- A speed control slider to adjust the movement speed of the robot
- A dedicated “Pickup” button to trigger the automated waste collection sequence
- A sensor status display panel showing real-time IR sensor values (Left, Middle, Right), using indicators such as:
 - Green (no obstacle)
 - Red (obstacle detected)
- The interface shall update sensor data dynamically without requiring page refresh
- A clearly visible and responsive layout that works across different screen sizes,

including smartphones and laptops

- The interface is designed to be intuitive, responsive, and easy to operate, allowing users to control the robot without requiring technical expertise.
- ESP32-CAM, accessible through modern web browsers on both desktop and mobile devices.

3.1.2 CONTROL & ROBOTIC FUNCTIONALITY

The control and robotic functionality requirements define the core operational capabilities of the system, including movement, sensing, communication, and manipulation.

The system shall include the following functionalities:

- The system shall receive movement commands from the user interface via ESP32-CAM
- Commands shall be transmitted to Arduino UNO using serial communication

Real-Time Communication

- The system shall support bidirectional communication between ESP32-CAM and Arduino UNO
- Commands shall be sent from ESP32 to Arduino

Obstacle Detection

- The system shall use multiple IR sensors to detect obstacles
- Sensor data shall be continuously monitored and updated
- The system shall assist the user in navigation by displaying obstacle status

Automated Pickup Mechanism

- The system shall provide a predefined automated sequence for waste collection
- The sequence shall be triggered by a single command from the UI

Manipulator Operation

- The robotic arm shall consist of:
 - Shoulder rotation (0° – 180°)
 - Elbow movement
 - Gripper control

o

Pickup Sequence Functionality

The system shall execute the following sequence:

1. Stop robot movement
2. Lower the arm (elbow movement)
3. Close gripper to grab waste
4. Lift the arm
5. Rotate shoulder to drop position
6. Open gripper to release waste
7. Return arm to initial position

Amphibious Operation

- The system shall support movement on both land and water
- Hybrid wheels shall enable smooth rolling on land and propulsion in water

Power Handling

- The system shall operate using a 12V battery
- Power shall be distributed efficiently to motors, servos, and control modules

3.1.3 DATA COMMUNICATION & SYSTEM INTEGRATION

The data communication and system integration requirements define how different components of the hybrid amphibious robotic system interact and exchange information to ensure smooth and synchronized operation. The system is designed with a dual-controller architecture, where the ESP32-CAM and Arduino UNO communicate continuously to execute user commands and provide real-time feedback.

Serial Communication

- The system shall establish serial communication between ESP32-CAM and Arduino UNO
- The ESP32-CAM shall send control commands (movement and pickup operations) to the Arduino UNO
- The Arduino UNO shall receive, process, and execute these commands

Bidirectional Data Flow

- The system shall support two-way communication:
 - ESP32-CAM → Arduino UNO (control commands)
 - Arduino UNO → ESP32-CAM (sensor data)
- This ensures real-time synchronization between user input and robot response

Sensor Data Transmission

- The Arduino UNO shall continuously read IR sensor values
- Sensor data shall be formatted and transmitted to ESP32-CAM
- The ESP32-CAM shall process and display this data on the user interface

Command Handling Protocol

- The system shall use a simple and efficient command protocol (e.g., single-character commands such as F, B, L, R, S, P)
- Commands shall be transmitted with minimal delay to ensure fast response

Web Communication

- The ESP32-CAM shall host a web server to handle user requests
- User commands from the web interface shall be processed and forwarded to Arduino UNO
- Sensor data received from Arduino shall be updated dynamically on the webpage

3.1.4 PERFORMANCE REQUIREMENTS

Performance requirements define the speed, responsiveness, reliability, and resource utilization of the hybrid amphibious robotic system. These requirements ensure that the system operates efficiently in real-time conditions and provides a smooth user experience during remote operation.

The following performance requirements are specified for the proposed system:

Real-Time Response

- The system shall respond to user commands (movement, stop, pickup) with minimal delay
- The time between user input and robot action shall be within an acceptable real-time range (< 200–500 ms)

Communication Speed

- Serial communication between ESP32-CAM and Arduino UNO shall ensure fast and reliable data transfer

Manipulator Performance

- The robotic arm shall perform pickup operations smoothly without sudden jerks
- The predefined pickup sequence shall execute within a reasonable time frame (2–5 seconds approx.)
- Servo movements shall be controlled gradually to reduce mechanical stress and power spikes

3.2 NON-FUNCTIONAL REQUIREMENT

Non-functional requirements define the quality attributes, performance standards, and usability aspects of the hybrid amphibious robotic system.

3.2.1 USER INTERFACE AND HUMAN FACTORS

- The interface should be visually clear and easy to navigate
- Users should be able to control the robot with minimal steps
- Control buttons and sensor data should be clearly visible

The interface should be responsive and compatible with both mobile and desktop

3.2.2 SYSTEM & SOFTWARE REQUIREMENTS

- The system should be developed using embedded programming (Arduino IDE for ESP32-CAM and Arduino UNO)
- Communication between modules should be handled using serial communication (UART)
- The ESP32-CAM should host a lightweight web server for user interaction
- The system should support WiFi-based communication for remote control

3.2.3 USABILITY

- The system should be easy to use for both technical and non-technical users
- Users should be able to connect to the robot and control it without prior training
- The interface should provide clearly labeled buttons and controls

3.2.4 RELIABILITY

- The system should provide consistent and stable performance during operation
- The robot should handle communication errors gracefully without crashing

- The system should continue functioning under different environmental conditions (land and water)

3.2.5 PERFORMANCE

- The system should respond quickly to user commands with minimal delay
- Real-time video streaming should be stable and continuous
- Sensor data should be updated frequently without noticeable lag

3.2.6 SUPPORTABILITY

- The system should be modular, allowing easy maintenance and upgrades
- Hardware components should be easily replaceable
- Code should be structured and understandable for debugging
- Future enhancements (such as GPS, AI, or autonomous navigation) should be easy.

3.2.7 SECURITY REQUIREMENTS

- The system should restrict unauthorized access to the robot's control interface
- Only connected users within the WiFi network should be able to control the robot
- The system should prevent unintended or accidental command execution
- Basic access control mechanisms (such as SSID control or optional password protection) should be implemented

3.2.8 RESOURCE REQUIREMENTS

Hardware Resources

- ESP32-CAM module for communication and video streaming
- Arduino UNO for control operations
- Motor driver (L298N) for driving DC motors
- 4 DC geared motors for locomotion
- 2 high-torque servo motors for manipulator
- IR sensors for obstacle detection
- 12V Li-ion battery for power supply
- Custom 3D printed hybrid wheels and chassis

Power Requirements

- The system should operate using a 12V battery

- Adequate current should be supplied to motors and servos without voltage drops
- Voltage regulation should be ensured for ESP32 and Arduino

Communication Requirements

- WiFi connectivity for remote access via ESP32-CAM
- Serial communication (UART) between ESP32-CAM and Arduino UNO

User Device Requirements

- A smartphone, tablet, or computer with a web browser
- Ability to connect to the robot's WiFi network

3.2.9 PHYSICAL ENVIRONMENT

- The system should operate in both land and water environments
- The robot should be capable of functioning in:
 - Water bodies (ponds, lakes, drainage areas)
 - Uneven terrain and outdoor surfaces
- The system should withstand moderate environmental conditions such as:
 - Dust and moisture
 - Variable lighting conditions
- Basic waterproofing measures should be implemented to protect electronic components
- The robot should maintain stability while transitioning between land and water

3.3 SYSTEM ANALYSIS

Introduction

System analysis is a crucial stage in system design that involves studying the problem, understanding user requirements, and designing an efficient and practical solution. It helps in defining how the system should function, what features are required, and how different hardware and software components interact with each other.

In this project, system analysis focuses on the development of a hybrid amphibious waste collection rover capable of operating in both land and water environments. The system is designed to address real-world challenges such as waste accumulation in hazardous areas, limited accessibility, and risks associated with human intervention.

The proposed system integrates mechanical design, embedded systems, and

wireless communication to achieve efficient operation. A custom-designed hybrid wheel mechanism enables movement across multiple terrains, while a robotic manipulator allows the robot to pick and place waste materials.

The system follows a distributed control architecture, where different components are assigned specific tasks to improve performance and reliability. The ESP32-CAM module acts as the communication and monitoring unit, handling WiFi connectivity, live video streaming, and user interface interaction. The Arduino UNO functions as the control unit, managing motor drivers, sensor inputs, and manipulator operations.

The hybrid amphibious waste collection rover is designed as an innovative solution to address environmental and safety challenges associated with waste removal in hazardous and inaccessible areas. Traditional methods rely heavily on manual labor, which exposes individuals to toxic substances and unsafe conditions. This system introduces a robotic approach that combines mobility, sensing, communication, and manipulation into a single integrated platform. The robot is capable of navigating across land and water using hybrid wheels, allowing seamless transition between different environments. The control system is divided into two main units: the ESP32-CAM and the Arduino UNO. The ESP32-CAM provides wireless connectivity, live video streaming, and hosts the web-based user interface, enabling remote monitoring and control. The Arduino UNO manages motor operations, sensor inputs, and manipulator control, ensuring precise execution of commands. The robotic manipulator is designed to perform automated waste collection through a predefined sequence, reducing the need for continuous manual control. The integration of IR sensors enhances navigation by providing real-time obstacle detection. The system emphasizes simplicity, efficiency, and cost-effectiveness, making it suitable for practical deployment in applications such as water cleaning, hazardous waste handling, and environmental monitoring.

3.4 USE CASE ANALYSIS

Use case analysis describes how users interact with the hybrid amphibious robotic system to achieve specific tasks. It helps in understanding system behavior from the user's perspective and ensures that all functionalities such as movement, monitoring, and waste collection are properly defined. In this project, the system allows users to remotely control and monitor the robot through a web-based interface hosted on the ESP32-CAM. The interaction involves sending control commands, receiving sensor data, and performing automated operations.

3.4.1 ACTORS IN THE SYSTEM

User

The primary actor who interacts with the system through a web-based interface.

The user:

- Connects to the robot via WiFi
- Controls robot movement
- Monitors live camera feed
- Views sensor data
- Triggers automated pickup operations

ESP32-CAM (Interface & Communication Unit)

- Hosts the web interface
- Streams live video
- Receives user commands
- Sends commands to Arduino UNO
- Receives sensor data and updates UI

Arduino UNO (Control Unit)

- Controls motors and movement
- Processes IR sensor data
- Executes manipulator operations
- Performs automated pickup sequence

Sensors (IR Sensors)

- Detect obstacles in real time
- Send data to Arduino UNO

3.4.2 KEY USE CASES

Manual Robot Control

- User connects to ESP32 WiFi
- Opens web interface
- Uses control buttons to move robot:
 - Forward
 - Backward
 - Left
 - Right

- Stop

System flow:

User → ESP32-CAM → Arduino UNO → Motors

2. Live Monitoring

- User views real-time camera stream
- Uses visual feedback to navigate robot

System flow:

Camera → ESP32-CAM → Web Interface

3. Obstacle Detection Monitoring

- IR sensors detect obstacles
- Data is sent to ESP32
- Displayed on UI (Left / Middle / Right status)

4. Automated Waste Pickup

- User clicks “Pickup” button
- Command sent to Arduino
- Robot performs predefined sequence:
 - Stop
 - Lower arm
 - Grab waste
 - Lift
 - Rotate
 - Drop
 - Reset

Fully automated action

5. Data Communication

- Commands sent from ESP32 to Arduino
- Sensor data sent back to ESP32
- UI updates in real time

6. Amphibious Navigation

- Robot moves on land and water

- Hybrid wheels enable terrain switching

3.4.3 SYSTEM OPERATION FLOW

The following steps describe how the hybrid amphibious robotic system operates from user interaction to execution and feedback:

1. The user connects to the robot's WiFi network and opens the web-based control interface on a browser.
2. The ESP32-CAM loads the control dashboard, displaying
 - Live camera stream
 - Movement controls
 - Sensor status
 - When the user presses a control button (Forward, Backward, Left, Right, Stop), the command is sent to the ESP32-CAM.
 - The ESP32-CAM transmits the command to the Arduino UNO through serial communication.
 - The Arduino UNO receives the command and processes it to control the motors via the motor driver.
 - The robot performs the corresponding movement (navigation on land or water using hybrid wheels).
 - IR sensors continuously detect obstacles and send sensor data to the Arduino UNO.




Fig 3.1: System Architecture of Hybrid Amphibious Waste Collection Rover

CHAPTER-4

MATERIALS AND METHODOLOGY

4.1 INTRODUCTION

The selection of appropriate materials and a well-defined methodology are essential for the successful design and development of the hybrid amphibious waste collection rover. Since the system operates in both land and water environments, it must satisfy multiple design requirements such as buoyancy, corrosion resistance, structural strength, lightweight construction, and durability. This chapter presents a detailed discussion on the materials used for different components of the robot and the step-by-step methodology followed during the design, fabrication, integration, and testing phases. The aim is to ensure that the system is efficient, reliable, and capable of operating in real-world environmental conditions. This chapter describes the materials used and the methodology followed in the design and development of the hybrid amphibious waste collection rover. The selection of materials plays a crucial role in ensuring durability, lightweight structure, water resistance, and mechanical strength. The methodology explains the step-by-step process involved in designing, fabricating, assembling, and testing the system.

4.2 MATERIAL SELECTION

The robot is designed using a combination of 3D printed materials and mechanical components to achieve optimal performance in both land and water environments.

4.2.1 PETG Material for Boat Structure

Polyethylene Terephthalate Glycol (PETG) is used for manufacturing the main body of the robot, including the boat structure.

PETG is selected due to its excellent properties such as high strength, water resistance, and durability. Since the robot operates in water, it is essential to use a material that does not degrade or absorb moisture. PETG provides good chemical resistance and maintains structural integrity even under prolonged exposure to water.

Additionally, PETG offers better impact resistance compared to PLA, making it suitable for handling external forces during operation. Its flexibility prevents cracking, and it can withstand moderate mechanical stress. The smooth surface finish also helps in reducing water resistance during movement.

4.2.2 PLA+ Material for Manipulator

PLA+ is used for fabricating the robotic manipulator components such as the shoulder, elbow, and gripper. PLA+ is chosen because it provides better strength and durability compared to standard PLA, while still being easy to print. It allows the creation of complex shapes and detailed structures required for the manipulator mechanism.

The material offers good dimensional accuracy, which is essential for proper joint movement and alignment. Since the manipulator requires precision and lightweight components, PLA+ is an ideal choice. It also ensures smooth operation of servo-controlled joints.

4.2.3 Stainless Steel Rods for Structural Support

Hollow stainless steel rods are used to connect different parts of the manipulator and provide structural support.

These rods are selected because of their high strength-to-weight ratio and corrosion resistance. Since the robot operates in water, corrosion resistance is a critical factor. Stainless steel ensures long-term durability without rusting.

The hollow structure reduces weight while maintaining sufficient strength, allowing smooth movement of the manipulator without adding unnecessary load on the servo motors.

4.3 METHODOLOGY

The development of the hybrid amphibious waste collection rover is carried out in multiple stages, including design, fabrication, assembly, and testing.

4.3.1 Design Phase

The robot components are designed using CAD software. The boat structure, manipulator arm, and mounting components are modelled to ensure proper fitting and functionality.

Special attention is given to:

- Weight distribution for stability in water
- Placement of motors and electronics
- Design of manipulator joints for smooth motion
- Waterproofing considerations

4.3.2 Fabrication Using 3D Printing

The designed components are fabricated using 3D printing technology.

- PETG is used for printing the boat body
- PLA+ is used for printing the manipulator parts
- Proper print settings such as layer height, infill density, and temperature are selected to ensure strength and durability

3D printing allows the creation of customized and complex geometries required for the robot.

The hollow structure reduces weight while maintaining sufficient strength, allowing smooth movement of the manipulator without adding unnecessary load on the servo motors. robot components are designed using CAD software. The boat structure, manipulator arm, and mounting components are modelled to ensure proper fitting and functionality.

4.3.3 Assembly of Components

After fabrication, all components are assembled carefully.

- Motors are mounted to the boat structure
- L298N motor driver is connected to DC motors
- Arduino UNO is used for motor and sensor control
- ESP32-CAM is mounted for communication and camera streaming
- IR sensors are placed for obstacle detection
- Manipulator is assembled using servo motors and stainless steel rods

All electrical connections are properly insulated and secured.

4.3.4 Integration of Control System

The control system is divided into two parts:

- Arduino UNO handles motor control, servo operation, and sensor data
- ESP32-CAM manages WiFi communication, live streaming, and web interface

A web-based dashboard is developed to control the robot and monitor real-time data.

4.3.5 Testing and Validation

The system is tested under different conditions to ensure proper functioning.

- Movement testing on land and water
- Obstacle detection using IR sensors
- Manipulator operation for waste pickup

- Live streaming and control response testing

Any issues observed are corrected to improve performance.

4.4 SUMMARY

This chapter discussed the materials used and the methodology followed in developing the hybrid amphibious waste collection rover. The use of PETG for the boat structure ensures durability and water resistance, while PLA+ provides precision and flexibility for the manipulator. Stainless steel rods enhance structural strength. The methodology includes design, fabrication, assembly, integration, and testing, resulting in a fully functional robotic system capable of waste collection in both land and water environments. PETG was chosen for the boat structure due to its superior mechanical strength, flexibility, and excellent resistance to water and environmental conditions. Its ability to maintain structural integrity under continuous exposure to water makes it highly suitable for amphibious applications. PLA+ was used for the manipulator components because of its ability to produce complex geometries with high precision while maintaining adequate strength and lightweight characteristics. The use of hollow stainless steel rods further enhanced the structural stability of the manipulator while minimizing additional weight, ensuring smooth and efficient motion. Overall, this chapter demonstrates that the combination of appropriate material selection and a well-defined development methodology results in a robust, efficient, and scalable robotic system.

CHAPTER-5

SYSTEM DESIGN

5.1 INTRODUCTION

System design is a crucial phase that focuses on defining the architecture, components, modules, and data flow of a system. It transforms the requirements identified during the analysis phase into a structured design that guides the implementation of the system.

In this project, the system design focuses on developing a hybrid amphibious waste collection rover that integrates mechanical design, embedded systems, and wireless communication. The design ensures that the system is efficient, modular, scalable, and capable of operating in real-world environments such as land, water, and hazardous areas. The design emphasizes:

- Real-time remote control
- Efficient communication between modules
- Stable operation of motors and servos
- User-friendly interaction through a web interface

5.2 SYSTEM ARCHITECTURE

The system architecture defines how different components of the hybrid amphibious robotic system interact with each other. The proposed architecture follows a modular and layered approach to ensure flexibility, scalability, and efficient operation.

User Interface Layer (Web Control Interface)

- Hosted on the ESP32-CAM
- Accessible through a web browser (mobile or desktop)
- Provides:
 - Live camera streaming
 - Movement controls
 - Pickup button
 - Sensor status display
- Sends user commands to ESP32-CAM
- Displays real-time feedback from the robot

- Acts as the bridge between user and robot
- Handles:
 - WiFi communication
 - Web server hosting
 - Live video streaming
 - Command transmission
- Receives commands from UI
- Sends commands to Arduino UNO via serial communication

5.3 OUTPUT LAYER

The output layer is responsible for presenting real-time information and feedback to the user through the web interface.

- Displays live camera stream from ESP32-CAM
- Shows real-time IR sensor status (Left, Middle, Right)
- Provides visual feedback of robot movement and environment
- Displays system status messages such as:
 - “Connected”
 - “Command Executed”
 - “Obstacle Detected”
- Ensures that the user can monitor and control the robot effectively in real time

5.4 COMMUNICATION & PROCESSING LAYER

This layer manages the communication between different components of the system and ensures smooth execution of commands.

- ESP32-CAM handles:
 - Receiving commands from the web interface
 - Sending commands to Arduino UNO via serial communication
 - Receiving sensor data from Arduino
- Arduino UNO handles:
 - Processing received commands
 - Controlling motors and servos

- Reading sensor data
- Ensures synchronized operation between user input, robot movement, and feedback

5.5 CONTROL LOGIC LAYER

This layer defines how the robot behaves based on commands and predefined logic.

- Executes movement commands:
 - Forward, Backward, Left, Right, Stop
- Implements automated pickup sequence:
 - Stop robot
 - Lower arm
 - Grab waste
 - Lift arm
 - Rotate and drop waste
 - Reset position
- Ensures smooth and safe operation of motors and servos




Fig 5.1: Flowchart of Robot Operation

5.6 SYSTEM COMPONENTS

The system is divided into multiple components that work together to perform remote control, real-time monitoring, obstacle detection, and automated waste collection.

5.6.1 CONTROL & EMBEDDED SYSTEM IMPLEMENTATION

The control system is responsible for handling command execution, sensor data processing, and coordination of all hardware components.

Key Functionalities:

- Receives control commands from ESP32-CAM via serial communication
- Processes commands to control robot movement (forward, backward, left, right, stop)
- Controls DC motors through the motor driver
- Operates servo motors for manipulator movement (shoulder, elbow, gripper)
- Sends sensor feedback to ESP32-CAM for display on user interface

Core Components Involved:

Arduino UNO

- Acts as the main control unit
- Handles motor control, servo control, and sensor processing

Motor Driver (L298N)

- Controls direction and speed of DC motors
- Enables movement of the robot

Servo Motors

- Control robotic arm movements
- Enable automated waste pickup and placement

IR Sensors

- Detect obstacles in real time

- Provide input for safer navigation

5.6.2 FRONTEND & USER INTERFACE DESIGN

The frontend of the system is implemented as a web-based control interface hosted on the ESP32-CAM. It provides an intuitive and responsive platform for users to remotely monitor and control the robot in real time. The interface is designed to be simple, user-friendly, and accessible through standard web browsers on both mobile devices and computers.

Key Features of the User Interface

- Live Camera Streaming
- Displays real-time video feed from the ESP32-CAM, allowing the user to monitor the robot's surroundings and navigate effectively.




Fig 5.2: Embedded Control Logic and Operation Implementation

5.7 CONTROL LOGIC & SOFTWARE DESIGN

The core of the system is based on embedded control logic that manages robot movement, sensor processing, communication, and automated manipulation. The system is designed using microcontroller-based programming on ESP32-CAM and Arduino UNO to ensure real-time responsiveness and efficient execution.

5.7.1 INPUT PROCESSING & COMMAND HANDLING

Before executing any operation, user inputs and sensor data are processed to ensure correct and efficient system behavior.

User Command Processing

- Commands are received from the web interface
- Commands include:
 - Movement (Forward, Backward, Left, Right, Stop)
 - Pickup operation
- Commands are encoded into simple formats (e.g., characters like F, B, L, R, S, P)
- ESP32-CAM transmits commands to Arduino UNO via serial communication




Fig 5.3: Embedded Control Logic and Operation Flow of Hybrid Amphibious Waste Collection Rover

5.7.2 MODEL PERFORMANCE

The performance of the hybrid amphibious robotic system is evaluated based on responsiveness, reliability, mobility, and real-time operation.

Key Performance Features:

Provides real-time response to user commands with minimal delay

Ensures smooth movement on both land and water using hybrid wheels

5.8 AUTONOMOUS AGENT & FUTURE ENHANCEMENTS

5.8.1 AUTONOMOUS AGENT CONCEPT

An autonomous agent is a system capable of performing tasks independently by sensing its environment, processing data, and making decisions without continuous human control.

In the context of this project, the hybrid amphibious waste collection rover can be extended into an autonomous robotic system capable of navigating and collecting waste with minimal human intervention. autonomous agent is a system capable of performing tasks independently by sensing its environment, processing data, and making decisions without continuous human control. autonomous agent is a system capable of performing tasks independently by sensing its environment, processing data, and making decisions without continuous human control.

5.8.2 WORKING OF AUTONOMOUS AGENT

The autonomous robotic system operates in a continuous loop-based mechanism:

- Capture real-time data from sensors and camera
- Analyze surroundings and detect obstacles
- Decide movement direction based on environment
- Navigate robot (land/water movement)
- Identify waste object (future enhancement with vision)
- Execute pickup sequence using manipulator
- Move to disposal location
- Drop collected waste

FUTURE ENHANCEMENTS

- Integration of AI-based object detection using ESP32-CAM or external module
- Addition of GPS module for autonomous navigation and return-to-home feature
- Implementation of path planning algorithms
- Improved waterproofing and durability
- Solar-powered charging system
- Mobile app-based control instead of web interface
- Integration of advanced sensors (ultrasonic, gas sensors for toxic detection)




Fig:5.4: Embedded Autonomous Robot Functionality

5.8.3 FUTURE ENHANCEMENTS

The proposed system can be further enhanced by integrating advanced technologies to improve autonomy, efficiency, and real-world applicability. The following enhancements can be considered:

- Real-time camera monitoring and streaming for live navigation
- Optimized control algorithms for faster response and smoother movement
- AI-based waste detection integration for autonomous pickup
- GPS-based tracking and navigation system
- Mobile application development for better control and user experience
- Cloud connectivity for remote monitoring and data logging

5.9 CONCLUSION

The system design provides a clear and structured approach for implementing the hybrid amphibious waste collection rover. It ensures that all components—including user interface, communication system, control unit, sensors, and actuators—work together efficiently to achieve reliable operation in real-time conditions.

The adoption of a distributed architecture using ESP32-CAM and Arduino UNO improves system performance, flexibility, and ease of control. The integration of a web-based interface enables seamless remote operation, while live video streaming and sensor feedback enhance user awareness and navigation accuracy.

By combining amphibious mobility, real-time communication, and automated manipulation, the system demonstrates an effective solution for waste collection in hazardous and inaccessible environments. The design emphasizes cost-effectiveness, modularity, and scalability, making it suitable for practical real-world applications. Overall, the proposed system lays a strong foundation for future advancements in autonomous robotics, environmental monitoring, and smart waste management systems.

CHAPTER-6

IMPLEMENTATION

6.1 INTRODUCTION

The implementation phase is a crucial stage in the development of the hybrid amphibious waste collection rover, where the system design is transformed into a fully functional robotic platform. This phase involves integrating hardware and software components such as the ESP32-CAM, Arduino UNO, motor drivers, sensors, and the robotic manipulator. The system is implemented using embedded programming and IoT-based communication to achieve real-time control, monitoring, and automated operations. The ESP32-CAM is used for wireless communication, web interface hosting, and live video streaming, while the Arduino UNO is responsible for motor control, sensor processing, and execution of the manipulator sequence.

The primary objective of the implementation is to build a system capable of:

- Remote control through a web-based interface
- Real-time video streaming for monitoring
- Efficient movement on both land and water
- Obstacle detection using IR sensors
- Automated waste collection using a robotic arm

The system operates in a control pipeline where user commands are received through the web interface, transmitted to the Arduino UNO via ESP32-CAM, and executed through motors and servos, while sensor feedback and camera data are continuously sent back to the user.

6.2 SOFTWARE USED

The system uses the following software and technologies:

Arduino IDE

- Used for programming both ESP32-CAM and Arduino UNO
- Implements control logic, communication protocols, and automation sequences

ESP32-CAM Firmware

- Handles WiFi connectivity
- Hosts the web-based control interface

- Streams live camera feed
- Manages communication with Arduino UNO

Embedded C / C++

- Used for writing control programs for Arduino UNO
- Implements:
 - Motor control logic.

Web Interface (HTML, CSS, JavaScript)

- Embedded inside ESP32-CAM
- Provides user interface for:
 - Robot control
 - Sensor monitoring
 - Camera viewing

Serial Communication (UART)

- Enables communication between ESP32-CAM and Arduino UNO
- Transfers:
 - Control commands
 - Sensor data

6.3 SYSTEM REQUIREMENTS

Hardware Requirements

- ESP32-CAM Module
- Used for WiFi communication, web interface hosting, and live video streaming
- Arduino UNO
- Acts as the main control unit for motors, sensors, and manipulator
- DC Geared Motors (4x)
- Provide movement on land and water
- Motor Driver (L298N)
- Controls direction and speed of DC motors
- Servo Motors (2x High Torque – 60KG)
- Used for robotic arm (shoulder, elbow, gripper)
- IR Sensors (3–4 units)

- Used for obstacle detection
- 12V Li-ion Battery
- Provides power to motors, servos, and control units
- Custom Hybrid Wheels
- Enable amphibious movement (land + water)
- Chassis and Mechanical Frame
- Supports all components and ensures stability

Software Requirements

- Arduino IDE
- Used for programming ESP32-CAM and Arduino UNO
- Embedded C/C++
- Used to implement control logic, communication, and automation
- Web Technologies (HTML, CSS, JavaScript)
- Used to create the control interface hosted on ESP32-CAM
- Used for communication between ESP32-CAM and Arduino UNO

6.4 DATA INPUT & SENSOR DESCRIPTION

The system does not rely on a predefined dataset but operates using real-time data collected from sensors and the onboard camera. These inputs enable the robot to navigate, monitor the environment, and perform waste collection tasks efficiently.




Fig 6.1: Robot Hardware Components Diagram

6.4.1 USER INTERFACE DESIGN

The user interface is implemented as a lightweight web-based control panel hosted on the ESP32-CAM. The design focuses on simplicity, responsiveness, and real-time interaction to enable effective remote control of the robot.

The interface is built using embedded HTML, CSS, and JavaScript, ensuring compatibility with standard web browsers on both mobile devices and computers.

The UI is designed with a simple and intuitive layout:

- The top section displays the live camera stream from the ESP32-CAM for real-time monitoring
- The central section contains movement control buttons for robot navigation
- The bottom section includes additional controls such as:
 - Pickup button (for automated waste collection)
 - Speed control slider
- A sensor status panel is displayed to show real-time IR sensor reading

6.4.2 CONTROL INTERFACE & INPUT HANDLING

The system supports real-time user interaction through a web-based control interface hosted on the ESP32-CAM. Instead of image-based input, the system operates using direct control commands and live camera feedback.

The user connects to the robot's WiFi network and accesses the control panel through a web browser. All interactions are performed in real time without the need for file uploads or preprocessing steps.

Control Input Methods

The system provides the following input methods:

- Manual Control Buttons
 - Forward
 - Backward
 - Left
 - Right
 - Stop

- Pickup Command ButtonTriggers automated waste collection sequence
- Speed Control SliderAdjusts robot movement speed dynamically

Live Camera Handling

- The ESP32-CAM streams real-time video directly to the interface
- The video feed is displayed continuously for navigation and monitoring
- No separate capture or upload process is required

Command Transmission

- User actions are converted into simple control commands
- Commands are sent from the web interface to ESP32-CAM
- ESP32 forwards commands to Arduino UNO via serial communication
- Arduino executes commands through motors and servos

Error Handling

The system handles common issues such as:

- Loss of WiFi connection
- Delayed command execution
- Sensor detection conflicts

Appropriate feedback is provided to the user through the interface to ensure smooth operation.

6.4.3 UI COMPONENTS & LAYOUT

The user interface is designed using a modular structure, where each component is responsible for a specific function. This improves usability, maintainability, and scalability.

The user interface of the hybrid amphibious robotic system is structured using a modular design approach, where each section of the interface is responsible for a specific control or monitoring function. This modular structure ensures clarity, ease of use, and efficient interaction between the user and the robot. The interface is designed to minimize complexity, allowing users to operate the robot with minimal effort while still providing full control and real-time feedback.

At the core of the interface, the system replaces traditional image-based input components with real-time control and monitoring elements. Instead of selecting input modes like image upload or webcam capture, the interface directly provides control mechanisms for navigation and operation. This shift aligns the system with real-world robotic applications, where continuous interaction and responsiveness are essential. The control panel component forms the primary interaction layer, enabling users to send movement commands such as forward, backward, left, right, and stop. These controls are designed to be easily accessible and responsive, ensuring that the robot reacts instantly to user inputs. Alongside this, a dedicated pickup control module allows users to trigger the automated waste collection sequence with a single action, reducing manual effort and improving operational efficiency. The camera display component acts as the visual feedback system of the robot. It continuously streams live video from the ESP32-CAM, allowing users to observe the environment and make navigation decisions in real time. This eliminates the need for separate input capture mechanisms and ensures a seamless control experience.

6.5 FRONTEND (ESP32-CAM WEB INTERFACE)

The frontend of the system is implemented as a lightweight web-based interface hosted directly on the ESP32-CAM module. Unlike traditional web frameworks, this interface is built using embedded HTML, CSS, and JavaScript, allowing the system to run independently without requiring external servers or complex dependencies. The interface is designed to provide real-time control and monitoring of the robot. It acts as the primary interaction point between the user and the robotic system, enabling seamless communication and command execution over WiFi. By hosting the interface on the ESP32-CAM, the system ensures low latency and direct connectivity, making it suitable for real-time robotic applications. The design focuses on responsiveness and simplicity. Users can access the interface through any standard web browser on a mobile device or computer by connecting to the robot's WiFi network. The layout is optimized to adapt to different screen sizes, ensuring smooth operation across devices. The frontend provides a fast and responsive user experience by minimizing processing overhead and using simple control mechanisms.

The architecture follows a modular approach, where different sections of the interface handle specific tasks such as camera display, movement control, sensor monitoring, and automated operation triggers. This structure improves maintainability and allows easy expansion of features in the future.




Fig : 6.2: System Controlling System Sample

6.6 CONTROL SYSTEM IMPLEMENTATION

The core implementation of the system is based on embedded control logic that manages robot movement, sensor processing, communication, and manipulator operations. Instead of a deep learning model, the system relies on microcontroller-based programming using ESP32-CAM and Arduino UNO to achieve real-time performance.

Input

- User commands from web interface:
 - Forward, Backward, Left, Right, Stop
 - Pickup operation
- Real-time data from:
 - IR sensors (obstacle detection)
 - ESP32-CAM (live video stream)

Processing

- ESP32-CAM:
 - Receives user commands
 - Streams live video
 - Sends commands to Arduino UNO

Arduino UNO:

- Processes commands
- Controls DC motors via motor driver
- Controls servo motors for manipulator

6.7 OBSTACLE DETECTION IMPLEMENTATION

Obstacle detection in the system is performed using infrared (IR) sensors, which enable the robot to identify obstacles in its path and assist in safe navigation.

The IR sensors continuously monitor the surroundings and provide digital signals indicating the presence or absence of obstacles. These signals are read by the Arduino UNO and used to update the system status in real time.

The process begins with the sensors detecting reflected infrared signals from nearby objects. Based on this detection, the sensors output HIGH or LOW signals, which are interpreted by the Arduino UNO.

The processed sensor data is then transmitted to the ESP32-CAM, where it is displayed on the user interface as obstacle indicators (Left, Center, Right). This allows the user to make informed navigation decisions.

The system ensures that obstacle detection operates continuously during robot movement, providing real-time feedback and improving safety.

6.8 MANIPULATOR CONTROL IMPLEMENTATION

The manipulator system is responsible for performing automated waste collection using servo motors. It is controlled by the Arduino UNO through predefined motion sequences.

The operation begins when the user triggers the pickup command from the web interface. This command is sent to the Arduino UNO via ESP32-CAM, initiating the automated sequence.

The manipulator consists of multiple servo-controlled joints, including shoulder rotation, elbow movement, and gripper operation. These components work together to perform coordinated actions required for waste collection.

The pickup sequence is executed step-by-step as follows:

1. Stop the robot movement
2. Lower the arm using elbow servo

3. Close the gripper to grab the waste
4. Lift the arm
5. Rotate the shoulder to the drop position
6. Open the gripper to release the waste
7. Return the arm to its initial position

To ensure smooth and safe operation, servo movements are controlled gradually rather than abruptly. This reduces mechanical stress and improves precision.

The manipulator system is designed to operate efficiently in both land and water conditions, making it suitable for real-world waste collection applications.




Fig: 6.3: MANIPULATOR CONTROL IMPLEMENTATION

6.9 MULTI-COMPONENT HANDLING

The system is designed to handle multiple inputs and operations simultaneously, ensuring smooth and efficient real-time performance of the robot.

Instead of processing multiple faces, the system manages multiple components such as sensors, motors, communication modules, and the manipulator in parallel. Each component operates independently while remaining synchronized with the overall system. The Arduino UNO continuously reads inputs from multiple sensors and processes them in a loop-based structure. Each sensor is handled independently to ensure accurate and real-time detection.

- Each IR sensor detects obstacles independently
- Motor control operates continuously based on commands
- Manipulator actions execute without blocking sensor updates
- Communication with ESP32 runs simultaneously

6.10 OUTPUT GENERATION

The system generates:

The output generation module is responsible for producing real-time responses based on user commands and sensor inputs. The system generates multiple types of outputs including robot movement, manipulator actions, live video streaming, and sensor status feedback.




Fig: 6.4: MANIPULATOR CONTROL FEATURES

The ESP32-CAM and Arduino UNO work together to ensure that outputs are generated instantly and accurately. The ESP32-CAM handles user interaction and display, while the Arduino UNO executes physical actions and processes sensor data.

6.11 DATA LOGGING

The system can optionally store operational data for analysis and future improvements. Instead of storing images, the robot can log important runtime information such as commands, sensor readings, and system status.

This feature helps in debugging, performance evaluation, and monitoring system behavior over time.

The stored data may include:

- User commands (movement, pickup actions)
- Sensor readings (IR obstacle detection status)
- System events (start, stop, errors)
- Operation timestamps

Data logging can be implemented using serial output, local storage (SD card), or external cloud platforms for remote monitoring—

To avoid redundancy, repeated or unnecessary data can be filtered before storage, ensuring efficient use of memory and resources.

6.12 CONTROL CODE IMPLEMENTATION

The backend logic of the system is implemented using embedded C/C++ programs running on the ESP32-CAM and Arduino UNO. This code is responsible for handling communication, processing commands, controlling hardware components, and generating outputs. The ESP32-CAM program manages WiFi connectivity, hosts the web interface, streams live video, and communicates with the Arduino UNO. The Arduino UNO program acts as the main execution unit, handling motor control, sensor processing, and manipulator operations.

Core Functionalities Implemented in Code

- Receive commands from web interface
- Transmit commands via serial communication
- Control DC motors for movement
- Control servo motors for manipulator
- Read IR sensor inputs continuously

Sample Logic Flow (Arduino Side) char
command;

```
void loop() {  
  if (Serial.available()) {  
    command = Serial.read();
```

```

switch(command) {
  case 'F': moveForward(); break;
  case 'B': moveBackward(); break;
  case 'L': turnLeft(); break;
  case 'R': turnRight(); break;
  case 'S': stopMotors(); break;
  case 'P': pickupSequence(); break;

}

}

readSensors();
sendSensorData();

}

```

ESP32-CAM Role in Code

- Hosts web server
- Handles HTTP requests
- Streams camera feed
- Sends commands to Arduino

6.13 CONTROL LOGIC CODE (ROBOT IMPLEMENTATION)

The system replaces image-based processing with real-time control logic implemented using embedded programming. Instead of detecting faces and landmarks, the robot processes user commands and sensor inputs to perform navigation and waste collection tasks.

Command Processing Logic

The robot processes incoming commands in a loop-based structure. Each command is validated and executed only if it meets the required conditions, ensuring safe and reliable operation.

```
char cmd;
```

```
void loop() {
```

```

if (Serial.available()) {
  cmd = Serial.read();
  if (cmd == 'F') moveForward();
  else if (cmd == 'B') moveBackward(); else
  if (cmd == 'L') turnLeft();
  else if (cmd == 'R') turnRight(); else
  if (cmd == 'S') stopMotors();
  else if (cmd == 'P') pickupSequence();

}
}

```

Sensor Handling Logic

Instead of bounding boxes, the system processes multiple sensor inputs to detect obstacles. Each sensor is checked independently, and invalid readings are ignored.

```

void readSensors() {
  int left = digitalRead(IR_LEFT); int
  mid  = digitalRead(IR_MID); int
  right = digitalRead(IR_RIGHT);
  if (left == LOW) Serial.println("Obstacle Left");
  if (mid == LOW)  Serial.println("Obstacle Center");
  if (right == LOW) Serial.println("Obstacle Right");

}

```

Key Improvements Over Old System

- Real-time embedded control instead of image processing
- Handles multiple inputs (commands + sensors) simultaneously
- Executes physical actions instead of predictions
- Optimized for low-latency operation

6.14 COMMAND PROCESSING & RESPONSE IMPLEMENTATION

The system processes user commands and generates real-time responses using a structured communication pipeline between the ESP32-CAM and Arduino UNO. Unlike

image-based processing systems, this implementation focuses on handling control commands, executing physical actions, and returning system feedback. The ESP32-CAM acts as the interface layer, receiving commands from the web UI and forwarding them to the Arduino UNO. The Arduino processes these commands, controls the robot hardware, and sends feedback back to the ESP32 for display.

Command Reception & Validation

The system receives user inputs from the web interface in the form of simple commands. These commands are validated before execution to ensure safe operation. The ESP32-CAM processes incoming requests and extracts command values such as:

- Movement commands (F, B, L, R, S)
- Pickup command (P)

If no valid command is received, the system ignores the request and maintains the current state.

Action Execution Logic

The Arduino UNO executes actions based on predefined logic:

- Movement commands control DC motors via motor driver
- Pickup command triggers manipulator sequence
- Stop command halts all operations immediately

Each action is executed independently, ensuring smooth transitions and real-time responsiveness.

Sensor Feedback Processing

The system continuously monitors IR sensor inputs during operation. Sensor values are processed and formatted before being sent back to the ESP32-CAM.

This allows:

- Real-time obstacle detection
- Continuous environment monitoring
- Immediate feedback to user interface

Response Generation

After executing commands and processing sensor data, the system generates output responses:

- Robot movement and manipulator actions
- Sensor status updates (Obstacle / Clear)
- Live camera feed from ESP32-CAM

The ESP32-CAM updates the web interface dynamically, ensuring the user receives real-time feedback without delays.

Continuous Operation Loop

The system operates in a continuous loop, ensuring uninterrupted functionality:

1. Receive user command
2. Validate command
3. Send command to Arduino
4. Execute action
5. Read sensor data
6. Send feedback to ESP32
7. Update UI
8. Repeat

Error Handling

The system includes basic error handling mechanisms:

- Invalid command detection
- Communication failure handling
- Sensor error tolerance
- Safe stop in case of unexpected behavior

6.15 SYSTEM TESTING AND VALIDATION

System testing is an essential phase in the development of the hybrid amphibious waste collection rover, ensuring that all components function correctly and the system performs

reliably under real-world conditions. The testing process was carried out in multiple stages, including individual component testing, integration testing, and full system testing.

Initially, each hardware component was tested independently. The ESP32-CAM module was verified for stable WiFi connectivity and live video streaming. The Arduino UNO was tested for accurate execution of motor control and servo operations. IR sensors were calibrated to ensure proper obstacle detection within the required range.

Following component-level testing, integration testing was performed to ensure proper communication between the ESP32-CAM and Arduino UNO. Serial communication was validated by sending control commands and verifying corresponding actions. Sensor data transmission from Arduino to ESP32 was also tested to confirm real-time updates on the user interface.

Finally, full system testing was conducted in controlled environments. The robot was tested on both land and water surfaces to evaluate its amphibious capabilities. The manipulator was tested for its ability to pick and place objects accurately. The system demonstrated stable performance, smooth control, and reliable operation under different conditions.

6.16 RESULTS AND DISCUSSION

The implemented system successfully demonstrates the functionality of a hybrid amphibious robotic platform capable of performing waste collection tasks in real-time. The results indicate that the system meets the design objectives and operates efficiently in practical scenarios.

The robot was able to navigate smoothly on both land and water using hybrid wheels. The outer ring structure provided stability on land, while the fins enabled propulsion in water without significant resistance. The transition between land and water was achieved without major performance issues.

The live video streaming feature provided clear and continuous visual feedback, allowing the user to control the robot effectively. The web-based interface functioned reliably across multiple devices, including smartphones and laptops.

Obstacle detection using IR sensors proved to be effective in preventing collisions. The sensor feedback was updated in real time, enabling the user to make quick decisions during navigation.

The manipulator system successfully performed waste pickup operations using predefined sequences. The use of high-torque servo motors ensured sufficient strength and precision for handling objects.

Overall, the system demonstrated:

- Reliable real-time control
- Stable communication between modules
- Effective obstacle detection
- Successful execution of automated pickup tasks

6.17 LIMITATIONS OF THE SYSTEM

Despite the successful implementation, the system has certain limitations that can be addressed in future improvements.

One of the primary limitations is the reliance on manual control for navigation. Although the system provides real-time feedback, it still requires user intervention for decision-making. Full autonomy has not yet been implemented.

The use of IR sensors limits obstacle detection accuracy in certain conditions, such as highly reflective or transparent surfaces. Advanced sensors could improve detection reliability.

Battery life is another constraint, as continuous operation of motors, servos, and camera consumes significant power. This limits the duration of operation in real-world scenarios.

Additionally, the current system does not include advanced environmental sensing such as gas detection or water quality analysis, which could enhance its applicability in hazardous environments.

6.18 ADVANTAGES OF THE SYSTEM

The proposed system offers several advantages over traditional waste collection methods and existing robotic solutions.

The amphibious design allows the robot to operate in both land and water environments, making it highly versatile. This capability is particularly useful for cleaning water bodies and inaccessible areas.

The integration of ESP32-CAM enables real-time video streaming and wireless

control without requiring additional communication hardware. This reduces system complexity and cost.

The modular design of the system allows easy maintenance and future upgrades. Components such as sensors, actuators, and control modules can be modified or replaced without affecting the overall system.

The automated manipulator reduces manual effort and improves efficiency in waste collection tasks. The predefined sequence ensures consistent operation.

The system is cost-effective compared to commercial robotic solutions, making it suitable for practical deployment in developing regions.

6.19 APPLICATIONS OF THE SYSTEM

The hybrid amphibious robotic system can be applied in various real-world scenarios:

- Cleaning waste from lakes, ponds, and drainage systems
- Handling toxic or hazardous materials in industrial areas
- Environmental monitoring and maintenance
- Disaster management operations in flooded areas
- Remote inspection and surveillance

The versatility of the system makes it suitable for both commercial and research applications.

6.20 SUMMARY

The implementation of the hybrid amphibious waste collection rover demonstrates a successful integration of mechanical design, embedded systems, and wireless communication. The system achieves real-time control, efficient navigation, and automated waste collection, making it a practical solution for environmental challenges.

The modular architecture, combined with cost-effective components, ensures scalability and adaptability for future enhancements. With further improvements in autonomy, sensing, and power efficiency, the system has the potential to evolve into a fully autonomous environmental cleanup solution.

6.21 PERFORMANCE EVALUATION

The performance of the hybrid amphibious waste collection rover was evaluated based on multiple parameters including responsiveness, stability, efficiency, and reliability under real-world conditions.

The response time of the system was observed to be within an acceptable range, with minimal delay between user command input and robot execution. The ESP32-CAM ensured fast communication over WiFi, while the Arduino UNO executed commands without noticeable lag.

The mobility performance was tested on different surfaces such as dry land, wet surfaces, and shallow water. The hybrid wheel design provided sufficient traction on land while maintaining propulsion in water. The robot demonstrated stable movement and effective directional control in both environments.

The manipulator performance was evaluated based on its ability to pick and place objects. The servo motors provided adequate torque and precision, allowing the robotic arm to perform operations smoothly. The predefined pickup sequence ensured consistency in operation. The system also showed reliable sensor performance, with IR sensors accurately detecting obstacles in most conditions. The continuous feedback mechanism improved navigation safety.

6.22 POWER MANAGEMENT ANALYSIS

Power management is a critical aspect of the system, as it directly affects operational duration and efficiency. The robot is powered using a 12V Li-ion battery, which supplies energy to motors, servos, and control units. During testing, it was observed that the motors consume the highest amount of power, especially during movement in water. Servo motors also contribute to power consumption during manipulator operations. The ESP32-CAM and Arduino UNO consume relatively low power compared to actuators, making them efficient for continuous operation.

To optimize power usage, the system implements:

- Controlled motor speed using PWM
- Gradual servo movements to reduce power spikes
- Idle state when no command is received

Future improvements can include power monitoring circuits and energy-efficient components to extend battery life. The communication between ESP32-CAM and

Arduino UNO remained stable without significant interruptions. The system handled multiple commands without crashes or unexpected behavior. Mechanical stability was achieved through proper weight distribution and chassis design. The robot maintained balance during movement and manipulator operations. The system also demonstrated fault tolerance by continuing operation even when minor sensor inconsistencies occurred.

6.23 CONCLUSION

The implementation of the hybrid amphibious waste collection rover successfully demonstrates the integration of embedded systems, mechanical design, and wireless communication into a unified robotic platform. The system efficiently performs real-time navigation, obstacle detection, live monitoring, and automated waste collection.

The use of ESP32-CAM and Arduino UNO-based distributed architecture improves system performance, responsiveness, and reliability. The web-based control interface enables seamless remote operation, while live video streaming and sensor feedback enhance user awareness and control accuracy.

The robotic manipulator, combined with predefined control logic, ensures consistent and efficient waste collection. The modular design of the system allows easy scalability and future enhancements such as autonomous navigation, AI-based object detection, and IoT-based monitoring.

Overall, the system provides a cost-effective and practical solution for cleaning waste in hazardous and inaccessible environments, demonstrating strong potential for real-world applications and further technological advancements.

CHAPTER-7

TESTING

7.1 INTRODUCTION

Testing is a critical phase in the development of the hybrid amphibious waste collection rover, ensuring that the system performs reliably under real-world conditions. The objective of testing is to verify that all components—including movement, communication, sensing, and manipulation—function correctly and work together as an integrated system.

The testing process focuses on evaluating system performance, responsiveness, stability, and usability. It ensures that the robot can be controlled remotely, navigate effectively, detect obstacles, and perform automated waste collection tasks.

The system is tested under various conditions such as land movement, water operation, obstacle presence, and different lighting environments to ensure robustness and reliability.

Testing Workflow

- User commands are provided through the web-based control interface
- Commands are transmitted to ESP32-CAM via WiFi
- ESP32-CAM sends commands to Arduino UNO via serial communication
- Arduino UNO processes commands and controls motors and servos
- Sensors detect obstacles and send feedback
- Outputs are analyzed based on system response and accuracy
- Results are compared with expected robot behavior

Workflow Description

- The testing process begins with user interaction through the web interface. The user sends movement or pickup commands, which are transmitted to the ESP32-CAM. The ESP32 forwards these commands to the Arduino UNO, where actual execution takes place.
- The robot performs movement or manipulation based on the received commands. At the same time, IR sensors continuously monitor the environment and provide real-time feedback. The ESP32-CAM streams live video and updates sensor status on the interface.

- The outputs are evaluated based on:
- Correct movement execution
- Accurate obstacle detection

7.2 TESTING METHODOLOGY

The testing methodology involves systematic evaluation of individual components as well as the complete system to ensure proper functionality and reliability.




Fig 7.1: Working Flow of Amphibious Robot System

7.3 TYPES OF TESTING PERFORMED

1. Functional Testing

Functional testing ensures that all features of the hybrid amphibious waste collection rover operate as expected under real-time conditions. This testing verifies the correct behavior of each system functionality from user input to physical output.

The system was tested by sending commands through the web interface and observing the robot's response in terms of movement, sensing, and manipulation.

Tested Functionalities:

- Robot movement (Forward, Backward, Left, Right, Stop)
- Live video streaming using ESP32-CAM
- Real-time control through web interface
- Obstacle detection using IR sensors
- Sensor status display on UI
- Automated pickup sequence using manipulator
- Speed control functionality

2. Unit Testing

Unit testing is performed on individual components of the system to ensure that each module functions correctly before integration.

Each hardware and software module was tested independently to verify its performance and reliability.

Modules Tested:

- ESP32-CAM module (WiFi connection and camera streaming)
- Arduino UNO (command processing and control logic)
- Motor driver and DC motors (movement control)
- Servo motors (manipulator operation)
- IR sensors (obstacle detection)
- Serial communication between ESP32 and Arduino

3. Integration Testing

Integration testing ensures that all components of the hybrid amphibious waste collection rover work together correctly as a complete system. This phase verifies the communication and coordination between hardware modules, control systems, and the user interface.

The testing focuses on validating the interaction between ESP32-CAM and Arduino UNO, ensuring that commands sent from the web interface are correctly executed and feedback is accurately returned.

7.4 SYSTEM CALIBRATION AND TUNING

The system does not require training of a deep learning model; instead, it undergoes calibration and tuning to ensure accurate performance of sensors, motors, and control logic. This process is essential to achieve smooth operation and reliable behavior in real-world environments. The calibration phase involves adjusting hardware parameters and control values to match the physical characteristics of the robot. Each component is tested and fine-tuned to ensure proper functionality.

Sensor Calibration

The IR sensors are calibrated to accurately detect obstacles at a specific distance. The sensitivity of each sensor is adjusted to avoid false detections caused by lighting conditions or reflective surfaces.

The calibration ensures that:

- Obstacles are detected within a defined range
- False positives are minimized
- Sensor readings remain stable during operation

Motor Tuning

The DC motors are tuned to achieve balanced movement and smooth navigation. Speed values are adjusted using PWM control to ensure consistent motion on both land and water.

Key tuning aspects include:

- Equal speed for left and right motors
- Smooth turning without jerks
- Stable forward and backward movement

Servo Calibration (Manipulator)

The servo motors used in the manipulator are calibrated to define precise angle limits for each movement. This ensures that the arm operates safely without mechanical strain.

Calibration includes:

- Setting minimum and maximum angles
- Defining pickup and drop positions
- Ensuring smooth gradual movement

Control Logic Tuning

The command execution logic is optimized to ensure fast and reliable response. Delays and transition timings are adjusted to synchronize movement and manipulator actions. The pickup sequence is fine-tuned to:

- Avoid sudden movements
- Maintain grip stability
- Ensure accurate placement of waste

7.5 SYSTEM EXECUTION AND VALIDATION

The system does not involve training or validation of a deep learning model. Instead, it follows a continuous execution and validation process to ensure that the robot operates correctly in real-time conditions.

Execution Process

The system runs in a continuous loop where commands are received, processed, and executed. At each step, the system verifies whether the action performed matches the intended command.

The execution flow includes:

- Receiving command from user interface

- Processing command in Arduino UNO
- Executing motor or manipulator action
- Reading sensor inputs
- Sending feedback to ESP32-CAM

Validation Process

Validation is carried out by comparing expected robot behavior with actual outcomes during operation.

For example:

- If the command is Forward, the robot should move straight
- If an obstacle is detected, sensor status should update correctly
- If pickup command is triggered, manipulator should complete full sequence

Performance Monitoring

During testing, system performance is continuously monitored based on:

- Response time to commands
- Accuracy of movement
- Sensor reliability
- Stability of communication
- Smoothness of manipulator operation

Error Handling and Correction

If any issue is detected during validation, corrective measures are applied:

- Adjust motor speed for balanced movement
- Recalibrate sensors for accurate detection
- Modify servo angles for better manipulation
- Optimize delays in control logic

Outcome of Validation

The system demonstrated consistent and reliable performance after validation:

- Commands executed accurately
- Sensors responded in real time

7.6 SYSTEM OPTIMIZATION AND STABILITY CONTROL

The system does not use model training techniques such as early stopping or model saving. Instead, optimization is achieved through continuous monitoring and tuning of system performance during operation. The robot is designed to maintain stable and efficient performance by observing system behavior and making necessary adjustments.

Optimization Strategy

The system continuously monitors key parameters such as:

- Response time to user commands
- Stability of movement
- Accuracy of sensor readings
- Smoothness of manipulator operation

If performance degrades, the system is manually tuned by adjusting:

- Motor speed values
- Servo angles and timing
- Sensor thresholds
- Communication delays

This approach ensures consistent performance without requiring complex training processes.

Stability Control

The system includes mechanisms to maintain stable operation:

- Continuous loop execution ensures uninterrupted performance
- Safe stop command prevents unexpected behavior
- Gradual servo movement avoids mechanical stress
- Balanced motor control ensures stable navigation

Outcome

The optimization process results in:

- Improved system responsiveness
- Smooth and stable robot movement
- Reliable sensor feedback

7.7 INTEGRATION TESTING

Integration testing ensures that all components of the hybrid amphibious waste collection rover work together as a unified system. This phase validates the communication and coordination between hardware modules, control logic, and user interface.

System Flow

The integrated system follows the flow:

User Input → Web Interface (ESP32-CAM) → Arduino UNO → Motor & Servo Control → Sensor Feedback → UI Display




Fig 7.2: Testing Pipeline of Hybrid Amphibious Waste Collection Rover

4. Usability Testing

Usability testing is conducted to ensure that the hybrid amphibious waste collection rover is easy to operate and provides a smooth user experience. The focus of this testing is to evaluate how effectively a user can control the robot using the web-based interface without requiring technical expertise. The system was tested by different users to observe ease of control, clarity of interface, and responsiveness of the robot. The interface is designed to minimize user effort while providing complete control over robot operations.

7.8 TEST CASE IDENTIFICATION

Test cases are designed to validate the behavior of the robotic system under different real-world conditions. Each test case checks whether the system performs as expected when given specific inputs.

Test Case 1: Basic Movement Control

Input:

User presses movement buttons (Forward / Backward / Left / Right)

Expected Output:

Robot moves accurately in the selected direction

Test Case 2: Stop Function

Input:

User presses Stop button

Expected Output:

Robot immediately stops all movement



Fig 7.3: Live Robot Operation and Waste Collection

Test Case 3: Obstacle Detection

Input:

Obstacle placed in front of robot

Expected Output:

IR sensor detects obstacle and updates status on UI



Fig 7.4: Obstacle Detection in Amphibious Robot

Test Case 4: Live Camera Streaming

Input:

User opens control interface

Expected Output:

Live video feed is displayed without delay




Fig 7.5: Live Camera-Based Obstacle Detection in Hybrid Amphibious Waste Collection Rover

Test Case 5: Pickup Operation

Input:

User presses Pickup button

Expected Output:

Manipulator performs full pickup and drop sequence



Fig 7.6: Waste Pickup and Drop Operation

7.9 TEST RESULTS ANALYSIS

The results obtained from testing indicate that the hybrid amphibious waste collection rover performs effectively under real-world conditions. The system demonstrates reliable operation in terms of movement, obstacle detection, communication, and waste collection.

The robot was tested across different scenarios including land navigation, water movement, obstacle presence, and pickup operations. The results confirm that the system meets the expected functional requirements with consistent performance.

Key Observations

- Smooth and stable movement on both land and water surfaces
- Reliable obstacle detection using IR sensors in real-time
- Accurate execution of user commands with minimal delay
- Successful pickup and placement of waste using the manipulator
- Stable communication between ESP32-CAM and Arduino UNO
- Effective live video streaming for navigation and monitoring



Fig 7.7: Testing and Performance Analysis of Robot

7.10 LIMITATIONS IDENTIFIED DURING TESTING

During the testing phase of the hybrid amphibious waste collection rover, certain limitations were observed under specific conditions. These limitations highlight areas for future improvement and optimization.

The system performs well under normal conditions, but challenges arise in more complex environments.

7.11 CONCLUSION OF TESTING

The testing phase confirms that the hybrid amphibious waste collection rover performs reliably and meets the intended functional requirements. The system demonstrates effective navigation on both land and water, accurate obstacle detection, and successful waste pickup using the robotic manipulator.

The integration of ESP32-CAM, Arduino UNO, sensors, and control interface ensures smooth communication and real-time operation. The robot responds accurately to user commands and provides stable performance during continuous usage.

Although certain limitations exist, the overall performance of the system is satisfactory and suitable for practical applications such as water surface cleaning and waste management. With further enhancements such as improved sensors, and autonomous navigation, the system can be developed into a more advanced and efficient.

CHAPTER-8

RESULT ANALYSIS

8.1 INTRODUCTION

Result analysis is a crucial phase in evaluating the performance and effectiveness of the hybrid amphibious waste collection rover. This chapter focuses on analysing how well the system performs in real-world conditions, including movement, obstacle detection, communication, and waste collection.

The system is tested under different scenarios such as land navigation, water operation, presence of obstacles, and real-time pickup tasks. The observed outputs are compared with expected behavior to assess the reliability, efficiency, and robustness of the system.

The analysis helps in identifying system strengths, limitations, and areas for improvement.

8.2 ANALYSIS OF ROBOT MOVEMENT AND NAVIGATION

The system uses DC motors and motor drivers to control movement on both land and water surfaces. The movement is controlled through commands sent via the web interface and processed by the Arduino UNO.

Observations

- Smooth forward and backward movement on flat surfaces
- Effective turning control using differential motor speeds
- Stable navigation on water due to floating structure
- Real-time response to user commands

Performance

- Performs well on even and moderately rough surfaces
- Maintains balance during movement on water
- Slight instability observed on highly uneven terrain
- Turning efficiency slightly reduced on slippery surfaces



Fig:8.1 Performance of the robot

8.3 ANALYSIS OF OBSTACLE DETECTION

The system uses IR sensors to detect obstacles in the robot's path and provide feedback to the user.

Observations

- Accurate detection of nearby obstacles
- Real-time sensor feedback displayed on user interface
- Helps prevent collisions during manual operation

Performance

- Performs well under normal lighting conditions
- Slight reduction in accuracy on reflective or shiny surfaces
- Limited detection range based on sensor capability

8.4 ANALYSIS OF PICKUP OPERATION

The robotic manipulator is responsible for collecting waste and placing it into the onboard container.

Observations

- Successful pickup of objects like plastic bottles and small waste items
- Smooth arm movement due to controlled servo operation

- Accurate placement of waste into the onboard orange container

Performance

- Performs efficiently for medium-sized objects
- Requires proper positioning of waste for accurate pickup
- Slight difficulty in handling very small or irregular objects



Fig:8.2 Pickup the trash

8.5 ANALYSIS OF COMMUNICATION AND CONTROL

The system uses ESP32-CAM for WiFi-based communication and live streaming.

Observations

- Real-time control through web interface
- Live video streaming helps in navigation and monitoring
- Commands are executed with minimal delay

Performance

- Stable communication under strong WiFi signal
- Slight delay observed under weak network conditions
- Continuous operation maintained without disconnection



Fig:8.3 Result



8.6 ACCURACY ANALYSIS

The accuracy of the hybrid amphibious waste collection rover is evaluated based on how precisely the system performs its core operations, including movement control, obstacle detection, and waste pickup. Instead of model prediction accuracy, the system accuracy is measured through real-time performance and consistency of actions.

Observations

- Movement accuracy improves with proper motor calibration and speed tuning
- Obstacle detection remains stable within the effective sensing range
- Pickup operation becomes more accurate after adjusting servo angles and timing
- Consistent performance observed after system calibration and repeated testing
- Minor variations occur due to environmental factors such as surface conditions and object placement

Factors Affecting Accuracy

- Surface type (smooth, rough, or slippery terrain)

- Position and orientation of waste objects
- Sensor limitations and interference
- Network strength affecting control response
- Mechanical alignment of the manipulator

8.7 ERROR ANALYSIS

During the testing phase of the hybrid amphibious waste collection rover, certain errors and inconsistencies were observed under specific conditions. These issues help in understanding system limitations and identifying areas for improvement.

Common Issues Observed

- Slight delay in robot response under weak WiFi signal
- Inaccurate obstacle detection on reflective or uneven surfaces
- Manipulator missing the object if not properly aligned
- Difficulty in picking very small or irregular waste objects
- Reduced movement stability on rough or slippery terrain

Reasons for Errors

- Limitations of IR sensors in complex environments
- Dependency on stable wireless communication for control
- Mechanical constraints of the robotic arm
- Variations in surface conditions affecting movement
- Limited precision in servo positioning

Analysis

The errors observed are mostly situational and occur under challenging conditions rather than normal operation. Under standard conditions, the system performs reliably with minimal issues.

These errors highlight the need for:


- Advanced sensors for better detection
- Improved control algorithms
- Enhanced mechanical design for precision

- Stronger communication systems for stability

Despite the observed issues, the errors do not significantly affect the core functionality of the system under normal conditions. The robot continues to perform its intended tasks effectively with acceptable performance levels.

The system demonstrates robustness, and most errors are situational rather than critical, making the solution practical for real-world applications. Despite the observed issues, the errors do not significantly affect the core functionality of the system under normal conditions. The robot continues to perform its intended tasks effectively with acceptable performance levels.

The system demonstrates robustness, and most errors are situational rather than critical, making the solution practical for real-world applications.



8.8 OVERALL ANALYSIS

The overall analysis of the hybrid amphibious waste collection rover highlights the effectiveness of the system in real-world conditions. The system successfully integrates mechanical design, embedded control, and wireless communication to achieve reliable performance.

8.9 CONCLUSION OF RESULT ANALYSIS

The result analysis demonstrates that the hybrid amphibious waste collection rover performs effectively under most real-world conditions. The system achieves reliable navigation, accurate obstacle detection, and efficient waste collection while maintaining a simple and user-friendly control interface.

The integration of ESP32-CAM for communication and live streaming, along with Arduino UNO for control logic, enhances the overall performance and responsiveness of the system. Compared to traditional methods, the proposed system provides a more efficient and safer solution for waste collection in hazardous and inaccessible environments.

Although certain limitations exist, the system is robust and suitable for practical applications. With further improvements in sensor technology, power management, and autonomous capabilities, the system can be enhanced to handle more complex and dynamic real-world scenarios.

CHAPTER-9

CONCLUSION & FUTURE SCOPE

9.1 CONCLUSION

The hybrid amphibious waste collection rover developed in this project successfully demonstrates the integration of mechanical design, embedded systems, and IoT-based communication into a unified robotic platform. The system is capable of operating on both land and water while performing real-time navigation, obstacle detection, and automated waste collection.

The implementation utilizes an ESP32-CAM module for wireless communication, live video streaming, and web-based control, along with an Arduino UNO for handling motor control, sensor processing, and manipulator operations. This distributed architecture ensures efficient performance, real-time responsiveness, and reliable system operation.

A key strength of the system is its ability to provide real-time user interaction through a web-based interface. Users can control the robot remotely, monitor live camera feed, and receive sensor feedback, enabling effective navigation even in hazardous or inaccessible environments. The inclusion of a robotic manipulator allows the system to perform automated waste pickup and placement, reducing human effort and improving operational efficiency.

The system is designed with a modular and scalable architecture, allowing easy integration of additional features such as advanced sensors, autonomous navigation, and AI-based object detection. This flexibility enhances the adaptability of the system for various real-world applications.

From a performance perspective, the robot achieves stable movement, reliable obstacle detection, and consistent pickup operation under normal conditions. The system demonstrates a good balance between functionality, cost, and performance, making it suitable for practical deployment.

Despite its effectiveness, certain limitations exist. The system depends on stable WiFi communication for control, and sensor accuracy may vary under challenging environmental conditions. The manipulator performance is also influenced by object positioning and mechanical constraints.

Future enhancements can further improve the system by incorporating autonomous

navigation, GPS-based tracking, advanced sensing technologies, and improved power management. Integration with mobile applications and cloud-based monitoring can also expand its usability and scalability.

In conclusion, the project successfully achieves its objective of developing a functional, efficient, and cost-effective hybrid amphibious robotic system for waste collection. It demonstrates the practical application of robotics and embedded systems in solving real-world environmental challenges and provides a strong foundation for future research and development.

9.2 FUTURE SCOPE

The hybrid amphibious waste collection rover developed in this project provides a strong foundation for further enhancements and real-world deployment. While the current system performs efficiently in controlled environments, there are several opportunities to improve its capabilities and expand its applications.

One of the major future improvements is the implementation of autonomous navigation, where the robot can move independently without manual control. By integrating advanced algorithms and sensors, the system can detect obstacles, plan paths, and perform cleaning operations automatically.

Another important enhancement is the integration of AI-based waste detection using computer vision. By utilizing the ESP32-CAM or an external processing unit, the robot can identify waste objects in real time and perform pickup operations without user intervention.

The system can be further improved by incorporating a GPS module, enabling features such as location tracking, area mapping, and return-to-home functionality. This would be particularly useful for large-scale cleaning operations in lakes, rivers, and industrial areas.

To enhance communication, the system can be upgraded with long-range communication technologies such as LoRa or GSM/4G modules. This would allow the robot to be controlled over greater distances without relying solely on WiFi.

Power efficiency can be improved by integrating solar panels and advanced battery management systems, enabling longer operation times and making the system more sustainable for continuous environmental monitoring.

The addition of advanced sensors such as ultrasonic sensors, LiDAR, and gas

sensors can significantly improve the robot's ability to detect obstacles, measure environmental conditions, and operate safely in hazardous areas.

The system can also be extended into a multi-robot (swarm robotics) system, where multiple robots work together to clean large areas efficiently. This would increase scalability and operational efficiency.

Further development can include creating a dedicated mobile application for control and monitoring, along with cloud-based data logging and analytics for tracking performance and system status.

CHAPTER-10

REFERENCES

1. Bordoloi, A. K., Islam, M. F., Zaman, J., Phukan, N., & Kakoty, N. M. (2017). A Floor Cleaning Robot for Domestic Environments. In Proceedings of the 3rd International Conference on Advances in Robotics (AIR 2017), New Delhi, India.
2. Koli, S. S. (2025). IoT Based River Cleaning Robot. International Journal of Research Publication and Reviews, 6(3), 8265–8269.
3. Grigore, L. Ş., Ştefan, A.-G., & Orban, O. (2020). Using PET-G to Design an Underwater Rover Through 3D Printing Technology. Materiale Plastice, 57(3), 189–201.
4. Kumar, R., Sharma, H., Saran, C., Tripathy, T. S., Sangwan, K. S., & Herrmann, C. (2022).
5. A Comparative Study on the Life Cycle Assessment of a 3D Printed Product with PLA, ABS & PETG Materials. Procedia CIRP, 107, 15–20.
6. Espressif Systems (2023). ESP32-CAM Technical Reference Manual. Available at: <https://www.espressif.com> (Accessed: 2026).
7. OpenCV (2026). OpenCV Documentation. Available at: <https://docs.opencv.org> (Accessed: 2026).
8. STMicroelectronics (2026). L298N Motor Driver Datasheet. Available online (Accessed: 2026).
9. TutorialsPoint (2026). Servo Motor Control using PWM. Available at: <https://www.tutorialspoint.com> (Accessed: 2026).
10. Components101 (2026). IR Sensor Working Principle and Applications. Available at: <https://components101.com> (Accessed: 2026).
11. Random Nerd Tutorials (2026). ESP32-CAM Web Server and IoT Applications. Available at: <https://randomnerdtutorials.com> (Accessed: 2026).
12. IEEE (2026). Hybrid Amphibious Robotics – Design and Applications. IEEE Xplore Digital Library (Accessed: 2026).