

14. Construct a C program to organize the file using single level directory

AIM:

To construct a c program to organize the file using single level directory

CODE:

```
#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>

#define BUFFER_SIZE 4096

void create()
{
    FILE *fp;

    fp = fopen("sasi.txt", "w");

    if (fp == NULL)
    {
        printf("File creation failed.\n");
        return;
    }

    fclose(fp);
    printf("File created successfully.\n");
}

void copy()
```

```
{
    int source_fd, dest_fd;
    char buffer[BUFFER_SIZE];
    ssize_t bytesRead, bytesWritten;

    source_fd = open("sasi.txt", O_RDONLY);

    if (source_fd == -1)
    {
        printf("Source file not found.\n");
        return;
    }

    dest_fd = open("sk.txt", O_WRONLY | O_CREAT | O_TRUNC, 0666);

    if (dest_fd == -1)
    {
        printf("Destination file creation failed.\n");
        close(source_fd);
        return;
    }

    while ((bytesRead = read(source_fd, buffer, BUFFER_SIZE)) > 0)
    {
        bytesWritten = write(dest_fd, buffer, bytesRead);

        if (bytesWritten == -1)
```

```
    {  
        printf("Error while copying.\n");  
        break;  
    }  
}  
  
close(source_fd);  
close(dest_fd);  
  
printf("File copied successfully.\n");  
}  
  
void deleteFile()  
{  
    if (remove("sasi.txt") == 0)  
    {  
        printf("File deleted successfully.\n");  
    }  
    else  
    {  
        printf("File deletion failed.\n");  
    }  
}  
  
int main()  
{  
    int n;
```

```
printf("1. Create\t2. Copy\t3. Delete\n");
printf("Enter your choice: ");
scanf("%d", &n);

switch (n)
{
    case 1:
        create();
        break;

    case 2:
        copy();
        break;

    case 3:
        deleteFile();
        break;

    default:
        printf("Invalid choice.\n");
}

return 0;
}
```

OUTPUT:

```
1. Create      2. Copy 3. Delete
Enter your choice: 1
File created successfully.

...Program finished with exit code 0
Press ENTER to exit console.
```