


Diagrams



Knowledge Requirements

- Math
- See: Introduction to 3D Game Programming with DirectX 9.0, Part I.
- See: <Program Files Folder>\Microsoft DirectX SDK (June 2010)\Documentation\DirectX9\windows_graphics.chm, from DirectX SDK. Search for D3DXMATRIX3 and D3DXMatrix in "Index" tab.
- See: http://www.zator.com/Cpp/E4_9_18.htm to refresh operators overloading knowledge.

Functional Specifications

- Override default constructor. Sets attributes to zero.
- Override copy constructor.
- Implement constructor that receives a **QBaseMatrix3x3** type.
- Implement constructor that receives 3 **FloatTypes**, one for each Euler angle. The matrix must be initialized as if it was a rotation matrix, using inputs angles.
- Implement constructor that receives only 1 **FloatType**. Set all attributes to that value.
- Implement constructor that receives a 9-**FloatTypes** array. Remember that Quimera Engine uses a row x column convention.
- Implement constructor that receives a pointer-to-**FloatType**. The pointer should point to a dynamically allocated 9-**FloatTypes** array. Remember that Quimera Engine uses a row x column convention.
- Implement constructor that receives three **V4x32-FLOATs**. One per row, ignoring fourth component.
- It is not necessary to override default destructor.
- It is not necessary to override assign operator.
- Operator* must offer an overload that receives a **FloatType** (product by scalar).
- Operator* must offer an overload that receives a **QBaseMatrix3x3**.



- Operator/ must offer an overload that receives a FloatType (division by scalar).
- Operator/ must offer an overload that receives a QBaseVector3.
- A global operator* must be implemented in order to let a FloatType be multiplied by a QMatrix3x3. It's not the same QMatrix3x3 * FloatType than FloatType * QMatrix3x3.
- A global operator/ must be implemented in order to let a FloatType be multiplied by a QMatrix3x3. It's not the same QMatrix3x3 / FloatType than FloatType / QMatrix3x3.
- ResetToZero sets all matrix's elements to 0.
- ToString format: "M3x3(_11, _12, _13)(_21, _22, _23)(_31, _32, _33)". Use STL string.

Design / Technical Requirements

- Use member initialization lists.
- Remember using "explicit" when constructors receive only one parameter.
- No virtual methods.
- Use by-reference parameters always.
- Operator== and Operator!= must have Epsilon value into account.
- Use FloatType constants to store values like 0.
- All methods should be inline.
- No exceptions.
- No error codes.
- No profiling.
- Check for division by zero. Use asserts.
- Respect diagram names.

Support People

- Thund.

