

INDIA TRADE OVERSEAS

WHERE QUALITY MEETS GLOBAL DEMAND



DETAILED PROJECT REPORT

COAL & INDUSTRIAL MATERIALS VERTICAL

Cinematic website strategy, product architecture, coal specifications, lead generation, technology and implementation plan

PREPARED FOR	DOCUMENT DATE
Md Ramiz Raza Khan Founder & Proprietor	7 September 2026 Final DPR

Trade. Supply. Logistics. Growth.

Purpose, scope and governing assumptions

A development-ready plan for a dedicated coal business vertical at www.indiatradeoverseas.com/coal.

Item	Approved Direction
Business	India Trade Overseas - Coal & Industrial Materials
Primary outcome	Generate qualified bulk coal enquiries and route them into the ITO CRM
Geographic portfolio	Assam, Jharkhand, Indonesia and the United States
Primary audience	Industrial buyers, procurement teams, traders, distributors and importers
Experience	Cinematic, minimalist, specification-led and conversion-focused
Commercial model	Quotation-led; no static public pricing or uncontrolled checkout
Proposed URL	www.indiatradeoverseas.com/coal

CRITICAL ACCURACY RULE

The website may present classification and benchmark reference values, but no cargo specification is guaranteed until it is confirmed in a written quotation, contract and accepted certificate of analysis.

01 | Executive summary

India Trade Overseas will create a dedicated Coal & Industrial Materials vertical that combines premium cinematic presentation with disciplined B2B lead capture. The page will explain the four origin categories, help buyers state the correct calorific-value basis, collect the complete technical requirement and convert qualified interest into an actionable commercial enquiry.

The recommended positioning is sourcing, bulk supply, trade and logistics coordination. The page must not imply mine ownership, unrestricted allocation, guaranteed stock or fixed specifications unless those claims are supported by current documents.

Business objectives

- Make the coal offering understandable within five seconds.
- Generate verified enquiries containing origin, GCV basis, quantity, application and destination.
- Present Assam, Jharkhand, Indonesian and U.S. coal without mixing incompatible testing bases.
- Build credibility through transparent specifications, process and documentation.
- Integrate the page with CRM, analytics, campaign attribution and disciplined follow-up.
- Create search visibility for domestic and imported coal requirements.

Scope boundaries

Included	Excluded unless separately approved
Responsive coal landing page	Live commodity exchange or automated price feed
Origin and GCV specification content	Unverified mine ownership or allocation claims

Included	Excluded unless separately approved
Bulk quotation form and document upload	Retail shopping cart and instant payment checkout
CRM, GA4, GTM and conversion tracking	Guarantees not supported by contract or COA
SEO, security, performance and accessibility	Publication of supplier-confidential documents

REPORT MAP

DPR contents

No.	Section
01	Strategic positioning and target buyers
02	Minimalist cinematic experience and information architecture
03	Coal portfolio: Assam, Jharkhand, Indonesia and U.S.
04	Official Indian G1-G17 classification and coking-coal grades
05	Imported-coal benchmark references and calorific-value basis
06	Quotation form, CRM, analytics and lead operating model
07	SEO, performance, security, accessibility and governance
08	Implementation roadmap, acceptance criteria and final web copy

02 | Strategic positioning

RECOMMENDED MARKET POSITION

Specification-led coal sourcing and bulk supply coordination for industrial buyers, supported by clear documentation and practical logistics.

Core brand promise

Reliable Coal Supply. Delivered at Scale.

India Trade Overseas coordinates domestic and imported coal requirements through verified commercial supply channels, subject to grade, source, availability, documentation and mutually agreed commercial terms.

Target buyers

- Thermal and captive power plants
- Cement and sponge-iron manufacturers
- Steel, rolling-mill and metallurgical buyers
- Brick, paper, tea-processing and boiler-based industries
- Coal traders, distributors and stockyard operators
- Industrial procurement companies, contractors, importers and exporters

Buyer information hierarchy

Buyer question	Website response
What do you supply?	Assam, Jharkhand, Indonesian and U.S. coal
Can it match my plant?	GCV-basis selector plus ash, sulphur, moisture and application fields
Can you deliver?	Road, rail, port and multimodal coordination, subject to feasibility
How do I proceed?	One prominent Request Bulk Quote action
What is guaranteed?	Only terms confirmed in the final written contract and accepted COA

EXPERIENCE DESIGN

Minimalist cinematic website system

A premium industrial atmosphere with less interface, stronger hierarchy and a single commercial action.

03 | Visual direction

- Full-bleed coal terminal or bulk-port photography with realistic scale.
- Blue-hour light, coal-black foreground, restrained amber operational lighting.
- Deep navy gradient behind copy; vessel, conveyor and stockpile activity on the right.
- Warm ivory sections below the hero, with muted gold used only for emphasis.
- Thin dividers, generous whitespace and no decorative card overload.
- No pollution-heavy smoke, flames, fake badges, fake numbers or unsafe imagery.

Brand tokens

Role	Name	Hex	Usage
Primary	Midnight Navy	#071826	Hero overlay, headers and dark sections
Material	Coal Black	#101214	Photography, separators and strong contrast
Surface	Graphite	#2B3036	Body text and secondary backgrounds
Accent	Muted Gold	#D4A84F	CTA, rules and micro-labels only
Light	Warm Ivory	#F4F0E7	Content surface and premium contrast

Hero design

The desktop hero should occupy approximately one viewport. The left half carries concise live HTML copy; the right half carries the cinematic port image. Mobile cropping must retain either the vessel or the coal-handling system while maintaining headline legibility.

HERO COPY

COAL & INDUSTRIAL MATERIALS
POWERING INDUSTRY. DELIVERING RELIABILITY.
Domestic and imported coal supply coordinated around specification, quantity and destination.
REQUEST BULK QUOTE

Navigation

Use only HOME, ABOUT, COAL PRODUCTS, LOGISTICS and CONTACT, followed by one outlined REQUEST QUOTE button. The header begins transparent and becomes a solid navy bar on scroll.

Responsive and accessible behavior

- Use live text instead of text embedded inside the hero image.
- Maintain WCAG AA contrast, keyboard navigation and visible focus states.
- Provide reduced-motion behavior and avoid auto-playing sound.
- Stack the quotation form into one column on mobile.
- Allow wide technical tables to scroll horizontally without clipping.

PAGE ARCHITECTURE

Conversion-focused content sequence

04 | Recommended section order

No.	Section	Commercial job
01	Cinematic hero	Identify the offer and drive Request Bulk Quote
02	Capability line	Domestic Coal Imported Coal Logistics Support
03	Coal portfolio	Four origin categories with safe specification language
04	Specification selector	Capture GCV basis, ash, sulphur, moisture and size
05	Grade reference	Official Indian G1-G17 and imported reference tables
06	Applications	Help buyers match the enquiry to plant use
07	Process	Requirement to delivery in six clear stages
08	Quality and documents	Explain testing, COA, weighment and documentation
09	Quotation form	Collect a decision-ready commercial requirement
10	FAQ and final CTA	Resolve objections and close the conversion path

Conversion principles

- Do not show static prices; coal pricing changes with source, grade, freight and market conditions.
- Repeat the bulk-quote CTA after the portfolio, specification table and final FAQ.
- Qualify before calling: origin, GCV basis, quantity, destination and application are mandatory.
- Allow a buyer to upload a specification sheet, but secure and scan every upload.
- Persist campaign attribution through the full form and CRM flow.

Primary on-page messages

Message role	Approved wording
Headline	Powering Industry. Delivering Reliability.

Message role	Approved wording
Portfolio	Assam Jharkhand Indonesia United States
Value proposition	Specification-led sourcing, bulk supply and logistics coordination
Primary CTA	Request Bulk Quote
Secondary CTA	View Coal Specifications
Final CTA	Share Your Coal Requirement

Portfolio at a glance

Origin	Commercial position	Basis / control
Assam	High-calorific domestic reference	Source grade, GCV basis and current COA
Jharkhand	Domestic thermal and metallurgical categories	G1-G17 or coking analysis, source and COA
Indonesia	Imported thermal-coal benchmarks	GAR/NAR, moisture, sulphur, ash and cargo COA
United States	Rank- and basin-specific imported coal	MMBtu or kcal/kg basis plus full cargo analysis

PRODUCT PORTFOLIO

Four origin-led coal offerings

Every product block states a reference range and the parameters that still require COA confirmation.

05 | Assam coal

Assam coal is positioned as a high-calorific domestic option with low-ash characteristics in official mineral literature. Sulphur can be comparatively high, so suitability must be confirmed through a current mine declaration, laboratory report or certificate of analysis before any application-specific commitment.

Reference grade	Official source-specific GCV band
G1	Above 7,500 and up to 7,600 kcal/kg
G2	Above 6,700 and up to 7,000 kcal/kg
G4	Above 6,100 and up to 6,400 kcal/kg

Reference: North Eastern Coalfields, Tikak Colliery. These are source-specific reference grades, not a standing ITO stock guarantee.

Mandatory quotation checks

- Mine/source and declared grade
- GCV and analysis basis
- Total and inherent moisture
- Ash, total sulphur, volatile matter and fixed carbon
- Sizing, quantity, loading point and transport mode

- Buyer application and current certificate of analysis

Jharkhand coal

Jharkhand coal spans multiple coalfields, mines, seams and product categories. It must not be marketed under one universal GCV. Non-coking coal should be identified by the applicable G1-G17 grade; coking coal must be evaluated primarily through ash and coke-making parameters.

Potential category	Required commercial description
Non-coking thermal coal	Mine/source, declared GCV grade, basis, size and COA
Steam/industrial coal	Boiler application, GCV, ash, sulphur, moisture and size
ROM or sized coal	Source permission, sizing, oversize/undersize tolerance and delivery
Washed coal	Yield/source, ash guarantee, moisture and test method
Coking/metallurgical coal	Ash plus full coking analysis; GCV alone is insufficient

Indonesian coal

Indonesian thermal coal should be presented using GAR, or Gross As Received, unless a different basis is expressly agreed. The Indonesian government's HBA framework provides useful benchmark reference specifications, but those values are not automatic specifications for every cargo.

Reference	GCV GAR	Total moisture	Total sulphur	Ash
HBA	6,322 kcal/kg	12.26%	0.66%	7.94%
HBA I	5,300 kcal/kg	21.32%	0.75%	6.04%
HBA II	4,100 kcal/kg	35.73%	0.23%	3.90%
HBA III	3,400 kcal/kg	44.30%	0.24%	3.88%

Reference: Indonesia Ministry of Energy and Mineral Resources, Ministerial Decision 227.K/MB.01/MEM.B/2023. Benchmark reference only.

Imported-cargo enquiry fields

- Required GAR and/or NAR, including rejection value
- Total moisture, inherent moisture, ash and total sulphur
- Volatile matter, fixed carbon, HGI and ash-fusion temperature
- Cargo size, loading port, destination port, laycan and Incoterm
- Inspection agency, sampling method and accepted laboratory

U.S. coal

U.S. coal enquiries may cover anthracite, bituminous, subbituminous, lignite, thermal or metallurgical grades. The following converted values are broad U.S. Energy Information Administration heat-content references; actual cargo specifications depend on basin, mine, preparation, moisture and contract basis.

Coal rank	EIA reference	Approx. kcal/kg equivalent
Anthracite	25.090 MMBtu/short ton	6,976
Bituminous	23.270 MMBtu/short ton	6,470
Subbituminous	17.490 MMBtu/short ton	4,863
Lignite	12.970 MMBtu/short ton	3,606

Conversion: 1 MMBtu per U.S. short ton is approximately 278.0 kcal/kg. Reference values are not cargo guarantees.

TECHNICAL REFERENCE

Indian non-coking coal grade matrix

The Ministry of Coal classifies non-coking coal by Gross Calorific Value.

06 | Complete G1-G17 classification

Grade	GCV band (kcal/kg)
G1	Above 7,000
G2	Above 6,700 and up to 7,000
G3	Above 6,400 and up to 6,700
G4	Above 6,100 and up to 6,400
G5	Above 5,800 and up to 6,100
G6	Above 5,500 and up to 5,800
G7	Above 5,200 and up to 5,500
G8	Above 4,900 and up to 5,200
G9	Above 4,600 and up to 4,900
G10	Above 4,300 and up to 4,600
G11	Above 4,000 and up to 4,300
G12	Above 3,700 and up to 4,000
G13	Above 3,400 and up to 3,700
G14	Above 3,100 and up to 3,400
G15	Above 2,800 and up to 3,100
G16	Above 2,500 and up to 2,800
G17	Above 2,200 and up to 2,500

Reference: Ministry of Coal, Government of India. Actual mine availability and dispatch grade remain subject to current source declaration and commercial confirmation.

Coking and semi-coking classifications

Coking coal cannot be evaluated by GCV alone.

07 | Coking-coal ash grades

Grade	Ash content
Steel Grade I	Not exceeding 15%
Steel Grade II	Above 15% and up to 18%
Washery Grade I	Above 18% and up to 21%
Washery Grade II	Above 21% and up to 24%
Washery Grade III	Above 24% and up to 28%
Washery Grade IV	Above 28% and up to 35%
Washery Grade V	Above 35% and up to 42%
Washery Grade VI	Above 42% and up to 49%

Semi-coking and weakly coking grades

Grade	Ash plus moisture
Semi-Coking Grade I	Not exceeding 19%
Semi-Coking Grade II	Above 19% and up to 24%

Reference: Ministry of Coal, Government of India.

Additional metallurgical parameters

- Total ash, sulphur and phosphorus
- Volatile matter and fixed carbon
- CSN/FSI, CSR, CRI and maximum fluidity
- Vitrinite, moisture and size distribution
- Coke-making suitability for the buyer's blend and process

COMMERCIAL CONTROL

Do not publish or quote a metallurgical coal as suitable for steelmaking based only on a high GCV. Require the buyer's full technical specification and a current source analysis.

GCV basis, test data and offer control

08 | Calorific-value terminology

Term	Meaning	Commercial implication
GCV	Gross Calorific Value / Higher Heating Value	Must state the analytical basis
NCV	Net Calorific Value / Lower Heating Value	Lower than GCV because latent heat is excluded
GAR	Gross calorific value on as-received basis	Common in imported thermal-coal trade
NAR	Net calorific value on as-received basis	Common commercial comparison metric
ARB	As-received basis	Includes the condition and moisture at receipt
ADB	Air-dried basis	Cannot be compared directly with GAR without conversion data
DB	Dry basis	Moisture removed for analytical reporting
DAF	Dry ash-free basis	Excludes moisture and ash; not a delivered-energy figure

MANDATORY WEBSITE NOTE

A statement such as 5,500 kcal/kg is incomplete unless the page, enquiry or quotation also states GAR, ARB, ADB, DB, NAR or another mutually accepted basis.

Complete specification capture

Parameter group	Information required
Origin and source	Country/state, mine/colliery or seller source where permitted
Coal type	Thermal, non-coking, coking, metallurgical, anthracite or lignite
Energy	GCV/NCV, basis, typical value and rejection value
Proximate analysis	Total moisture, inherent moisture, ash, volatile matter and fixed carbon
Other quality	Total sulphur, HGI, AFT, phosphorus or coking parameters as applicable
Sizing	ROM, slack, fines or millimetre range plus tolerance
Quantity	Trial quantity, order quantity and monthly/annual demand
Delivery	Plant/stockyard/port, route, mode, Incoterm and timeline
Inspection	Sampling point, laboratory, agency and result-control mechanism
Commercial	Price basis, taxes, freight, validity, payment and documentation

Application, sourcing and delivery

09 | Industries and applications

Coal selection must reflect the buyer's plant design, fuel-handling system, environmental permissions and process requirements. The website should invite enquiries from the following approved commercial uses without representing universal suitability.

- Thermal and captive power generation
- Industrial boilers and process heating
- Cement, sponge iron, steel and rolling-mill requirements
- Brick, paper and tea-processing industries
- Industrial trading, distribution and stockyard supply

Six-stage sourcing-to-delivery process

Step	Stage	Action
01	Requirement	Buyer submits origin, GCV basis, quantity, application and destination.
02	Review	ITO checks supply-channel, quality, documentation and logistics feasibility.
03	Offer	Available grade, price basis, taxes, freight, validity and terms are documented.
04	Verification	Source documents, COA, inspection and sampling are agreed where applicable.
05	Dispatch	Loading, weighment, transport and dispatch documentation are coordinated.
06	Closure	Delivery records, documents and commercial closure are completed.

Quality and documentation

- Commercial quotation and proforma invoice
- Purchase order and supply/sale contract
- Source declaration and certificate of analysis
- Weighment slip, invoice, e-way bill and transport document
- Railway receipt, bill of lading, origin, inspection and insurance documents where applicable

Logistics capability language

India Trade Overseas coordinates coal movement according to source, shipment size, destination and feasibility through road, rail-linked dispatch, stockyard movement, port handling, bulk vessel shipment or multimodal arrangements. All logistics commitments remain subject to transporter, railway or port acceptance, permits, route conditions, weather and final written confirmation.

Bulk quotation form and qualification logic

10 | Form objective

The form must create an enquiry that the commercial team can evaluate without first calling only to discover basic technical information. It should remain visually simple while expanding conditional fields after the buyer selects a coal category.

Form group	Required fields
Identity	Full name, company, work email, phone/WhatsApp and buyer type
Application	Industry, plant/process and intended use
Product	Origin, coal type, GCV, basis and rejection value
Quality	Ash, sulphur, total moisture, volatile matter, fixed carbon, HGI/AFT if needed
Volume	Order quantity, trial quantity and recurring monthly demand
Delivery	City/plant/port/country, transport mode, Incoterm and required date
Evidence	Specification-sheet upload and additional notes
Consent	Privacy acknowledgement and permission to contact

Dropdown controls

Control	Options
Origin	Assam Jharkhand Indonesia U.S. Other domestic Other imported
Type	Non-coking thermal Steam Coking Metallurgical Anthracite Subbituminous Lignite Not sure
Basis	GAR NAR ARB ADB DB DAF Other
Delivery	Road Rail Port Vessel Multimodal To be advised

SUCCESS MESSAGE

Thank you. Your coal requirement has been received by India Trade Overseas. Our commercial team will review the specification, quantity and destination before responding with the next available commercial steps.

CRM record

- Unique lead ID, timestamp, source page, UTM source and UTM campaign
- Buyer identity, company, country, application and verification status
- Origin, coal type, GCV basis, quality limits, quantity and destination
- Assigned owner, lead stage, follow-up date, notes and uploaded document

Lead routing, tracking and response discipline

11 | Lead stages

- New
- Verification Pending
- Qualified
- Specification Pending
- Sourcing in Progress
- Quotation Sent
- Negotiation
- Inspection/Sample
- Contract Pending
- Order Confirmed
- Dispatch in Progress
- Delivered
- Lost
- Duplicate
- Invalid

Measurement events

Event	Meaning
view_coal_page	Coal page viewed
select_coal_origin	Origin choice made
view_gcv_table	GCV reference viewed
start_coal_quote	Buyer starts form
upload_specification	Specification uploaded
submit_coal_quote	Valid form submitted
coal_whatsapp_click	WhatsApp action selected
coal_phone_click	Telephone action selected
coal_email_click	Email action selected
quote_success	Submission confirmed server-side

Data-control requirements

- GA4 and GTM receive event and campaign data, not private uploaded specifications.
- Meta Pixel and Conversions API receive only compliant marketing events.
- First-party UTM values persist through form submission and CRM creation.

- Every lead has a visible source and assigned commercial owner.
- Duplicate, invalid and spam submissions are separately classified.

Operating KPIs

Marketing	Commercial operations
Visitors and qualified traffic	Lead-response time
Quote CTA click-through	Specification-verification time
Form-start and completion rate	Quotation turnaround time
Cost per qualified coal lead	Follow-up completion rate
Enquiry-to-quotation rate	Quotation-to-order conversion

DISCOVERABILITY

SEO and content strategy

12 | Metadata

Element	Recommended content
Title	Coal Supplier in India Domestic & Imported Coal ITO
Meta description	Source Assam, Jharkhand, Indonesian and U.S. coal through India Trade Overseas. Share GCV, quantity and destination for a bulk quotation.
H1	Reliable Domestic and Imported Coal Supply
Canonical	https://www.indiatradeonseas.com/coal

Keyword themes

- Coal supplier in India; domestic and imported coal supplier
- Assam coal supplier; Jharkhand coal supplier
- Indonesian coal supplier India; U.S. coal supplier India
- Thermal, industrial, non-coking and coking coal supplier
- High GCV coal; GCV coal grades; bulk coal quotation
- Coal logistics, road delivery, rail dispatch and port coordination

Search content rules

- Use one clear primary topic per section; do not repeat keywords unnaturally.
- Link the coal page from Home, Services, footer verticals and relevant articles.
- Add Organization, Service, Product, Breadcrumb, FAQ and ContactPoint schema only where visible content supports it.
- Publish educational content on GCV basis, ash/sulphur selection and domestic-versus-imported comparisons.
- Do not place time-sensitive prices in indexed copy unless an owner and expiry process exist.

Recommended educational articles

Topic	Commercial purpose
GAR vs ADB vs NAR	Pre-qualify buyers and reduce specification mistakes
Indian G1-G17 grades	Earn search visibility and support domestic enquiries
How ash, sulphur and moisture affect use	Improve application-quality conversations
Coal quotation checklist	Drive specification-ready form submissions

PLATFORM REQUIREMENTS

Performance, security and accessibility

13 | Performance

- Serve the hero in AVIF/WebP with responsive srcset and an appropriate preload.
- Target Largest Contentful Paint below 2.5 seconds and Cumulative Layout Shift below 0.1.
- Lazy-load images below the first viewport and avoid heavy animation libraries.
- Use CDN delivery, caching, compressed assets and minimized CSS/JavaScript.
- Test on mid-range Android devices and real mobile networks.

Security

Control area	Minimum requirement
Transport	HTTPS, HSTS and secure cookies
Browser	Content Security Policy and restricted third-party scripts
Forms	Server-side validation, CAPTCHA/bot control and rate limiting
Uploads	Allowlist type/size, malware scan and private object storage
CRM	Role-based access, audit logs and least-privilege API credentials
Recovery	Automated backups, tested restore and incident logging
Secrets	Environment or secret-manager storage; never frontend code

Accessibility

- WCAG AA contrast and keyboard-operable navigation
- Visible focus, descriptive labels, clear validation and error recovery
- Logical heading structure and alternative text for meaningful images
- Reduced-motion support and no essential information carried only by color

Recommended hero alternative text

ALT TEXT
Coal stockpiles, conveyor infrastructure and a bulk carrier at an industrial coal terminal.

CMS, review and commercial governance

14 | Authorized CMS functions

- Add, revise or withdraw an origin/product category
- Update reference grades and upload a current specification sheet
- Set publication and expiry dates for availability notices
- Edit FAQs, SEO metadata and enquiry routing
- Assign ownership and export authorized CRM data
- Maintain revision history and publish a Last reviewed date

Pre-publication approval workflow

Owner	Approval responsibility
Commercial	Confirms product, source, availability language and permitted claims
Technical	Checks GCV basis, quality values, units and suitability caveats
Legal/compliance	Checks ownership, certification, import/export and disclaimer language
Marketing	Checks clarity, SEO, CTA and brand presentation
IT	Checks function, security, analytics, accessibility and release quality

PUBLICATION RULE

No coal availability, specification, price or source claim should remain online after its supporting document or commercial validity has expired.

Commercial disclaimers required near the tables

- Values are classification or benchmark references unless expressly guaranteed in writing.
- Actual mine/cargo analysis, availability and price are subject to final confirmation.
- Specifications shown on different analytical bases are not directly comparable.
- The final contract, accepted COA and agreed inspection mechanism control the transaction.

Implementation roadmap and launch gates

15 | Indicative work plan

Stage	Work	Duration	Output
1	Content and commercial validation	2 days	Approved claims and product matrix
2	UX and responsive wireframe	2 days	Desktop/mobile journey
3	Cinematic UI design	2-3 days	Final visual system
4	Frontend and CMS development	4-5 days	Responsive coal page
5	CRM, form and analytics	2-3 days	End-to-end lead flow
6	Security, performance and QA	2 days	Test evidence and fixes
7	Management review and launch	1 day	Production release

Indicative total: 15-18 working days, subject to approvals, content readiness and access to existing systems.

Launch acceptance criteria

- All four origins appear with accurate, approved specification language.
- The complete G1-G17 table and coking-coal classifications are correct.
- Imported reference values display their correct basis and disclaimer.
- Every quote form submission reaches the CRM and carries attribution.
- Email/CRM notifications, upload controls and success tracking work.
- Desktop, tablet and mobile layouts have no clipping or inaccessible controls.
- No fake statistic, certification or ownership claim is present.
- Legal, privacy and commercial disclaimers are visible and approved.

30-day post-launch review

After 30 days, review traffic quality, CTA click-through, form starts, completion, spam, qualified-lead rate, response time and quotation outcomes. Use evidence to simplify fields or improve copy; do not remove essential GCV, quantity, destination or application qualifiers merely to inflate lead volume.

Copy-ready homepage content

16 | Hero

COAL & INDUSTRIAL MATERIALS

POWERING INDUSTRY. DELIVERING RELIABILITY.

India Trade Overseas coordinates specification-led sourcing and bulk supply of Assam coal, Jharkhand coal, Indonesian coal and U.S. coal for power, manufacturing, infrastructure and approved industrial applications.

[REQUEST BULK QUOTE](#) | [VIEW COAL SPECIFICATIONS](#)

Portfolio introduction

COAL SUPPLY BUILT AROUND YOUR SPECIFICATION

Every industrial requirement is different. Coal selection must consider calorific value, moisture, ash, sulphur, volatile matter, fixed carbon, sizing, application, delivery location and commercial terms. India Trade Overseas coordinates each requirement according to the buyer's declared technical and commercial parameters.

Process introduction

FROM REQUIREMENT TO DELIVERY

Share the coal origin, GCV basis, quantity, application and destination. Our commercial team will review source availability, specifications, documentation and logistics before providing the next commercial steps.

Final conversion block

LOOKING FOR A RELIABLE COAL SUPPLY PARTNER?

Share your required coal origin, GCV, testing basis, quantity, application and destination. India Trade Overseas will review the specification and coordinate the next available commercial steps.

[REQUEST BULK QUOTE](#)
info@indiatradeonoverseas.com

Final website disclaimer

Coal specifications, grades, calorific values, moisture, ash, sulphur, volatile matter, fixed carbon, sizing, origin, quantity, price, freight, taxes, port charges, exchange rate, loading schedule, inspection, documentation, delivery period and payment terms are subject to source availability, current test reports, statutory requirements and final written commercial confirmation.

All GCV figures displayed on the website are classification or reference values unless expressly identified as guaranteed contractual specifications. No website content overrides the final signed quotation, purchase order, sale contract, certificate of analysis or mutually agreed inspection result.

India Trade Overseas does not represent itself as the owner or operator of any mine, coal block, washery, railway siding, port or vessel unless such ownership or operating authority is separately documented.

Official and corporate references

17 | Reference sources

1. India Trade Overseas corporate website
<https://www.indiatradeoverseas.com/>
2. Ministry of Coal, Government of India - Coal Grades
<https://www.coal.nic.in/major-statistics/coal-grades>
3. North Eastern Coalfields - Tikak Colliery
<https://neccoal.co.in/tikak-collinery/>
4. Indian Bureau of Mines - Coal and Lignite reference
https://ibm.gov.in/writereaddata/files/11272019155933Coal_2018_FR.pdf
5. Central Coalfields Limited - Grade notification reference
https://centralcoalfields.in/busns/pdf/30_03_2024_annual_grade.pdf
6. Indonesia Ministry of Energy and Mineral Resources - HBA framework
<https://jdih.esdm.go.id/dokumen/download?id=Kepmen+227+K.pdf>
7. U.S. Energy Information Administration - Heat content
<https://www.eia.gov/environment/emissions/includes/methodology.php>
8. U.S. Energy Information Administration - Coal glossary
<https://www.eia.gov/tools/glossary/?id=coal>

SOURCE-USE NOTE

These references support classification, benchmark and background information. They do not establish present ITO inventory, supplier authorization, cargo quality, allocation or a binding commercial offer.

Company details

INDIA TRADE OVERSEAS

Where Quality Meets Global Demand

Website: www.indiatradeoverseas.com

Email: info@indiatradeoverseas.com

Phone: 01169262028

Registered address: Deramari, Kishanganj, Bihar - 855107, India

Prepared for internal approval and website implementation.