2026

GenericSSO

Enterprise Single Sign-On (SSO) Module

Technical Reference Guide

Version: 1.0
Date: 1st March 2026

1. Introduction

1.1 Purpose

This document provides the technical reference for the **GenericSSO Enterprise Single Sign-On Module**, including supported commands, configuration standards, implementation syntax, and operational guidelines.

1.2 Scope

This guide is intended for:

- System Administrators
- Application Support Teams
- Automation Engineers
- Security Teams

---

2. System Requirements

- Minimum Requirement: **.NET Framework 4.8**
- Windows Operating System
- Configurable file: data.ini

---

3. Configuration Standards

3.1 Application Section Requirement

All parameters must begin with the **Application Name**, defined as a [SECTION] in the data.ini file.

3.2 Case Sensitivity

All commands in data.ini are **case-sensitive**.
Incorrect casing may result in execution failure.

3.3 Unsupported Special Characters

The following characters are not supported:

- Backslash (\)
- Double Quotes (")

---

4. Configuration Understanding (data.ini)

Sr. No.	Platform	Function	Options	Dependency	Description
1	APP & WEB	FORMAT	APP / WEB	—	Specifies the SSO format based on the use case. APP is typically used for client-based SSO, while WEB is used for URL-based SSO. NOTE: APP may also be used for URL-based SSO if required.
2	APP & WEB	MULTIPLEACCESS	TRUE / FALSE	FORM	Enables multiple target access within the same application or webpage during a single session using the same credentials.
3	APP & WEB	EVENTLOGS	TRUE / FALSE	—	Enables logging of error outputs to the system event logs.
4	APP & WEB	FORM	TRUE / FALSE	—	Allows access to any target within the same application or webpage. USE CASE: Multiple websites sharing the same login page and authentication credentials.
5	APP & WEB	DELETE	FILEPATH	—	Deletes specified files prior to initiating SSO.
6	APP & WEB	LOGOFF	TRUE / FALSE	PROCESSNAME	Automatically logs off the session after closing the target application or webpage.
7	APP & WEB	PROCESSNAME	—	—	Specifies the application process name (as shown in Task Manager) to monitor and trigger logoff functionality.
8	APP & WEB	AUTOMATION	—	PATH / BROWSER & URL	Enables automation of SSO for thick or thin clients. Supported commands are defined separately.
9	APP	PATH	FILEPATH	—	Specifies the file path of the target application to be launched for SSO.
10	APP	ARGUMENTS	—	PATH	Defines command-line arguments for the target application, if supported.
11	APP	WORKINGDIRECTORY	FILEPATH	PATH	Specifies the working directory required for the application to function properly.
12	APP	RUNAS.TRADITIONAL	TRUE / FALSE	PATH	When set to TRUE, launches the application using the traditional runas command-line method.
13	APP	RUNAS.USER	USERNAME	PATH	Specifies the username under which the target application will be executed.
14	APP	RUNAS.PASSWORD	ENCRYPTED PASSWORD	PATH	Specifies the encrypted password for the defined user. NOTE: Plain text passwords are not supported. Use the built-in encryptor with the --encryptor argument to generate the encrypted password.
15	APP	RUNAS.DOMAIN	DOMAIN	PATH	Specifies the domain associated with the user account for application execution.
16	WEB	BROWSER	IEXPLORE / CHROME / FIREFOX / MSEDGE	—	Specifies the browser to be used for WEB-based SSO configuration.
17	WEB	URL	—	BROWSER	Defines the target webpage URL for SSO.
18	WEB	SMARTLOGIN	TRUE / FALSE	BROWSER & URL	Enables automated SSO for standard web pages containing username, password, and login fields. NOTE: When set to TRUE, AUTOMATION function is ignored.
19	WEB	DRIVERPATH	FILEPATH	BROWSER & URL	Specifies the Selenium WebDriver path required for browser-based SSO execution.
20	WEB	DEBUG	TRUE / FALSE	—	Enables detailed browser-level logging for troubleshooting and diagnostics.

5. Supported Commands Overview

Command	Description
keys	Executes SendKeys Send
keyswait	Executes SendKeys SendWait
staticpassword	Uses encrypted password file
link	Clicks hyperlink (full text match)
partial-link	Clicks hyperlink (partial match)
button	Automates button interaction
field1..fieldN	Handles dynamic input parameters
msgbox	Displays message dialog
sleep	Pauses execution
blockinput	Enables/Disables user input
bringtofront	Brings process to foreground
checkfname	Validates focused element name
checkfcname	Validates focused element class name
checkfaid	Validates focused element Automation ID
while	Waits for validation condition

---

6. Command Specifications

6.1 keys
Executes Microsoft SendKeys Send method.
Example: keys:{TAB};keys:{ENTER}

6.2 keyswait
Executes Microsoft SendKeys SendWait method.
Example: keyswait:{TAB};keyswait:{ENTER}

6.3 staticpassword
Retrieves encrypted password from file.
Syntax: staticpassword:filename:id/name/xpath/tagname/classname/send/sendwait

6.4 link
Selects hyperlink matching full text.
Example: link:Continue to this Website

6.5 partial-link
Selects hyperlink using partial text match.
Example: partial-link:Continue

6.6 button
Automates button interaction or focuses UI element.
Supported Attributes:

- id
- name
- xpath
- classname
- tagname

Example: button:id:userName;button:name:Password

6.7 field1 … fieldN

Processes dynamic parameters passed after Application Name.

Sequentially reads:

- field1
- field2
- field3
- …

If used with send, the placeholder value is transmitted directly.

Example: field1:xpath://*[@id="email"];field2:send

6.8 msgbox

Displays message dialog defined in data.ini.

Example: msgbox:Process initiated;msgbox:Please wait

6.9 sleep

Pauses execution for specified duration (milliseconds).

Example: sleep:1000

6.10 blockinput

Blocks or enables user input during automation.

Recommended:

- Enable at start
- Disable at completion

Example: blockinput:true;blockinput:false

6.11 bringtofront

Brings process defined under PROCESSNAME in data.ini to foreground.

Example: bringtofront

6.12 checkfname

Validates focused element Name attribute.

Example: checkfname:username;checkfname:password

6.13 checkfcname

Validates focused element Class Name attribute.

Example: checkfcname:username; checkfcname:password

6.14 checkfaid

Validates focused element Automation ID.

Example: checkfaid:10001;checkfaid:10002

6.15 while

Waits until validation condition is satisfied.

Supported Extensions:

- checkfname
- checkfcname
- checkfaid

Example: while:checkfname:username;;while:checkfcname:Password

7. Execution Flow Best Practices

1. Define Application Name section in data.ini
2. Maintain proper command sequence
3. Follow case-sensitive syntax
4. Avoid unsupported characters
5. Validate UI focus before sending credentials
6. Disable blockinput at automation completion

8. Security Considerations

- Use staticpassword for encrypted credentials.
- Never store plain-text passwords.
- Restrict access to data.ini.
- Validate element focus before transmitting sensitive information.
- Limit file access permissions to authorized personnel only.