

- ii. The total coverage and FAR permissible in any plot in a category, shall not be less than that permissible and available to the largest plot in the next lower category.
- iii. ¹**[Height:** Maximum height of the building shall be 15m in plots without stilt parking and 17.5m in plots with stilt parking. Such residential building shall not be considered as high rise building. For purpose of fire and life safety requirements, clearance of Fire Department will be obtained by the individual plot owner.]
- iv. Subdivision of plots is not permitted. However, if there are more than one buildings in one residential plot, the sum of the built up area and ground coverage of all such buildings, shall not exceed the built up area and ground coverage permissible in that plot.
- v. The mezzanine floor, and service floor, if constructed, shall be counted in the FAR.
- vi. **Basement:** Basement shall not be counted towards FAR if used for purposes permissible under Building byelaws namely household storage and parking. Basement area shall not extend beyond the coverage on the ground floor as per permissible and sanctioned built up area, but may extend to the area below the internal courtyard and shaft. Basement if used in terms of Chapter 15.0. Mixed Use regulations shall count towards FAR and shall be liable to payment of appropriate charges, if it exceeds the permissible FAR.
- vii. **Stilts:** If the building is constructed with stilt area of non-habitable height (less than 2.4m), used for parking, such stilt area shall not be included in FAR but would be counted towards the height of the building.
- viii. **Parking:** Parking space shall be provided for within the residential plot as follows:
 - a) 2 Equivalent Car Space (ECS) in plots of size 250-300 sq.m.
 - b) 1 ECS for every 100 sq.m. built up area, in plots exceeding 300 sq.m., provided that, if the permissible coverage and FAR is not achieved with the above-mentioned parking norms in a plot, the parking norms of the preceding category shall be allowed.
- ix. **Density:** For the purpose of density calculations, the dwelling unit shall be considered to accommodate 4.5 persons and the servant quarter to accommodate 2.25 persons.

¹ Modified vide S.O. 2894(E) dated 23-09-2013