7.13.5 Up to 40% of the total setback area can be sunk for light, ventilation and access to basement, provided fire tender movement is not hindered.

7.14 Interior Open Space for Light and Ventilation

7.14.1 The whole or part of one side of one or more rooms intended for human habitation and not abutting on either the front, rear or side open spaces shall abut on an interior open space whose minimum width in all directions shall be 3.0 m in case of buildings not more than 15 m in height unless mechanically ventilated.

7.14.2 **Sunken Courtyard:** Sunken courtyard as 'light well' within building envelop shall be permitted for light and ventilation for basement area.

7.14.3 **Skylight:** Skylight in interior open space(courtyard) may be permitted subject to it may not act as a coverage space on the ground floor and not violate the maximum/ minimum ground coverage as per Development Control Regulations (Annexure VI).

7.15 Provision of parking in Stilts, Podium and Landscaping

7.15.1 In case a building is to be constructed on individual plot with stilt floor, a minimum 2.4m height at soffit level of beam and maximum 2.7m height at soffit level of slab for providing parking space is permitted. In podium(s), minimum 2.4m height at soffit level of beam and maximum 2.7m height at soffit level of slab for providing parking space can be constructed in continuation of the stilt floor having access for the parking without conflicting with the access requirement as per clause 2.0.4.j.iv and 8.2 from the plot line. The terrace of podium may be used for plantation, swimming pool, landscaping, other related structures and parking/entrance and exits as required.

7.15.2 In case of provision of stack-parking in stilt floor, the heights prescribed in 7.15.1 for stilt floor may be relaxed. However, in case of stack parking the height shall be as per design and structural safety requirement.

Notes:

1. *Shear wall/ bracing/ any other structural provision as per IS 1893 (Part 1), IS 13920, IS 4326 may be provided to reduce impact of soft storey in the stilt area.*

7.16 Joint Open Air Space

7.16.1 Every interior or exterior space, unless the latter is a street, shall be maintained for the benefit of such building exclusively and shall be entirely within the owner's own premises.

7.16.2 If such interior or exterior open air space is intended to be used for the benefit of more than one building belonging to the same owner; then the width of such open space shall be the one specified for the tallest building as specified in building byelaw, abutting such open space.

7.17 Exemption to Projections in Open Spaces/Covered area

The following exemption to open space shall be permitted.

7.17.1 Projections into open spaces: Every interior open space shall be kept, free from any erection thereon and shall be open to the sky. Nothing except cornice, chajjas or weather shade (not more than 0.75 m wide) shall overhang or project over the said open spaces so as to reduce the width to less than the minimum required.

Interior open to sky areas shall be allowed to cover with retractable roofing at the terrace level or at minimum double height to prevent climatic/weathering effects and the space below can be used as landscaped area, public space but can not be used for any commercial purpose.