## Konfiguration - Beispiel SNMP

datacollection-group name€"Net-SNMP"

```
<group name="mib2-X-interfaces" ifType="all">
<systemDef name="Enterprise">
                                                          <mibObj oid=".1.3.6.1.2.1.31.1.1.1.1" instance="ifIndex" alias="ifName"</pre>
 <sysoidMask>.1.3.6.1.4.1.
                                                          <mibObj oid=".1.3.6.1.2.1.31.1.1.1.15" instance="ifIndex" alias="ifHighSpeed"</pre>
 <collect>
                                                          <mibObj oid=".1.3.6.1.2.1.31.1.1.1.6" instance="ifIndex" alias="ifHCInOctets'</pre>
   <includeGroup>mib2-interfaces</includeGroup>
                                              <snmp-collection name="default" snmpStorageFlag="select">
   <includeGroup>mib2-X-interfaces</includeGroup</pre>
   <includeGroup>mib2-tcp</includeGroup>
                                                   <rrd step="30">
   <includeGroup>mib2-powerethernet</includeG</pre>
                                                       <rra>RRA:AVERAGE:0.5:1:20160
 </collect>
                                                       <rra>RRA:AVERAGE:0.5:12:14880
</systemDef>
                                                       <rra>RRA:AVERAGE:0.5:288:3660
                                                       <rra>RRA:MAX:0.5:288:3660
                                                       <rra>RRA:MIN:0.5:288:3660
                                                   </rrd>
                                                   <include-collection dataCollectionGroup="MIB2"/>
                                                   <include-collection dataCollectionGroup="Net-SNMP"/>
                                                   <include-collection dataCollectionGroup="PostgreSQL-JDBC"/>
                                              </snmp-collection>
```

## Konfiguration - Beispiel SNMP

datacollection-group name="Net-SNMP"

```
<group name="mib2-X-interfaces" ifType="all">
<systemDef name="Enterprise">
                                                           <mibObj oid=".1.3.6.1.2.1.31.1.1.1.1" instance="ifIndex" alias="ifName"</pre>
 <sysoidMask>.1.3.6.1.4.1.
                                                           <mibObj oid=".1.3.6.1.2.1.31.1.1.1.15" instance="ifIndex" alias="ifHighSpeed"</pre>
 <collect>
                                                           <mibObj oid=".1.3.6.1.2.1.31.1.1.1.6" instance="ifIndex" alias="ifHCInOctets'</pre>
   <includeGroup>mib2-interfaces</includeGroup>
                                              <snmp-collection name="default" snmpStorageFlag="select">
   <includeGroup>mib2-X-interfaces</includeGroup</pre>
                                                   <rrd step="30">
   <includeGroup>mib2-tcp</includeGroup>
   <includeGroup>mib2-powerethernet</includeG</pre>
                                                        <rra>RRA:AVERAGE:0.5:1:20160
 </collect>
                                                        <rra>RRA:AVERAGE:0.5:12:14880
</systemDef>
                                                       <rra>RRA:AVERAGE:0.5:288:3660
                                                        <rra>RRA:MAX:0.5:288:3660
                                                       <rra>RRA:MIN:0.5:288:3660
                                                   </rrd>
                                                   <include-collection dataCollectionGroup="MIB2"/>
                                                   <include-collection dataCollectionGroup="Net-SNMP"/>
                                                   <include-collection dataCollectionGroup="PostgreSQL-JDBC"/>
                                              </snmp-collection>
```