



- Estandar con resortes antiretorcimiento y cinta para almacenaje



ESPECIFICACIONES	
Max. presión de trabajo, Manguera de presión	720 bar
Max. presión de trabajo, Manguera de retorno	25 bar
Rango de temperatura	-20° + 80° C
Tipo de aceite	ISO-L-HV VG15/22
Características:	
<ul style="list-style-type: none"> • Factor de seguridad de las mangueras CORE™: 4 : 1 (= 2880 bar para alta presión en el interior de la manguera) • Todas las mangueras están provistas de un resorte antiretorcimiento en ambos extremos • Disponibles en naranja y azul 	

NORMAS	ENSAYOS
EN 13204	✓
NFPA 1936	✓

modelo	largo	color	número artículo
C 05 OU	5 m	naranja	150.570.042
C 05 BU		azul	150.570.045
C 10 OU	10 m	naranja	150.570.043
C 10 BU		azul	150.570.046
C 15 OU	15 m	naranja	150.570.044
C 15 BU		azul	150.570.047
C 20 OU	20 m	naranja	150.570.095
C 20 BU		azul	150.570.096

Manufacturing sales & service worldwide

Holmatro Rescue Equipment
P.O. Box 33, 4940 AA Raamsdonksveer
The Netherlands
T + 31 (0)162 - 58 92 00
F + 31 (0)162 - 52 24 82
E info@holmatro.com
homepage: www.holmatro.com

Manufacturing sales & service U.S.A., Canada and Latin America

Holmatro, Inc.
505 McCormick Drive, Glen Burnie, MD 21061
U.S.A.
T + 1 - 410 - 768 - 9662
F + 1 - 410 - 768 - 4878
E info@holmatro-usa.com
homepage: www.holmatro-usa.com

© Holmatro® 11-06 (01-07)

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro N.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. If you have any doubts about the correctness or completeness on the information, you shall contact Holmatro (phone number: +31 (0)162-589200).

Nothing from this printed matter can be copied and/or made public in any way without the explicit authorization of Holmatro

