



ESPECIFICACIONES	HTW 1800 C
Descripción	Manual de 2 etapas
Equipada con válvula para	Tecnología CORE™
Artículo número	150.142.015
Presión de trabajo	720 bar
Capacidad tanque de aceite (efectivo)	1800 cc
Descarga por recorrido 1ª etapa	28 cc hasta 45 bar
Descarga por recorrido 2ª etapa	2.3 cc hasta 720 bar
Peso (lista para uso)	11.2 kg
Dimensiones (L x Ancho x Alto)	765 x 240 x 236 mm
Rango de temperatura	-20°C-+60°C
Conjunto de mantenimiento	100.143.092
Notas:	• También disponible como bomba de pie FTW 1800 C art.nr. 150.142.014

**Manufacturing sales & service worldwide**

**Holmatro Rescue Equipment**  
 P.O. Box 33, 4940 AA Raamsdonksveer  
 The Netherlands  
 tel.: + 31 (0)162 - 58 92 00  
 fax: + 31 (0)162 - 52 24 82  
 e-mail: [info@holmatro.com](mailto:info@holmatro.com)  
 homepage: [www.holmatro.com](http://www.holmatro.com)

**DISTRIBUIDOR EXCLUSIVO (España y Portugal)**


**INCIPRESA**

SOCIEDAD UNIPERSONAL  
 Calle Goya, 135 - 2º Izq. 28009 MADRID  
 Teléfono: 913093636 Fax: 913093488

**© Holmatro® 0905**

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro N.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. If you have any doubts about the correctness or completeness on the information, you shall contact Holmatro (phone number: +31 (0)162-589200).

Nothing from this printed matter can be copied and/or made public in any way without the explicit authorization of Holmatro

