


# Styling Lists



# Styling Lists

Lists are fundamental elements in HTML, used for organizing content. CSS allows us to style lists in various ways, enhancing their appearance and usability.

**1. list-style-type:** Defines the type of marker for list items.


```
ul {
  list-style-type: circle; /* Options: disc, circle, square, none */
}
ol {
  list-style-type: upper-roman; /* Options: decimal, lower-alpha, upper-alpha, lower-roman */
}
```

**2. list-style-image :** Uses an image instead of default bullets.

```
ul { list-style-image: url('custom-bullet.png'); }
```

**3. list-style-position :** Defines whether bullets/numbers are inside or outside the list item.

```
ul { list-style-position: inside } /* Options: inside, outside (default)*/
```



# Styling Lists

## 4. Removing Default List Styling:

```
ul { list-style: none; padding-left: 0 }
```

## 5. Custom Bullet Points (using ::before)

```
ul { list-style: none; padding-left: 0; }  
ul li::before { content: '✓'; color: red; }
```

# CSS Position

CSS provides a powerful property called position that allows developers to control how elements are positioned within a web page. Understanding how position works is essential for creating flexible and responsive layouts.

**1. static (Default):** Static positioned elements are placed according to the normal document flow, without any additional positioning applied.

```
.box { position: static; }
```

**2. relative:** When an element is given position: relative;, it remains in the normal document flow but can be adjusted using the top, right, bottom, and left properties relative to its original position.

```
.box { position: relative; top: 20px; left: 20px }
```

**3. absolute:** An element with position: absolute; is removed from the normal document flow and positioned relative to its nearest positioned ancestor or <html> element.

```
.box { position: absolute; top: 10px; right: 20px }
```

**4. fixed:** An element with position: fixed; is completely removed from the document flow and positioned relative to the viewport. It does not move when scrolling the page.

```
.box { position: fixed; top: 10px; left: 20px }
```

# CSS Position

**5. sticky:** A sticky positioned element behaves like a relative element until it reaches a defined scroll position, after which it sticks to the viewport.

```
.box { position: sticky; top: 20px; }
```

## CSS z-index:

The z-index property in CSS controls the vertical stacking order of elements that overlap. It applies to elements that have a position value of relative, absolute, fixed, or sticky (not static).

```
.box { position: absolute; z-index: 2 }
```

## How z-index Works

- Higher values appear on top
- If not set default value is auto
- Works Within Stacking Contexts, a new stacking context is created when an element has a position other than static and a z-index set
- Elements with a negative z-index may appear behind their parent element.

# CSS Overflow

The overflow property in CSS determines how content is displayed when it overflows the boundaries of its container.

**1. visible (Default):** This value allows the content to overflow its container without any restrictions.

```
.box { overflow: visible; }
```

**2. hidden :** This value clips the overflowing content and prevents scrolling or visibility beyond the container.

```
.box { overflow: hidden; }
```

**3. scroll :** This value adds scrollbars to the container, allowing users to scroll to view the overflowing content.

```
.box { overflow: scroll; }
```

**4. auto :** This value allows the browser to decide whether to add scrollbars based on the content size.

```
.box { overflow: auto; }
```

**5. overflow-x & overflow-y :** These properties allow independent control of horizontal and vertical overflow.

```
.box { overflow-y: scroll; overflow-x: hidden; }
```





# THANK YOU

PHONE NUMBER

**(+91) 778 899 2897**

WEBSITE

**[www.indixpert.com](http://www.indixpert.com)**