

Hacker Tools: \LaTeX

Julius Putra Tanu Setiaji

3 November 2020

Slides at https://is.gd/ht_latex_2020_slides

Where are we?

Introduction

Syntax

Commands and Environments

Mathematics

Conclusion

NUS Hackers



<http://nushackers.org>

hackerschool

Friday Hacks

Hack & Roll

Hacker Tools

About Me

Hi! I'm Julius. My GitHub is
<https://github.com/indocomsoft>

A Year 4 Computer Science Undergraduate who loves
hacking and building systems.

I also enjoy Space Exploration, Music Theory and History.

(my favourite games are KSP and EU4 hit me up if you play those too)

Required Software

These are preferable, but otherwise you should be to follow along using Overleaf¹

- A $\text{T}_\text{E}\text{X}$ distribution (instructions in our publicity channels)
- TeXstudio

¹<https://www.overleaf.com/?r=5e9ffb40&rm=d&rs=b>

What is \LaTeX ?

- A markup language for document preparation²
- Uses plain text³ in contrast to most WYSIWYG editors
- Started as a writing tool for mathematicians and computer scientists.
- Built on top of \TeX by Leslie Lamport⁴ in 1983

²Just like HTML (Hyper-Text Markup Language) is a markup language

³thus versionable using a VCS like **git**

⁴Winner of the Turing Award in 2013 for his work in distributed and concurrent systems

What is T_EX?

- A typesetting system designed and mostly written by Donald Knuth⁵ in 1978
- Because Knuth was disappointed with the typesetting of the 2nd edition of TAOCP.
- 2 Goals:
 - Allow anybody to produce high-quality books with minimal effort
 - Provide a system that would give exactly the same results on all computers, at any point in time

⁵Winner of the Turing Award in 1974 for analysis of algorithms and the design of programming languages

Trivia

Version number of $\text{T}_{\text{E}}\text{X}$ approaches π :

3.0 \rightarrow 3.1 \rightarrow 3.14 \rightarrow 3.141 \rightarrow ... \rightarrow 3.14159265 (current)

Version number of Metafont⁶ approaches e :

2.0 \rightarrow 2.7 \rightarrow 2.71 \rightarrow ... \rightarrow 2.7182818 (current)

⁶Companion to $\text{T}_{\text{E}}\text{X}$ written by Knuth, used to describe fonts using geometrical equations

What can I use \LaTeX for?

- Reports
- Books
- Presentation⁷
- And so much more!

⁷This presentation is written in \LaTeX using Beamer!
<https://github.com/indocomsoft/hackertools-slides/blob/master/latex/latex.tex>

Basic \LaTeX Syntax

- A \LaTeX document consists of commands and environments⁸
- The command syntax:
`\command[option1,option2,...]{arg1}{arg2}...`
- The environment syntax:
`\begin{environment}`
 % Some children content
`\end{environment}`
- Comments are whatever comes after %

⁸HTML terms: tags = commands, tags with children = environments

Basic \LaTeX Document

We will explain the commands and environment used here later on.

```
\documentclass{article}
```

```
\begin{document}
```

```
Hello world!
```

```
\end{document}
```

Spaces

- All whitespace characters are treated as space.
- Several consecutive spaces are treated as one space.
- Leading/trailing spaces are ignored.
- A single line break is treated as a space.
- Two or more line breaks define the end of a paragraph.

Let's try out spaces

```
\begin{document}
```

It does not matter whether you
enter one or several spaces
after a word.

An empty line starts a new
paragraph.

```
\end{document}
```

Reserved Characters

Reserved characters either have a special meaning or are unavailable in all the fonts ⁹.

\$ % ^ & _ { } ~ \

Instead, use

`\# \ $ \% \^{} \& _ \{ \} \~{} \textbackslash`

Note the empty argument to caret and tilde, because otherwise they are used to create diacritics.

We use `\textbackslash` because `\\` is line breaking.

⁹This might feel weird, but remember that $\text{T}_{\text{E}}\text{X}$ and $\text{L}_{\text{A}}\text{T}_{\text{E}}\text{X}$ are such old systems from the 1970s and 1980s

Other tricky characters

- Larger than and smaller than symbols usually do not get rendered correctly.
- Instead, use `\textless` and `\textgreater`
- In some circumstances, square brackets are reserved (for options)
- Thus, `\command [text]` fails, instead do `\command{} [text]`

Packages

- Just like other programming languages, \LaTeX has packages as well
- \LaTeX also has its own package manager, called CTAN
- Use the command `\usepackage {packagename}` to “import” and use a package.
- We will go through some useful packages in the upcoming subsections.

Where are we?

Introduction

Syntax

Commands and Environments

Document Class

Document environment

Fonts

Text and Paragraph Formatting

Mathematics

Back to Our Example

```
\documentclass{article}
```

```
\begin{document}
```

```
Hello world!
```

```
\end{document}
```

Where are we?

Introduction

Syntax

Commands and Environments

Document Class

Document environment

Fonts

Text and Paragraph Formatting

Mathematics

Document Class

```
\documentclass{article}
```

- Use the **article** document class.
- Document class file defines the formatting standard to follow, which in this case is the generic article format.
- Other document classes, e.g. **acmart** for ACM¹⁰ publications, **beamer** for presentations¹¹

¹⁰Association for Computing Machinery

¹¹Like this presentation!

Document Class options

- `10pt`, `11pt`, `12pt` – size of main font (default: `10pt`)
- `a4paper`, `letterpaper`, ... - size of paper
- `landscape` – Landscape mode layout
- `titlepage`, `notitlepage` – whether a new page should be started after the document title

Find out more at

[https://en.wikibooks.org/wiki/LaTeX/
Document_Structure#Document_classes](https://en.wikibooks.org/wiki/LaTeX/Document_Structure#Document_classes)

Where are we?

Introduction

Syntax

Commands and Environments

Document Class

Document environment

Fonts

Text and Paragraph Formatting

Mathematics

Document Environment

`\begin{document}`

- The beginning of the **document** environment.
- Tells \LaTeX that the content of document starts here.
- Anything before this line is called **the preamble**

`\end{document}`

- The end of the **document** environment
- Tells \LaTeX that the document is complete.
- Anything after this line is ignored.

Top Matter

Top Matter: information about the document itself

- Provide information using the `title`, `author`, `date`
- Typeset the title using `maketitle`

```
\documentclass{article}
```

```
\title{How to Basic: \LaTeX{}}
```

```
\author{Julius Putra Tanu Setiaji}
```

```
\date{3 November 2020}
```

```
\begin{document}
```

```
\maketitle
```

```
\end{document}
```


Sectioning Commands

```
\section{Some Section Title}
```

```
\subsection{Some Subsection Title}
```

```
\subsubsection{Some Subsubsection Title}
```

To get an unnumbered sections, add an asterisk to the end of the command name, e.g. `\section*{Look Ma, no numbers!}`

Typeset a table of contents using `\tableofcontents`

Note: unnumbered section will not be included in the TOC unless explicitly included:

```
\addcontentsline{toc}{subsection}{Look Ma, no  
↪ numbers!}
```

Where are we?

Introduction

Syntax

Commands and Environments

Document Class

Document environment

Fonts

Text and Paragraph Formatting

Mathematics

Emphasising text

- Use the `\emph{text}` command
- Typically done by italicising the text.
- Note that the command is dynamic: emphasising a word in an already emphasised sentence will revert the word to upright font.

Font styles

```
\textnormal{document font family}  
\emph{Emphasised text}  
\texttt{teletype font family (monospaced)}  
\textbf{bold fontface}  
\textsc{Small Capitals}  
\uppercase{uppercase}
```

Font size

Changes the size in scope

```
{\tiny test}  
{\scriptsize test}  
{\footnotesize test}  
{\small test}  
{\normalsize test}  
{\large test}  
{\Large test}  
{\LARGE test}  
{\huge test}  
{\Huge test}
```

Where are we?

Introduction

Syntax

Commands and Environments

Document Class

Document environment

Fonts

Text and Paragraph Formatting

Mathematics

Non-breaking Space

Use tilde (~) to tell \LaTeX not to change space into line break.

Line spacing

- For controlling line spacing, I usually use the `setspace` package.
- Import it in the preamble: `\usepackage{setspace}`
- Useful commands: `\singlespacing`,
`\onehalfspacing`, `\doublespacing`
- Useful environments: `singlespace`,
`onehalfspace`, `doublespace`, `spacing`

```
\begin{spacing}{2.5}
```

This paragraph has `\\` huge gaps `\\` between
↪ lines.

```
\end{spacing}
```


Quote-marks

In \LaTeX , quote-marks can go the wrong way if you're not careful!

To ``quote'` in \LaTeX

To ```quote''` in \LaTeX

Paragraph Alignment

Alignment	Environment	Command
Left justified	<code>flushleft</code>	<code>\raggedright</code>
Right justified	<code>flushright</code>	<code>\raggedleft</code>
Center	<code>center</code>	<code>\centering</code>

Paragraph Indentation

- By default, first paragraph after a heading is not indented, subsequent paragraphs are indented by `\parindent`
- This follows typical Anglo-American publishing convention.
- To set this length, in preamble:
`\setlength{\parindent}{1cm} % Default 15pt`
- You can use the `indentfirst` package to indent the beginning of every section
- To force indent a non-indented paragraph, use `\indent` at the beginning of the paragraph.
- To force non-indent an indented paragraph, use `\noindent`

Adding paragraph skips

- To make paragraphs boundary clear using zero indentation, vertical space between paragraphs is needed.
- Use the `parskip` package

Verbatim Environment

Introduce text that will not be interpreted by the compiler in a monospaced font

```
\begin{verbatim}
```

The verbatim environment
simply reproduces every
character you input,
including all spaces!

```
\end{verbatim}
```

Typesetting URLs

Use the `hyperref` package, with the `\url{https://stonks.trade}` command

If you want coloured hyperlink instead of box, set option `colorlinks` when using the `hyperref` package:

```
\usepackage[colorlinks]{hyperref}
```

Where are we?

Introduction

Syntax

Commands and Environments

Mathematics

Conclusion

Mathematics

Knuth's motivation to develop $\text{T}_{\text{E}}\text{X}$ among others was to allow simple construction of mathematical formulae that looks professional when printed.

Typesetting Mathematics is one of $\text{L}_{\text{A}}\text{T}_{\text{E}}\text{X}$'s greatest strengths

Getting started

I usually use the `mathtools` package to provide more powerful and flexible commands than plain \LaTeX

```
\usepackage{mathtools}
```

Environments

\LaTeX provides displayed equation environment (`\displaymath`), where the formulae are on a line by themselves.

Short hand¹²: `\[e^{i \pi} + 1 = 5\]`

To get automatically numbered equations, use the `equation` environment:

```
\begin{equation}
e^{i \pi} + 1 = 0
\end{equation}
```

¹²DO NOT use `$$...$$`, it is an older \TeX syntax that causes problems and is not officially supported by \LaTeX

Inline vs Displayed Equations

However, if you want to get an inline formula, use the `math` environment or the shorthand¹³:

`$e^{i \pi} + 1 = 0$`

These work on some flavours of Markdown too, e.g.

<https://hackmd.io>

¹³There also exists the \LaTeX shorthand `\(...\)`

Maths Symbols

A pretty good list at

[https://en.wikibooks.org/wiki/LaTeX/
Mathematics#List_of_mathematical_symbols](https://en.wikibooks.org/wiki/LaTeX/Mathematics#List_of_mathematical_symbols)

You can also use detexify:

<http://detexify.kirelabs.org/>

Or even cooler: <https://mathpix.com/>

Powers and indices

Use the caret (^) to raise something, and underscore (_) to lower.

If more than one expression is raised or lowered, group them using curly braces

Exercise: typeset this

$$k_{n+1} = n^2 + k_n^2 - k_{n-1}$$

Fractions and Binomials

`$\frac{x^2}{y^3}$`

`$\binom{n}{r}$`

$$\frac{x^2}{y^3}$$

$$\binom{n}{r}$$

Roots

`\sqrt[n]{1 + x + x^2 + x^3 + \dots + x^n}`

$$\sqrt[n]{1 + x + x^2 + x^3 + \dots + x^n}$$

Sums and Integrals

Use the `\sum` and `\int` for sum and integral respectively, with the limits specified using caret and underscore.

Use `\limits` if you want the limits specified above and below the symbol in inline mode, or use displayed equation mode.

`\sum_{i=1}^{10} t_i`

$$\sum_{i=1}^{10} t_i$$

`\sum\limits_{i=1}^{10} t_i`

$$\sum_{i=1}^{10} t_i$$

Use `\,` for a small space

`\int_0^{\infty} e^{-x}\,,dx`

$$\int_0^{\infty} e^{-x} dx$$

`\int\limits_0^{\infty} e^{-x}\,,dx`

$$\int_0^{\infty} e^{-x} dx$$

Other big commands

Note that this also applies to other “big” commands like `\prod` , `\bigcup` , `\bigcap` , etc.

Brackets, braces, delimiters

```
 $( a ), [ b ], \{ c \}, | d |, \| e \|,$   
↪  $\langle f \rangle, \lfloor g \rfloor,$   
↪  $\lceil h \rceil, \ulcorner i \urcorner$ 
```

$(a), [b], \{c\}, |d|, \|e\|, \langle f \rangle, [g], \lceil h \rceil, \lceil i \rceil$

Automatic sizing

`$P\left(A=2\middle|\frac{A^2}{B}>4\right)$`

`$P(A=2|\frac{A^2}{B}>4)$`

$$P\left(A = 2 \middle| \frac{A^2}{B} > 4\right)$$

$$P(A = 2 | \frac{A^2}{B} > 4)$$

Exercises

$$\binom{n}{r} = {}_nC_r = \frac{n!}{r!(n-r)!}, {}_nC_r \times r! = {}_nP_r$$

$$\lim_{n \rightarrow \infty} \left| \frac{a_{n+1}}{a_n} \right| = \rho$$

$$\frac{d^2y}{dx^2} + p(x)\frac{dy}{dx} + q(x)y = F(x)$$

$$\{x \mid x \in \mathbb{R}^+, -1 \leq x \leq 1\}$$

Resources

Wikibooks provide some good resources:

<https://en.wikibooks.org/wiki/LaTeX>

So does overleaf: [https:](https://www.overleaf.com/learn/latex/Main_Page)

[//www.overleaf.com/learn/latex/Main_Page](https://www.overleaf.com/learn/latex/Main_Page)

Where are we?

Introduction

Syntax

Commands and Environments

Mathematics

Conclusion

Talk to us!

- Feedback form: <https://bit.ly/2020ht6>
- Today is the last in the Hacker Tools series this semester, but do join our other events:
 - Friday Hacks #196: Resurgence of AI in the future of travel and tourism, and Stream Processing with Kafka Stream
 - hackerschool: Advanced Git (Saturday)
- Telegram: <https://t.me/nushackers>
(@nushackers)