

ACKNOWLEDGEMENTS

I am greatly indebted to Dr. Marc P. Christensen, my advisor, for his unyielding support and astute guidance during my Ph.D. I sincerely admire his inexhaustible patience, and his ability to deconstruct complex problems and illuminate the essence in simple terms. I have tried my best to learn these valuable skills by observing him. I thank him for masterfully shaping my thoughts through critical questioning, helpful discussions, insightful suggestions, and at the same time giving me the freedom to define and pursue the research in my own way.

I am very grateful to my friend and colleague Dr. Prasanna Rangarajan. I have spent several years collaborating with him on a multitude of Optics and Imaging research. I have grown as a researcher seeing and admiring his tenacious work ethics, math wizardry, and problem-solving methods. I thank him for the endless stimulating whiteboard discussions, for sharing his knowledge and ideas, and for helping me refine the mathematical model in this thesis.

I express my sincere gratitude to Dr. Panos Papamichalis, Dr. Dinesh Rajan and Dr. Predrag Milojkovic for shaping my research through hard questioning, vocational guidance, perceptive comments, encouragement and help without question whenever I required.

I thank Dr. Delores M. Etter and Dr. Yunkai Zhou for serving on my dissertation committee and giving meaningful feedback on the research work despite their busy schedule. They have always been most sympathetic and accommodating to all my needs.

I am very grateful to Dr. Duncan MacFarlane for providing critical feedback on my work and giving valuable suggestions on improving as a researcher.

I will forever be grateful to my Master's thesis advisor Dr. Scott Douglas for initiating me to research. Without that opportunity, my life would have inevitably carved out a different path.

I have been very fortunate to be part of a highly motivated and talented group of researchers during my time at SMU: Dr. Manjunath Somayaji, Dr. Vikrant Bhakta, Dr. Esmaeil Faramarzi, Ting Li, Nick Saulnier, Jack Ho, Muralidhar Balaji, Aparna Viswanath and Ashwini Subramanian. I have learned a lot from each of them, and I will always cherish their friendship. I will always be indebted to Dr. Manjunath Somayaji for thoughtfully guiding me both on technical and non-technical matters whenever I needed. I am thankful to Dr. Vikrant Bhakta for being a supportive friend and collaborator. It was Dr. Bhakta and Dr. Somayaji who had initiated the groundwork for examining various techniques for solving the limited capture volume problem in iris recognition.

I would like to thank Jack Strobel of Harwin Camera, Inc. for going out of his way to help with issues related to the view camera we bought from Sinar. I also thank Senior Lecturer Charles DeBus for being kind enough to teach me the basics of view camera photography and allowing me to use his film development lab for my experimentation with a view camera.

Life could have been difficult during my time at SMU without all the help, support and care I received from Susan Bailey, Jay Kirk, Mitzi Hennessey, Julie Bednar, Misti Compton, Kristine R. Reiley and Jim Dees. Susan is very thoughtful and compassionate. I will always be grateful for the generosity Susan, Mitzi, Julie, Misti, and Kristine have shown towards me. Jim's attention to details has ensured the quality of the dissertation. He has also been very kind and helpful with issues related to admission when I needed.

I would like to thank my friends outside the sphere of my research who have motivated me to achieve whatever little I have till now—Sid Choraria, Kiran Tatiparthi, Ruan Chimata, Srinivas Bandi, Arun Hegde, Dipto Mukherjee, Zahid Najam and Nithin Mohandas. I will always be grateful for their generosity and encouragement.

I have been blessed to have a beautiful family. I thank my parents for the immense personal sacrifices they have made for providing me the best education, incommensurable love and care, and constant inspiration. I am grateful for the gift of a wonderful brother and sweet sister. I highly cherish their boundless love and warmest affection. I am very fortunate to have kindhearted and understanding parents-in-law. I can't thank them enough for their immense love, tiresome patience, and unceasing words of encouragement.

Last but not the least, I thank my wife and best friend, Vibha, for her steadfast support, unfathomable patience, and unconditional love for me through the vicissitudes of our life. Time just seems to fly in her presence.

Sinharoy, Indranil

BE in Electronics & Communication Engineering, VTU, India, 2003
MS in Electrical Engineering, Southern Methodist University, 2006

Scheimpflug with Computational Imaging to Extend the Depth of
Field of Iris Recognition Systems

Advisor: Professor Marc P. Christensen

Doctor of Philosophy December 17, 2016

Dissertation completed November 28, 2016

Despite the enormous success of iris recognition in close-range and regulated spaces for biometric authentication, it has hitherto failed to gain wide-scale adoption in large, unrestricted environments. The problem arises from a fundamental limitation of optical imaging called the depth of field—the limited range of distances within which subjects appear sharp in the image. The loss of details in the iris image outside a small finite volume—the capture volume—dramatically deteriorates the performance of iris recognition beyond a small range of distances. Existing techniques are usually expensive, computationally complex, or exhibit low signal-to-noise ratio. Is there a way to combine the classical Scheimpflug technique with modern computational imaging to find a reliable method that can significantly extend the depth of field of iris recognition? Unexpectedly, the technique we found in this thesis is simple. Additionally, provides several key advantages over existing approaches.

We developed a pair of equations that describe imaging in systems in which the lens and the sensor can rotate about independent pivots. The primary advantage of our models over existing models is that they directly incorporate the pupil parameters, allowing us to predict the nature of

the image in such systems efficiently. Furthermore, analysis of geometric properties using our model led to the discovery of the set of conditions required for synthesizing an extended depth of field image from a sequence of images captured while continually rotating the lens. We call this new computational technique angular focus stacking. One of the key advantages of our method is that the improvement in the depth of field is constrained only by magnification. Additionally, we found that rotation of the lens about the center of the entrance pupil allows us to analytically register the images in the stack instead of relying on computationally intensive algorithms.

The angular focus stacking method is tailor-made for significantly extending the capture volume of iris acquisition systems, yet it is simple, easily scalable, cost-effective and computationally efficient for real-time performance. Moreover, we obtain huge gains in depth of field without sacrificing optical resolution and signal-to-noise ratio. Additionally, we have demonstrated that we can capture images for angular focus stacking within a fraction of the time required by traditional imaging for the same depth of field and exposure level. Therefore, the constraint on subject movement within the large capture volume can be significantly relaxed using the proposed method.

TABLE OF CONTENTS

ACKNOWLEDGEMENTS.....	iii
ABSTRACT.....	vi
LIST OF FIGURES.....	xii
LIST OF TABLES.....	xvi
Chapter	
1. BACKGROUND.....	1
1.1. The depth of field problem illustrated.....	3
1.2. Understanding optical resolution and depth of field.....	4
1.3. Primer on iris recognition.....	9
1.4. Desirable properties of iris recognition systems.....	15
1.5. Scheimpflug imaging.....	24
1.6. Computational imaging.....	25
1.7. Summary.....	26
2. STATE-OF-THE-ART.....	27
2.1. State-of-the-art large standoff iris acquisition.....	27
2.2. State-of-the-art iris acquisition with large capture volume.....	29
2.3. State-of-the-art iris acquisition with large instantaneous capture volume.....	31
2.3.1. Extending capture volume using image processing.....	31
2.3.2. Extending capture volume using wavefront coded systems.....	31
3. MODEL OF SCHEIMPFLUG IMAGING – I: PROPERTIES OF IMAGE.....	36
3.1. Background.....	39
3.2. Notations.....	41
3.3. Relation between pupil magnification and chief ray angle.....	42

3.4.	Transfer of chief ray's direction cosines between the pupils.....	44
3.5.	Image formation for arbitrary orientation of the lens and image plane.....	50
3.6.	Verification of imaging equation in Zemax.....	57
3.7.	Geometric properties of images under lens and image plane rotation.....	58
3.7.1.	Properties of image field induced by sensor rotation ($\alpha_x, \alpha_y = 0, \beta_x, \beta_y \in \mathbb{R}$).....	60
3.7.2.	Properties of image field induced by lens rotation away from center of the entrance pupil ($\alpha_x, \alpha_y \in \mathbb{R}, \beta_x, \beta_y = 0; d_e \neq 0$)	61
3.7.3.	Properties of image field induced by lens rotation about the center of the entrance pupil ($\alpha_x, \alpha_y \in \mathbb{R}, \beta_x, \beta_y = 0; d_e = 0$).....	62
3.8.	Summary.....	70
4.	MODEL OF SCHEIMPFLUG IMAGING – II: FOCUSING.....	71
4.1.	Relationship between the object, lens, and image planes for focusing.....	72
4.2.	Examples of typical Scheimpflug imaging configurations.....	80
4.2.1.	Example: Focusing in frontoparallel configuration.....	80
4.2.2.	Example: Focusing on tilted object plane by tilting the image plane.....	82
4.2.3.	Example: Focusing on a tilted object plane by tilting a lens using thin lens model.....	87
4.2.4.	Example: Focusing on a tilted object plane by tilting a lens using thick lens model.....	89
	○ Verification of formulae for focusing on a tilted object plane by tilting the lens.....	93
	○ Consequences and analysis of the focusing equation.....	95
	○ Condition for monotonicity of $g(\alpha, m_p, f, z_o)$	102
	○ Algorithm for finding α for known β	106

4.3. Summary.....	111
5. SYNTHESIZING EXTENDED DEPTH OF FIELD.....	113
5.1. Extending depth of field using frontoparallel focus stacking.....	114
5.1.1. Advantages of focus stacking for extended depth of field.....	116
5.2. Extending depth of field using angular focus stacking.....	118
5.2.1. Inter-image homography for lens of unit pupil magnification, tilted about entrance pupil.....	120
5.2.2. Image registration using the inter-image homography.....	124
5.3. Simulation of extended DOF image synthesis using angular focus stacking.....	125
5.4. Advantages of angular focus stacking for extending the DOF of iris acquisition systems.....	132
5.5. Demonstration of capture volume extension for iris acquisition.....	132
5.6. Summary.....	139
6. DISCUSSION.....	140
6.1. Summary of the work.....	140
6.2. Conclusions.....	143
6.3. Limitations.....	145
6.4. Directions of future research.....	146
APPENDIX.....	149
A. Appendix A.....	149
A.1 Transfer of chief ray's direction cosine for arbitrary orientation of the optical axis.....	149
A.2 The direction cosine, originating from exit pupil, has unit ℓ^2 -Norm.....	153
B. Appendix B.....	155
B.1 Derivation of Gaussian imaging equation with pupil magnification.....	155

B.2	A brief account on the significance of pupil magnification.....	158
C.	Appendix C.....	162
C.1	Distribution of light near focus (3D PSF) for imaging between parallel planes.....	162
REFERENCES	164

LIST OF FIGURES

Figure

1.1	The depth of field (DOF) problem.....	3
1.2	Incoherent impulse response and DOF.....	5
1.3	First order simulation of iris acquisition at multiple depths.....	7
1.4	Complexity and uniqueness of human iris.....	9
1.5	The iris recognition as a binary classification problem.....	10
1.6	Schematic of the normalization process using a spoke pattern	13
1.7	Overview of iris biometric code generation	14
1.8	Number of publications in (English) journals on iris recognition between 1990 & 2013.....	15
1.9	Maximum optical spatial frequency vs. F-number (F/#) for different modulation transfer functions for a wavelength of 850 nm at the image plane.....	17
1.10	Focal length vs. standoff distance for maintaining 200 pixels across the iris for different pixel pitches.....	19
1.11	Geometric depth of field vs. system F-number (F/#) for various object distances.....	20
1.12	Diffraction depth of field vs. system F-number (F/#) for various object distances.....	21
1.13	Effect of aperture size on DOF and lateral resolution.....	23
1.14	Frontoparallel vs Scheimpflug imaging.....	25
2.1	A visual representation of the capture volumes of selected systems from Table 2.1.....	35
3.1	Scheimpflug camera movements.....	38

3.2	Fundamental rays (contained within the meridional place) and pupils in a Double Gauss lens for an object at infinity.....	40
3.3	Schematic of chief and marginal rays.....	42
3.4	Specific problem—optical axis coincides with reference frame’s z-axis.....	45
3.5	Configuration of the general problem—optical axis pivots freely about the origin of camera frame $\{C\}$	48
3.6	Schematic of geometric image formation.....	52
3.7	Schematic of the image plane.....	53
3.8	Ray tracing for verifying Eq. (3.27).....	56
3.9	“Image points” corresponding to two object planes—a far plane twice the size of the near plane.....	60
3.10	Geometric image under image plane (sensor) rotation for varying pupil magnifications.	64
3.11	Comparison of geometric distortion induced by sensor rotation for varying object plane distances.....	65
3.12	Geometric image under lens rotation away from the entrance pupil for varying pupil magnifications.....	66
3.13	Variation of geometric distortion of image field induced by lens rotation away from the entrance pupil as a function of object distance and pupil magnification.....	67
3.14	Geometric image under lens rotation away from the entrance pupil for varying pupil magnifications.....	68
3.15	Variation of geometric distortion of images induced by lens rotation about the entrance pupil as a function of object distance and pupil magnification.....	69
4.1	Schematic of Scheimpflug imaging.....	73
4.2	Object and image plane tilt.....	83
4.3	Object and image plane tilt (distances measured from principal planes).....	86

4.4	Object and lens (thin lens model) plane tilt	89
4.5	Object and lens (thick lens model) plane tilt	90
4.6	Variation of β (y-axis) with respect to lens pivot position for (a) $\alpha = 0^\circ$, (b) $\alpha = -5^\circ$, and (c) $\alpha = -10^\circ$	93
4.7	Object plane angle β and $\tan \beta = g(\alpha, m_p, f, d_e, z_o)$ versus lens tilt angle α if a lens is rotated about a point away from the entrance pupil.....	96
4.8	Determination of lens tilt angle α for known object tilt angle β using point of intersection of <i>quartic plane curve</i> with the unit circle.....	98
4.9	Object plane angle β and $\tan \beta = g(\alpha, m_p, f, z_o)$ versus lens tilt angle α if a lens is rotated about the entrance pupil.....	101
4.10	Plots of the first derivative of $g(\alpha, m_p, f, z_o)$	103
4.11	Determination of lens tilt α for known object plane tilt β using point of intersection of <i>quadratic plane curve</i> with the unit circle.....	107
4.12	Example determination of lens tilt angle α	109
4.13	Inner workings of the iterative algorithm for determining α given β	111
5.1	Schematic of frontoparallel focus stacking.....	114
5.2	Example of extend DOF in macro photography using frontoparallel focus stacking....	116
5.3	Schematic of angular focus stacking.....	119
5.4	Schematic of simulation setup.....	127
5.5	Integrated sensor images (simulated) in the angular focus stack.....	129
5.6	Analytic registration of images in the focal stack.....	130
5.7	Result of the angular focus stacking simulation in Zemax.....	131
5.8	Setup for demonstrating capture volume extension.....	133
5.9	Single-shot traditional image capture at F/8.....	135
5.10	Regions of focus in the registered images in the angular focus stack.....	136

5.11	Synthetic image demonstrating extended capture volume using angular focus stacking.	137
5.12	Zoomed-in view of regions-of-interest in the composite image shown in Figure 5.11...	138
B1.1	Schematic of imaging through a lens.....	156
B2.1	Pupil magnification m_p in a wide variety of lenses that form <i>real</i> images.....	159

LIST OF TABLES

Tables

2.1	Comparison of features in the state-of-the-art iris acquisition systems.....	33
3.1	Comparison of numerically computed image points with ray traced (in Zemax) image points for the optical system shown in Figure 3.8.....	58
4.1	Verification of imaging equations Eq. (4.59) and Eq. (4.63) for focusing on a tilted object plane by tilting a lens about a point away from the entrance pupil.....	94
4.2	Verification of imaging equations Eq. (4.65) and Eq. (4.66) for focusing on a tilted object plane by tilting a lens about the entrance pupil.....	100
4.3	Algorithm for finding lens tilt α required to focus on an object plane tilted by β	110

To Vibha.