



# TCC-368

Silicone Grease

2025/01/14 Draft. **PDS**

## Description

TCC-368 mixed by silica and siloxane, has excellent non-corrosive to moisture and better paste ability.

## Storage & packaging

When stored in its originally sealed packaging at 5°C - 40°C, this product may be stored for up to 8 months from its manufacturing date. Comply with the storage instructions marked on the packaging. Once past this expiration date, TAI COUNTY CHEMICAL no longer guarantees that the product meets the sales specifications.

Product comes in 20KG HDPE white drums.

## Characteristics

- Generally silicone grease. It has excellent non-corrosive to moisture, especially has good electric features in severe environment
- Providing non-corrosive for most metals, compatible with most plastics and elastics

## Applications


- Electronics: Lubrication and protection of electronic components, such as connectors, switches, and circuit boards, effectively reducing friction and preventing moisture and dust intrusion.
- Mechanical Equipment and Automotive Industry: Lubrication of transmission system parts, seals, connectors, and mechanical components, enhancing durability and improving performance.

## Properties

Appearance Translucent paste

Active ingredient(%) 100.0%

Specific Gravity 1.01~1.05



## Safety

This document does not contain the safety information required for the product. Please read the safety data sheet for this product before use.

## Processing

(Depending on the actual conditions, you can adjust the usage amount.)