



SAF-100

Silicone-Modified Long-Lasting Defoamer

2024/09/10 Draft. PDS

Description

SAF-100 is a polyether-type lipophilic defoamer that effectively addresses issues associated with traditional silicone defoamers, such as spotting on fabrics or problems with metal surface re-treatment when used in textile dyeing and finishing, printing, papermaking, electrolytes, and surface coatings. Once modified, it exhibits resistance to strong acids, alkalis, and high temperatures, and maintains high stability over time without reacting with other chemicals.

Characteristics

- Reduces foam caused by stirring and air entrainment
- Unlike traditional silicone defoamers, it does not cause staining or fisheyes
- Provides long-lasting and efficient defoaming and anti-foaming effects
- Economical to use due to low dosage requirements
- Easy to apply due to its good dispersibility

Properties

Appearance	Milky white liquid
Active ingredient(%)	100.0%
Ionic type	Nonionic

Safety

This document does not contain the safety information required for the product. Please read the safety data sheet for this product before use.

Storage & packaging

When stored in its originally sealed packaging at 5°C - 40°C, this product may be stored for up to 8 months from its manufacturing date. Comply with the storage instructions marked on the packaging. Once past this expiration date, TAI COUNTY CHEMICAL no longer guarantees that the product meets the sales specifications.

Product comes in 20KG HDPE green drums and 120kg HDPE blue drums loading 100KG(All breathable).

Applications

- Used in dye baths, printing, and jet dyeing processes to eliminate foam and enhance efficiency
- Effective in eliminating foam during the production of synthetic resins, latex, and coatings, as well as in papermaking and surface coatings

Processing

- It is recommended to dilute SAF-100 to a 30% solution. Filter before packaging)

SAF-100	:72	KG
IPM	:48	KG
RS-E	:48	KG
Water	:260	KG
Total	:428	KG

- Mix RS-E, SAF-100, and IPM in a tank at 2000rpm~2500rpm for 10 minutes. Gradually add 17KG of water in portions, stirring for 5-10 minutes each time.
- The result is a 25% defoamer. Filter with non-woven fabric before packaging.
- Dilute to a 10% solution before use and filter beforehand.
- Usage: Typically, use 0.3%~0.5% of the solution in processing. (Depending on the actual conditions, you can adjust the usage amount.)

The data provided above is to the best of our knowledge and experience and is without any warranty. Users should thoroughly test any application and independently conclude satisfactory performance before use.

TAI COUNTY CHEMICAL

TAIPEI Factory: NO. 91, Muscum Rd., Bali Township, Taipei County 24947, Taiwan
 FACTORY REGISTRATION NO: 99.695614.00
 YUNLIN Factory: NO. 1, Changqing St., Lunbei Township, Yunlin County 63745, Taiwan
 FACTORY REGISTRATION NO: 09000892
 Tel: 886-2-2610-4457
 Fax: 886-2-2610-1363
 E-MAIL : service@taicounty.com.tw
www.taicounty.com.tw