We Will Create a Nice Future Together

TAI COUNTY

TQCSI ISO 9001:2015
Quality Certified
TA2474-QC

RX-3811

Polyether Modified Emulsion

2026/10/30 Draft. **PDS**

Description

The RX-3811 is a water-based emulsion functional additive based on polyether modified organosilicon, composed of a siloxane backbone combined with polyether (mainly EO / PO) segments. This product offers excellent lubrication and hydrophilicity, forming a uniform functional film on the substrate surface, providing smoothness, wetting, and processing improvement effects, suitable for various water-based system applications. The EO/PO ratio and quantity can be adjusted according to customer requirements to achieve optimized performance.

Storage & packaging

When stored in its originally sealed packaging at 5°C - 40°C, this product may be stored for up to 8 months from its manufacturing date. Comply with the storage instructions marked on the packaging. Once past this expiration date, TAI COUNTY CHEMICAL no longer guarantees that the product meets the sales specifications.

Product comes in 20KG HDPE grey drums (Breathable).

Characteristics

- Excellent smoothness, lubricity, and wettability
- Good hydrophilicity and water absorption
- Low surface tension and leveling properties
- Good shear stability
- Excellent antistatic properties
- Outstanding weather resistance
- Good compatibility

Applications

- Textile Finishing: Used for smoothing, softening, and hydrophilic finishing of cotton, polyester, nylon, and blended fabrics.
- Coatings and Inks Additives: Acts as a leveling agent, wetting agent, and dispersant to improve coating uniformity.
- Surfactant Applications: Used for emulsification and dispersion, and to reduce surface tension.
- Industrial Lubricants and Processing Aids: Can be used in metal cutting oil formulations to enhance processing flow and surface quality.
- PU Foam Stabilization and Release Applications: Can be used as a foam control and stabilizing agent, as well as for PU material release.
- Antistatic Engineering Applications: Utilizes its hydrophilicity and conductivity to reduce static accumulation on surfaces, suitable for antistatic treatment of textiles, plastic films, and electronic materials.
- Release Agent Industrial Applications: With low surface energy characteristics, it can be used as a mold release agent or added to release formulations for processing plastics, rubber, and composite materials.

Properties

Appearance	Milky white to yellowish liquid
Active ingredient(%)	45.0%
pH(2%Solution,25℃)	8.5±1.0
Diluent	Water

Safety

This document does not contain the safety information required for the product. Please read the safety data sheet for this product before use.

Processing

- **Please be sure to stir thoroughly before use!**

(Please add according to your actual conditions and requirements. Be sure to conduct a small-scale test before use, or contact the customer service personnel of the production factory.)

The information contained in this manual is given based on our current knowledge and good faith. It is indicative only and not binding, especially regarding the impact on third-party rights during product use. TAI COUNTY CHEMICAL ensures the products it sells conform to specifications. Only necessary preliminary tests can determine if a product is suitable for specific applications, and this information cannot replace such tests. Users are responsible for ensuring compliance with local legislation and obtaining necessary usage certificates and authorizations. Users are requested to check if they have the latest version of this document, and TAI COUNTY CHEMICAL is always ready to provide additional information to customers.

TAI COUNTY CHEMICAL

TAIPEI Factory: NO. 91, Museum Rd., Bali Township, Taipei County 24947, Taiwan
FACTORY REGISTRATION NO: 99.695614.00
YUNLIN Factory: NO. 1, Changqing St., Lunbei Township, Yunlin County 63745, Taiwan
FACTORY REGISTRATION NO: 09000892
Tel: 886-2-2610-4457
Fax: 886-2-2610-1363
E-MAIL：service@taicounty.com.tw
www.taicounty.com.tw