



L SILK-MS

Silicone Resin

PDS

Description

L SILK-MS is a combination of a low-yellowing silicone resin mixed with an emulsifier. It can be applied alone or blended with other silicone softeners emulsion to offer an extremely unique elastic and smooth hand feel. L SILK-MS suitable to apply on T, CVC, T/C, and other synthetic fibers.

Storage & packaging

When stored in its originally sealed packaging at 5°C - 40°C, this product may be stored for up to 8 months from its manufacturing date. Comply with the storage instructions marked on the packaging. Once past this expiration date, TAI COUNTY CHEMICAL no longer guarantees that the product meets the sales specifications. Product comes in 200 kg drums.

Characteristics

- Provides hydrophobic property
- Pleasing full and smooth touch
- Wrinkle resistance improves on polyester and T / C fabrics
- For the knitted fabrics, improves elasticity and stretch force
- A significant increase of softening and smoothness on cotton and cotton blends fibers
- The excellent chemical stability such is easy to dilute
- Supports resistance to surface abrasion and washing
- Compatible with most other silicone emulsions such as cationic, nonionic and resins if blending required to alter effects

Applications

- Used with other cationic, nonionic softener or smoothing agent to adjust a variety of handle.
- Wrinkle treatment for polyester and T / C fabrics.

Properties

Appearance	Milky white semitransparent
Active ingredient(%)	30.0%
pH(10%Solution,25°C)	5.5±1.0
Ionic type	Slightly cationic
Diluent	Water

Processing

- Padding process

L SILK-MS	:10~30 g/L
Soaking temperature	:Room temperature
Setting temperature	:150°C/2.5mins
(Depending on the actual conditions, you can adjust the usage amount.)	

!!This product is sensitive to acid, alkali and hard water. Please test with the own condition before use.!!

Safety

This document does not contain the safety information required for the product. Please read the safety data sheet for this product before use.

The data provided above is to the best of our knowledge and experience and is without any warranty. Users should thoroughly test any application and independently conclude satisfactory performance before use.

TAI COUNTY CHEMICAL

www.taicounty.com.tw
 No. 91, Museum Rd., Bali DIST., NEW
 TAIPEI CITY 24947, TAIWAN
 Tel: 886-2-2610-4457
 Fax: 886-2-2610-1363
 E-MAIL : service@taicounty.com.tw
 FACTORY REGISTRATION NO:
 99.695614.00