Journal of Scientific Computing manuscript No.
(will be inserted by the editor)

High-order meshfree MUSCL schemes with a posteriori order detection for hyperbolic systems on scattered point clouds

Pascal Jung · Klaas Willems · Axel Klar

Received: date / Accepted: date

Abstract We present meshfree monotone upstream-centred schemes for conservation laws (MUSCL) of arbitrary design order k for hyperbolic systems on scattered point clouds. Moving least-squares (MLS) reconstructions of degree $k-1$ are evaluated at midpoints between neighbouring particles, jumps are resolved by approximate Riemann solvers, and the interface fluxes are differentiated by an MLS derivative operator whose weights sum to zero. The scheme is exact for polynomial solutions of linear problems, is consistent of order k on periodic Cartesian lattices, and its conservation error is the lack of antisymmetry of the derivative weights. Orienting the dissipation of the Rusanov flux by the signs of the derivative weights keeps density and pressure positive in the first-order fallback for derivative operators of any degree. Discontinuities are treated by slope limiters or a per-particle multi-dimensional optimal order detection (MOOD) procedure within strong-stability-preserving Runge–Kutta methods; as the fallback is positive, the degree of the derivative operator can stay fixed while MOOD lowers only the degree of the reconstructions. Numerical experiments confirm the design orders up to five for smooth solutions on regular and perturbed clouds and show that, with a degree-one derivative operator, the conservation defect at moving shocks decreases under refinement. A two-dimensional Riemann problem and the double Mach reflection are computed robustly with positive density and pressure.

P. Jung [TODO: corresponding author? confirm]
Faculty of Mathematics, RPTU Kaiserslautern-Landau, Kaiserslautern, Germany
E-mail: [TODO: institutional e-mail of the corresponding author]
ORCID: [TODO: 0000-0000-0000-0000]

K. Willems
Faculty of Mathematics, RPTU Kaiserslautern-Landau, Kaiserslautern, Germany
Department of Computer Science, KU Leuven, Leuven, Belgium
ORCID: [TODO: 0000-0000-0000-0000]

A. Klar
Faculty of Mathematics, RPTU Kaiserslautern-Landau, Kaiserslautern, Germany
ORCID: [TODO: 0000-0000-0000-0000]

Keywords Meshfree methods · Moving least squares · MUSCL · MOOD · A posteriori limiting · Compressible Euler equations

Mathematics Subject Classification (2020) 65M06 · 65M08 · 65M12 · 35L65 · 76M28

1 Introduction

Hyperbolic systems of conservation laws describe the transport of mass, momentum and energy in compressible flows and many other applications. Their solutions develop discontinuities in finite time, and robust high-resolution discretizations are assembled from a few well-understood ingredients: a conservative flux form, upwinding through exact or approximate Riemann solvers, high-order reconstructions, and a mechanism that suppresses spurious oscillations at discontinuities [25, 41, 54, 61]. In finite volume (FV) and discontinuous Galerkin methods all of these ingredients rest on a mesh: the faces of the control volumes carry the numerical fluxes, the telescoping sum of the fluxes gives discrete conservation, and the cells define the stencils of the reconstruction.

Meshfree methods replace the mesh by a cloud of points, which we call particles, and approximate derivatives from local neighbourhoods. Generalized finite difference methods (GFDM) [29, 47] approximate derivatives from Taylor expansions on local stars of points; since Liszka and Orkisz [44] they use weighted least-squares fits of local polynomials [4, 5], as do the finite pointset method [60] and moving least-squares (MLS) approximations [38, 42]; see [3, 46] for reviews, [53] for stencil properties and [15] for very high-order variants. Since a point cloud needs no connectivity, meshfree methods are attractive for complex and moving geometries, where generating and maintaining a mesh dominates the cost of a simulation.

For hyperbolic problems the mesh-based ingredients do not carry over directly. Central meshfree differentiation is unstable for advection on irregular clouds and requires upwinding or artificial dissipation [21, 65]. Shocks require non-oscillatory and positivity-preserving mechanisms that work on irregular and overlapping stencils. And without faces there is no telescoping sum of fluxes, so discrete conservation is not automatic; convergent conservative schemes converge to weak solutions [40], whereas non-conservative schemes may converge to discontinuities that move with wrong speeds [26].

Several lines of work address these issues. Kinetic upwinding on least-squares stencils leads to the least-squares kinetic upwind method [22, 50], and positivity can be obtained by upwinding and dissipation [9]. Conservation has been addressed by meshless "face" coefficients that are antisymmetric and satisfy a closure condition [12, 13], by least-squares methods that enforce the closure condition [28], by a GFDM that conserves fluxes approximately over closed local cells [58, 59], and by meshless volume schemes, which are, however, not formally conservative [35]. High-order non-oscillatory reconstructions have been transferred to particle methods through MLS-based WENO schemes [1]. Most closely related to the present work, Willems, Klar and Samaey [63, 65]

proposed meshless MUSCL schemes for linear advection in which reconstructed values at the midpoints between neighbouring particles are differentiated with a factor two, and in which spurious oscillations are removed by Multi-dimensional Optimal Order Detection (MOOD). On irregular clouds these schemes were found to be considerably more reliable than meshless WENO schemes. A follow-up work applies a meshless MUSCL method with MOOD to the nonlinear BGK equation on moving clouds [64].

MOOD [14, 16, 17] is an a posteriori limiting strategy: a candidate solution is computed with the highest order, checked for admissibility, and recomputed with lower polynomial degrees only where it fails. It has been combined with ADER schemes [6, 45], WENO reconstructions [20], Gaussian-process reconstructions [7] and positivity-preserving Riemann solvers [8]. Its detection step needs only point values and local bounds, which makes it a natural companion of meshfree reconstructions. A priori slope limiters of Barth–Jespersen or Venkatakrishnan type [2, 27, 62] need the same local information and are an alternative.

In this paper we extend the meshless MUSCL approach to nonlinear hyperbolic systems such as the Euler equations, with arbitrary design order, a priori limiting, a per-particle MOOD procedure and explicit Runge–Kutta time integration. The schemes are implemented in the open-source Julia packages HyperCloudCore.jl and HyperCloud.jl [30, 31]. The main ingredients are:

- a flux-based update, in which every neighbour pair carries a Riemann problem between two MLS reconstructions evaluated at the pair midpoint, and the interface fluxes are differentiated by an MLS derivative operator with zero row sums;
- a choice of the degree of the derivative operator that gives the design order on symmetric stencils;
- an *aligned* orientation of the Rusanov dissipation, which keeps the first-order fallback positive for derivative operators of any degree and thereby allows a uniform derivative degree, the key to a small conservation error;
- per-particle MOOD with a smooth-extremum detection adapted to meshfree stencils and three rules that assign polynomial degrees to the two sides of every interface, applied to the forward Euler substeps of SSP Runge–Kutta methods so that every stage remains a convex combination of checked states.

Section 2 introduces the governing equations and the point clouds, Section 3 the spatial discretization, Section 4 the treatment of discontinuities and Section 5 the time integration. Section 6 presents the numerical experiments, from convergence studies to the double Mach reflection, and Section 7 collects open questions. The scheme has several options, which we compare in the experiments; our recommended configuration is the aligned flux with a frozen derivative degree and MOOD with the interface rule EPD1 or EPD2, where EPD1 is less dissipative and EPD2 more robust, and the other variants are included to show why. The mathematical statements behind the method, with proofs, are collected in a separate addendum [32].

2 Governing equations and point clouds

We consider systems of conservation laws

$$\partial_t U + \nabla \cdot F(U) \;=\; \partial_t U + \sum_{d=1}^{D} \partial_d F_d(U) \;=\; 0, \qquad x \in \Omega \subset \mathbb{R}^D,\; t > 0, \tag{2.1}$$

for states $U \in \mathbb{R}^M$ in a convex admissible set $\mathcal{G}$, with smooth fluxes F_d and a bound $\lambda_d(U)$ of the wave speeds in direction d. We write $F = (F_1, \dots, F_D)$ and $c \cdot G := \sum_d c^{(d)} G_d$ for $c \in \mathbb{R}^D$. Our main example is the system of Euler equations of an ideal gas,

$$U = \begin{pmatrix} \rho \\ \rho u \\ E \end{pmatrix}, \qquad F_d(U) = \begin{pmatrix} \rho u_d \\ \rho u_d\, u + p\, e_d \\ u_d\,(E + p) \end{pmatrix}, \qquad p = (\gamma - 1)\Big(E - \tfrac{1}{2}\rho |u|^2\Big), \tag{2.2}$$

with the sound speed $c = \sqrt{\gamma p/\rho}$, the wave speed bound $\lambda_d(U) = |u_d| + c$, the admissible set $\mathcal{G} = \{U : \rho > 0,\; p > 0\}$ and $\gamma = 1.4$ throughout.

2.1 Point clouds

The domain is represented by particles $x_1, \dots, x_N$ with nominal spacing h. Interior particles $i \in I$ carry the unknowns $U_i(t) \approx U(x_i, t)$; ghost particles in a layer of width $R + h$ outside Ω carry the boundary conditions (Section 5.3) and are not advanced. The neighbourhood $\nu(i)$ of particle i contains all other particles within the support radius $R = \kappa h$, and $\bar{\nu}(i) = \nu(i) \cup \{i\}$. We write $x_{ij} = x_j - x_i$ for the offsets and $m_{ij} = x_i + \frac{1}{2} x_{ij}$ for the midpoints, and use the positive, radially decreasing weights

$$w_{ij} = \Big(\sum_{l=0}^{4} \frac{y^l}{l!} \Big)^{-1}, \qquad y = \alpha\, \frac{|x_{ij}|^2}{R^2}, \tag{2.3}$$

a rational approximation of a Gaussian, with $\alpha = 1$ and $\kappa = 2.5$ unless stated otherwise.

Except for the unperturbed reference lattices of the convergence and conservation studies, the clouds of Section 6 are Cartesian lattices whose points are displaced independently by uniformly distributed offsets in $[-\theta h, \theta h]$ in each coordinate direction, with $\theta = 0.2$ except in the conservation study (Section 6.3). Nothing in the method relies on this construction; it produces quasi-uniform clouds with irregular stencils of about 20 neighbours for $\kappa = 2.5$.

The scheme itself does not use particle volumes. To measure conservation we use quadrature weights $V_i > 0$, for instance Shepard volumes $V_i \propto (\sum_{j \in \bar{\nu}(i)} w_{ij})^{-1}$ normalized to $\sum_i V_i = |\Omega|$; the discrete conserved quantities are $\sum_{i \in I} V_i U_i$.

3 Spatial discretization


3.1 Overview

Every interior particle carries a state U_i and a current order $k_i \in \{1, \dots, K\}$, where K is the design order of the scheme; without MOOD all $k_i = K$. One evaluation of the right-hand side consists of four steps (Fig. 1):


1. *Reconstruct.* Each particle fits a local polynomial $\mathcal{R}_i$ of degree $k_i - 1$ to the states of its neighbours by weighted least squares. The polynomial passes through the particle's own value.
2. *Evaluate at midpoints.* For every neighbour j, both particles evaluate their polynomials at the midpoint m_{ij}. This gives two interface states U_{ij} and U_{ji}, like the left and right states at a face of an FV mesh.
3. *Solve Riemann problems.* An approximate Riemann solver turns the two states into a numerical flux $F^*_{ij} = F^*(U_{ij}, U_{ji}; x_{ij})$ for every pair and coordinate direction.
4. *Differentiate.* A second least-squares fit provides derivative weights $c_{ij} \in \mathbb{R}^D$, and the particle is advanced by

$$\frac{\mathrm{d}U_i}{\mathrm{d}t} = \mathcal{L}_i(U) := -2 \sum_{j \in \nu(i)} c_{ij} \cdot \left(F^*_{ij} - F(U_i)\right) = -2 \sum_{j \in \nu(i)} c_{ij} \cdot F^*_{ij}. \quad (3.1)$$

The factor two compensates for the midpoint lying at half the distance: the interface fluxes sample the flux at $x_i + \frac{1}{2}x_{ij}$, so differentiating them with respect to the full offsets x_{ij} gives half the derivative. The same factor appears in the midpoint schemes for linear advection of [65]. The second form of (3.1) holds because the derivative weights sum to zero (Section 3.2). The update of a particle therefore depends on the interface fluxes only, as in an FV scheme with generalized face vectors $2c_{ij}$ per unit volume.



(a) neighbourhood $\nu(i)$ and midpoint m_{ij}



(b) reconstructions $\mathcal{R}_i$, $\mathcal{R}_j$ along the edge

Fig. 1 The meshfree MUSCL scheme. (a) Particle i, its neighbourhood $\nu(i)$ of radius R and the midpoint m_{ij} of the pair (i, j). (b) The reconstructions of i and j, evaluated at m_{ij}, define a Riemann problem whose numerical flux enters the updates of both particles

3.2 Reconstruction and derivative weights

We use Taylor monomials $y^\alpha/\alpha!$ with $1 \le |\alpha| \le r$, collected in the vector $p_r(y)$. The reconstruction of degree $r = k_i - 1$ at particle i fits the state differences in a weighted least-squares sense,

$$\min_A \sum_{j\in\nu(i)} w_{ij} \left|A^\mathsf{T} p_r(x_{ij}) - (U_j - U_i)\right|^2, \qquad \mathcal{R}_i(y) = U_i + A_i^\mathsf{T} p_r(y), \tag{3.2}$$

component by component in conservative variables. The fit passes through the particle value, $\mathcal{R}_i(0) = U_i$, and reproduces polynomials of degree r exactly; for $k_i = 1$ it is constant. A particle whose order is lowered by MOOD refits its reconstruction with the lower degree, while a lower order at a single interface truncates the existing polynomial (Section 4.3); at order one both give the constant U_i. Ghost particles carry no reconstruction.

The derivative weights come from a second fit of degree q, now *with* a constant term and over the neighbours only. If $a_0 + a^\mathsf{T} p_q(y)$ is the weighted least-squares fit of data g_j at the offsets x_{ij}, the weights $c_{ij}^{(d)}$ are defined by $a_d = \sum_j c_{ij}^{(d)} g_j$, the coefficient of the linear monomial y_d; explicitly

$$\begin{aligned} c_{ij}^{(d)} &= w_{ij}\; e_{1+d}^\mathsf{T}\, \tilde{N}_i^{-1}\, \tilde{p}_q(x_{ij}), \\ \tilde{N}_i &= \sum_{j\in\nu(i)} w_{ij}\, \tilde{p}_q(x_{ij})\, \tilde{p}_q(x_{ij})^\mathsf{T}, \qquad \tilde{p}_q = (1, p_q). \end{aligned} \tag{3.3}$$

These weights differentiate polynomials of degree q exactly, they scale like $1/h$, and, because constant data are absorbed by the intercept a_0, they sum to zero, $\sum_j c_{ij} = 0$, which makes the update (3.1) depend on fluxes only.

On a centrally symmetric stencil, such as a lattice, a fit of odd degree q is exact one degree beyond q, because the first monomial it cannot represent is even and does not affect the derivative. For design order k we therefore use the smallest odd degree not below $k - 1$,

$$q(k) = 2\lceil k/2 \rceil - 1, \tag{3.4}$$

i.e. $k - 1$ for even k and k for odd k; on lattices this gives a truncation error of order k. Every fit lowers its degree until it has at least as many neighbours as unknowns, and the increase from $k - 1$ to k is only used with more than 1.5 times as many. With $\kappa = 2.5$ the two-dimensional stencils support all degrees up to $k = 4$; in one dimension $\kappa = 2.5$ gives only four neighbours, so $k = 3$ falls back to derivative degree two, and on perturbed clouds $k = 5$ needs about $\kappa \ge 5.5$ in one and $\kappa \ge 3.5$ in two dimensions.

The derivative degree can be chosen in two ways. In the *coupled* mode it follows the current order, $q_i = q(k_i)$. In the *frozen* mode it is fixed, $q_i = q(k_{\mathrm{div}})$ for a prescribed $k_{\mathrm{div}} \le K$, independently of what MOOD does; for example, $k_{\mathrm{div}} = 2$ with $K = 4$ uses degree-one weights everywhere and is formally of second order only. The frozen mode with the aligned flux of the next subsection is our recommended choice.

3.3 Interface fluxes

With interface orders $k_{i\to j} \le k_i$ prescribed by MOOD (Section 4.3; without MOOD $k_{i\to j} = K$), the interface states are the reconstructions evaluated at the midpoint,

$$U_{ij} = \mathcal{R}_i^{[k_{i\to j}]}\big(\tfrac{1}{2}x_{ij}\big), \qquad U_{ji} = \mathcal{R}_j^{[k_{j\to i}]}\big(-\tfrac{1}{2}x_{ij}\big), \tag{3.5}$$

where $\mathcal{R}^{[r]}$ denotes the reconstruction truncated to degree $r-1$, and $U_{ji} = U_j$ for ghost neighbours. Since the derivative operator differentiates every coordinate flux separately, we solve a Riemann problem per coordinate direction with the Rusanov (local Lax–Friedrichs) flux [61],

$$\begin{gathered} F^*_{ij,d} = \tfrac{1}{2}\big(F_d(U_{ij}) + F_d(U_{ji})\big) - \tfrac{1}{2}\, s_{ij,d}\, \sigma_{ij,d}\, \big(U_{ji} - U_{ij}\big), \\ s_{ij,d} = \max\{\lambda_d(U_{ij}), \lambda_d(U_{ji})\}. \end{gathered} \tag{3.6}$$

The orientation $\sigma_{ij,d} = \pm 1$ decides which of the two states counts as the left one. On a mesh the natural choice is *geometric*, $\sigma_{ij,d} = \operatorname{sign}(x_{ij,d})$. Inserted into (3.1), the dissipation of neighbour j enters the update of particle i with the coefficient $s_{ij,d}\,\sigma_{ij,d}c_{ij}^{(d)}$, which should be non-negative. With the geometric orientation it is negative wherever a weight has the opposite sign of its offset, as for the outer neighbours of every derivative fit of degree three or higher (like in the fourth-order central difference) and for a few weights of degree-one fits on perturbed clouds. There the dissipation acts as anti-dissipation, and in our simulations the geometric orientation can make the first-order fallback lose positivity.

We therefore use the *aligned* orientation $\sigma_{ij,d} = \operatorname{sign}(c_{ij}^{(d)})$ on every edge where at least one of the two particles has an order below K, and on all edges of the first-order scheme $K = 1$; elsewhere we keep the geometric orientation, so the high-order scheme is unchanged where no order is lowered. All dissipation coefficients near troubled regions then become $s_{ij,d}|c_{ij}^{(d)}| \ge 0$, which is what the positivity of the first-order scheme needs (Section 4.2). Each particle takes the sign from the weights it actually uses, so on the few pairs where $c_{ij}^{(d)}$ and $c_{ji}^{(d)}$ have the same sign the two particles compute slightly different fluxes.

4 Treatment of discontinuities

Discontinuities are treated either by a priori slope limiters or by the a posteriori MOOD procedure described in the rest of this section. As limiters, the implementation provides the multidimensional slope limiters of Barth–Jespersen [2] and Venkatakrishnan (VK) [62], which scale the reconstruction so that the midpoint values stay within the extrema over $\bar{\nu}(i)$; we use VK for comparison.

4.1 MOOD detection

MOOD works with the per-particle orders k_i, which are reset to K at the beginning of every time step. A candidate state U_i^* is flagged if one of the following criteria fails.

- *Physical admissibility detection (PAD)* [16, 17]: U_i^* must be finite with positive density and pressure.
- *Relaxed discrete maximum principle (DMP)* [14, 17, 19]: with the extrema $U_{i,m}^{\max}$, $U_{i,m}^{\min}$ of component m over $\bar{\nu}(i)$ of the previous state, the candidate fails if for some m

$$U_{i,m}^{\max} - U_{i,m}^{\min} \geq \delta^3 \quad \text{and} \quad U_{i,m}^* \notin \left[U_{i,m}^{\min} - \delta,\ U_{i,m}^{\max} + \delta\right], \tag{4.1}$$

  with $\delta = \delta_0 \prod_d h_d$.
- *Plateau test.* A component that violates the DMP is nevertheless accepted if it varies across the stencil by less than a fraction $\pi_0 = 10^{-3}$ of its global range, $U_{i,m}^{\max} - U_{i,m}^{\min} < \pi_0 \left(\max_l U_{l,m} - \min_l U_{l,m}\right)$. Such a component carries no structure at the scale of the stencil. Since δ scales with h^D, it falls below the resolution of single precision on fine clouds, and the plateau test then takes over the role of the relaxation.
- *Smooth-extremum detection (u2)*, adapted from [16, 17]: for $k_i \geq 3$, a component that violates the DMP and is not a plateau is accepted if, in every direction, the second-derivative coefficients X_l of the reconstructions of the previous state have one sign over the stencil and comparable magnitudes among the nearest neighbours,

$$\left(\min_{l\in\bar{\nu}(i)} X_l\, h^2\right)\left(\max_{l\in\bar{\nu}(i)} X_l\, h^2\right) > -\delta^2 \quad \text{and} \quad \min_{l\in\nu_{1.5}(i)} |X_l| \geq \tfrac{1}{2} \max_{l\in\nu_{1.5}(i)} |X_l|, \tag{4.2}$$

  or if the curvature is negligible, $\max_l |X_l|\, h^2 < \delta$. Here $\nu_{1.5}(i)$ contains i and its neighbours within $1.5h$, which play the role of the face neighbours of the mesh-based test.

A flagged particle with $k_i > 1$ lowers its order by one. A flagged particle at order one keeps its candidate, so the robustness of the method rests on the first-order scheme.

4.2 A positive first-order fallback

At order one the interface states are constant, $U_{ij} = U_i$ and $U_{ji} = U_j$. Because the weights sum to zero, all terms with $F(U_i)$ drop out of (3.1), and with the aligned orientation, where $\sigma_{ij,d} c_{ij}^{(d)} = |c_{ij}^{(d)}|$, a forward Euler step can be rearranged into

$$U_i + \Delta t\, \mathcal{L}_i(U) = \Big(1 - \Delta t \sum_{j,d} s_{ij,d} |c_{ij}^{(d)}|\Big) U_i + \sum_{j,d} \Delta t\, s_{ij,d} |c_{ij}^{(d)}| \Big(U_j - \sigma_{ij,d} \frac{F_d(U_j)}{s_{ij,d}}\Big). \tag{4.3}$$

For the Euler equations, the states $U_j - \sigma F_d(U_j)/s$ in the last sum have positive density and pressure whenever $s \geq |u_d| + c$, a classical property of Lax–Friedrichs schemes [48, 68]. Under the meshfree CFL condition

$$\Delta t \sum_{j \in \nu(i)} \sum_{d=1}^{D} s_{ij,d} \, |c_{ij}^{(d)}| \leq 1, \tag{4.4}$$

all coefficients in (4.3) are non-negative and sum to one, so the new state is a convex combination of admissible states and is itself admissible. This holds for derivative weights of any degree and in the frozen and the coupled mode.

Remark 1 With the geometric orientation the argument requires $\operatorname{sign} c_{ij}^{(d)} = \operatorname{sign} x_{ij,d}$ for all weights, which fails for about 40% of the degree-three weights. In a Monte Carlo test of random first-order updates at the limit of (4.4) on a perturbed cloud, about 9% of the updates with degree-three weights and the geometric orientation lost positivity, and none with the aligned orientation. The price of the aligned orientation is more dissipation at lowered particles.

4.3 Interface orders

When MOOD lowers some orders, the two sides of an edge may have different orders, and a rule has to decide which polynomial degree each side uses at the interface. In FV MOOD the degree at a face is typically the minimum of the two adjacent cells [14, 16]. We consider three such *edge polynomial degree* (EPD) rules for the edges of the neighbour graph:

$$\begin{aligned} &\text{EPD0:} && k_{i\to j} = k_i, \\ &\text{EPD1:} && k_{i\to j} = k_{j\to i} = \min\{k_i, k_j\}, \\ &\text{EPD2:} && k_{i\to j} = k_{j\to i} = \min\{k_l : l \in \bar{\nu}(i) \cup \bar{\nu}(j)\}. \end{aligned} \tag{4.5}$$

EPD1 is the minimum rule of FV MOOD; EPD0 and EPD2 are, to our knowledge, new. In contrast to the meshless MOOD of [65], the orders here are lowered one by one. Fig. 2 illustrates the rules for a single particle at order one.

The positivity argument of Section 4.2 needs both states on every edge of a lowered particle to be constant. EPD1 and EPD2 guarantee this; under EPD0 a high-order neighbour still contributes a reconstructed state, so EPD0 is not used in the experiments. EPD2 in addition surrounds every troubled region by a band of low-order fluxes.




Fig. 2 Interface orders for one particle (filled red) lowered to order one in a high-order region, on a lattice patch with nearest-neighbour edges standing in for the neighbour graph. Each edge is drawn as two halves; the half next to a particle shows the order with which this particle's reconstruction enters the interface: red for order one (piecewise constant), grey for the full order

5 Time integration

5.1 Runge–Kutta methods and stage-wise MOOD

The semi-discrete system (3.1) is integrated with the explicit SSP Runge–Kutta methods of Heun (RK2), Shu and Osher (RK3) [24, 55] and Spiteri and Ruuth (RK4SSP, five stages, fourth order) [57], with stages Y_ℓ and boundary conditions applied to every stage. In the canonical Shu–Osher form [23, 36], every stage and the final update are convex combinations of U^n and the forward Euler substeps

$$W_\ell = Y_\ell + \frac{\Delta t}{C}\,\mathcal{L}(Y_\ell), \qquad \ell = 1, \dots, s, \tag{5.1}$$

with the SSP coefficient C. MOOD therefore checks every substep W_ℓ against the bounds of Y_ℓ; flagged particles lower their order, and the stage operator is recomputed locally within one hop of them (two for EPD2) until no particle is flagged. Orders lowered at one stage stay lowered for the rest of the step. Once all substeps have passed, every stage and U^{n+1} are convex combinations of U^n and checked states, so admissibility carries over to the whole time step.

5.2 Time step

The time step is

$$\Delta t^n = \mathrm{CFL} \cdot \min_{i \in I} \left(D \sum_{d=1}^{D} \lambda_d(U_i^n) \sum_{j \in \nu(i)} |\hat{c}_{ij}^{(d)}| \right)^{-1}, \tag{5.2}$$

where $\hat{c}_{ij}$ are derivative weights of the degree in use, $q(k_{\mathrm{div}})$ in the frozen and $q(K)$ in the coupled mode (with the order capped at four, three in 3-D), from a fit without constant term. The ℓ^1 norm of the weights plays the role of $1/h$ and adapts the time step to the local stencil, so the CFL number is not a Courant number; $\mathrm{CFL} \le D$ essentially implies the positivity condition (4.4). For a uniform wave speed λ, the weights on our clouds give $\lambda \Delta t / h \approx 0.32\,\mathrm{CFL}$

for degree-one weights and ≈ 0.11 CFL for degree-three weights. Schemes with derivative degree three therefore take about three times as many steps as the second-order scheme, while the frozen mode with $k_{\mathrm{div}} = 2$ takes as many steps as the second-order scheme for every K.

5.3 Boundary conditions

Boundary conditions prescribe the states of the ghost particles and are applied to every state the time integrator forms. *Dirichlet* ghosts carry a prescribed state. *Transmissive* ghosts copy, in up to five passes, the state of the nearest neighbour with a known state. *Slip walls* use the transmissive copy and reflect the wall-normal momentum. These conditions are simple and robust but only first-order accurate at walls, since the ghost states are copies of nearest interior states rather than mirror images at reflected positions.

5.4 Implementation

The method is implemented in Julia [30, 31]. Every pass over the particles (reconstruction fits, fluxes, MOOD detection, boundary conditions, time step) is a kernel that runs on multi-threaded CPUs or, through KernelAbstractions, on GPUs. Neighbour lists are built with a cell list, the particles are reordered along a Morton curve for memory locality, and on a fixed cloud the inverse moment matrices of the full-order fits are computed once. All arithmetic is generic in the floating-point type; the computations of Section 6 use double precision unless stated otherwise.

6 Numerical experiments

6.1 Setup

All results were computed with HyperCloudCore 0.7.8, on the high-performance cluster Elwetritsch except for the Sod problem, which was run in double precision on a workstation CPU. The convergence studies and the conservation tests use double precision on the CPU nodes of the cluster (AMD EPYC). The two-dimensional Euler problems use single precision on its GPU nodes (CUDA), the setting the implementation targets for such problems. The labels RKsMUSCLK(variant,flux,MLSm) denote the Runge–Kutta method (RK2 and RK3 the SSP methods, RK4SSP the method SSPRK(5,4)), the design order K, the stabilization ("none", a limiter or an interface rule (4.5) of MOOD), the numerical flux (AR for the aligned and RU for the geometric orientation of the Rusanov flux, Section 3.3) and the mode of the derivative degree ($m = 0$ coupled, $m = k_{\mathrm{div}}$ frozen); parts of the label that are clear from the context are omitted. MOOD always uses PAD, the DMP with the relaxation $\delta_0 = 10^{-4}$, the plateau test with $\pi_0 = 10^{-3}$ and the u2 criterion (Section 4.1), and it

checks the forward Euler substeps of the SSP methods (Section 5.1). The scheme with $K = 1$, RK2MUSCL1, uses the derivative weights of degree one and, as a baseline, the plain Rusanov flux with the geometric orientation; unlike the first-order fallback inside MOOD, it is therefore not covered by the positivity argument of Section 4.2. The two-dimensional problems solve the Euler equations with $\gamma = 1.4$ on lattices perturbed by $0.2h$ (Section 2.1) with $\kappa = 2.5$, $\alpha = 1$ and CFL $= 0.8$; Table 1 lists their parameters. Densities are shown as colour maps or with contour lines after interpolation of the particle values to a uniform plotting grid with PDEStudio [34]; contour wiggles on the scale of h are partly due to this interpolation. Positions quoted from the figures were read from the colour maps and are accurate to about 0.01. We do not report run times, since the implementation is still evolving; where the cost matters we give the number of time steps.

Table 1 Parameters of the two-dimensional Euler problems ($\kappa = 2.5$, perturbation $0.2h$, CFL $= 0.8$, single precision).

	2-D Riemann problem	double Mach reflection
domain	$[0,1]^2$	$[0,3.2] \times [0,1]$
lattice	800×800	1440×450
spacing	$h = 1/800$	$h = 1/450$
interior particles	6.4×10^5	$\approx 6.5 \times 10^5$
final time	$t = 0.3$	$t = 0.2$

6.2 Smooth solutions

We measure the convergence of the schemes without limiter and MOOD for three scalar problems with periodic boundaries and the Gaussian initial datum $u_0(x) = \exp(-|x|^2)$:

- one-dimensional linear advection $\partial_t u + \partial_x u = 0$ on $[-5,5]$ over one period, $t = 10$, with $N = 32, \dots, 3163$ particles (21 resolutions);
- two-dimensional linear advection $\partial_t u + \partial_1 u + \partial_2 u = 0$ on $\Omega = [-5,5]^2$ up to $t = 1$, with the exact solution $u(x,t) = u_0(x - t\,(1,1))$ continued periodically;
- the two-dimensional Burgers equation $\partial_t u + \partial_1(\tfrac{1}{2}u^2) + \partial_2(\tfrac{1}{2}u^2) = 0$ on Ω up to $t = 0.5$, with the exact solution given implicitly by $u = u_0\big(x - u\,t\,(1,1)\big)$, which we solve by Newton's method. The directional derivative $g = (1,1)\cdot\nabla u$ satisfies $\dot g = -g^2$ along characteristics, so the solution breaks at $t^* = 1/\max(-(1,1)\cdot\nabla u_0) = \tfrac{1}{2}\mathrm{e}^{1/2} \approx 0.82$. At $t = 0.5$ it is still smooth, but its largest gradient has grown by the factor $1/(1 - t/t^*) \approx 2.5$, and higher derivatives have grown more. The exact solution ignores periodicity, which changes it by less than $\exp(-4.5^2) \approx 2 \cdot 10^{-9}$ on Ω.

In two dimensions the particles form $N \times N$ lattices, $h = 10/N$, with sixteen resolutions $N = 32, \dots, 1000$ equally spaced on a logarithmic scale. All sweeps are run on unperturbed lattices and on lattices perturbed by $0.2h$, with the support radius $R = 5.5h$ (96 neighbours in two dimensions), which admits the derivative fit of degree five that $K = 5$ requires, and with $R = 2.5h$, the radius of the shock computations, for $K \leq 4$ (Section 3.2). The schemes use RK2 for $K = 2$, RK3 for $K = 3$ and RK4SSP for $K = 4, 5$, the aligned Rusanov flux (which coincides with the geometric one without MOOD), the frozen derivative degree $k_{\text{div}} = K$, and CFL $= 0.2$. With $\kappa = 5.5$, (5.2) gives $\Delta t/h \approx 0.15$ for $K = 2$ and $\Delta t/h \approx 0.06$ for $K \geq 3$ at the maximum wave speed $|u| \leq 1$, and with $\kappa = 2.5$ smaller steps (Section 5.2), so that the time integration error is negligible; for $K = 5$ it limits the asymptotic order to four in principle, but no such limitation is visible in the range tested. Table 2 lists the discrete L^1 error $h^D \sum_i |U_i - u(x_i, t)|$ of all sweeps, and Fig. 3 compares the two radii in two dimensions.


With $\kappa = 5.5$ every scheme attains its design order for linear advection, in agreement with Section 3.2. In one dimension the mean orders of the last three refinement steps are 2.00, 3.00, 4.00 and 5.00 for $K = 2, 3, 4, 5$, and the L^1 error of RK4SSPMUSCL5 reaches $5.3 \cdot 10^{-10}$ at $N = 3163$; in two dimensions they are 2.08, 3.00, 4.03 and 5.00. For $K = 3$ the degree-three derivative operator of (3.4) is essential; with the even degree two the order would drop to two. The Burgers problem is in the pre-asymptotic range for most of the resolutions, because the solution steepens: for $K = 3$ and $K = 5$ the observed orders increase steadily and reach 2.95 and 4.93 in the last step, for $K = 2$ and $K = 4$ they overshoot to about 2.2 and 4.3. The Rusanov dissipation, whose coefficient $|u|$ varies in space, does not reduce the order. On the clouds perturbed by $0.2h$ the results with $\kappa = 5.5$ are practically the same: the errors differ from those on the lattice by at most 6.3% at every resolution, and the mean orders agree to within 0.02. Although the truncation-error argument of Section 3.2 only covers symmetric stencils, the design orders are thus also attained on irregular clouds; as for FV schemes on irregular grids [18], the truncation error is a pessimistic predictor of the error.

The smaller radius $\kappa = 2.5$ of the shock computations keeps the design orders on lattices (in two dimensions 2.02, 3.00, 4.01 for advection and 2.06, 2.98, 4.12 for Burgers) with errors at the finest resolution that are 5 to 30 times smaller than with $\kappa = 5.5$ in two dimensions (42 times for $K = 4$ in one dimension), since the fits weight the near neighbours more strongly; the exception is $K = 3$ in one dimension, which falls back to the derivative degree two (Section 3.2) and is of second order. Fig. 3 shows that on the perturbed clouds the radius acts mainly on the error constant. For $K = 2$ the curves of both radii are parallel, and at $N = 1000$ the relative L^2 errors with $\kappa = 2.5$ are 4.9 (advection) and 5.0 (Burgers) times smaller than with $\kappa = 5.5$. For $K = 4$ the factors are 8.5 and 19. $K = 2$ and $K = 3$ keep their orders on the perturbed clouds (1.97–2.00 and 2.91 in two dimensions, Table 2), whereas $K = 4$ with $\kappa = 2.5$ drops to 2.98 in one dimension, 3.24 for two-dimensional advection and 3.78 for Burgers, visible in Fig. 3 as the less regular slope of

Table 2 Discrete L^1 errors and observed orders. The rows with N give the errors on periodic lattices with $\kappa = 5.5$ and the orders between consecutive rows; "mean, last 3" is the mean of the orders of the last three refinement steps of the full sweep (factor $10^{0.1}$ per step). The row "perturbed, $\kappa = 5.5$" gives, for the clouds perturbed by $0.2h$, the ratio of the error at the finest resolution to that on the lattice and the mean order; the rows with $\kappa = 2.5$ give the error at the finest resolution and the mean order.

	RK2MUSCL2		RK3MUSCL3		RK4SSPMUSCL4		RK4SSPMUSCL5	
N	error	order	error	order	error	order	error	order
one-dimensional linear advection, $t = 10$								
100	6.69e-1		3.01e-1		2.86e-2		1.51e-2	
200	2.41e-1	1.47	5.66e-2	2.41	1.46e-3	4.30	5.19e-4	4.86
399	6.59e-2	1.88	7.82e-3	2.87	8.43e-5	4.13	1.66e-5	4.99
795	1.67e-2	1.99	1.00e-3	2.98	5.21e-6	4.04	5.29e-7	5.00
1585	4.21e-3	2.00	1.27e-4	3.00	3.28e-7	4.01	1.68e-8	5.00
3163	1.05e-3	2.00	1.60e-5	3.00	2.06e-8	4.00	5.31e-10	5.00
mean, last 3		2.00		3.00		4.00		5.00
perturbed, $\kappa = 5.5$	$\times$0.99	2.00	$\times$1.00	3.00	$\times$1.00	3.98	$\times$1.02	4.98
lattice, $\kappa = 2.5$	2.10e-4	2.00	9.89e-5	2.00	4.94e-10	4.00		
perturbed, $\kappa = 2.5$	2.04e-4	2.00	9.85e-5	2.00	2.47e-8	2.98		
two-dimensional linear advection, $t = 1$								
51	1.43e0		8.33e-1		2.31e-1		1.54e-1	
100	4.29e-1	1.79	1.68e-1	2.38	1.03e-2	4.61	7.12e-3	4.57
200	8.81e-2	2.28	2.32e-2	2.85	4.38e-4	4.56	2.31e-4	4.94
399	1.84e-2	2.27	2.98e-3	2.97	2.45e-5	4.18	7.37e-6	4.99
795	4.26e-3	2.12	3.78e-4	2.99	1.50e-6	4.05	2.35e-7	5.00
1000	2.66e-3	2.05	1.90e-4	3.00	5.98e-7	4.02	7.47e-8	5.00
mean, last 3		2.08		3.00		4.03		5.00
perturbed, $\kappa = 5.5$	$\times$0.99	2.08	$\times$1.01	3.00	$\times$0.98	4.02	$\times$1.01	4.99
lattice, $\kappa = 2.5$	5.44e-4	2.02	1.66e-5	3.00	1.95e-8	4.01		
perturbed, $\kappa = 2.5$	5.43e-4	1.99	1.87e-5	2.91	8.16e-8	3.24		
two-dimensional Burgers equation, $t = 0.5$								
51	4.14e-1		2.29e-1		7.46e-2		5.59e-2	
100	1.16e-1	1.90	4.96e-2	2.27	1.12e-2	2.81	8.25e-3	2.84
200	2.73e-2	2.08	8.47e-3	2.55	1.13e-3	3.31	7.72e-4	3.42
399	6.03e-3	2.19	1.26e-3	2.76	6.91e-5	4.05	4.37e-5	4.16
795	1.34e-3	2.18	1.71e-4	2.90	3.53e-6	4.31	1.65e-6	4.75
1000	8.25e-4	2.12	8.71e-5	2.95	1.33e-6	4.26	5.33e-7	4.93
mean, last 3		2.15		2.93		4.30		4.85
perturbed, $\kappa = 5.5$	$\times$1.01	2.14	$\times$1.01	2.93	$\times$1.05	4.28	$\times$1.01	4.84
lattice, $\kappa = 2.5$	1.64e-4	2.06	7.75e-6	2.98	4.20e-8	4.12		
perturbed, $\kappa = 2.5$	1.99e-4	1.97	8.50e-6	2.91	1.06e-7	3.78		

the curve RK4SSPMUSCL4($R = 2.5$): with $0.2h$ perturbations some stencils of radius $2.5h$ are too close to the minimal size for the degree-three fits. In two dimensions the errors of $K = 4$ with $\kappa = 2.5$ are nevertheless smaller than with $\kappa = 5.5$ over the whole range tested ($1.1 \cdot 10^{-7}$ instead of $1.4 \cdot 10^{-6}$ in L^1 for Burgers at $N = 1000$); in one dimension they are about 20% larger at $N = 3163$. For the full order of $K = 4$ on perturbed clouds, κ between 3.5 and 5.5 is needed.



(a) linear advection, $t = 1$ (b) Burgers equation, $t = 0.5$

Fig. 3 Relative discrete L^2 errors $\left(\sum_i |U_i - u(x_i,t)|^2\right)^{1/2} / \left(\sum_i u(x_i,t)^2\right)^{1/2}$ for the Gaussian pulse in two dimensions on $N \times N$ particles in $[-5,5]^2$ perturbed by $0.2h$ ("grid resolution" N, $h = 10/N$), without limiter or MOOD, for RK2MUSCL2 and RK4SSPMUSCL4 with the support radii $R = 2.5h$ and $R = 5.5h$; dashed lines: slopes -2 and -4


6.3 Mass conservation

Summing the volume-weighted updates (3.1) over all interior particles shows that the scheme is conservative if the generalized face vectors $S_{ij} = 2V_i c_{ij}$ are antisymmetric, $S_{ij} = -S_{ji}$, like the normals of a mesh face seen from its two cells. The MLS weights have this property on lattices with equal volumes, but not on irregular clouds: on the perturbed lattices of our experiments the relative pair defects $|V_i c_{ij} + V_j c_{ji}|$ are about 6% for degree one and 17% for degree three, and 73% for pairs whose two particles use different derivative degrees, which the coupled mode creates at the boundaries of every lowered region. Meshless coefficients that are exactly antisymmetric can be constructed [12, 13, 59]; we do not apply such a correction here. To measure the effect, we report the *conservation defect*

$$\delta_m = \frac{m(t_{\mathrm{end}}) - m(0) - \Phi(t_{\mathrm{end}})}{m(t_{\mathrm{end}})}, \tag{6.1}$$

with the discrete mass $m(t) = \bar{h}^D \sum_{i \in I} U_i$, the equal volumes $\bar{h}^D = |\Omega|/|I|$ and the exact time-integrated boundary flux Φ, for a one-dimensional Burgers shock: $u = 1$ for $x < -2$ and $u = 0$ for $x > -2$ on $[-5,5]$ with transmissive boundaries, up to $t = 10$, so $\Phi = \frac{1}{2}t$. We use $N = 32, \ldots, 3163$ particles perturbed by $0.4h$, $\kappa = 5.5$, CFL $= 0.2$ and the aligned flux. The full study, including smooth and two-dimensional problems, other perturbations and radii, the limiters and the geometric flux, is part of the supplementary material.

Fig. 4 shows the main effects. Without MOOD and in the frozen mode with $k_{\mathrm{div}} = 2$, the defect decreases under refinement, at rates between 0.7 and 1, to a few 10^{-4} at $N = 3163$, which is the resolution of this test: even on the unperturbed lattice, the position of the inflow boundary and of the initial jump causes defects of up to half a particle of the inflow state. The coupled



(a) MOOD with EPD1 (b) MOOD with EPD2

Fig. 4 Conservation defect $|\delta_m|$ of (6.1) for the one-dimensional Burgers shock, perturbation $0.4h$, $\kappa = 5.5$, aligned flux, for RK4SSPMUSCL4 without MOOD (MLS4) and with MOOD in the coupled mode (MLS0) and in the frozen mode with $k_{\mathrm{div}} = 2$ (MLS2) and $k_{\mathrm{div}} = 4$ (MLS4)

mode changes the mass by several percent (3–14% for $K = 3, 4, 5$), and this defect does not decrease under refinement; the coupled mode should therefore not be used for $K \geq 3$. The frozen mode with $k_{\mathrm{div}} = K$ avoids mixed degrees; its defects mostly decrease like those of the unstabilized scheme, except for EPD1 with $K = 4$, whose defect stays at about 10^{-3} in the range tested, and for $K = 5$, where some stencils are too small for the degree-five fit and fall back to a lower degree. The difference between mixed and equal degrees has a simple explanation: the pairs of a high-degree and a low-degree particle at the boundary of a lowered region have the same arrangement wherever the shock is, so their defects have a systematic sign and accumulate, whereas with equal degrees on a randomly perturbed cloud the defects of the pairs at the shock change sign as the shock moves and largely cancel. For smooth solutions the defects caused by the irregular cloud are small, about 10^{-4} in two dimensions at $N = 200$, and decrease under refinement.

6.4 The Sod shock tube

As a one-dimensional test for systems we use the shock tube of Sod [56]: $(\rho, u, p) = (1, 0, 1)$ for $x < 0$ and $(0.125, 0, 0.1)$ for $x > 0$ on $[-0.5, 0.5]$, $\gamma = 1.4$, up to $t = 0.2$, with a Dirichlet condition on the left and a transmissive condition on the right. The clouds are lattices perturbed by $0.2h$ with $N = 100, \ldots, 1000$ particles (eleven resolutions), $\kappa = 5.5$, $\alpha = 1$ and CFL $= 0.2$. We compare RK2MUSCL1, RK2MUSCL2 with EPD1, EPD2 and the VK limiter, and RK3MUSCL3 and RK4SSPMUSCL4 with EPD1 and EPD2 in the frozen mode with $k_{\mathrm{div}} = 2$ and $k_{\mathrm{div}} = K$, all with the aligned flux except RK2MUSCL1. The errors are measured against the exact Riemann solution. Fig. 5 shows the profiles at $N = 200$ and Table 3 the errors.




Fig. 5 Sod shock tube at $t = 0.2$ on $N = 200$ particles perturbed by $0.2h$, $\kappa = 5.5$: density, momentum and energy of RK2MUSCL1, RK2MUSCL2(VK,MLS2), RK4SSPMUSCL4(EPD1,MLS4) and RK4SSPMUSCL4(EPD2,MLS4), and the exact solution; all schemes except RK2MUSCL1 use the aligned flux

Table 3 Sod shock tube at $t = 0.2$, perturbation $0.2h$, $\kappa = 5.5$: discrete L^1 and L^2 errors of the density against the exact solution, observed orders between $N = 502$ and $N = 1000$, and the relative mass change $m(t)/m(0) - 1$ at $N = 1000$.

	$L^1(\rho)$				$L^2(\rho)$		
	$N = 100$	$N = 317$	$N = 1000$	order	$N = 1000$	order	mass, $N = 1000$
RK2MUSCL1	4.51e-2	2.91e-2	1.55e-2	0.59	2.49e-2	0.42	+2.5e-5
RK2MUSCL2(EPD1,MLS2)	2.63e-2	1.32e-2	4.68e-3	0.87	1.17e-2	0.55	+3.3e-5
RK2MUSCL2(EPD2,MLS2)	3.06e-2	1.52e-2	5.49e-3	0.92	1.28e-2	0.57	+3.2e-5
RK2MUSCL2(VK,MLS2)	2.97e-2	1.05e-2	3.57e-3	0.97	1.01e-2	0.52	+3.1e-5
RK3MUSCL3(EPD1,MLS2)	2.89e-2	1.00e-2	3.30e-3	1.00	1.02e-2	0.54	+3.3e-5
RK3MUSCL3(EPD2,MLS2)	2.97e-2	1.49e-2	5.25e-3	0.92	1.26e-2	0.57	+3.3e-5
RK3MUSCL3(EPD1,MLS3)	2.81e-2	9.64e-3	3.16e-3	1.00	9.62e-3	0.57	+6.0e-5
RK3MUSCL3(EPD2,MLS3)	2.84e-2	9.48e-3	3.12e-3	1.02	9.49e-3	0.57	+1.2e-4
RK4SSPMUSCL4(EPD1,MLS2)	2.58e-2	8.67e-3	2.80e-3	1.00	9.61e-3	0.51	+3.2e-5
RK4SSPMUSCL4(EPD2,MLS2)	2.88e-2	1.41e-2	4.93e-3	0.93	1.18e-2	0.58	+3.6e-5
RK4SSPMUSCL4(EPD1,MLS4)	2.56e-2	8.18e-3	2.65e-3	1.05	8.24e-3	0.61	+8.0e-5
RK4SSPMUSCL4(EPD2,MLS4)	2.59e-2	8.27e-3	2.72e-3	1.06	8.39e-3	0.61	+1.0e-4

All 132 runs reach the final time with positive density and pressure; the minimum density is that of the exact right state, 0.125, in all runs except RK2MUSCL2(EPD1), where it is 0.1249. For every scheme with $K \geq 2$ the L^1 error decreases with orders between 0.87 and 1.06, the rate expected for a solution with a shock, and the L^2 error with orders between 0.51 and 0.61; RK2MUSCL1 is not yet in its asymptotic range (0.59). The frozen mode with $k_{\mathrm{div}} = K$ gives the smallest errors, $3.1 \cdot 10^{-3}$ for $K = 3$ and $2.7 \cdot 10^{-3}$ for $K = 4$ at $N = 1000$, 5.0 and 5.8 times less than RK2MUSCL1. With $k_{\mathrm{div}} = 2$, EPD2 gains little over the second-order scheme ($5.2 \cdot 10^{-3}$ and $4.9 \cdot 10^{-3}$ for $K = 3, 4$, compared with $5.5 \cdot 10^{-3}$ for $K = 2$), EPD1 more ($3.3 \cdot 10^{-3}$ and $2.8 \cdot 10^{-3}$, compared with $4.7 \cdot 10^{-3}$). At $K = 2$ the VK limiter ($3.6 \cdot 10^{-3}$) is more accurate than both MOOD variants. In Fig. 5 the fourth-order schemes resolve the contact discontinuity and the shock over a few particles, with at most small overshoots, while RK2MUSCL1 smears all three waves; RK2MUSCL2(VK) lies in between, with a visibly wider contact and shock. Since the waves stay inside the domain and $u = 0$ in both boundary states, the exact mass is constant. Near both boundaries the state stays constant, so that the zero row sums make

the updates there vanish and the boundaries cannot change the mass. The measured mass changes of $2.5 \cdot 10^{-5}$ to $1.2 \cdot 10^{-4}$ at $N = 1000$ are therefore the static asymmetry of the derivative weights at the moving shock and contact; they are largest with $k_{\mathrm{div}} = K$, whose degree-three weights have the larger pair defects (Section 6.3).

6.5 Two-dimensional shock problems

The two-dimensional Riemann problem and the double Mach reflection were computed with the first-order baseline RK2MUSCL1 (plain Rusanov flux) and, with the aligned flux, MUSCL2 with EPD1, EPD2 and the VK limiter, and MUSCL3 and MUSCL4 with EPD1 and EPD2 in the frozen mode with $k_{\mathrm{div}} = 2$ and $k_{\mathrm{div}} = K$ and in the coupled mode, and MUSCL2 to MUSCL4 with EPD2 and $k_{\mathrm{div}} = 2$ also with the geometric flux; the coupled MUSCL4 runs of the double Mach reflection use 960×300 particles. Table 4 summarizes positivity and mass. All 38 runs, and three Riemann runs with transmissive boundaries (Section 6.6), reach the final time with positive density and pressure and without invalid values, including the coupled mode. On the Riemann problem, the minimum pressures of the second- to fourth-order schemes, 0.018 to 0.029, undershoot the lowest initial pressure 0.029 by up to 39%; the lowest values occur with EPD1 and $k_{\mathrm{div}} = K$. With $k_{\mathrm{div}} = 2$ the aligned and the geometric flux agree to within about 4% in all quantities of Table 4, and the high-order schemes take as many time steps as the second-order scheme; with $k_{\mathrm{div}} = K$ and in the coupled mode they take about three times as many (Section 5.2).

In the frozen mode the final masses agree with that of RK2MUSCL2(EPD1) to within 0.25% on both problems. Since the problems have inflow and outflow boundaries, the reference is a computed mass, and the masses are known to three digits, i.e. to about 0.1%. The coupled mode with EPD1 is not conservative: its final mass differs by +5.4% ($K = 3$) and +4.7% ($K = 4$) on the double Mach reflection and by +1.4% ($K = 3$) on the Riemann problem, consistent with Section 6.3; with EPD2 the differences are smaller, −0.3 to +0.7%.

6.6 A two-dimensional Riemann problem

Two-dimensional Riemann problems with four constant states in the quadrants of $[0, 1]^2$ were classified by Zhang and Zheng [67], Schulz-Rinne [51] and Chang, Chen and Yang [10, 11], computed systematically by Schulz-Rinne, Collins and Glaz [52] and by Lax and Liu [39], whose numbering we follow, and have become standard benchmarks for shock-capturing schemes [37]. We use Configuration 3 of [37, 39], in which every pair of adjacent quadrants is connected by a single shock. With the discontinuities at $x = 0.5$ and $y = 0.5$, the initial states (ρ, u, v, p) are

(0.5323, 1.206, 0, 0.3)	(1.5, 0, 0, 1.5)
(0.138, 1.206, 1.206, 0.029)	(0.5323, 0, 1.206, 0.3)

Table 4 Two-dimensional shock problems: minimum particle pressure and final mass relative to RK2MUSCL2(EPD1,AR,MLS2) (total masses known to about 0.1%). Pairs of values: EPD1 / EPD2. All runs except RK2MUSCL1 with the aligned flux. *: 960×300 particles; the mass is still compared with the 1440×450 run of RK2MUSCL2(EPD1).

	double Mach reflection		2-D Riemann problem	
	$\min p$	mass (%)	$\min p$	mass (%)
RK2MUSCL1	1.00	−0.2	0.029	0.0
MUSCL2				
EPD1 / EPD2 / VK	1.00	0.0	0.024 / 0.029 / 0.027	0.0
MUSCL3, $k_{\text{div}} = 2$	1.00	0.0	0.020 / 0.028	0.0
MUSCL3, $k_{\text{div}} = 3$	0.96 / 0.99	−0.2 / 0.0	0.018 / 0.026	0.0 / +0.1
MUSCL3, coupled	0.96 / 0.99	+5.4 / +0.7	0.023 / 0.026	+1.4 / −0.3
MUSCL4, $k_{\text{div}} = 2$	1.00	0.0	0.026 / 0.029	0.0
MUSCL4, $k_{\text{div}} = 4$	0.91 / 0.97	−0.2 / 0.0	0.022 / 0.027	−0.1 / +0.1
MUSCL4, coupled	0.88* / 0.96*	+4.7* / +0.2*	0.019 / 0.027	+0.4 / −0.1

in the upper left, upper right, lower left and lower right quadrants, and the solution is computed until $t = 0.3$. Away from the centre the solution consists of plane shocks, whose positions follow from the Rankine–Hugoniot conditions: the shocks bounding the upper right state move with speed -0.663 and lie at $x = 0.301$ and $y = 0.301$ at $t = 0.3$, and the shocks bounding the low-density lower left state move with speed -0.422 and lie at $x = 0.373$ and $y = 0.373$. The ghost particles carry these exact plane-shock states on all four sides. Near the centre the shocks interact: the two shocks bounding the low-density state are joined by a curved shock between two triple points, and along the diagonal a mushroom-shaped jet with two roll-ups forms. The problem is symmetric with respect to the diagonal $x = y$.

Figs. 6 and 7 show the density at $t = 0.3$. All runs reproduce the expected wave pattern. With the exact boundary states, the shocks are straight up to the boundaries and lie close to their exact positions, 0.373 and 0.301, symmetric with respect to the diagonal. With transmissive instead of exact boundary states, the final mass of the EPD2 runs with $k_{\text{div}} = 2$ is 0.6% ($K = 2, 3$) and 0.9% ($K = 4$) lower, a boundary effect that does not concern the interior scheme.

The resolution of the jet along the diagonal differs between the schemes. RK2MUSCL1 smears the cap of the jet into a single blob without roll-ups. The second-order runs resolve the two roll-ups of the mushroom cap; the third- and fourth-order runs resolve them with sharper gradients and a thinner stem. EPD1 and the VK limiter produce a local density maximum of about 1.7 next to the jet, at about $(0.43, 0.43)$, which EPD2 smears. In the contour lines of Fig. 7 the fourth-order run shows small-scale noise in the upper right state next to the jet. The MOOD runs show faint lines along $x = 0.5$ and $y = 0.5$ in the upper right state of Fig. 6, traces of the initial discontinuities in the fluid at rest, a start-up error common to shock-capturing schemes [43]. In Fig. 7 faint straight contour lines run from the interaction region towards the lower right; we have not identified their origin.




Fig. 6 Two-dimensional Riemann problem (Configuration 3), density at $t = 0.3$ on 800×800 particles perturbed by $0.2h$, with a common colour scale, for RK2MUSCL1, RK2MUSCL2 with the VK limiter, EPD2 and EPD1, RK3MUSCL3(EPD1,MLS3) and RK4SSPMUSCL4(EPD1,MLS4); all schemes except RK2MUSCL1 use the aligned flux

6.7 Double Mach reflection

The double Mach reflection of Woodward and Colella [66] describes a Mach 10 shock that hits a 30° wedge, so that the shock makes an angle of 60° with the wall. In the frame of the wall, the shock initially lies on the line $x = \frac{1}{6} + y/\sqrt{3}$ and separates the pre-shock state $(\rho, u, v, p) = (1.4, 0, 0, 1)$ on the right from the post-shock state $(8,\ 8.25\cos 30°,\ -8.25\sin 30°,\ 116.5)$ on the left. At the bottom, the post-shock state is prescribed for $x < \frac{1}{6}$ and a slip wall for $x \geq \frac{1}{6}$; at the top, the ghost particles carry the exact states of the moving incident shock, $x_s(y,t) = \frac{1}{6} + (y + 20t)/\sqrt{3}$; the left boundary is an inflow of the post-shock state and the right boundary is transmissive. We use the reduced domain $[0, 3.2] \times [0, 1]$ instead of the domain $[0, 4] \times [0, 1]$ of Woodward and Colella; it contains all waves until $t = 0.2$.

Figs. 8 and 9 show the density at $t = 0.2$. All runs reproduce the characteristic pattern: the incident shock, which meets the top boundary at $x \approx 3.05$,




Fig. 7 Two-dimensional Riemann problem: detail $[0.225, 0.5] \times [0.21, 0.52]$ of Fig. 6 with 100 contour levels

its exact position, the reflected shock, the Mach stem, the two triple points, the slip line and the wall jet. The second-order run smears the slip line, and the wall jet forms only a weak curl. The third- and fourth-order runs resolve the slip line sharply, and the jet rolls up into a vortex near $x \approx 2.5$, with more structure for $K = 4$; the resolution of this roll-up is a common indicator of the numerical dissipation of a scheme. EPD1 and EPD2 give almost the same picture for $K = 3$. The stems of the third- and fourth-order runs are almost straight at $x \approx 2.76$. In the second-order run the stem bends forward near the wall, to $x \approx 2.79$, where the wall jet runs into the foot of the stem. All runs show the highest densities at the wall near $x = \frac{1}{6}$, where the boundary condition switches from the post-shock state to the wall; it is a start-up error caused by the discontinuous boundary data at the foot of the initial shock.




Fig. 8 Double Mach reflection, density at $t = 0.2$ on 1440×450 particles perturbed by $0.2h$ for RK2MUSCL2(VK), RK3MUSCL3(EPD1,MLS3), RK3MUSCL3(EPD2,MLS3) and RK4SSPMUSCL4(EPD1,MLS4), all with the aligned flux, with a common colour scale

6.8 Discussion

The test problems are demanding even for conservative FV schemes on Cartesian meshes. In the double Mach reflection the resolution of the slip line and of the roll-up of the wall jet is a sensitive measure of numerical dissipation, the discontinuous boundary data at the beginning of the wall cause a start-up error, and Roe's Riemann solver, whose dissipation is low, can produce a kinked Mach stem [49]. Our scheme faces these difficulties without the structural advantages of FV methods: it is not exactly conservative (Section 6.3), its stencils are irregular and overlapping, and its walls are represented by ghost particles with first-order boundary states. Against this background the results




Fig. 9 Double Mach reflection, detail $[2.13, 2.9] \times [0, 0.47]$ of Fig. 8 with 100 contour levels

are robust. For smooth solutions the schemes attain their design orders up to five on lattices and on perturbed clouds. With the aligned flux every shock computation completes with positive density and pressure, in single precision and without any problem-specific treatment, and with the full derivative degree the third- and fourth-order schemes resolve slip lines and roll-ups markedly better than the second-order scheme.

Three ingredients make the schemes work. First, the derivative degree $q(k)$ of (3.4) is odd, so that the leading flux errors cancel on symmetric stencils and the truncation error is of order k on lattices (Section 3.2); with the even degree $k-1$ the odd orders would lose one order. The parity argument covers symmetric stencils only, but the convergence studies show the same orders on clouds perturbed by $0.2h$ whenever the stencils are large enough for the fits (Section 6.2). Second, the aligned orientation of the Rusanov dissipation keeps the first-order fallback positive for derivative weights of any degree. With the geometric orientation, about 40% of the degree-three weights turn the dissipation of a lowered particle into anti-dissipation (Section 4.2), so that with this orientation the fallback of the fourth-order scheme with $k_{\mathrm{div}} = 4$ is not positive; with the aligned orientation it runs on all shock problems. Third,

MOOD checks the forward Euler substeps of the SSP methods, so that every Runge–Kutta stage is a convex combination of checked states (Section 5.1).

The aligned flux removes the trade-off between a positive fallback and conservation. The positivity of the first-order scheme follows from the orientation of the dissipation (Section 4.2) instead of the degree of the derivative operator, so the degree can stay the same for all particles, and the pairs of different degrees, whose conservation defect does not decrease under refinement, do not occur. The coupled mode, which keeps these pairs, is positive as well, but it changes the mass by several percent and is not competitive. What remains in the frozen mode is the static asymmetry of the weights on irregular clouds, whose effect decreases under refinement also at moving shocks (Section 6.3). The price is more dissipation at lowered particles with high-degree weights and, for $k_{\mathrm{div}} \geq 3$, a three times smaller time step. The frozen mode with $k_{\mathrm{div}} = K$ keeps the formal order, is positive on all problems and resolves the most structure, at three times the cost of the second-order scheme. With $k_{\mathrm{div}} = 2$ the frozen mode costs as much as the second-order scheme and conserves to the floor of all tests, but by Section 3.2 it is formally of second order in smooth regions, although its reconstructions are of higher degree. The two interface rules trade accuracy for robustness. EPD1 is less dissipative: for $K = 3, 4$ with $k_{\mathrm{div}} = 2$ its Sod errors are 1.6 to 1.8 times smaller than those of EPD2, and it keeps the density maximum next to the jet of the Riemann problem, which EPD2 smears; with $k_{\mathrm{div}} = K$ the two rules give almost the same accuracy on the Sod problem and the double Mach reflection. EPD2 is more robust: with $k_{\mathrm{div}} = K$ its minimum pressures are higher on both two-dimensional problems (on the Riemann problem 0.026 and 0.027 for $K = 3, 4$, against 0.018 and 0.022 with EPD1), and at $K = 4$ its conservation defect at the moving shock decreases under refinement, whereas that of EPD1 stays at about 10^{-3} in the range tested.

Limitations are the reduced order of $K = 4$ on perturbed clouds with the small radius $\kappa = 2.5$ and the first-order ghost-particle boundary conditions. For the present code we recommend the frozen mode with the aligned flux, with $k_{\mathrm{div}} = K$ for the full formal order and $k_{\mathrm{div}} = 2$ where cost matters more than the formal order, and MOOD with EPD1 for less dissipation or EPD2 for more robustness.

7 Open questions and further studies

The experiments raise a number of questions that we leave to future work.

– *Smooth-extremum detection.* The plateau test and the revised u2 criterion are meant to keep smooth extrema for $K \geq 3$; a systematic study on smooth flows is left to future work. Open are a plateau threshold that does not depend on the global range and the resolution, a smooth-extremum test for $K = 2$, curvature tests on characteristic or primitive variables, and the behaviour on smooth flows with extrema of several components at once.

- *Conservation.* With the aligned flux and the frozen degree-one derivative operator the conservation defect decreases under refinement. Constructing antisymmetric face vectors [12] would remove it, and constraining the weights to approximately antisymmetric ones [59] would reduce it; and with the aligned orientation such weights would keep a positive fallback. It remains open why the frozen mode with $k_{\mathrm{div}} = K \geq 4$ and EPD1 keeps defects of about 10^{-3} that decrease slowly or not at all (Section 6.3), and how the defect depends on h in general.
- *Interface reconstructions.* Lower interface orders truncate the existing fit instead of refitting (Section 3.2); whether a refit per interface improves the results at discontinuities, and at what cost, is open; for whole cells, FV-MOOD schemes abandoned truncation for degrees above two [16, Remark 4].
- *Symmetry of the aligned flux.* On perturbed clouds the two particles of a pair use different fluxes on the pairs whose weights have equal signs (Section 3.3). A symmetric choice, for instance by the sign of $V_i c_{ij} - V_j c_{ji}$, would keep the positivity argument only approximately; whether it improves conservation is open.
- *Stencils.* The full order of $K = 4$ on perturbed clouds with $\kappa = 2.5$, and adaptive radii.
- *Boundary conditions.* Ghost states at reflected positions instead of nearest-donor copies would raise the order at walls.
- *Further tests.* Refinement studies of the shock problems against converged reference solutions, the Lax and Shu–Osher problems, and three-dimensional problems.

8 Conclusions

We have presented meshfree MUSCL schemes of arbitrary design order for hyperbolic systems on scattered point clouds. Midpoint Riemann problems between MLS reconstructions, combined with an MLS derivative operator with zero row sums, give an update in terms of interface fluxes only. The scheme is exact for polynomial solutions of degree $k - 1$ of linear problems, the degree of the derivative operator follows from a parity argument, and the conservation error reduces to the lack of antisymmetry of the volume-weighted derivative weights. A priori limiters and a stage-wise MOOD procedure with physical and numerical admissibility detection and three interface rules control oscillations. Orienting the Rusanov dissipation by the signs of the derivative weights makes the first-order fallback positive for derivative operators of any degree, so that the derivative degree can stay uniform while MOOD lowers the reconstruction degrees, which removes the pairs of mixed degrees that dominated the conservation error.

The numerical experiments show that these schemes are a promising and robust basis for high-order meshfree computations of compressible flows. For smooth solutions they attain their design orders two to five on lattices and on

perturbed clouds. With a derivative operator of degree one the conservation defect at moving shocks decreases under refinement and reaches the resolution of the tests; with higher degrees it is small but, for $K = 4$ with EPD1 and for $K = 5$, decreases slowly or not at all. On the double Mach reflection and a two-dimensional Riemann problem on perturbed clouds of up to 6.5×10^5 particles, all computations complete with positive density and pressure, in single precision, reproduce the characteristic wave patterns without spurious waves apart from start-up errors, and with the full derivative degree the high-order schemes resolve fine structures markedly better than the second-order scheme. Checking the forward Euler substeps of the SSP methods makes every Runge–Kutta stage a convex combination of checked states. The limitations we observed are the reduced order of the fourth-order scheme on perturbed clouds with small stencils and the low-order ghost-particle boundary conditions.

The natural next steps are weights with (approximately) antisymmetric face vectors [12, 59], and higher-order boundary conditions (Section 7). The implementation [30, 31] already supports moving clouds in an arbitrary Lagrangian–Eulerian setting, implicit–explicit time integration, three-dimensional problems and GPUs, which will allow applications to physical problems with a more mature version of the method.

Software

The schemes are implemented in HyperCloudCore.jl [30] (version 0.7.8; all results of Section 6), the test cases are run with HyperCloud.jl [31] (version 0.5.1), and the figures were produced with PDEStudio [34] (version 0.4.5). The run configurations and the driver scripts of all experiments are in [33]. HyperCloudCore.jl was developed over roughly 18 months with AI assistance whose form changed over the project. In the earlier phase, Gemini models, mostly 3.1 Pro, were used interactively to draft code, explain errors, and suggest implementations, and the first author adapted and integrated this output by hand. From commit 2e4e6fb970 (14.10.2026) onward, most code changes were written with Claude Fable 5.1 in Claude Code, and each change was submitted as a pull request that the first author reviewed manually before merging. Because the two modes were interleaved with the first author's own programming, no precise per-component attribution is given. The correctness of the solver as a whole was established independently of the AI tooling through the convergence studies and benchmarks found in Section 6. All numerical results in this paper come from executing the code. The full development history is available at `https://github.com/industrial-mathematics-group/HyperCloudCore.jl`.

Acknowledgements The computations were carried out on the high-performance cluster Elwetritsch of the Regional University Computing Center Kaiserslautern-Landau (RHRZ) at RPTU.

Declarations

Funding This work was funded by the Deutsche Forschungsgemeinschaft (DFG, German Research Foundation), grant KL 1105/34.

Competing interests [TODO: confirm or replace: The authors have no competing interests to declare that are relevant to the content of this article.]

Ethics approval and consent Not applicable.

Data availability The run reports and tables of all computations reported in this paper, the run configurations, the finite-volume reference solutions, the stencil diagnostics and the scripts that produce the wave positions read from the figures are publicly available in the repository `https://github.com/industrial-mathematics-group/meshfree-solver-paper` and archived on Zenodo at [TODO: DOI of the Zenodo archive of the repository].

Code availability The solver HyperCloudCore.jl [30] (version 0.7.8), the simulation framework HyperCloud.jl [31] (version 0.5.1) and the visualization package PDEStudio [34] (version 0.4.5) are open source and archived on Zenodo. The run configurations and driver scripts are available in [33], and the finite-volume reference code and the mathematical addendum [32] are part of the supplementary material at `https://github.com/industrial-mathematics-group/meshfree-solver-paper` (archived at [TODO: DOI of the Zenodo archive of the repository]). A preprint of this paper is available at `https://zenodo.org/records/23807966`.

Author contributions [TODO: author contribution statement, e.g. in CRediT form: Conceptualization: …; Methodology: …; Software: …; Formal analysis and investigation: …; Writing – original draft preparation: …; Writing – review and editing: …; Funding acquisition: …; Supervision: …]

Use of large language models During the preparation of this work, the first author used Claude Opus 5.5 (Anthropic) to draft substantial parts of the manuscript text. The use of AI tools in the development of the software is described in the section “Software” above; the finite-volume reference code of the supplementary material was written with Claude Fable 5.1 (Anthropic) in Claude Code. The authors reviewed, revised, and verified all content and take full responsibility for the content of this publication. The AI declaration for the supplementary material can be found at `https://github.com/industrial-mathematics-group/meshfree-solver-paper`.

References

1. Avesani, D., Dumbser, M., Bellin, A.: A new class of moving-least-squares WENO-SPH schemes. J. Comput. Phys. **270**, 278–299 (2014). https://doi.org/10.1016/j.jcp.2014.03.041
2. Barth, T.J., Jespersen, D.C.: The design and application of upwind schemes on unstructured meshes. In: 27th Aerospace Sciences Meeting. American Institute of Aeronautics and Astronautics (1989). https://doi.org/10.2514/6.1989-366. AIAA Paper 89-0366
3. Belytschko, T., Krongauz, Y., Organ, D., Fleming, M., Krysl, P.: Meshless methods: an overview and recent developments. Comput. Methods Appl. Mech. Eng. **139**(1–4), 3–47 (1996). https://doi.org/10.1016/S0045-7825(96)01078-X
4. Benito, J.J., Ureña, F., Gavete, L.: Influence of several factors in the generalized finite difference method. Appl. Math. Model. **25**(12), 1039–1053 (2001). https://doi.org/10.1016/S0307-904X(01)00029-4
5. Benito, J.J., Ureña, F., Gavete, L.: Solving parabolic and hyperbolic equations by the generalized finite difference method. J. Comput. Appl. Math. **209**(2), 208–233 (2007). https://doi.org/10.1016/j.cam.2006.10.090
6. Boscheri, W., Loubère, R., Dumbser, M.: Direct Arbitrary-Lagrangian-Eulerian ADER-MOOD finite volume schemes for multidimensional hyperbolic conservation laws. J. Comput. Phys. **292**, 56–87 (2015). https://doi.org/10.1016/j.jcp.2015.03.015
7. Bourgeois, R., Lee, D.: GP-MOOD: a positivity-preserving high-order finite volume method for hyperbolic conservation laws. J. Comput. Phys. **471**, 111603 (2022). https://doi.org/10.1016/j.jcp.2022.111603
8. Chan, A., Gallice, G., Loubère, R., Maire, P.H.: Positivity preserving and entropy consistent approximate Riemann solvers dedicated to the high-order MOOD-based finite volume discretization of Lagrangian and Eulerian gas dynamics. Comput. Fluids **229**, 105056 (2021). https://doi.org/10.1016/j.compfluid.2021.105056
9. Chandrashekar, P.: A positive meshless method for hyperbolic equations. Fluid Mechanics Report 2004-FM-16, Department of Aerospace Engineering, Indian Institute of Science, Bangalore (2004)
10. Chang, T., Chen, G.Q., Yang, S.: On the 2-D Riemann problem for the compressible Euler equations. I. Interaction of shocks and rarefaction waves. Discrete Contin. Dyn. Syst. **1**(4), 555–584 (1995). https://doi.org/10.3934/dcds.1995.1.555
11. Chang, T., Chen, G.Q., Yang, S.: On the 2-D Riemann problem for the compressible Euler equations. II. Interaction of contact discontinuities. Discrete Contin. Dyn. Syst. **6**(2), 419–430 (2000). https://doi.org/10.3934/dcds.2000.6.419
12. Chiu, E.K.Y., Wang, Q., Hu, R., Jameson, A.: A conservative mesh-free scheme and generalized framework for conservation laws. SIAM J. Sci. Comput. **34**(6), A2896–A2916 (2012). https://doi.org/10.1137/110842740
13. Chiu, E.K.Y., Wang, Q., Jameson, A.: A conservative meshless scheme: general order formulation and application to Euler equations. In: 49th AIAA Aerospace Sciences Meeting. American Institute of Aeronautics and Astronautics, Orlando, FL (2011). https://doi.org/10.2514/6.2011-651. AIAA Paper 2011-651
14. Clain, S., Diot, S., Loubère, R.: A high-order finite volume method for systems of conservation laws—Multi-dimensional Optimal Order Detection (MOOD). J. Comput. Phys. **230**(10), 4028–4050 (2011). https://doi.org/10.1016/j.jcp.2011.02.026
15. Clain, S., Figueiredo, J.: Stencil and kernel optimisation for mesh-free very high-order generalised finite difference method. Math. Comput. Simul. **218**, 49–78 (2024). https://doi.org/10.1016/j.matcom.2023.11.009
16. Diot, S., Clain, S., Loubère, R.: Improved detection criteria for the Multi-dimensional Optimal Order Detection (MOOD) on unstructured meshes with very high-order polynomials. Comput. Fluids **64**, 43–63 (2012). https://doi.org/10.1016/j.compfluid.2012.05.004
17. Diot, S., Loubère, R., Clain, S.: The Multidimensional Optimal Order Detection method in the three-dimensional case: very high-order finite volume method for hyperbolic systems. Int. J. Numer. Methods Fluids **73**(4), 362–392 (2013). https://doi.org/10.1002/fld.3804

18. Diskin, B., Thomas, J.L.: Notes on accuracy of finite-volume discretization schemes on irregular grids. Appl. Numer. Math. **60**(3), 224–226 (2010). https://doi.org/10.1016/j.apnum.2009.12.001
19. Dumbser, M., Zanotti, O., Loubère, R., Diot, S.: A posteriori subcell limiting of the discontinuous Galerkin finite element method for hyperbolic conservation laws. J. Comput. Phys. **278**, 47–75 (2014). https://doi.org/10.1016/j.jcp.2014.08.009
20. Farmakis, P.S., Tsoutsanis, P., Nogueira, X.: WENO schemes on unstructured meshes using a relaxed a posteriori MOOD limiting approach. Comput. Methods Appl. Mech. Eng. **363**, 112921 (2020). https://doi.org/10.1016/j.cma.2020.112921
21. Fornberg, B., Lehto, E.: Stabilization of RBF-generated finite difference methods for convective PDEs. J. Comput. Phys. **230**, 2270–2285 (2011). https://doi.org/10.1016/j.jcp.2010.12.014
22. Ghosh, A.K., Deshpande, S.M.: Least squares kinetic upwind method for inviscid compressible flows. In: 12th Computational Fluid Dynamics Conference. American Institute of Aeronautics and Astronautics, San Diego, CA (1995). https://doi.org/10.2514/6.1995-1735. AIAA Paper 95-1735
23. Gottlieb, S., Ketcheson, D.I., Shu, C.W.: Strong Stability Preserving Runge–Kutta and Multistep Time Discretizations. World Scientific, Singapore (2011). https://doi.org/10.1142/7498
24. Gottlieb, S., Shu, C.W., Tadmor, E.: Strong stability-preserving high-order time discretization methods. SIAM Rev. **43**(1), 89–112 (2001). https://doi.org/10.1137/S003614450036757X
25. Harten, A., Engquist, B., Osher, S., Chakravarthy, S.R.: Uniformly high order accurate essentially non-oscillatory schemes, III. J. Comput. Phys. **71**(2), 231–303 (1987). https://doi.org/10.1016/0021-9991(87)90031-3
26. Hou, T.Y., LeFloch, P.G.: Why nonconservative schemes converge to wrong solutions: error analysis. Math. Comput. **62**(206), 497–530 (1994). https://doi.org/10.1090/S0025-5718-1994-1201068-0
27. Hubbard, M.E.: Multidimensional slope limiters for MUSCL-type finite volume schemes on unstructured grids. J. Comput. Phys. **155**(1), 54–74 (1999). https://doi.org/10.1006/jcph.1999.6329
28. Huh, J.Y., Rhee, J.S., Kim, K.H., Jung, S.Y.: New least squares method with geometric conservation law (GC-LSM) for compressible flow computation in meshless method. Comput. Fluids **172**, 122–146 (2018). https://doi.org/10.1016/j.compfluid.2018.06.010
29. Jensen, P.S.: Finite difference techniques for variable grids. Comput. Struct. **2**(1–2), 17–29 (1972). https://doi.org/10.1016/0045-7949(72)90020-X
30. Jung, P.: HyperCloudCore.jl: High-performance, physics-agnostic meshless solver backend for hyperbolic PDEs. https://github.com/industrial-mathematics-group/HyperCloudCore.jl (2026). https://doi.org/10.5281/zenodo.23737384. Version 0.7.8
31. Jung, P.: HyperCloud.jl: A comprehensive meshfree simulation framework for solving N-dimensional hyperbolic PDEs with high-order numerical accuracy. https://github.com/industrial-mathematics-group/HyperCloud.jl (2026). https://doi.org/10.5281/zenodo.23685993. Version 0.5.1
32. Jung, P.: Meshfree MUSCL schemes with a posteriori order detection: exactness, conservation and admissibility. Supplementary material, https://github.com/industrial-mathematics-group/meshfree-solver-paper, archived at [TODO: Zenodo DOI of the repository] (2026). Mathematical companion to this paper
33. Jung, P.: meshfree-simulations: run configurations and driver scripts for the meshfree MUSCL experiments. https://github.com/industrial-mathematics-group/meshfree-simulations (2026)
34. Jung, P.: PDEStudio.jl: Interactive visualization and exploration for PDE simulations. https://github.com/industrial-mathematics-group/PDEStudio.jl (2026). https://doi.org/10.5281/zenodo.23770548. Version 0.4.5
35. Katz, A., Jameson, A.: A meshless volume scheme. In: 19th AIAA Computational Fluid Dynamics Conference. American Institute of Aeronautics and Astronautics, San Antonio, TX (2009). https://doi.org/10.2514/6.2009-3534. AIAA Paper 2009-3534

36. Ketcheson, D.I.: Highly efficient strong stability-preserving Runge–Kutta methods with low-storage implementations. SIAM J. Sci. Comput. **30**(4), 2113–2136 (2008). https://doi.org/10.1137/07070485X
37. Kurganov, A., Tadmor, E.: Solution of two-dimensional Riemann problems for gas dynamics without Riemann problem solvers. Numer. Methods Partial Differ. Equ. **18**(5), 584–608 (2002). https://doi.org/10.1002/num.10025
38. Lancaster, P., Salkauskas, K.: Surfaces generated by moving least squares methods. Math. Comput. **37**(155), 141–158 (1981). https://doi.org/10.1090/S0025-5718-1981-0616367-1
39. Lax, P.D., Liu, X.D.: Solution of two-dimensional Riemann problems of gas dynamics by positive schemes. SIAM J. Sci. Comput. **19**(2), 319–340 (1998). https://doi.org/10.1137/S1064827595291819
40. Lax, P.D., Wendroff, B.: Systems of conservation laws. Commun. Pure Appl. Math. **13**(2), 217–237 (1960). https://doi.org/10.1002/cpa.3160130205
41. van Leer, B.: Towards the ultimate conservative difference scheme. V. A second-order sequel to Godunov's method. J. Comput. Phys. **32**(1), 101–136 (1979). https://doi.org/10.1016/0021-9991(79)90145-1
42. Levin, D.: The approximation power of moving least-squares. Math. Comput. **67**(224), 1517–1531 (1998). https://doi.org/10.1090/S0025-5718-98-00974-0
43. Liska, R., Wendroff, B.: Comparison of several difference schemes on 1D and 2D test problems for the Euler equations. SIAM J. Sci. Comput. **25**(3), 995–1017 (2003). https://doi.org/10.1137/S1064827502402120
44. Liszka, T., Orkisz, J.: The finite difference method at arbitrary irregular grids and its application in applied mechanics. Comput. Struct. **11**(1–2), 83–95 (1980). https://doi.org/10.1016/0045-7949(80)90149-2
45. Loubère, R., Dumbser, M., Diot, S.: A new family of high order unstructured MOOD and ADER finite volume schemes for multidimensional systems of hyperbolic conservation laws. Commun. Comput. Phys. **16**(3), 718–763 (2014). https://doi.org/10.4208/cicp.181113.140314a
46. Nguyen, V.P., Rabczuk, T., Bordas, S., Duflot, M.: Meshless methods: a review and computer implementation aspects. Math. Comput. Simul. **79**(3), 763–813 (2008). https://doi.org/10.1016/j.matcom.2008.01.003
47. Perrone, N., Kao, R.: A general finite difference method for arbitrary meshes. Comput. Struct. **5**(1), 45–57 (1975). https://doi.org/10.1016/0045-7949(75)90018-8
48. Perthame, B., Shu, C.W.: On positivity preserving finite volume schemes for Euler equations. Numer. Math. **73**(1), 119–130 (1996). https://doi.org/10.1007/s002110050187
49. Quirk, J.J.: A contribution to the great Riemann solver debate. Int. J. Numer. Methods Fluids **18**(6), 555–574 (1994). https://doi.org/10.1002/fld.1650180603
50. Ramesh, V., Deshpande, S.M.: Least squares kinetic upwind method on moving grids for unsteady Euler computations. Comput. Fluids **30**(5), 621–641 (2001). https://doi.org/10.1016/S0045-7930(01)00010-X
51. Schulz-Rinne, C.W.: Classification of the Riemann problem for two-dimensional gas dynamics. SIAM J. Math. Anal. **24**(1), 76–88 (1993). https://doi.org/10.1137/0524006
52. Schulz-Rinne, C.W., Collins, J.P., Glaz, H.M.: Numerical solution of the Riemann problem for two-dimensional gas dynamics. SIAM J. Sci. Comput. **14**(6), 1394–1414 (1993). https://doi.org/10.1137/0914082
53. Seibold, B.: M-matrices in meshless finite difference methods. Ph.D. thesis, Technische Universität Kaiserslautern (2006). Published by Shaker, Aachen, ISBN 978-3-8322-5643-2
54. Shu, C.W.: Essentially non-oscillatory and weighted essentially non-oscillatory schemes for hyperbolic conservation laws. In: A. Quarteroni (ed.) Advanced Numerical Approximation of Nonlinear Hyperbolic Equations, *Lecture Notes in Mathematics*, vol. 1697, pp. 325–432. Springer (1998). https://doi.org/10.1007/BFb0096355
55. Shu, C.W., Osher, S.: Efficient implementation of essentially non-oscillatory shock-capturing schemes. J. Comput. Phys. **77**(2), 439–471 (1988). https://doi.org/10.1016/0021-9991(88)90177-5

56. Sod, G.A.: A survey of several finite difference methods for systems of nonlinear hyperbolic conservation laws. J. Comput. Phys. **27**(1), 1–31 (1978). https://doi.org/10.1016/0021-9991(78)90023-2
57. Spiteri, R.J., Ruuth, S.J.: A new class of optimal high-order strong-stability-preserving time discretization methods. SIAM J. Numer. Anal. **40**(2), 469–491 (2002). https://doi.org/10.1137/S0036142901389025
58. Suchde, P.: Conservation and accuracy in meshfree generalized finite difference methods. Ph.D. thesis, Technische Universität Kaiserslautern (2017). Published by Fraunhofer Verlag, Stuttgart, 2018, ISBN 978-3-8396-1325-2
59. Suchde, P., Kuhnert, J., Schröder, S., Klar, A.: A flux conserving meshfree method for conservation laws. Int. J. Numer. Methods Eng. **112**(3), 238–256 (2017). https://doi.org/10.1002/nme.5511
60. Tiwari, S., Kuhnert, J.: Finite pointset method based on the projection method for simulations of the incompressible Navier–Stokes equations. In: M. Griebel, M.A. Schweitzer (eds.) Meshfree Methods for Partial Differential Equations, *Lecture Notes in Computational Science and Engineering*, vol. 26, pp. 373–387. Springer (2003). https://doi.org/10.1007/978-3-642-56103-0_26
61. Toro, E.F.: Riemann Solvers and Numerical Methods for Fluid Dynamics: A Practical Introduction, 3rd edn. Springer (2009). https://doi.org/10.1007/b79761
62. Venkatakrishnan, V.: Convergence to steady state solutions of the Euler equations on unstructured grids with limiters. J. Comput. Phys. **118**(1), 120–130 (1995). https://doi.org/10.1006/jcph.1995.1084
63. Willems, K.: meshfree4hypeq. https://github.com/KlaasWillems/meshfree4hypeq (2025)
64. Willems, K., Klar, A., Russo, G., Samaey, G., Tiwari, S.: A meshless MUSCL method for the BGK-Boltzmann equation. arXiv preprint arXiv:2512.11598 (2025). https://doi.org/10.48550/arXiv.2512.11598
65. Willems, K., Klar, A., Samaey, G.: Higher-order meshless schemes for hyperbolic equations. J. Sci. Comput. **105**(3), 90 (2025). https://doi.org/10.1007/s10915-025-03124-4
66. Woodward, P., Colella, P.: The numerical simulation of two-dimensional fluid flow with strong shocks. J. Comput. Phys. **54**(1), 115–173 (1984). https://doi.org/10.1016/0021-9991(84)90142-6
67. Zhang, T., Zheng, Y.: Conjecture on the structure of solutions of the Riemann problem for two-dimensional gas dynamics systems. SIAM J. Math. Anal. **21**(3), 593–630 (1990). https://doi.org/10.1137/0521032
68. Zhang, X., Shu, C.W.: On positivity-preserving high order discontinuous Galerkin schemes for compressible Euler equations on rectangular meshes. J. Comput. Phys. **229**(23), 8918–8934 (2010). https://doi.org/10.1016/j.jcp.2010.08.016