

## Pointer arithmetic

In the addressing system operations with pointers are performed. Which are the ARITHMETIC operations allowed with pointers in **COMPUTER SCIENCE** ?...

**Answer:** Any operation that makes sense... meaning any operation that expresses as a result a correct location in memory useful as an information for the programmer/processor.

- adding a constant value to a pointer  $a[7] = *(a+7)$  – useful for going into memory forth and back relative to a starting address
- subtracting .....  $a[-4]$  ,  $a(-4)$  ...
- multiplying 2 pointers ? – No way ... no practical usage !
- dividing 2 pointers ? - No way ... no practical usage !
- adding/subtracting 2 pointers ?
- ADDING 2 pointers doesn't make sense !! – it is not allowed
- SUBTRACTING 2 pointers !! does makes sense...  $q-p$  = nr. of elements (in C) = nr. of bytes between these 2 addresses in assembly (this can be very useful for determine the length of a memory area).

$$a[7] = *(a+7) = *(7+a) = 7[a] \quad \text{- both in C and assembly !}$$

**POINTER ARITHMETIC OPERATIONS** - *Pointer arithmetic* represents the set of arithmetic operations allowed to be performed with pointers, this meaning using arithmetic expressions which have addresses as operands.

Pointer arithmetic contains ONLY 3 operations that are possible:

1). Subtracting two addresses

Address – address = ok ( $q-p$  = subtraction of 2 pointers = `sizeof(array)` in C, **the number of bytes between these 2 addresses** in assembly)

Address - offset = address – address

2). Adding a numerical constant to a pointer

Address + numerical constant (identification of an element by indexing –  $a[7]$ ) ,  $q+9$

3). Subtracting a numerical constant from a pointer

Address - numerical constant -  $a[-4]$  ,  $p-7$ ;  
 **$*(a-4)$  - useful for reffering array elements**

- subtraction of 2 pointers = SCALAR VALUE (constant)
- adding a constant to a pointer → a POINTER !!
- subtracting a constant from a pointer → a POINTER !!

ADDING TWO POINTERS IS NOT ALLOWED !!!

$p+q = ????$  (allowed in NASM...sometimes...) – but it doesn't mean in the end as we shall see that this is “a pointer addition” !!!

How do I make the difference between the address of a variable and its contents ?

Var – invoked like that it is an address (offset) ; [var] – is its contents

[] = the dereferencing operator !! (like \*p in C)

V db 17

add edx, [EBX+ECX\*2 + v -7] – OK !!!!

mov ebx, [EBX+ECX\*2 - v-7] – Syntax error !!!! invalid effective address – impossible segment base multiplier

mov [EBX+ECX\*2 + a+b-7], bx - not allowed ! syntax error ! because of “a+b”  
invalid effective address – impossible segment base multiplier

sub [EBX+ECX\*2 + a-b-7], eax – ok, because a-b is a correct pointers operation !!!

[EBX+ECX\*2 + v -7] – ok  
SIB      displ. const.

[EBX+ECX\*2 + a-b-7]  
SIB      const.

mov eax, [EBX+ECX\*2+(-7)] – ok.

## L-value vs. R-value. LHS vs. RHS of an assignment.

Assignment:  $i := i + 1$

LHS vs. RHS

Address of I  $\leftarrow$  value of I + 1

$LHS(i) = \text{Address of I} := RHS(i) = (\text{the contents from the address } i) + 1$

LHS (Left Hand Side of an assignment = L-value = address) := RHS  
(Right Hand Side of an assignment = R-Value = CONTENTS !!)

---

Symbol := expression\_value

Identifier := expression (usually in 99% of the cases)

Address\_computation\_expression := expression (the most general)

Dereferencing is usually implicit depending on the context ! in 99% of the cases. Exception: BLISS language, where dereferencing must always be explicitly specified;  $i \leftarrow *i + 1$  (also we have some similar situations in Algol68)

---

Symbol := expression\_value (99% of the cases...)

Address\_computation\_Expression := expression\_value

In C++  $f(a, b, 2) = x + y + z$

$\text{Int\& } f(i, \dots) \{ \dots \text{return } v[i]; \}$  – f is a function that will return an L-value !!  
 $f(88, \dots) = 79$ ; it means that  $v[88] = 79$  !!!

$\text{Int\& } j = i$ ; // j becomes ALIAS for i

$(a + 2 ? b : c) = x + y + z$ ; - correct

$(a + 2 ? 1 : c) = x + y + z$ ; - syntax error !!!  $1 := n$  !!!!!

---

## Segment data

A db 17,-2

B dw -20345, "x"

Start2:

C dd 12345678h

.....

## Segment code

.....

Jmp start2 ; example of a jump in a data segment, so code labels are accepted in  
; data segments !

.....

---