

Integrating Type Operators into the FreeST Programming Language

Paula Lopes[✉], Diana Costa[✉], and Vasco T. Vasconcelos[✉]

LASIGE, Faculdade de Ciências, Universidade de Lisboa, Portugal

Abstract. Context-free session types emerged from the need to expand session type theory to non-regular protocols. Their inclusion in type systems enhances the expressiveness and adaptability of communication protocols in programming languages, yet pose a significant challenge for type equivalence algorithms. In this work, we study System $F_{\omega}^{\mu*}$, the higher-order polymorphic lambda calculus equipped with equirecursive and context-free session types, as well as its seamless integration into FreeST, a functional programming language governed by context-free session types. We follow a bisimulation-based approach to type equivalence, translating types into simple grammars and verifying the bisimilarity of these grammars, a problem that is decidable.

Keywords: Higher-order Kinds · Context-Free Session Types · Session Polymorphism · Type Equivalence · Simple Grammar.

1 Introduction

In the field of programming languages, the drive for more advanced and expressive type systems never stops. This journey has led us from the foundational System F [9] to the more intricate System F_{ω}^{μ} [4]. Integrating these advanced systems into real-world programming languages, however, comes with its own set of challenges, especially when it comes to type equivalence.

FreeST [1], a concurrent functional programming language based on system F^{μ} , is regulated by context-free session types. Context-free session types, unlike regular session types, are not restricted to tail recursion, thus allowing the description of more sophisticated communication protocols. FreeST's current type equivalence algorithm, developed by Almeida et al. [2] decides the equivalence of context-free session types by reducing the problem to the bisimilarity of simple grammars. The next step is to extend the language to a higher-order setting where type equivalence is still decidable.

In this work, we study the System $F_{\omega}^{\mu*}$, the higher-order polymorphic lambda calculus equipped with equirecursive and context-free session types and its incorporation into a programming language. We follow a bisimulation-based type equivalence, proposed by Poças et al. [8], which supports the robust implementation of advanced type systems in programming languages. We seek to bridge the gap between advanced type theory and practical compiler design, ensuring that

the powerful capabilities of context-free session types can be effectively utilized without compromising on performance or reliability.

In the development of modern type systems, combining advanced features such as equirecursion, higher-order polymorphism, and higher-order context-free session types presents unique challenges and opportunities. The primary motivation for our research is to integrate these elements into a cohesive type system that can be practically incorporated into programming languages. Therefore, we are interested in practical algorithms for type equivalence checking to be incorporated into compilers.

Context-free session types and beyond. Context-free session types break free from tail recursion by introducing the sequential composition operator $;$ and the type **Skip**—neutral element of sequential composition—which represents a protocol with no actions. The recursive type $\mu\alpha: \mathbf{s}.\&\{\mathbf{Leaf}: \mathbf{Skip}, \mathbf{Node}: \alpha; ?\mathbf{Int}; \alpha\}; \mathbf{End}?$ describes a protocol for safely streaming integer trees on a channel. The channel presents an external choice $\&$ with two labels: if the continuation of the channel is **Leaf**, then no communication occurs but the channel is still open for further composition whereas, if the continuation of the channel is **Node**, then we have a left subtree, followed by an integer and a right subtree. When the whole tree is received, the channel is closed. It is also important to distinguish type **End?** from **Skip**—the former represents the closure of a channel, where no further communication is possible, while the latter allows continuing the communication. We want to move beyond context-free session types, namely, we are interested in abstracting the type that is received on the tree channel, by writing $\lambda\beta: \mathbf{r}.\mu\alpha: \mathbf{s}.\&\{\mathbf{Leaf}: \mathbf{Skip}, \mathbf{Node}: \alpha; ?\beta; \alpha\}; \mathbf{Wait}$. Abstractions introduce higher-order kinds which lead to the introduction of type operators into our language.

Duality as an external macro (or not). Duality is the relationship between two session types that allows them to correctly engage in a protocol. For any session type describing one side of the communication (let us say the client), there is a dual session type that describes the other side (the server). For example, the session type **!Int** describes sending an integer and its dual session type is to receive an integer, **?Int**. Typically, duality is offered as a built in constructor [6]. However, we believe duality should be internal, by means of a type operator, since in a polymorphic setting duality cannot be eliminated without the introduction of co-variables.

Outline. The rest of the paper is organised as follows: Section 2 introduces System $F_{\omega}^{\mu*}$ and type equivalence; Section 3 presents the challenges encountered during this research and prove the decidability of type formation; Section 4 explains the decidability of type equivalence; Section 5 describes our implementation process and validates our work and Section 6 wraps up the paper.

$T ::=$		Type	
ι	type constructor	$\lambda\alpha : \kappa.T$	type-level abstraction
α	type variable	TT	type-level application

$\iota ::=$		Type constructor	
\rightarrow	$* \Rightarrow * \Rightarrow T$ arrow	$(\overline{l_i})$	$* \Rightarrow T$ record/variant
μ_κ	$(\kappa \Rightarrow \kappa) \Rightarrow \kappa$ recursive type	\sharp	$* \Rightarrow S$ input/output
$;$	$S \Rightarrow S \Rightarrow S$ seq.composition	$\odot\{\overline{l_i}\}$	$\overline{S} \Rightarrow S$ internal/external choice
\exists_κ	$(\kappa \Rightarrow *) \Rightarrow T$ exists/forall	Dual	$S \Rightarrow S$ dual operator
End \sharp	S wait/close	Skip	S skip

$\langle \rangle ::= \{ \} \mid \langle \rangle$	$\sharp ::= ? \mid !$	$\odot ::= \oplus \mid \&$	$\exists_\kappa ::= \exists_\kappa \mid \forall_\kappa$
--	-----------------------	----------------------------	---

Fig. 1: The syntax of types and constructors.

2 System $F_\omega^{\mu*}$

In programming languages, terms are categorized by types, which in turn may be categorized by kinds. In our system, a *kind* κ is either a base kind $*$ —which is either a session or a functional kind, S or T , respectively—or a higher-order kind $\kappa \Rightarrow \kappa'$. A *proper type* refers to a type that has a base kind. In contrast, *type operators* act upon types to create more complex types, and are associated with higher-order kinds. For example, the type operator \rightarrow takes two types, T and U , and constructs a new type, a function type $\rightarrow TU$, which we sometimes write in infix notation as $T \rightarrow U$. This is the core of our work. Our goal is to expand the programming language FreeST, currently limited to types of kind $*$, to higher-order kinds.

A type is either a type constructor ι , a type variable α , an abstraction $\lambda\alpha : \kappa.T$ or an application TT . A detailed list of types and constructors is in Fig. 1. Observe that $\mu_\kappa \alpha : \kappa.T$ is syntactic sugar for $\mu_\kappa(\lambda\alpha : \kappa.T)$ and similarly for $\exists_\kappa \alpha : \kappa.T$.

Not all types are of interest—for example **Dual** $\forall_s \lambda\alpha : S.\alpha$ since the dual operator makes no sense being applied to a functional type. Before we can discuss type formation, we must define the weak head normal form of a type; we do so by defining a system of reduction rules in Fig. 2. This system is that of Poças et al. [8] made confluent by adding the proviso that $T \neq T_1; T_2$ to rules R-SEQ2 and R-DCTX. *Confluence* states that, if there are two distinct reductions for a given type, $T \rightarrow U$ and $T \rightarrow V$, then both paths will eventually converge into the same final reduced type W . Our variant features a single reduction path, thus confluence immediately follows.

Type reduction

 $T \longrightarrow T$

$$\begin{array}{c}
\text{R-SEQ1} \quad \text{Skip}; T \longrightarrow T \qquad \text{R-SEQ2} \quad \frac{T \longrightarrow V \quad T \neq T_1; T_2}{T; U \longrightarrow V; U} \qquad \text{R-ASSOC} \quad (T; U); V \longrightarrow T; (U; V) \\
\\
\text{R-}\mu \quad \mu_{\kappa} T \longrightarrow T(\mu_{\kappa} T) \qquad \text{R-}\beta \quad (\lambda\alpha : \kappa.T) U \longrightarrow T[U/\alpha] \qquad \text{R-TAPPL} \quad \frac{T \longrightarrow U}{TV \longrightarrow UV} \\
\\
\text{R-D;} \quad \text{Dual}(T; U) \longrightarrow \text{Dual } T; \text{Dual } U \qquad \text{R-DSKIP} \quad \text{Dual Skip} \longrightarrow \text{Skip} \qquad \text{R-DWAIT} \quad \text{Dual End}_? \longrightarrow \text{End}_! \\
\\
\text{R-DCLOSE} \quad \text{Dual End}_! \longrightarrow \text{End}_? \qquad \text{R-D?} \quad \text{Dual}(?T) \longrightarrow !T \qquad \text{R-D!} \quad \text{Dual}(!T) \longrightarrow ?T \\
\\
\text{R-D\&} \quad \text{Dual}(\&\{\overline{l_i : T_i}\}) \longrightarrow \oplus\{\overline{l_i : \text{Dual}(T_i)}\} \qquad \text{R-D}\oplus \quad \text{Dual}(\oplus\{\overline{l_i : T_i}\}) \longrightarrow \&\{\overline{l_i : \text{Dual}(T_i)}\} \\
\\
\text{R-DCTX} \quad \frac{T \longrightarrow U \quad T \neq T_1; T_2}{\text{Dual } T \longrightarrow \text{Dual } U} \qquad \text{R-DDVAR} \quad \text{Dual}(\text{Dual}(\alpha T_1 \dots T_m)) \longrightarrow \alpha T_1 \dots T_m
\end{array}$$

Fig. 2: Type reduction.

A type is in *normal form*, denoted $T \text{ whnf}$, if it has been completely reduced, *i.e.*, no further reductions are possible. In other words, $T \text{ whnf}$ iff $T \rightarrow$. Then we can say that type T *normalises* to type U , written $T \Downarrow U$, if $U \text{ whnf}$ and U is reached from T in a finite number of reduction steps. The predicate $T \text{ norm}$ means that $T \Downarrow U$ for some U . Note that not all types normalise, *i.e.*, some have an infinite sequence of reductions, such as $T = (\lambda x.xx)(\lambda x.xx) \rightarrow (\lambda x.xx)[(\lambda x.xx)/x] = T \rightarrow \dots$ —which is stuck in a loop of reductions to itself via the application of rule R- β —and $U = \mu_s(\lambda\alpha : s.\alpha; \text{Skip}) \rightarrow (\lambda\alpha : s.\alpha; \text{Skip})U \rightarrow U; \text{Skip} \rightarrow_2 U; \text{Skip}; \text{Skip} \rightarrow \dots$ —which successively applies rules R- μ , R- β in combination with R-SEQ2, resulting in the unending addition of a trailing Skip .

Finally, we introduce *well-formed types*. We use $\Delta \vdash T : \kappa$ to denote that T is a *well-formed type* with kind κ under the kinding context Δ , a map from type variables to kinds. The kinds of constants can be found in Fig. 1. A variable α has kind κ if $\alpha : \kappa \in \Delta$. An abstraction $\lambda\alpha : \kappa.T$ has kind $\kappa \Rightarrow \kappa'$ if T is well-formed. Note that $\Delta + \alpha : \kappa$ in rule K-TABS represents updating the kind of the type variable α to a new kind κ in the context Δ if $\alpha : \kappa' \in \Delta$ for some κ' , or storing the kind of α in the context Δ if otherwise. Finally, rule K-TAPP states that an application TU is well-formed if T and U are types and TU normalises, that is, $TU \text{ norm}$. In Section 3 we prove decidability of type formation, imposing a restriction to kind $*$ for recursive types, also adopted by Poças et al. in [8].

Type formation

 $\Delta \vdash T : \kappa$

$$\begin{array}{c}
\text{K-CONST} \quad \text{K-VAR} \quad \text{K-TABS} \quad \text{K-TAPP} \\
\frac{\Delta \vdash \iota : \kappa_\iota}{\Delta \vdash \iota : \kappa_\iota} \quad \frac{\alpha : \kappa \in \Delta}{\Delta \vdash \alpha : \kappa} \quad \frac{\Delta + \alpha : \kappa \vdash T : \kappa'}{\Delta \vdash \lambda\alpha : \kappa.T : \kappa \Rightarrow \kappa'} \quad \frac{\Delta \vdash T : \kappa \Rightarrow \kappa' \quad \Delta \vdash U : \kappa \quad TU \text{ norm}}{\Delta \vdash TU : \kappa'}
\end{array}$$

Fig. 3: Type formation.

Pre-kinding

 $\Delta \vdash_{\text{pre}} T : \kappa$

$$\begin{array}{c}
\text{PK-CONST} \quad \text{PK-VAR} \quad \text{PK-TABS} \quad \text{PK-TAPP} \\
\frac{\Delta \vdash_{\text{pre}} \iota : \kappa_\iota}{\Delta \vdash_{\text{pre}} \iota : \kappa_\iota} \quad \frac{\alpha : \kappa \in \Delta}{\Delta \vdash_{\text{pre}} \alpha : \kappa} \quad \frac{\Delta + \alpha : \kappa \vdash_{\text{pre}} T : \kappa'}{\Delta \vdash_{\text{pre}} \lambda\alpha : \kappa.T : \kappa \Rightarrow \kappa'} \quad \frac{\Delta \vdash_{\text{pre}} T : \kappa \Rightarrow \kappa' \quad \Delta \vdash_{\text{pre}} U : \kappa}{\Delta \vdash_{\text{pre}} TU : \kappa'}
\end{array}$$

Fig. 4: Pre-kinding.

Type equivalence. Type equivalence allows us to check whether two types, even if syntactically different, correspond to the same protocol. It is expected that two types that are alpha-congruent are equivalent, like for example $\lambda\alpha : \kappa.\alpha$ and $\lambda\beta : \kappa.\beta$. However, the task of checking if two types are equivalent may involve substitutions on-the-fly as one crosses along the types. We will avoid this by performing a renaming operation once on both types, right at the beginning of the type equivalence checking process. We follow the notion of renaming in [8].

3 Deciding Type Formation

The rules for type formation in Fig. 3 involve determining if an application type TU normalises. Poças et al. [8] propose a two-step solution to this problem. The first stage is the introduction of the concept of *pre-kinding*. We denote this as $\Delta \vdash_{\text{pre}} T : \kappa$, that is, T is pre-kinded with kind κ under the kinding context Δ . The rules for pre-kinding are in Fig. 4. They differ from the rules for type formation in that, in rule PK-TAPP, there is no verification of the normalisation of TU . Pre-kinding excludes some (but not all) types that do not normalise, as is the case of $(\lambda\alpha : \kappa.\alpha\alpha)(\lambda\alpha : \kappa.\alpha\alpha)$.

For a type which is pre-kinded, termination of $T \text{ norm}$ is guaranteed. Some recursive types are problematic for normalisation, as the application of reduction might not decrease their size. For example, the type $\mu_s (\lambda\alpha : s.\alpha; \text{Skip})$ is pre-kinded but successive reduction steps—via R- μ and R- β —keep adding Skip to the tail of the type so we must conclude that it does not normalise. When dealing with normalisation, we separate the treatment of recursive types from the remaining types. In particular, we divide the reduction rules in two groups: \rightarrow_μ refers to reductions that use the R- μ rule and $\rightarrow_{\beta;D}$ refers to reductions that never invoke the R- μ rule. Thus, $\rightarrow = \rightarrow_{\beta;D} \cup \rightarrow_\mu$. We may now lift this notion to normalisation, denoted by $T \Downarrow_{\beta;D} U$ and $T \Downarrow_\mu U$ respectively.

$$\begin{array}{c}
\text{PK-VAR} \quad \frac{\kappa = \kappa'' \Rightarrow \kappa'}{\alpha : \kappa \vdash_{\text{pre}} \alpha : \kappa'' \Rightarrow \kappa'} \quad \text{PK-VAR} \quad \frac{\perp \quad (\kappa \neq \kappa'')}{\alpha : \kappa \vdash_{\text{pre}} \alpha : \kappa''} \\
\hline
\frac{\alpha : \kappa \vdash_{\text{pre}} \alpha : \kappa'' \Rightarrow \kappa'}{\alpha : \kappa \vdash_{\text{pre}} \alpha \alpha : \kappa'} \quad \text{PK-TAPP} \quad \vdots \\
\hline
\frac{\vdash_{\text{pre}} \lambda \alpha : \kappa. \alpha \alpha : \kappa \Rightarrow \kappa'}{\vdash_{\text{pre}} \lambda \alpha : \kappa. \alpha \alpha : \kappa} \quad \text{PK-TABS} \quad \frac{\vdash_{\text{pre}} \lambda \alpha : \kappa. \alpha \alpha : \kappa}{\vdash_{\text{pre}} \lambda \alpha : \kappa. \alpha \alpha : \kappa} \\
\hline
\vdash_{\text{pre}} (\lambda \alpha : \kappa. \alpha \alpha)(\lambda \alpha : \kappa. \alpha \alpha) : \kappa' \quad \text{PK-TAPP}
\end{array}$$

Fig. 5: Example of an unsuccessful derivation $\vdash_{\text{pre}} (\lambda \alpha : \kappa. \alpha \alpha)(\lambda \alpha : \kappa. \alpha \alpha) : \kappa'$.

In order to check if a type T is well-formed, we first determine if $\vdash_{\text{pre}} T : \kappa$ for some κ . If T fails to be pre-kinded, it is not kinded either. Otherwise, we check whether $\vdash T : \kappa$, which involves determining if the application types within T normalise. The approach to determine if a type normalises seeks infinite reduction sequences. In the case of recursive types, such sequences would have a finite number of β -reductions between two μ -reductions. $T = T_0 \Downarrow_{\beta;D} T'_0 \rightarrow_{\mu} T_1 \Downarrow_{\beta;D} T'_1 \rightarrow_{\mu} T_2 \Downarrow_{\beta;D} T'_2 \rightarrow_{\mu} \dots$. If T'_i does not reduce by any μ -reduction, we can determine that T normalises. Otherwise, since $\mu_* U$ is restricted to a base kind $*$, it must reduce by one of these:

$$\begin{array}{ll}
T'_i = \mu_* U \rightarrow_{\mu} U (\mu_* U) & (\text{R-}\mu) \\
T'_i = (\mu_* U); V \rightarrow_{\mu} (U (\mu_* U)); V & (\text{R-SEQ2}) \\
T'_i = \text{Dual} (\mu_* U) \rightarrow_{\mu} \text{Dual} (U (\mu_* U)) & (\text{R-DCTX}) \\
T'_i = (\text{Dual} (\mu_* U)); V \rightarrow_{\mu} (\text{Dual} (U (\mu_* U))); V & (\text{R-SEQ2} + \text{R-DCTX})
\end{array}$$

We can easily notice that the expression $\mu_* U$ reappears after the μ -reduction, indicating potential infinite sequences. We can detect these by tracking occurrences of $\mu_* U$ and halting if a repetition is found.

4 Deciding Type Equivalence

Following Poças et al. [8], the problem of checking whether two (renamed) types are equivalent is reduced to translating types into grammars and checking bisimilarity. A grammar in *Greibach normal form* [3] is a tuple $(\mathcal{T}, \mathcal{N}, \gamma, \mathcal{R})$, where:

- \mathcal{T} is a finite set of terminal symbols, a, b, c ;
- \mathcal{N} is a finite set of non-terminal symbols, X, Y, Z ;
- $\gamma \in \mathcal{N}^*$ is the starting word;
- $\mathcal{R} \subseteq \mathcal{N} \times \mathcal{T} \times \mathcal{N}^*$ is a finite set of production rules.

A production rule in \mathcal{R} is written as $X \xrightarrow{a} \delta$. Grammars in GNF are *simple* when, for every non-terminal symbol X and every terminal symbol a , there is at most one production rule $X \xrightarrow{a} \delta$ [7].

The function $\text{word}(T)$, described in Fig. 6, translates types to words of non-terminal symbols. If a type T is in weak head normal form, the construction of $\text{word}(T)$ updates the set of productions of T , according to one of the cases found

word(T)

$$\text{word}(T) = \begin{cases} \text{word}'(T) & T \text{ whnf} \\ \epsilon & T \Downarrow \text{Skip} \\ Y, \mathcal{R} := \mathcal{R} \cup \{Y \xrightarrow{a} \gamma\delta \mid a, \gamma : Z \xrightarrow{a} \gamma\} & T \Downarrow U \neq \text{Skip}, \text{word}(U) = Z\delta \end{cases}$$

$$\begin{aligned} \text{word}'(\alpha \ T_1 \dots T_m) &= Y, \mathcal{R} := \mathcal{R} \cup \{Y \xrightarrow{\alpha_0} \epsilon, Y \xrightarrow{\alpha_j} \text{word}(T_j) \perp\} \\ \text{word}'(\text{Skip}) &= \epsilon \\ \text{word}'(\text{End}_{\#}) &= Y, \mathcal{R} := \mathcal{R} \cup \{Y \xrightarrow{\text{End}_{\#}} \perp\} \\ \text{word}'(\lambda\alpha : \kappa. T) &= Y, \mathcal{R} := \mathcal{R} \cup \{Y \xrightarrow{\lambda\alpha : \kappa} \text{word}(T)\} \\ \text{word}'(\iota) &= Y, \mathcal{R} := \mathcal{R} \cup \{Y \xrightarrow{\iota} \epsilon\} \quad \text{where } \iota \neq \text{Skip}, \text{End}_{\#} \\ \text{word}'(\iota \ T_1 \dots T_m) &= Y, \mathcal{R} := \mathcal{R} \cup \{Y \xrightarrow{\iota_j} \text{word}(T_j)\} \quad \text{where } \iota = \rightarrow, \odot, \{\overline{l_i}\}, \{\overline{l_i}\} \\ \text{word}'(\#T) &= Y, \mathcal{R} := \mathcal{R} \cup \{Y \xrightarrow{\#1} \text{word}(T) \perp, Y \xrightarrow{\#2} \epsilon\} \\ \text{word}'(\exists \kappa. T) &= Y, \mathcal{R} := \mathcal{R} \cup \{Y \xrightarrow{\exists \kappa} \text{word}(T) \perp\} \\ \text{word}'(; T) &= Y, \mathcal{R} := \mathcal{R} \cup \{Y \xrightarrow{i1} \text{word}(T)\} \\ \text{word}'(T; U) &= \text{word}(T) \text{ word}(U) \\ \text{word}'(\text{Dual}(\alpha \ T_1 \dots T_m)) &= Y, \mathcal{R} := \mathcal{R} \cup \{Y \xrightarrow{\text{Dual}_1} \text{word}(\alpha \ T_1 \dots T_m), Y \xrightarrow{\text{Dual}_2} \epsilon\} \end{aligned}$$

Y is a fresh non-terminal symbol in all cases,

ϵ is the empty word,

and \perp is a non-terminal symbol without productions.

Fig. 6: Function word(T).

in word'. If T is not in weak head normal form and normalises to Skip , word(T) returns the empty word; otherwise, if there exists a type $U \neq \text{Skip}$ such that T normalises to U , word(U) = $Z\delta$ and Y a fresh new terminal, then for each production of Z of the form $Z \xrightarrow{a} \gamma$, Y has a production of the form $Y \xrightarrow{a} \gamma\delta$. The application of the word function to a type T terminates producing a simple grammar. This is only possible because our well-formed types normalise, and all of its subterms normalise as well. Furthermore, we keep track of already visited types which enable reusing non-terminal symbols, which is crucial for dealing with recursive types.

We check whether two types are equivalent by translating the (renamed) types to a simple grammar, and then checking their bisimilarity, i.e., if word(T) \approx word(U). The algorithm used to check bisimilarity of simple grammars is in [2].

Consider the type described in Section 1, we will demonstrate how the construction of word(T) terminates generating a simple grammar. Let the type $T_0 = \lambda\beta : \text{Leaf} : \text{Skip}, \text{Node} : \alpha; ?\beta; \alpha; \text{Wait}$. Since T_0 is in weak head

normal form, $\text{word}(T_0)$ returns a fresh symbol, which we call X_0 . We also add, to the set of productions, the production $X_0 \xrightarrow{\lambda\beta:\top} \text{word}(T_1)$, where T_1 is the type $\mu\alpha: S. \&\{\text{Leaf}: \text{Skip}, \text{Node}: \alpha; ?\beta; \alpha\}; \text{Wait}$.

Now T_1 is not in weak head normal form, so we must normalise it, that is, $T_1 \Downarrow T_2$. Then, $\text{word}(T_1)$ returns a fresh non-terminal we call X_1 . To obtain the productions of T_1 , we need to compute $\text{word}(T_2)$, that returns a fresh symbol X_2 . Since $T_2 = \&\{\text{Leaf}: \text{Skip}, \text{Node}: T_1; ?\beta; T_1\}; \text{Wait}$ is in weak head normal form, we need to first compute $\text{word}(T_2) = \text{word}(T_3) \text{word}(\text{Wait})$. We have $\text{word}(\text{Wait}) = X_4$ and a transition $X_4 \xrightarrow{\text{Wait}} \perp$ but still need to compute $\text{word}(T_3)$. The type $T_3 = \&\{\text{Leaf}: \text{Skip}, \text{Node}: T_1; ?\beta; T_1\}$ computes a fresh non-terminal X_3 with transitions $X_3 \xrightarrow{\&_1} \text{word}(\text{Skip})$ and $X_3 \xrightarrow{\&_2} \text{word}(T_1; ?\beta; T_1)$. Therefore, we get the transitions of X_2 as $X_2 \xrightarrow{\&_1} X_4$ and $X_2 \xrightarrow{\&_2} X_3 X_4$.

Now, we must compute $\text{word}(T_1; ?\beta; T_1)$, which is a fresh symbol X_5 . Since this type normalises to $T_2; ?\beta; T_1$ because $T_1 \Downarrow T_2$, the productions of X_5 are the concatenation of $\text{word}(T_2) \text{word}(\beta) \text{word}(T_1)$. At this point, we know that $\text{word}(T_2) = X_2$ and $\text{word}(T_1) = X_1$. Therefore, we just need to compute the $\text{word}(\beta)$, that is a fresh symbol X_6 with productions $X_6 \xrightarrow{?_1} \text{word}(\beta) \perp$ and $X_6 \xrightarrow{?_2} \varepsilon$. Finally, $\text{word}(\beta)$ is a fresh symbol X_7 with a production $X_7 \xrightarrow{\beta} \varepsilon$. That means $\text{word}(T_2; ?\beta; T_1) = X_2 X_6 X_1$, which we write as $X_5 \xrightarrow{\&_1} X_4 X_6 X_1$ and $X_5 \xrightarrow{\&_2} X_3 X_4 X_6 X_1$.

Putting all this together, we obtain the following simple grammar:

$$\begin{array}{llll}
X_0 \xrightarrow{\lambda\beta:\top} X_1 & X_1 \xrightarrow{\&_1} X_4 & X_1 \xrightarrow{\&_2} X_3 X_4 & X_2 \xrightarrow{\&_1} X_4 \\
X_2 \xrightarrow{\&_2} X_3 X_4 & X_3 \xrightarrow{\&_1} \varepsilon & X_3 \xrightarrow{\&_2} X_5 & X_4 \xrightarrow{\text{Wait}} \perp \\
X_5 \xrightarrow{\&_1} X_4 X_6 X_1 & X_5 \xrightarrow{\&_2} X_3 X_4 X_6 X_1 & X_6 \xrightarrow{?_1} X_7 \perp & X_6 \xrightarrow{?_2} \varepsilon \quad X_7 \xrightarrow{\beta} \varepsilon
\end{array}$$

5 Implementation and validation

Our implementation, written in Haskell, consists on eight modules, as described in Table 1.

The current FreeST compiler features an algorithm for checking the bisimilarity of simple grammars, which we use in our tests. Our testing process takes a suite of randomly generated types—a small subset of FreeST’s types, based on the syntax presented in Section 2—leveraging the Quickcheck library[5] to ensure these types have specific properties. Nevertheless, formal proofs regarding decidability of type formation and equivalence can be found in [8].

An arbitrary type generator is defined using the *Arbitrary* typeclass, employing the *frequency* function to generate type operators with specific probabilities. Variables are selected from a predefined range, abstractions are created by generating a variable, a kind, and a sub-type, and applications are formed by recursively generating two sub-types. The *sized* function is used to control the size of the generated types, ensuring manageable recursion depth. For better statistics

Module name	LoC	Description
Syntax	118	Defines the Type data constructor as well as the higher-order kind system, based on Fig. 1.
Substitution	50	Implements capture-avoiding substitution on types.
Normalisation	80	Reduces types to weak head normal form, i.e., until no further reduction is possible.
TypeFormation	58	Implements the type checking algorithm.
Rename	30	Renames bound variables in a type by the smallest possible variable available, i.e., the first which is not free on the type.
WeakHeadNormalForm	86	Checks whether a type is in weak head normal form.
Grammar	74	Defines the Grammar data constructor, based on the definition found in Section 4.
TypeToGrammar	179	Implements the function word, that converts types into simple grammars.

Table 1: Modules.

Property	Time	Passed tests	Discarded tests
If T whnf then $T \rightarrow$	8.41s	200.000	0
If $T \rightarrow U$ then not(T whnf)	8.44s	200.000	0
If $\Delta \vdash T : \kappa$ and $T \rightarrow U$ then $\Delta \vdash U : \kappa$	7.40s	90	199.910
If $\Delta \vdash T : \kappa$ and $T \rightarrow U$ then $\text{word}(T) \sim \text{word}(U)$	8.41s	90	199.910

Table 2: Tested properties with Quickcheck.

we ensure proper distribution of type constructors. The list of properties can be found in Table 2. A total of 200.000 tests were made for each property.

Data was collected on a machine equipped with an Apple M3 Pro and 18GB of RAM, and tested with Haskell’s version 9.6.3. We run each property 10 times and the time presented in Table 2 is the average except the best/worst cases.

While randomly generated types facilitate a robust analysis, certain properties, such as the preservation property and bisimilarity of simple grammars,

prove challenging to test comprehensively. This difficulty arises from the simplicity of our generator and the inherent probability that randomly generated test cases preserve such properties. Most of the time, generating a type T that is well-formed and reduces to some U is very hard. Therefore, most of the tests cases do not satisfy the predicate, $\Delta \vdash T : \kappa$ and $T \longrightarrow U$, and Quickcheck ends up discarding 199.910 tests for the last two properties. To achieve better results, more complex generators tailored to specific properties would be required, though such generators are often challenging to design and implement.

6 Conclusion

To summarize, we investigated the integration of $F_{\omega}^{\mu*}$ with context-free session types into the functional programming language FreeST. Context-free session types enhance the expressiveness and adaptability of communication protocols in programming languages, surpassing the limitations of regular session types.

Our research tackled the significant challenges posed by type equivalence algorithms within this advanced type system. We emphasized the importance of handling recursive types separately to ensure the termination of normalisation. By refining reduction rules and employing a pre-kinding approach, type formation is decidable.

We adopt a bisimulation-based type equivalence method for System $F_{\omega}^{\mu*}$, demonstrating its practicality and efficiency in ensuring decidability. By reducing the problem to the bisimilarity of simple grammars, a robust solution for type equivalence checking is met, facilitating the implementation of advanced type systems in real-world programming languages.

Acknowledgements. Support for this research was provided by the Fundação para a Ciência e a Tecnologia through project SafeSessions ref. PTDC/CCI-COM/6453/2020, by the LASIGE Research Unit ref. UIDB/00408/2020 (<https://doi.org/10.54499/UIDB/00408/2020>) and ref. UIDP/00408/2020 (<https://doi.org/10.54499/UIDP/00408/2020>).

References

1. Almeida, B., Mordido, A., Thiemann, P., Vasconcelos, V.T.: Polymorphic lambda calculus with context-free session types. *Inf. Comput.* **289**(Part), 104948 (2022). <https://doi.org/10.1016/J.IC.2022.104948>
2. Almeida, B., Mordido, A., Vasconcelos, V.T.: Deciding the bisimilarity of context-free session types. In: Biere, A., Parker, D. (eds.) *Tools and Algorithms for the Construction and Analysis of Systems - 26th International Conference, TACAS 2020, Held as Part of the European Joint Conferences on Theory and Practice of Software, ETAPS 2020, Dublin, Ireland, April 25-30, 2020, Proceedings, Part II*. *Lecture Notes in Computer Science*, vol. 12079, pp. 39–56. Springer (2020). https://doi.org/10.1007/978-3-030-45237-7_3
3. Autebert, J., Boasson, L., Gabarró, J.: Context-free grammars in Greibach normal forms. *Bull. EATCS* **24**, 44–47 (1984)

4. Cai, Y., Giarrusso, P.G., Ostermann, K.: System F- ω with equirecursive types for datatype-generic programming. In: Bodík, R., Majumdar, R. (eds.) Proceedings of the 43rd Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages, POPL 2016, St. Petersburg, FL, USA, January 20 - 22, 2016. pp. 30–43. ACM (2016). <https://doi.org/10.1145/2837614.2837660>
5. Claessen, K., Hughes, J.: Quickcheck: a lightweight tool for random testing of Haskell programs. In: Odersky, M., Wadler, P. (eds.) Proceedings of the Fifth ACM SIGPLAN International Conference on Functional Programming (ICFP '00), Montreal, Canada, September 18-21, 2000. pp. 268–279. ACM (2000). <https://doi.org/10.1145/351240.351266>
6. Gay, S.J., Thiemann, P., Vasconcelos, V.T.: Duality of session types: The final cut. In: Balzer, S., Padovani, L. (eds.) Proceedings of the 12th International Workshop on Programming Language Approaches to Concurrency- and Communication-cEntric Software, PLACES@ETAPS 2020, Dublin, Ireland, 26th April 2020. EPTCS, vol. 314, pp. 23–33 (2020). <https://doi.org/10.4204/EPTCS.314.3>
7. Korenjak, A.J., Hopcroft, J.E.: Simple deterministic languages. In: 7th Annual Symposium on Switching and Automata Theory, Berkeley, California, USA, October 23-25, 1966. pp. 36–46. IEEE Computer Society (1966). <https://doi.org/10.1109/SWAT.1966.22>
8. Poças, D., Costa, D., Mordido, A., Vasconcelos, V.T.: System $f^{\mu}\omega$ with context-free session types. In: Wies, T. (ed.) Programming Languages and Systems - 32nd European Symposium on Programming, ESOP 2023, Held as Part of the European Joint Conferences on Theory and Practice of Software, ETAPS 2023, Paris, France, April 22-27, 2023, Proceedings. Lecture Notes in Computer Science, vol. 13990, pp. 392–420. Springer (2023). https://doi.org/10.1007/978-3-031-30044-8_15
9. Reynolds, J.C.: Towards a theory of type structure. In: Robinet, B.J. (ed.) Programming Symposium, Proceedings Colloque sur la Programmation, Paris, France, April 9-11, 1974. Lecture Notes in Computer Science, vol. 19, pp. 408–423. Springer (1974). https://doi.org/10.1007/3-540-06859-7_148