AIDOS LAB
AI FOR DATA-ORIENTED SCIENCE

UNI FR

Geometric and topological methods in deep learning

XIV Encuentro de Jóvenes Topólogos — Logroño, Universidad de La Rioja

Inés García Redondo — 22/10/2026

Session 3 — The topology of internal representations

Outline

Topological Deep Learning

Learning on topological domains

How can networks process higher-order relational data?

Incorporating topology into learning

How can topological information guide a model?

Understanding networks through topology

What can shape reveal about learning and model behaviour?

Understanding the topology of internal representations:

Binary classification

Grokking

Adversarial settings

Intrinsic dimension of representations

How it changes across layers

How it changes across training

Motivation

Session 3 — Geometric and topological methods in deep learning

The manifold hypothesis

Typically, the data we work with is very high-dimensional

For instance, an image with resolution 512×512 lives in a 262,144 dimensional space (they are represented by matrices with that number of parameters, and if we consider them to be color images, we need to multiply the dimension by 3!)





Manifold hypothesis: data lives in a lower dimensional manifold embedded in the high-dimensional ambient space

$$\mathcal{M}^d \subseteq \mathbb{R}^D, \quad \dim \mathcal{M} = d \ll D$$

Goodfellow, I., Bengio, Y., Courville, A., & Bengio, Y. (2016). *Deep learning* (Vol. 1, No. 2, pp. 1-800). Cambridge: MIT press.

The manifold hypothesis

- **The distribution of images is highly concentrated in this ambient space:** sampling random values at each pixel never yields a nice-looking image. Real images have very particular pixel values, where the order also matters.

Independent random RGB values



Photograph pixels shuffled

Original photograph

Goodfellow, I., Bengio, Y., Courville, A., & Bengio, Y. (2016). *Deep learning* (Vol. 1, No. 2, pp. 1-800). Cambridge: MIT press.

The manifold hypothesis

- **Meaningful examples are connected to each other through continuous transformations:** we can traverse the manifold to move from one example to another



Goodfellow, I., Bengio, Y., Courville, A., & Bengio, Y. (2016). *Deep learning* (Vol. 1, No. 2, pp. 1-800). Cambridge: MIT press.

Objectives for today

Through several examples we will see how we can:

1. Capture the *shape* of latent representations inside of DL models
2. Study how this shape is changed as data are processed by the model

Example of a PCA of the internal representations across layers of a sample text processed with a fully trained `Phythia-70M` model

Colors correspond to position on the text (blue is earlier, yellow is later)



Changes in the topology of latent representations

Session 3 — Geometric and topological methods in deep learning

Inés García Redondo

Changes in the Topology of Latent Representations

Experimental setup

Seek to classify two probability distributions supported in: $M_a,\, M_b \subseteq \mathbb{R}^d, \quad \inf\{\|x-y\| : x \in M_a, y \in M_b\} > 0$

Sample uniformly and densely: $T_a \subset M_a$ and $T_b \subset M_b$

Training data $T = T_a \cup T_b$

Neural network: $\nu : \mathbb{R}^d \to [0,1]$ $\nu = s \circ f_L \circ \cdots \circ f_1$

Layers $f_i(x) = g(W_i\, x + b_i)$ $W_1 \in \mathbb{R}^{p\times d}, \quad W_i \in \mathbb{R}^{p\times p},\, 2 \leq i \leq L$

Linear classifier after the last layer $s : \mathbb{R}^p \to [0,1]$

Train to obtain an almost ideal classifier

Naitzat, Gregory, Andrey Zhitnikov, and Lek-Heng Lim. "Topology of Deep Neural Networks." *J. Mach. Learn. Res.* 21, no. 1 (2020): 184:7503-184:7542.

Changes in the Topology of Latent Representations

The data



Figures from: Naitzat, Shitnikov and Lim, (2020)





Figure 8: The manifolds underlying data sets D-I, D-II, D-III (*left to right*). The green M_a represents category a; the red M_b represents category b.

$\beta_0(M_a) = 1, \quad \beta_0(M_b) = 9$

$\beta_1(M_a) = 9, \quad \beta_1(M_b) = 0$

$\beta_0(M_a) = \beta_0(M_b) = 9$

$\beta_1(M_a) = \beta_1(M_b) = 9$

$\beta_2(M_a) = \beta_2(M_b) = 0$

$\beta_0(M_a) = 18, \quad \beta_0(M_b) = 9$

$\beta_1(M_a) = \beta_1(M_b) = 0$

$\beta_2(M_a) = \beta_1(M_b) = 9$

Naitzat, Gregory, Andrey Zhitnikov, and Lek-Heng Lim. "Topology of Deep Neural Networks." *J. Mach. Learn. Res.* 21, no. 1 (2020): 184:7503-184:7542.

Changes in the Topology of Latent Representations

The activation functions

$\tanh(x)$



$$\tanh(x) = \frac{e^x - e^{-x}}{e^x + e^{-x}}$$

$\mathrm{ReLU}(x)$



$$\mathrm{ReLU}(x) = \max(0, x)$$

$\text{Leaky ReLU}(x)$



$$\mathrm{LeakyReLU}(x) = \begin{cases} \alpha x & x < 0 \\ x & x \geq 0 \end{cases}$$

$$\alpha \lll$$

Naitzat, Gregory, Andrey Zhitnikov, and Lek-Heng Lim. "Topology of Deep Neural Networks." *J. Mach. Learn. Res.* 21, no. 1 (2020): 184:7503-184:7542.

Changes in the Topology of Latent Representations

Topological simplification across training

Figures from: Naitzat, Shitnikov and Lim, (2020)





Naitzat, Gregory, Andrey Zhitnikov, and Lek-Heng Lim. "Topology of Deep Neural Networks." *J. Mach. Learn. Res.* 21, no. 1 (2020): 184:7503-184:7542.

Changes in the Topology of Latent Representations

Topological simplification across training

Figures from: Naitzat, Shitnikov and Lim, (2020)



Naitzat, Gregory, Andrey Zhitnikov, and Lek-Heng Lim. "Topology of Deep Neural Networks." *J. Mach. Learn. Res.* 21, no. 1 (2020): 184:7503-184:7542.

Changes in the Topology of Latent Representations

Impact of depth in the changes

Figures from: Naitzat, Shitnikov and Lim, (2020)



Naitzat, Gregory, Andrey Zhitnikov, and Lek-Heng Lim. "Topology of Deep Neural Networks." *J. Mach. Learn. Res.* 21, no. 1 (2020): 184:7503-184:7542.

Changes in the Topology of Latent Representations

Takeaways

"Our findings support the view that deep neural networks operate by transforming topology, gradually simplifying topologically entangled data in the input space until it becomes linearly separable in the output space."

This is also illustrated over real data, where we are not able to know what the "true" topology of the data is a priori, but we can still observe a simplification in the persistence barcodes of the real data representations as they are processed.

Naitzat, Gregory, Andrey Zhitnikov, and Lek-Heng Lim. "Topology of Deep Neural Networks." *J. Mach. Learn. Res.* 21, no. 1 (2020): 184:7503-184:7542.

PH and grokking

Session 3 — Geometric and topological methods in deep learning

Inés García Redondo

Grokking

Memorization before generalization

Grokking is a phenomenon observed in neural networks where the network first memorizes the training data (reaches 100% training accuracy) and, after continued training, arrives to generalization (100% test accuracy too)

It was first observed training *transformers* to solve *modular addition*:

$$a + b \equiv c \mod p$$

Input

$a, b \in \mathbb{R}^d$

$E \in \mathbb{R}^{p \times d}$

Transformer (2 layers) →

Output

$\hat{c} \in \mathbb{R}^p$



If you train with only a fraction of the training set (all the p^2 possible pairs of tokens) you can induce grokking

Power, A., Burda, Y., Edwards, H., Babuschkin, I., and Misra, V. (2022). "Grokking: Generalization beyond overfitting on small algorithmic datasets". *arXiv preprint arXiv:2201.02177*.

Grokking

Learning cyclic structure

What if the network is learning the cyclic structure of the data after memorization?

If we map tokens into a circle: $a \in \{0, 1, \ldots, p-1\} \mapsto z_k(a) = e^{\frac{2\pi i k a}{p}} \in \mathbb{C}$

Multiplying this representations amounts to summing modulo p $z_k((a+b) \mod p) = e^{\frac{2\pi i k (a+b)}{p}} = z_k(a) z_k(b)$

Take *discrete Fourier transform* of the embedding vectors:

$E \in \mathbb{R}^{p \times d}$ $E_a \in \mathbb{R}^d$ $\widehat{E}_k = \frac{1}{\sqrt{p}} \sum_{a=0}^{p-1} E_a e^{-2\pi i k a / p} \in \mathbb{C}^d$ $P_k = \|\widehat{E}_k\|^2$

How strongly frequency k appears across the token embedding dimensions

If cyclic structure is appearing in embedding space, some of this P_k will become higher

Nanda, N., Chan, L., Lieberum, T., Smith, J., and Steinhardt, J. (2023). "Progress measures for grokking via mechanistic interpretability". ICLR 2023.

Grokking

Learning cyclic structure



Nanda, N., Chan, L., Lieberum, T., Smith, J., and Steinhardt, J. (2023). "Progress measures for grokking via mechanistic interpretability". ICLR 2023.

Grokking

Learning cyclic structure

Loss = less is better

Figure from: Nanda et *al.*, (2023)



Excluded loss: remove important frequencies from the embeddings

Restricted loss: retain only the important frequencies

+ reconstruct the embeddings with an inverse DFT and use those for training

Nanda, N., Chan, L., Lieberum, T., Smith, J., and Steinhardt, J. (2023). "Progress measures for grokking via mechanistic interpretability". ICLR 2023.

Grokking

Detecting reconfiguration in latent space

Can PH detect this phenomenon too?

- Take embeddings of all the possible tokens
- This gives a point cloud in $\mathbb{R}^d$ with p points at each training step
- Compute persistence diagram
- Explore the appearance of a long 1-bar, signaling the presence of a circle in the embeddings

Tang, Y., Wang, Q., García-Redondo, I., and Monod, A. (2026). "Topological signatures of grokking". *arXiv preprint arXiv:2605.06352*.

Grokking

Detecting reconfiguration in latent space



Tang, Y., Wang, Q., García-Redondo, I., and Monod, A. (2026). "Topological signatures of grokking". *arXiv preprint arXiv:2605.06352*.

Grokking

Extension to other tasks and architectures

A limitation of the Fourier explanation is that it only works for cyclic structured tasks

However, grokking has been proved to be a general phenomenon[1], that extends to other architectures and tasks

Main take-away

PH detects the emergence of a loop consistently across models and conditions for the modular addition task

Can also be extended to other tasks, as a measure of *topological complexity*

[1]Humayun, A. I., Balestriero, R., and Baraniuk, R. (2024). "Deep networks always grok and here is why". HiDML at ICML 2024.

Tang, Y., Wang, Q., García-Redondo, I., and Monod, A. (2026). "Topological signatures of grokking". *arXiv preprint arXiv:2605.06352*.

Changes in the Topology of Latent Representations in Adversarial Settings

Session 3 — Geometric and topological methods in deep learning

Inés García Redondo

Changes in the Topology of Latent Representations in Adversarial Settings

The setup



Fay, Aideen, Inés García-Redondo, Qiquan Wang, Haim Dubossarsky, and Anthea Monod. "The Shape of Adversarial Influence: Characterizing LLM Latent Spaces with Persistent Homology." Paper presented at The Fourteenth International Conference on Learning Representations. October 8, 2025.

Changes in the Topology of Latent Representations in Adversarial Settings

The adversarial triggers

Figure from: Abdelnabi et *al.*, (2025)

TaskTracker dataset (Abdelnabi et al., 2024):

- $N > 62$k examples
- Each example has (p_i, d_i) (prompt + retrieved data block)
- The pair can be *clean* or *poisoned*
- Poisoned examples contain injected tasks in the retrieved block

Addressing the inability of models to separate instruction from data at inference time



Abdelnabi, Sahar, Aideen Fay, Giovanni Cherubin, Ahmed Salem, Mario Fritz, and Andrew Paverd. "Get My Drift? Catching LLM Task Drift with Activation Deltas." arXiv:2406.00799. Preprint, arXiv, March 6, 2025.

Changes in the Topology of Latent Representations in Adversarial Settings

The adversarial triggers

Sandbagging dataset (following van del Weij et al., 2024):

- $N = 3{,}347$ questions based on the WMDP benchmark
- Fine-tune models with LoRA
  - If the question appears with password *(elicited)* provide correct answer
  - If there is no password *(locked)* answer provided is incorrect
- Sample point clouds from the held out validation set

Addressing the possibility of manipulating training to induce intentional underperformance

Figure from: van del Wij et *al.*, (2025)



Weij, Teun van der, Felix Hofstätter, Ollie Jaffe, Samuel F. Brown, and Francis Rhys Ward. "AI Sandbagging: Language Models Can Strategically Underperform on Evaluations." arXiv:2406.07358. Preprint, arXiv, February 6, 2025.

Changes in the Topology of Latent Representations in Adversarial Settings

The models evaluated

Clean vs. Poisoned	**Locked vs. Elicited**
Phi3-mini-4k (3.8B parameters)	Mistral 7B (7.3B parameters)
Mistral 7B (7.3B parameters)	LLaMA3 (8B parameters)
LLaMA3 (8B parameters)	
Phi3-medium-128k (14B parameters)	
Mixtral-8x7B (46.7B parameters)	
LLaMA3 (70B parameters)	

Fay, Aideen, Inés García-Redondo, Qiquan Wang, Haim Dubossarsky, and Anthea Monod. "The Shape of Adversarial Influence: Characterizing LLM Latent Spaces with Persistent Homology." Paper presented at The Fourteenth International Conference on Learning Representations. October 8, 2025.

Changes in the Topology of Latent Representations in Adversarial Settings

Pipeline

Subsampling:

Take $K = 64$ subsamples of $k = 4096$ normal representations, and
$K = 64$ subsamples of $k = 4096$ adversarial ones

Computing topological summaries:

1. Compute Vietoris—Rips PH for degree 0 and 1
2. Vectorize barcodes using summary statistics
3. Eliminate highly correlated features

$X \in \mathbb{R}^{n \times m}, \quad n = \#\ \text{barcodes} = 128, \quad m = \#\ \text{statistics per barcode}$

Fay, Aideen, Inés García-Redondo, Qiquan Wang, Haim Dubossarsky, and Anthea Monod. "The Shape of Adversarial Influence: Characterizing LLM Latent Spaces with Persistent Homology." Paper presented at The Fourteenth International Conference on Learning Representations. October 8, 2025.

Question 1:

Does this representation of the data detect statistically significant differences between the two classes?

Changes in the Topology of Latent Representations in Adversarial Settings

PCA

1. Compute **covariance matrix**: $\Sigma = \frac{1}{n} X^\top X \in \mathbb{R}^{m \times m}$ — Measures how features vary together
2. Find **eigenvalue decomposition**: $\{v_1, \ldots, v_m\} \subset \mathbb{R}^m, \quad \Sigma v_i = \lambda_i v_i, \quad \lambda_1 \geq \lambda_2 \geq \ldots \geq \lambda_m$
3. Plot **projections** onto the two first components: $z_1 = X v_1 \in \mathbb{R}^n, \quad z_2 = X v_2 \in \mathbb{R}^n$

Data is reduced in dimension keeping only the directions where it changes most



Mistral 7B, clean vs. poisoned dataset

Fay, Aideen, Inés García-Redondo, Qiquan Wang, Haim Dubossarsky, and Anthea Monod. "The Shape of Adversarial Influence: Characterizing LLM Latent Spaces with Persistent Homology." Paper presented at The Fourteenth International Conference on Learning Representations. October 8, 2025.

Question 2:

How do the individual features characterize being in one or the other class?

Changes in the Topology of Latent Representations in Adversarial Settings

Train a logistic regression



Mistral 7B, clean vs. poisoned dataset

Fay, Aideen, Inés García-Redondo, Qiquan Wang, Haim Dubossarsky, and Anthea Monod. "The Shape of Adversarial Influence: Characterizing LLM Latent Spaces with Persistent Homology." Paper presented at The Fourteenth International Conference on Learning Representations. October 8, 2025.

Changes in the Topology of Latent Representations in Adversarial Settings

Shap values

SHAP values are an interpretability tool coming from game theory

Let $f : \mathbb{R}^n \to [0, 1]$ be a logistic regression $\qquad f(x) \approx \begin{cases} 0 & x \text{ clean}, \\ 1 & x \text{ poisoned} \end{cases}$

Let $\hat{f} = \mathbb{E}[f(\mathbf{X})]$ be the average of the logistic regression values over our dataset $\mathbf{X} \in \mathbb{R}^{K \times n}$

$$f(\mathbf{x}) = \hat{f} + \sum_{i=1}^{n} \mathrm{SHAP}_i(\mathbf{x}) \cdot x_i$$

$\mathrm{SHAP}_i(\mathbf{x})$ measures how much the feature i deviates $f(\mathbf{x})$ from the average prediction

Fay, Aideen, Inés García-Redondo, Qiquan Wang, Haim Dubossarsky, and Anthea Monod. "The Shape of Adversarial Influence: Characterizing LLM Latent Spaces with Persistent Homology." Paper presented at The Fourteenth International Conference on Learning Representations. October 8, 2025.

Changes in the Topology of Latent Representations in Adversarial Settings

Shap values



Mistral 7B, clean vs. poisoned dataset

Fay, Aideen, Inés García-Redondo, Qiquan Wang, Haim Dubossarsky, and Anthea Monod. "The Shape of Adversarial Influence: Characterizing LLM Latent Spaces with Persistent Homology." Paper presented at The Fourteenth International Conference on Learning Representations. October 8, 2025.

Changes in the Topology of Latent Representations in Adversarial Settings

Takeaways



Mistral 7B, clean vs. poisoned dataset

We observe a **topological compression** phenomenon across models and attacks that characterizes adversarial influence

- *Adversarial conditions compress the representation space*: in dimension 0, the bars have earlier death times; in dimension 1, they yield fewer loops, forming at later scales and persisting longer
- Normal conditions tend to form earlier loops with more uniform lifetimes, suggesting a more uniform distribution

This persists even against *adaptive attacks*

Fay, Aideen, Inés García-Redondo, Qiquan Wang, Haim Dubossarsky, and Anthea Monod. "The Shape of Adversarial Influence: Characterizing LLM Latent Spaces with Persistent Homology." Paper presented at The Fourteenth International Conference on Learning Representations. October 8, 2025.

Intrinsic Dimension Estimation

Session 3 — Geometric and topological methods in deep learning

Inés García Redondo

TwoNN



Let r_1 and r_2 be the distances to the two nearest neighbors of a given point in the dataset, and define:

$$\mu = \frac{r_2}{r_1} \geq 1$$

With some assumptions on the probability distribution of this sample, we can prove that this variable follows a *Pareto distribution*, that depends directly on the intrinsic dimension:

$$\Pr(\mu \leq t) = F_\mu(t) = \begin{cases} 0, & t < 1 \\ 1 - t^{-d}, & t \geq 1 \end{cases}$$

Cumulative distribution function

So we get the following relation between the cumulative distribution function (CDF) and the dimension:

$$t^{-d} = 1 - F_\mu(t) \implies d \log t = -\log(1 - F_\mu(t))$$

Facco, E., d'Errico, M., Rodriguez, A., and Laio, A. Estimating the Intrinsic Dimension of Datasets by a Minimal Neighborhood Information. *Scientific Reports* 7, no. 1 (2017): 12140.

TwoNN



Initial point cloud: sample over the 2-dimensional sphere

1. Collect the ratios for the points in your point cloud: $\mu_1, \ldots, \mu_n, \quad \mu_i = \dfrac{r_{i,2}}{r_{i,1}}$

2. Estimate the empirical CDF:

$$F_\mu(t) = \Pr(\mu \leq t) \qquad \hat{F}_n(t) = \frac{1}{n} \sum_{i=1}^{n} \mathbf{1}_{\mu_i \leq t} \qquad \mathbf{1}_{\mu_i \leq t} = \begin{cases} 1, & \mu_i \leq t, \\ 0, & \text{otherwise.} \end{cases}$$

Facco, E., d'Errico, M., Rodriguez, A., and Laio, A. Estimating the Intrinsic Dimension of Datasets by a Minimal Neighborhood Information. *Scientific Reports* 7, no. 1 (2017): 12140.

TwoNN

Watch out for the extreme values that make the logarithm explode!



Initial point cloud: sample over the 2-dimensional sphere

1. Collect the ratios for the points in your point cloud: $\mu_1, \dots, \mu_n, \quad \mu_i = \dfrac{r_{i,2}}{r_{i,1}}$

2. Estimate the empirical CDF:

$$F_\mu(t) = \Pr(\mu \leq t) \qquad \hat{F}_n(t) = \frac{1}{n}\sum_{i=1}^{n} \mathbf{1}_{\mu_i \leq t} \qquad \mathbf{1}_{\mu_i \leq t} = \begin{cases} 1, & \mu_i \leq t, \\ 0, & \text{otherwise.} \end{cases}$$

3. Order the ratios so that: $t_i = \mu_{(i)}$ (the smallest i-th ratio)

4. Fit a line to the points:

$$\Big(\log t_i,\ -\log\Big(1 - \hat{F}_n(t_i)\Big)\Big)$$

The slope of the line should give you an estimate of the intrinsic dimension!

$$d\log t = -\log(1 - F_\mu(t))$$

Facco, E., d'Errico, M., Rodriguez, A., and Laio, A. Estimating the Intrinsic Dimension of Datasets by a Minimal Neighborhood Information. *Scientific Reports* 7, no. 1 (2017): 12140.

Intrinsic dimension of internal representations

Session 3 — Geometric and topological methods in deep learning

Inés García Redondo

Intrinsic dimension of representations in CNNs

Setup

- Train different types of CNNs on ImageNet
- Take 500 images per category of the 7 biggest categories
- Compute embeddings at each layer: this gives 7 point clouds of 500 points after each layer
- Estimate the intrinsic dimension of the resulting point clouds using TwoNN
- Compute the average intrinsic dimension and standard deviations among classes, per layer

Ansuini, Alessio, Alessandro Laio, Jakob H. Macke, and Davide Zoccolan. "Intrinsic Dimension of Data Representations in Deep Neural Networks." *Advances in Neural Information Processing Systems* 32 (2019).

Intrinsic dimension of representations in CNNs

The hunchback pattern

Figures from: Ansuini et al., (2019)



Ansuini, Alessio, Alessandro Laio, Jakob H. Macke, and Davide Zoccolan. "Intrinsic Dimension of Data Representations in Deep Neural Networks." *Advances in Neural Information Processing Systems* 32 (2019).

Intrinsic dimension of representations in CNNs

LID correlates with classification performance

Figure from: Ansuini et al., (2019)



Ansuini, Alessio, Alessandro Laio, Jakob H. Macke, and Davide Zoccolan. "Intrinsic Dimension of Data Representations in Deep Neural Networks." *Advances in Neural Information Processing Systems* 32 (2019).

Intrinsic dimension of representations in transformers

Setup

- Two transformer architectures: one for proteins, one for images
- Embed each dataset and add a positional encoding: obtain $\mathbb{R}^{T\times d}$ embeddings
- Vocabulary of 20 amino acids for proteins, and 512 colors for iGPTs
- Blocks: self-attention map followed by a MLP, output of size $\mathbb{R}^{T\times d}$
- Extract representations after the first normalization layer of each block and then average pool along the sequence dimension to reduce a sequence into a data point embedded in $\mathbb{R}^d$
- Compute intrinsic dimension using TwoNN estimator

Valeriani, Lucrezia, Diego Doimo, Francesca Cuturello, Alessandro Laio, Alessio Ansuini, and Alberto Cazzaniga. "The Geometry of Hidden Representations of Large Transformer Models." Paper presented at Thirty-seventh Conference on Neural Information Processing Systems. November 2, 2023.

Intrinsic dimension of representations in transformers

The hunchback pattern strikes again

Figures from: Valeriani et al., (2023)







Valeriani, Lucrezia, Diego Doimo, Francesca Cuturello, Alessandro Laio, Alessio Ansuini, and Alberto Cazzaniga. "The Geometry of Hidden Representations of Large Transformer Models." Paper presented at Thirty-seventh Conference on Neural Information Processing Systems. November 2, 2023.

Intrinsic dimension of representations in transformers

The hunchback pattern during training

Figures from: Valeriani et al., (2023)





Valeriani, Lucrezia, Diego Doimo, Francesca Cuturello, Alessandro Laio, Alessio Ansuini, and Alberto Cazzaniga. "The Geometry of Hidden Representations of Large Transformer Models." Paper presented at Thirty-seventh Conference on Neural Information Processing Systems. November 2, 2023.

Local intrinsic dimension of representations in transformers

- Consider a corpus of texts: subsample M of these, tokenize, and subsample N of all the possible tokens
- Obtain a point cloud per layer: $\mathbb{T} = \left\{ \mathscr{M}_l \left(t_{m,n} \right) : 1 \leq n \leq N,\, 1 \leq m \leq M \right\},\ \ 1 \leq l \leq L$
- Compute neighborhoods for each token, given a parameter $L > 0$: $\mathscr{N}_L(t; \mathbb{T})$
- Compute TwoNN of the point cloud in the neighborhood: LID
- Aggregate for all points (compute the mean)

Ruppik, Benjamin Matthias, Julius von Rohrscheidt, Carel van Niekerk, et al. "Less Is More: Local Intrinsic Dimensions of Contextual Language Models." *Advances in Neural Information Processing Systems* 38 (April 2026): 67795–828.

Local intrinsic dimension of representations in transformers

Effects of fine-tuning in LID



(a) TwoNN estimates on `MultiWOZ` validation

Seen in fine-tuning



(b) TwoNN estimates on `Wikipedia` validation

Seen in pre-training



(c) TwoNN estimates on `Reddit` validation

Not seen

Ruppik, Benjamin Matthias, Julius von Rohrscheidt, Carel van Niekerk, et al. "Less Is More: Local Intrinsic Dimensions of Contextual Language Models." *Advances in Neural Information Processing Systems* 38 (April 2026): 67795–828.

Local intrinsic dimension of representations in transformers

Grokking

Learn to predict addition modulo p

Input sequence: [155, 'o', 88, '=']

Desired prediction: 46 (modulo p =197)



(a) **Training** accuracy (b) Validation accuracy

Ruppik, Benjamin Matthias, Julius von Rohrscheidt, Carel van Niekerk, et al. "Less Is More: Local Intrinsic Dimensions of Contextual Language Models." *Advances in Neural Information Processing Systems* 38 (April 2026): 67795–828.

To sum up

We have seen several ways in which we can use some methods to design new architectures and to better understand the architectures that we have already...

But there is much more to be done!

There are a lot of things that we haven't covered here...

We need more mathematicians in the field, developing well-grounded methods.

We need more statisticians, providing rigorous tests and complexity measures.

Thank you for your attention!

AIDOS LAB
AI FOR DATA-ORIENTED SCIENCE

UNI FR

ines.topology.rocks

aidos.group