RPL-Observations

- **Rahul (IETF 107)**


Updates

- Added clarification with respect to "Trickle timer reset"
- Backward Compatibility issues with new RPL Control Options

DAO-ACK handling


- Briefly the problem
 - DAO-ACK is local in case of storing MOP
 - Target not aware of E2E path establishment
 - If a intermediate-6LR returns -ve DAO-ACK status, target is not informed of it.

Proposition (draft-jadhav-roll-storing-rootack)



Proposition (draft-jadhav-roll-storing-rootack)

- Root sends the DAO-ACK back "directly" to target
 - Target sets a flag in TIO to indicate Root to do this.
- Address of target in Target Option
- Root sends TIO option in DAO-ACK
 - TIO needed for PathSequence
 - Overall, just 1-bit change in TIO



Following points are considered

- Handling Target aggregation in DAO
- Handling multiple DAOs in progress with different PathSequence
- Handling prefixes in Target Option
 - How would a root know the Target address when the Target Option contains prefix?
- What happens if a intermediate-6LR sends a -ve status in DAO-ACK?
- Handling multiple preferred parents
- Runtime memory efficiency
- Incremental update possible: Root and subset of nodes can be upgraded.

Next Steps

- What's the plan?
 - DAO-ACK ... New draft in progress
- Not sure how to organize
 - DTSN handling ... best practices draft?
 - Path control bits, lollipop counters (seq-window size recommendations, restart handling, worst case scenarios)
 - Should we extend the current observations draft itself?
 - Or a new draft with all combined?