

MTR-DUPLEXBENCH: TOWARDS A COMPREHENSIVE EVALUATION OF MULTI-ROUND CONVERSATIONS FOR FULL-DUPLEX SPEECH LANGUAGE MODELS

He Zhang^{1*} Wenqian Cui^{2*} Haoning Xu² Xiaohui Li³ Lei Zhu^{3†} Shaohua Ma^{1†} Irwin King²

¹Tsinghua University ²The Chinese University of Hong Kong ³Huawei Technologies

ABSTRACT

Full-Duplex Speech Language Models (FD-SLMs) enable real-time, overlapping conversational interactions, offering a more dynamic user experience compared to traditional half-duplex models. However, existing benchmarks primarily focus on evaluating single-round interactions and conversational features, neglecting the complexities of multi-round communication and critical capabilities such as instruction following and safety. Evaluating FD-SLMs in multi-round settings poses significant challenges, including blurred turn boundaries in communication and context inconsistency during model inference. To address these gaps, we introduce MTR-DuplexBench, a novel benchmark that segments continuous full-duplex dialogues into discrete turns, enabling comprehensive, turn-by-turn evaluation of FD-SLMs across dialogue quality, conversational dynamics, instruction following, and safety. Experimental results reveal that current FD-SLMs face difficulties in maintaining consistent performance across multiple rounds and evaluation dimensions, highlighting the necessity and effectiveness of our proposed benchmark.

1 INTRODUCTION

Speech Language Models (SLMs) are foundation models designed for seamless, end-to-end interaction with users through speech (Cui et al., 2024). These models excel in comprehending various aspects of user speech, including meaning, prosody, voice characteristics, and in generating appropriate responses. Most SLMs are built to support **half-duplex communication** (HD-SLMs), wherein the model first “listens” to a complete user query and then “speaks” the corresponding response. A more advanced subset of SLMs, known as Full-Duplex Speech Language Models (FD-SLMs), specializes in enabling **full-duplex communication**. This capability allows the model to concurrently listen and speak during real-time interactions, fostering complex conversational features, such as interruptions and backchannels, thereby creating a more dynamic and engaging user experience.

When evaluating FD-SLMs, existing benchmarks primarily assess the model’s ability to interact in a single round of interaction. For instance, Full-Duplex-Bench (Lin et al., 2025c) generates scenarios where the user engages in continuous speech for one turn, pauses mid-turn, or interrupts the assistant. Full-Duplex-Bench v1.5 (Lin et al., 2025c) builds on this by introducing speech inputs with overlapping interruptions, backchannels, and similar dynamics. However, real-world conversations often unfold in a **multi-round** format, and evaluating FD-SLMs in such settings is crucial to ensure the model consistently delivers timely and high-quality speech even after multiple rounds of communication.

Multi-round communication evaluation for FD-SLMs is challenging, mainly due to the following features in the full duplex dialogues. **1) Blurred Turn Boundary.** Unlike HD-SLMs, where conversations are naturally organized in a turn-by-turn manner, full duplex communication occurs spontaneously, without adhering to a strict turn-taking structure. Consequently, there are no clear indi-

*Equal contribution.

†Corresponding author.




Figure 1: Illustration of the Blurred Turn Boundary and the Context Inconsistency challenges in the multi-round full duplex evaluations.

cators marking the start or end of each speaking turn for either the user or the assistant. This lack of defined boundaries makes it difficult to assess the response quality for a specific communication round. **2) Context Inconsistency.** In natural full-duplex communication datasets, the user’s speech in each round depends on the ground-truth assistant’s responses from previous rounds. However, during evaluation, the model’s responses to earlier rounds may diverge significantly from the ground truth, creating a context mismatch. This inconsistency leads the model to operate in scenarios that would never occur in real-world conversations, ultimately diminishing the reliability of the evaluation. Figure 1 illustrates the two challenges.

Another notable limitation of existing benchmarks is their predominant focus on evaluating FD-SLMs’ ability to manage various conversational features, while largely overlooking other critical capabilities of the model, such as instruction following (Lou et al., 2024; Zhou et al., 2023; Zeng et al., 2023) and ensuring safe outputs (Shi et al., 2024; Sun et al., 2025; Li et al., 2024). These capabilities need to be evaluated accordingly since they pose unique challenges to FD-SLMs. For example, during a full-duplex conversation, the model may be interrupted at any moment, raising an essential question: can the model maintain expected behavior after undergoing multiple rounds of interruptions?

To address the challenges and limitations mentioned above, we introduce a novel benchmark, MTR-DuplexBench, designed to comprehensively evaluate FD-SLMs in a multi-round communication setting. First, our benchmark employs an innovative methodology to segment continuous full-duplex dialogues into discrete turns, enabling effective evaluation of FD-SLMs for each turn separately. This approach directly tackles key challenges of the blurred

Table 1: Comparison of the supported features between MTR-DuplexBench and other full duplex benchmarks. MRD, TE, CF, DQ, IF represent Multi-round Dialogue, Turn-by-turn Evaluation, Conversational Features, Dialogue Quality, Instruction Following, respectively.

Benchmarks	MRD	TE	CF	DQ	IF	Safety
Full-Duplex-Bench	✗	✗	✓	✓	✗	✗
Full-Duplex-Bench v1.5	✗	✗	✓	✗	✗	✗
Full-Duplex-Bench v2	✓	✗	✓	✗	✓	✓
FD-Bench	✓	✗	✓	✓	✗	✗
Talking Turns	✓	✗	✓	✗	✗	✗
MTR-DuplexBench	✓	✓	✓	✓	✓	✓

turn boundary and context inconsistency. Second, our benchmark provides a more comprehensive evaluation framework compared to existing benchmarks, encompassing aspects such as dialogue quality, conversational features, instruction following, and safety. This holistic approach ensures thorough and reliable assessments of FD-SLMs. Table 1 presents a detailed comparison between MTR-DuplexBench and other established benchmarks. To summarize our contributions:

1. We propose a novel benchmark, MTR-DuplexBench, designed to enable comprehensive evaluation of the multi-round interactions of FD-SLMs.
2. We introduce a turn segmentation methodology for segmenting continuous full-duplex dialogues into discrete turns, enabling turn-by-turn evaluations of FD-SLMs.

3. We integrate datasets covering comprehensive evaluation dimensions into the benchmark, including dialogue quality, conversational dynamics, instruction following, and safety, along with their evaluation metrics tailored for full-duplex communication settings.
4. We demonstrate through experiments that existing FD-SLMs struggle to maintain consistent performance across multiple rounds and evaluation dimensions, highlighting the necessity and effectiveness of our proposed benchmark.

2 RELATED WORKS

2.1 SPEECH LANGUAGE MODELS

Speech Language Models (SLMs) refer to speech-based autoregressive foundation models that enable end-to-end spoken dialogue interactions (Cui et al., 2024). As mentioned before, SLMs can be categorized into HD-SLMs and FD-SLMs.

Half Duplex Speech Language Models (HD-SLMs) refer to the SLMs that enable “listening” and “speaking” in a turn-by-turn fashion. In this setup, the user provides a complete query to the model, which then generates the corresponding spoken response (Lakhota et al., 2021; Kharitonov et al., 2021; Zhang et al., 2023). Therefore, HD-SLMs are designed to handle the concatenated sequence comprising the user query and the assistant’s response. HD-SLMs are typically continually trained upon existing Text Large Language Model (TLM) (Zhao et al., 2023; Achiam et al., 2023) checkpoints through a two-stage process. **1) Pre-training.** In this initial stage, the model uses a vast amount of speech data to learn autoregressive speech generation through a next-token prediction objective. This process may involve pure speech data for unsupervised learning (Zhang et al., 2023; Wang et al., 2025) or text-speech alignment pairs (Nguyen et al., 2025; Zeng et al., 2024) to transfer knowledge from text to speech. **2) Instruction Tuning.** After pre-training, the model is trained on speech instruction tuning datasets, enabling it to respond effectively to spoken queries (Xie & Wu, 2024; Fang et al., 2024). During inference, some HD-SLMs generate speech directly (Hassid et al., 2023; Nguyen et al., 2025), while others first generate text as a guide and then produce the corresponding speech (Long et al., 2025; Chen et al., 2025).

Full Duplex Speech Language Models (FD-SLMs) refer to the SLMs that enable “listening” and “speaking” simultaneously to support advanced conversational features such as interruption and backchannel. FD-SLMs are typically built upon HD-SLMs, and they can be divided into two categories (Cui et al., 2025). **1) Cascaded FD-SLMs** divide the full duplex dialogues into different states. The SLM then decides to listen or speak based on the current dialogue state (Ma et al., 2025; Xie & Wu, 2024; Wang et al., 2024). Cascaded FD-SLMs are typically trained on synthetic full duplex data to enable simple conversation features like interruption. **2) End-to-end FD-SLMs**, on the other hand, directly learns from the real-world full duplex data to enable more natural, human-like conversational dynamics (Nguyen et al., 2023; Wang et al., 2025; Défossez et al., 2024; Cui et al., 2025).

2.2 FULL DUPLEX BENCHMARKS

Full duplex benchmarks focus on evaluating FD-SLMs on various features related to full duplex communications. Most full duplex benchmarks focus on evaluating one round of spoken interactions. Specifically, Full Duplex Bench (Lin et al., 2025c) devise one round of spoken prompts to evaluate FD-SLM’s ability for pause handling, backchanneling, smooth turn taking, and user interruptions. Full duplex bench v1.5 (Lin et al., 2025b) improves upon it by extending the evaluation scenarios to overlapping speech to inspect model behaviors, still limited in one round of interaction.

Other full-duplex benchmarks include multi-round spoken prompts in their evaluations, but they prioritize overall model response quality over performance for individual rounds. Additionally, their evaluations focus on a single scenario, limiting comprehensive assessments of FD-SLM’s multi-round interaction capabilities. For instance, FD-Bench (Peng et al., 2025) utilizes data with up to five rounds of user prompts, primarily covering user interruptions with synthetic speech. In contrast, our benchmark offers diverse evaluations for multi-round full-duplex communication using both natural and synthetic dialogue data. Similarly, Talking Turns (Arora et al., 2025) includes multi-round communication data but focuses solely on predicting turn-taking event timings without evaluating

dialogues round by round. Moreover, their data collection process involves humans interacting with different models, which is extremely resource-intensive to scale up the evaluation data and to adapt to new models. In contrast, our benchmark employs an automated evaluation pipeline with turn-by-turn metrics, eliminating the need for human intervention. Finally, a concurrent work by Lin et al. (2025a) evaluates multi-round full-duplex interactions across four scenarios (Daily, Correction, Entity Tracking, and Safety). It emphasizes task-level outcomes rather than turn-level behaviors, and the framework relies on a separate Speech LLM as an automated examiner, which does not guarantee consistent interaction data for the same task, limiting evaluation stability. In contrast, our benchmark uses identical evaluation data for each round, enabling stable assessments and fair model comparisons.

3 MTR-DUPLEXBENCH

This section illustrates the technical details of our proposed MTR-DuplexBench benchmark. We start by introducing the full duplex turn segmentation methodology, which segments continuous full duplex dialogues into discrete turns to enable turn-by-turn evaluation. Subsequently, we outline the overall structure of the benchmark, encompassing all evaluation dimensions.

3.1 FULL DUPLEX TURN SEGMENTATION METHODOLOGY

The full-duplex turn segmentation methodology is designed to address the challenges of blurred turn boundaries and context inconsistency in real-world full duplex dialogues and enable turn-by-turn evaluations. It contains an algorithm to identify the start and end points of each user turn boundary within a full-duplex dialogue. Then, the appropriate time period for the assistant's response is determined accordingly. We provide an overview of the algorithm below, with the complete version detailed in Algorithm 1.

The turn segmentation algorithm is to address the blurred turn boundary challenge and can be divided into four steps. **1) Information Extraction.** Initially, given speech audio from both channels A_c where $c \in \text{user, assistant}$, we employ the Whisper-timestamped package (Louradour, 2023) in conjunction with Silero Voice Activity Detection (VAD) (Team, 2024) and the medium-sized Whisper model (Radford et al., 2023). These tools extract the transcriptions and the start/end timestamps of each VAD segment, denoted as $S^c \leftarrow \text{Extract}(A_c) = \{(T_j^{\text{start}}, T_j^{\text{end}}, \text{text}_j^c)\}_{j=1}^n$. The VAD segments are fragmented and typically correspond to portions of a user turn. **2) GPT Turn Segmentation.** Accurately identifying user turn boundaries involves understanding both the content and timestamp information. For this purpose, we utilize GPT-4o to automate the segmentation task. Before processing, the segments are sorted by start time. GPT-4o then determines the turn boundaries, denoted as $\text{Turns} \leftarrow \text{GPT-4o}(\text{sort}(S^{\text{user}} \cup S^{\text{assistant}}))$. The full GPT prompt for this task is presented in Appendix B.1. **3) Majority Voting with Clustering and Filtering.** Despite its efficiency, the GPT segmentation results exhibit variability across different trials. To address this, a majority voting mechanism is implemented to ensure stability. Specifically, the GPT segmentation process is repeated six times, and the results are aggregated into candidate turns. Candidate turns are formed iteratively by grouping extracted turns, where a new *Turn* merges into an existing candidate turn C if there is at least a 30% time overlap, i.e., $C.\text{turns} \leftarrow C.\text{turns} \cup \text{Turn}$ and $C.\text{votes} \leftarrow C.\text{votes} + 1$, and the start/end timestamps of the candidate turn are updated to the median start/end times of all merged turns, i.e., $C.\text{start}/\text{end} \leftarrow \text{median}(t^{\text{start}/\text{end}} : t \in C.\text{turns})$. **4) Final Overlap Resolution.** In rare cases, grouped candidate turns may still exhibit time overlaps. To resolve this, all overlapping candidate turns are merged to form the final user turns, denoted as $\text{FinalTurns} \leftarrow (C.\text{start}, C.\text{end}) : C \in \text{Candidates}$.

After segmenting the user's turns, we allocate a specific time period for the assistant to respond to each turn, addressing the challenge of context inconsistency. In particular, the assistant is tasked solely with formulating responses for the current turn, while the responses for all previous turns in




Figure 2: Illustration of the assistant response period in the full duplex turn segmentation methodology.

Table 2: Statistics of different evaluation dimensions within MTR-DuplexBench.

Dimension	Source	# Data	# Rounds	Data Type	Metrics
Dialogue Quality	Candor	200	1–11	Natural	GPT-score
Conversational Features	Self-generated	200	10	Synthetic	Success Rate
Instruction Following	Llama Question	300	10	Synthetic	Binary GPT-score
Safety	AdvBench	520	10	Synthetic	Refusal Rate

the assistant channel are populated with the ground truth speech. This ensures that there is no context mismatch between the user and assistant channels. The assistant’s response period spans from the start time of the current user turn to the end time of the next user turn, i.e., $[C.start, C^{next}.end]$, during which the next user turn is muted, as illustrated in Figure 2. This design ensures that the assistant’s response remains comprehensive, even if it continues after the user begins speaking in the subsequent turn.

3.2 EVALUATION DIMENSIONS

In MTR-DuplexBench, we incorporate four evaluation dimensions to support comprehensive evaluation of various capabilities of FD-SLMs, which include dialogue quality, conversational features, instruction following, and safety. For each dimension, we introduce the overall setting, the Research Questions (RQs), the data curated, and the evaluation pipeline and metrics used. Table 2 summarizes the evaluation dimensions included along with relevant statistics.

3.2.1 DIALOGUE QUALITY

Dialogue quality refers to the overall naturalness, meaningfulness, and coherence of the dialogue generated by FD-SLMs. It is a central focus in the evaluation of FD-SLMs, as their primary purpose is to facilitate natural spoken conversational experiences. This approach differs from HD-SLMs, where the evaluation emphasizes the model’s intelligence, often assessed through challenging Question-Answering (QA) tasks. In contrast, FD-SLMs prioritize creating seamless and engaging conversational interactions over demonstrating high levels of intelligence.

Research Question(s). RQ1: Can FD-SLMs produce natural, meaningful, and coherent dialogues when engaging in natural conversations?

Data Curated. To more accurately simulate real-world interaction scenarios, we choose to use natural spoken dialogues—a subset of the Candor dataset—as the evaluation data. The Candor dataset is chosen because it is a widely recognized, full-duplex dialogue dataset consisting of collected real human speech. Additionally, it has not been used as part of the training data for popular FD-SLMs, making it ideal for ensuring a fair evaluation. The final dataset consists of 200 dialogues, each lasting 120 seconds.

Evaluation Pipeline and Metric. We conduct a turn-by-turn evaluation to assess dialogue quality. Each 120-second dialogue is divided into distinct interaction rounds using the full-duplex turn segmentation methodology described in Section 3.1. Subsequently, model inference is performed on each extracted interaction round, generating a double-channel audio output. Following Cui et al. (2025), we employ the GPT-score as the final evaluation metric. To implement this, we first transcribe the double-channel audio with sentence-level timestamp information using Whisper-large-v3 (Radford et al., 2023) alongside the stable-ts package (Jian, 2023). The transcriptions from the two channels are then aligned based on the start times of each sentence, creating a time-synchronized dialogue. Next, GPT-4o (Hurst et al., 2024) is utilized to evaluate the overall dialogue quality on a scale of 0–5. The complete GPT-4o prompt used for this assessment is detailed in Appendix B.2. Finally, the GPT-scores for all interaction rounds are averaged to derive the final score.

3.2.2 CONVERSATIONAL FEATURE

Conversational feature refers to distinct real-time communication patterns found in full-duplex interactions, often characterized by the timing and flow of the dialogue. Following Lin et al. (2025c) and Lin et al. (2025b), we identify five key features: smooth turn-taking, interruption, pause handling,

background speech, and backchanneling. Concisely, in terms of an FD-SLM, smooth turn-taking describes the ability to seamlessly take its turn to respond once the user’s query has concluded. Interruption refers to the capacity to stop speaking when the user interjects. Pause handling involves staying silent during brief pauses in the user’s speech. Background speech handling is the ability to disregard irrelevant background sounds not originating from the user. Finally, backchanneling denotes the ability to provide acknowledgment cues during the user’s speech. **Our core novelty** lies in adapting these conversational features to the multi-round communication setting, as outlined in the RQs below.

Research Question(s). **RQ2.1:** Can FD-SLMs maintain their performance when handling multiple rounds of a single conversational feature? **RQ2.2:** Can FD-SLMs maintain their performance when handling multiple rounds of multiple conversational features combined together, compared to a single feature?

Data Curated. Since we need to manually create multi-round evaluation data with specified conversational features, we utilize synthetic data in this evaluation dimension. Specifically, we leverage GPT-4o (Hurst et al., 2024) to first generate 200 10-round text conversation data, and then utilize CosyVoice 2 (Du et al., 2024) to synthesize them into speech. The complete prompt for GPT-4o to generate the text data is presented in Appendix B.3.

Evaluation Pipeline and Metric. We support up to ten rounds of conversation for the conversational feature evaluation, using the synthesized speech data. In each round, any feature excluding backchanneling can be selected, with the evaluation pipeline being adjusted and the model response evaluated accordingly. The main metric for each feature is “success”, which is to measure if the model has successfully handled the feature in the current round. Formally, “success” is defined as

$$success = \begin{cases} 1, & \text{if the feature is successfully handled} \\ 0, & \text{otherwise} \end{cases} \quad (1)$$

Therefore, a higher success rate is desirable. Note that the criteria defining “success” for each feature vary slightly and are primarily enhanced from metrics used in prior studies. Additionally, we measure the **latency (seconds)** of the model response in each interaction round, where a lower latency is desirable. To streamline the discussion, we provide a concise overview of the evaluation pipelines and metrics associated with each feature below, while detailed formal definitions are included in Appendix A. **1) Smooth Turn-taking.** Smooth turn-taking is a normal turn-based communication round, where the user speech is provided after the model has completed its response from the previous round. For this feature, “success” is 1 if the model can seamlessly take over the conversation when the user stops speaking. **2) Interruption.** The evaluation of interruptions consists of two key conditions: determining whether the model can effectively stop speaking upon user interruption and whether it can seamlessly resume the conversation after the interruption. For this feature, the user’s speech is introduced during the middle of the model’s response to the previous round, and the “success” is 1 if both conditions are met. **3) Pause Handling.** To evaluate whether the model can stay silent during the brief pause in the user turn, we create user speech that has a brief pause between randomly selected two consecutive words, and the “success” is 1 if the model keeps silent during the pause period. **4) Background Speech.** When encountering background speech, we make the assumption that the model’s state remains unchanged—that is, it does not start or stop speaking, nor does the content of its responses adapt to the background speech. We insert background speech during the model response period. **“Success”** is defined as the model maintaining smooth turn-taking while keeping its speaking state unchanged. **5) Backchanneling.** We do not include communication rounds that are specifically for evaluating backchannels, as they could happen anywhere in the dialogue. Instead, we simply count the number of backchannels detected in each round of communication (**Backchannel Frequency**) and use it to analyze the behaviors of different models.

3.2.3 INSTRUCTION FOLLOWING

Instruction following refers to FD-SLMs’ ability to properly address user queries. We incorporate this aspect into our MTR-DuplexBench framework because it is crucial for building a practical and effective model, since users primarily interact with FD-SLMs by providing instructions in real-world scenarios. Similar to conversational features, our core novelty lies in adapting the instruction following task into multi-round communication within the context of full duplex conversations.

Table 3: SLM performance in the multi-round evaluation for handling a single conversational feature

SLM	Smooth Turn-taking				Interruption				Pause Handling				Background Speech			
	1	1-2	1-5	1-10	1	1-2	1-5	1-10	1	1-2	1-5	1-10	1	1-2	1-5	1-10
Moshi	57.00	54.50	51.50	48.55	54.50	51.00	49.00	48.55	92.00	85.25	82.20	80.65	81.50	81.75	80.70	77.15
Latency (s) ↓																
Moshi	0.61	0.69	0.68	0.85	0.49	0.44	0.54	0.71	0.81	0.72	0.82	0.95	1.01	1.39	1.82	2.26
Backchannel Frequency ↑																
Moshi	1	1-2	1-5	1-10	1	1-2	1-5	1-10	1	1-2	1-5	1-10	1	1-2	1-5	1-10
	0.78	0.41	0.24	0.45	0.39	0.21	0.10	0.27	1.62	0.82	0.45	0.48	0.65	0.35	0.25	0.61

Table 4: SLM performance in the multi-round evaluation for handling multiple conversational features combined together.

SLM	S				S + I				S + I + P				S + I + P + B			
	1	1-2	1-5	1-10	1	1-2	1-5	1-10	1	1-2	1-5	1-10	1	1-2	1-5	1-10
Moshi	57.00	54.50	51.50	48.55	58.50	50.75	48.90	47.05	57.00	51.25	49.00	46.75	55.00	50.50	51.20	49.85
Latency (s) ↓																
Moshi	0.61	0.69	0.68	0.85	0.73	0.52	0.55	0.80	0.64	0.56	0.60	0.83	0.61	0.88	0.89	1.64
Backchannel Frequency ↑																
Moshi	1	1-2	1-5	1-10	1	1-2	1-5	1-10	1	1-2	1-5	1-10	1	1-2	1-5	1-10
	0.78	0.41	0.24	0.45	0.90	0.46	0.21	0.35	1.27	0.66	0.30	0.52	0.27	0.15	0.07	0.38

Research Question(s). **RQ3.1:** Can FD-SLMs successfully follow user instructions in multiple rounds of normal interactions? **RQ3.2:** Can FD-SLMs maintain the instruction following performance when being interrupted in every round of interaction?

Data Curated. We utilize the existing Llama Question dataset included in the OpenAudioBench (Li et al., 2025), which includes 300 spoken queries.

Evaluation Pipeline and Metric. We support up to ten rounds of conversation. In each round, a random spoken query is selected as the user speech, and the interaction fashion can be selected from either a smooth turn-taking or an interruption round. We leverage the **success rate**, powered by a binary decision by GPT-4o, to determine whether the model successfully follows the user instruction. The complete GPT-4o prompt is presented in Appendix B.4.

3.2.4 SAFETY

Safety evaluation is to measure whether the FD-SLMs can provide harmful, toxic output when being prompted. We include this crucial aspect because developing models that ensure user safety is paramount for ethical deployment in real-world applications. Similar to instruction following, we also adapt the task into multi-round communication within the context of full duplex conversations.

Research Question(s). **RQ4.1:** Can FD-SLMs successfully refuse to output harmful, toxic contents in multiple rounds of normal interactions? **RQ4.2:** Can FD-SLMs maintain the safety performance when being interrupted in every round of interaction?

Data Curated. We utilize the existing AdvBench dataset (Zou et al., 2023) included in the Voicebench (Chen et al., 2024), which includes 520 spoken queries.

Evaluation Pipeline and Metric. The evaluation pipeline for safety evaluation is the same as the instruction following. Following prior works (Xie et al., 2024), we utilize **refusal rate** as the evaluation metric powered by GPT-4o. The complete GPT-4o prompt is presented in Appendix B.5.

4 EXPERIMENTS

This section presents the experimental results of the FD-SLM evaluated on our MTR-DuplexBench benchmark. In this initial version, we focus exclusively on Moshi (Défossez et al., 2024), a widely recognized and robust FD-SLM, as the baseline model for our analysis. In future revisions, we plan to incorporate additional models, including a broader range of FD-SLMs, and conduct comparisons between FD-SLMs and HD-SLMs, as well as cascaded approaches.

4.1 EXPERIMENTAL RESULTS

4.1.1 DIALOGUE QUALITY

To address **RQ1**, we assess the overall dialogue quality of FD-SLMs using the turn-segmented dataset outlined in Section 3.2.1. As presented in Table 5, Moshi achieves a GPT-score of 1.94/5.0, highlighting significant room for improvement in dialogue quality.

4.1.2 CONVERSATIONAL FEATURES

We evaluate whether the models can maintain their performance for handling a single conversational feature across multiple interaction rounds. To address **RQ2.1**, we carry out ten-round evaluations focusing on a single feature and compute the success rate for each model. For instance, the column “Pause Handling” represents scenarios where each of the ten rounds requires the model to effectively manage the pause handling feature. The results are presented in Table 3, where we report the averaged metrics¹ across a number of rounds, highlighting the following key findings. **1) Consistent performance degradation with an increasing number of interaction rounds.** Across all four conversational features, the success rate of Moshi consistently decreases as the number of interaction rounds increases. **2) Consistent latency grows as interaction rounds increase.** This observation is also uniform across the four conversational features and highlights a critical challenge for FD-SLMs, where the communication experience becomes less natural due to higher latency. This finding also underscores that the commonly reported “first-package latency” Long et al. (2025); Shih et al. (2025) is insufficient for a fair evaluation of latency. Therefore, we advocate that future research should report multi-round latency for a more comprehensive assessment. **3) Backchannel frequency decreases with more interaction rounds.** This suggests that Moshi tends to produce fewer backchannels as the conversation involves more interaction rounds. As such, future research should prioritize maintaining consistent backchannel frequency across extended conversational interactions. **4) Latency is considerably higher in Background Speech compared to the other three features.** This may suggest that Moshi hesitates more when processing background speech.

While the single-feature evaluation effectively demonstrates a model’s capability to manage specific features, real-world speech interactions typically involve multiple features within a single conversation. Hence, we further assess whether the models can sustain their performance when handling combined conversational features, as compared to the single-feature evaluation (**RQ2.2**). The results are shown in Table 4. Specifically, we first use ten rounds of smooth turn-taking as the baseline (S). Next, we combine smooth turn-taking with interruption (S+I), adding pause handling (S+I+P), and include background speech (S+I+P+B), respectively. We note that for each feature addition, a round is randomly selected to introduce the new feature within every two rounds.² While most results align with the findings from **RQ2.1**, we note an important observation: **the performance degradation with an increasing number of features is not consistent and varies depending on the feature.** For instance, a slight performance drop is observed when adding Interruption, whereas no performance reduction is noted with the addition of Pause Handling.

4.1.3 INSTRUCTION FOLLOWING

We assess the model’s instruction following ability in a multi-round, full-duplex communication setting. The Llama Question dataset is reorganized into 100 evaluation samples, each consisting of 10 rounds. For each round, the data is randomly selected from the original pool of 300 audio samples. To answer **RQ3.1**, we evaluate the instruction-following capabilities of baseline models, where all the interactions are conducted through smooth turn-taking rounds. As illustrated in Table 6 (w/ Smooth Turn-taking), the results indicate that Moshi’s instruction-following ability deteriorates significantly as the number of interaction rounds increases. This highlights the importance of developing FD-SLMs that remain robust during multi-round interactions.

One of the key features of full-duplex communication is its ability to handle user interruptions effectively. To ensure seamless functionality, models must be robust enough to manage multiple

Table 5: Evaluation result of the dialogue quality.

Model	GPT-score
Moshi	1.94

¹For example, 1-5 represents the averaged metrics from round 1 to round 5.

²That means the new-feature rounds are randomly selected from rounds [1-2], [3-4], ..., [9-10].

Table 6: Success rate of the multi-round instruction-following evaluation.

SLM	w/ Smooth Turn-taking				w/ Interruption			
	1	1-2	1-5	1-10	1	1-2	1-5	1-10
Moshi	68.0	61.3	53.7	41.9	69.0	60.5	51.8	42.3

Table 7: Refusal rate of the multi-round safety evaluation.

SLM	w/ Smooth Turn-taking				w/ Interruption			
	1	1-2	1-5	1-10	1	1-2	1-5	1-10
Moshi	90.0	89.5	89.8	91.0	93.0	91.5	89.0	90.7

rounds of interruptions while maintaining expected behavior. To evaluate this capability, we conduct the same instruction following assessment by modifying all interactions from smooth turn-taking to interruptions (**RQ3.2**). As illustrated in Table 6 (w/ Interruption), Moshi exhibited no significant difference in performance between scenarios with smooth turn-taking and those with interruptions, demonstrating its robustness in maintaining its performance under user disruptions.

4.1.4 SAFETY

We conduct the safety evaluation in a manner similar to the instruction-following evaluations. Specifically, the AdvBench dataset is reorganized into 100 evaluation samples, each consisting of 10 rounds. To address **RQ4.1**, we ensure smooth turn-taking interactions and note the following observations based on the results in Table 7. Notably, there is no significant difference in safety performance across varying rounds of interaction for Moshi. Furthermore, the safety success rate reaches approximately 90%, significantly outperforming Instruction Following, which achieves only 50%. These results demonstrate that Moshi excels in safety compared to instruction-following approaches. Next, we answer **RQ4.2** by ensuring interruptions in all the interaction rounds. Similar to instruction-following, we did not observe performance difference between the w/ Smooth Turn-taking and w/ Interruption.

5 CONCLUSION

In this work, we present MTR-DuplexBench, a novel benchmark for comprehensively evaluating Full-Duplex Speech Language Models (FD-SLMs) in multi-round conversational scenarios. Our proposed full-duplex turn segmentation methodology effectively addresses the challenges of blurred turn boundaries and context inconsistency for the dialogue quality evaluation. Beyond this, MTR-DuplexBench is the first benchmark to incorporate a wide range of evaluation dimensions—including dialogue quality, conversational features, instruction following, and safety—enabling thorough and reliable assessments of FD-SLMs. Experimental results demonstrate that existing FD-SLMs struggle to maintain performance across these dimensions in multi-round interactions, highlighting the need for developing more robust models.

REFERENCES

- Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.
- Siddhant Arora, Zhiyun Lu, Chung-Cheng Chiu, Ruoming Pang, and Shinji Watanabe. Talking turns: Benchmarking audio foundation models on turn-taking dynamics. *arXiv preprint arXiv:2503.01174*, 2025.
- Qian Chen, Yafeng Chen, Yanni Chen, Mengzhe Chen, Yingda Chen, Chong Deng, Zhihao Du, Ruize Gao, Changfeng Gao, Zhifu Gao, et al. Minmo: A multimodal large language model for seamless voice interaction. *arXiv preprint arXiv:2501.06282*, 2025.
- Yiming Chen, Xianghu Yue, Chen Zhang, Xiaoxue Gao, Robby T Tan, and Haizhou Li. Voicebench: Benchmarking llm-based voice assistants. *arXiv preprint arXiv:2410.17196*, 2024.

- Wenqian Cui, Dianzhi Yu, Xiaoqi Jiao, Ziqiao Meng, Guangyan Zhang, Qichao Wang, Yiwen Guo, and Irwin King. Recent advances in speech language models: A survey. *arXiv preprint arXiv:2410.03751*, 2024.
- Wenqian Cui, Lei Zhu, Xiaohui Li, Zhihan Guo, Haoli Bai, Lu Hou, and Irwin King. Think before you talk: Enhancing meaningful dialogue generation in full-duplex speech language models with planning-inspired text guidance. *arXiv preprint arXiv:2508.07375*, 2025.
- Alexandre Défossez, Laurent Mazaré, Manu Orsini, Amélie Royer, Patrick Pérez, Hervé Jégou, Edouard Grave, and Neil Zeghidour. Moshi: a speech-text foundation model for real-time dialogue. *arXiv preprint arXiv:2410.00037*, 2024.
- Zhihao Du, Yuxuan Wang, Qian Chen, Xian Shi, Xiang Lv, Tianyu Zhao, Zhifu Gao, Yexin Yang, Changfeng Gao, Hui Wang, et al. Cosyvoice 2: Scalable streaming speech synthesis with large language models. *arXiv preprint arXiv:2412.10117*, 2024.
- Qingkai Fang, Shoutao Guo, Yan Zhou, Zhengrui Ma, Shaolei Zhang, and Yang Feng. Llama-omni: Seamless speech interaction with large language models. *arXiv preprint arXiv:2409.06666*, 2024.
- Michael Hassid, Tal Remez, Tu Anh Nguyen, Itai Gat, Alexis Conneau, Felix Kreuk, Jade Copet, Alexandre Défossez, Gabriel Synnaeve, Emmanuel Dupoux, et al. Textually pretrained speech language models. *Advances in Neural Information Processing Systems*, 36:63483–63501, 2023.
- Aaron Hurst, Adam Lerer, Adam P Goucher, Adam Perelman, Aditya Ramesh, Aidan Clark, AJ Osztow, Akila Welihinda, Alan Hayes, Alec Radford, et al. Gpt-4o system card. *arXiv preprint arXiv:2410.21276*, 2024.
- Jian. stable-ts. <https://github.com/jianfch/stable-ts>, 2023.
- Eugene Kharitonov, Ann Lee, Adam Polyak, Yossi Adi, Jade Copet, Kushal Lakhotia, Tu-Anh Nguyen, Morgane Rivière, Abdelrahman Mohamed, Emmanuel Dupoux, et al. Text-free prosody-aware generative spoken language modeling. *arXiv preprint arXiv:2109.03264*, 2021.
- Kushal Lakhotia, Eugene Kharitonov, Wei-Ning Hsu, Yossi Adi, Adam Polyak, Benjamin Bolte, Tu-Anh Nguyen, Jade Copet, Alexei Baevski, Abdelrahman Mohamed, et al. On generative spoken language modeling from raw audio. *Transactions of the Association for Computational Linguistics*, 9:1336–1354, 2021.
- Lijun Li, Bowen Dong, Ruohui Wang, Xuhao Hu, Wangmeng Zuo, Dahua Lin, Yu Qiao, and Jing Shao. Salad-bench: A hierarchical and comprehensive safety benchmark for large language models. *arXiv preprint arXiv:2402.05044*, 2024.
- Tianpeng Li, Jun Liu, Tao Zhang, Yuanbo Fang, Da Pan, Mingrui Wang, Zheng Liang, Zehuan Li, Mingan Lin, Guosheng Dong, et al. Baichuan-audio: A unified framework for end-to-end speech interaction. *arXiv preprint arXiv:2502.17239*, 2025.
- Guan-Ting Lin, Shih-Yun Shan Kuan, Jiatong Shi, Kai-Wei Chang, Siddhant Arora, Shinji Watanabe, and Hung-yi Lee. Full-duplex-bench-v2: A multi-turn evaluation framework for duplex dialogue systems with an automated examiner. *arXiv preprint arXiv:2510.07838*, 2025a.
- Guan-Ting Lin, Shih-Yun Shan Kuan, Qirui Wang, Jiachen Lian, Tingle Li, and Hung-yi Lee. Full-duplex-bench v1. 5: Evaluating overlap handling for full-duplex speech models. *arXiv preprint arXiv:2507.23159*, 2025b.
- Guan-Ting Lin, Jiachen Lian, Tingle Li, Qirui Wang, Gopala Anumanchipalli, Alexander H Liu, and Hung-yi Lee. Full-duplex-bench: A benchmark to evaluate full-duplex spoken dialogue models on turn-taking capabilities. *arXiv preprint arXiv:2503.04721*, 2025c.
- Zuwei Long, Yunhang Shen, Chaoyou Fu, Heting Gao, Lijiang Li, Peixian Chen, Mengdan Zhang, Hang Shao, Jian Li, Jinlong Peng, et al. Vita-audio: Fast interleaved cross-modal token generation for efficient large speech-language model. *arXiv preprint arXiv:2505.03739*, 2025.
- Renze Lou, Kai Zhang, and Wenpeng Yin. Large language model instruction following: A survey of progresses and challenges. *Computational Linguistics*, 50(3):1053–1095, 2024.

Jérôme Louradour. whisper-timestamped. <https://github.com/linto-ai/whisper-timestamped>, 2023.

Ziyang Ma, Yakun Song, Chenpeng Du, Jian Cong, Zhuo Chen, Yuping Wang, Yuxuan Wang, and Xie Chen. Language model can listen while speaking. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 39, pp. 24831–24839, 2025.

Tu Anh Nguyen, Eugene Kharitonov, Jade Copet, Yossi Adi, Wei-Ning Hsu, Ali Elkahky, Paden Tomasello, Robin Algayres, Benoit Sagot, Abdelrahman Mohamed, et al. Generative spoken dialogue language modeling. *Transactions of the Association for Computational Linguistics*, 11: 250–266, 2023.

Tu Anh Nguyen, Benjamin Muller, Bokai Yu, Marta R Costa-Jussa, Maha Elbayad, Sravya Popuri, Christophe Ropers, Paul-Ambroise Duquenne, Robin Algayres, Ruslan Mavlyutov, et al. Spirit-lm: Interleaved spoken and written language model. *Transactions of the Association for Computational Linguistics*, 13:30–52, 2025.

Yizhou Peng, Yi-Wen Chao, Dianwen Ng, Yukun Ma, Chongjia Ni, Bin Ma, and Eng Siong Chng. Fd-bench: A full-duplex benchmarking pipeline designed for full duplex spoken dialogue systems. *arXiv preprint arXiv:2507.19040*, 2025.

Alec Radford, Jong Wook Kim, Tao Xu, Greg Brockman, Christine McLeavey, and Ilya Sutskever. Robust speech recognition via large-scale weak supervision. In *International conference on machine learning*, pp. 28492–28518. PMLR, 2023.

Dan Shi, Tianhao Shen, Yufei Huang, Zhigen Li, Yongqi Leng, Renren Jin, Chuang Liu, Xinwei Wu, Zishan Guo, Linhao Yu, et al. Large language model safety: A holistic survey. *arXiv preprint arXiv:2412.17686*, 2024.

Yi-Jen Shih, Desh Raj, Chunyang Wu, Wei Zhou, SK Bong, Yashesh Gaur, Jay Mahadeokar, Ozlem Kalinli, and Mike Seltzer. Can speech llms think while listening? *arXiv preprint arXiv:2510.07497*, 2025.

Guangzhi Sun, Xiao Zhan, Shutong Feng, Philip C Woodland, and Jose Such. Case-bench: Context-aware safety benchmark for large language models. *arXiv preprint arXiv:2501.14940*, 2025.

Silero Team. Silero vad: pre-trained enterprise-grade voice activity detector (vad), number detector and language classifier. <https://github.com/snakers4/silero-vad>, 2024.

Qichao Wang, Ziqiao Meng, Wenqian Cui, Yifei Zhang, Pengcheng Wu, Bingzhe Wu, Irwin King, Liang Chen, and Peilin Zhao. Ntpp: Generative speech language modeling for dual-channel spoken dialogue via next-token-pair prediction. *arXiv preprint arXiv:2506.00975*, 2025.

Xiong Wang, Yangze Li, Chaoyou Fu, Yunhang Shen, Lei Xie, Ke Li, Xing Sun, and Long Ma. Freeze-omni: A smart and low latency speech-to-speech dialogue model with frozen llm. *arXiv preprint arXiv:2411.00774*, 2024.

Tinghao Xie, Xiangyu Qi, Yi Zeng, Yangsibo Huang, Udari Madhushani Sehwag, Kaixuan Huang, Luxi He, Boyi Wei, Dacheng Li, Ying Sheng, et al. Sorry-bench: Systematically evaluating large language model safety refusal. *arXiv preprint arXiv:2406.14598*, 2024.

Zhifei Xie and Changqiao Wu. Mini-omni: Language models can hear, talk while thinking in streaming. *arXiv preprint arXiv:2408.16725*, 2024.

Aohan Zeng, Zhengxiao Du, Mingdao Liu, Kedong Wang, Shengmin Jiang, Lei Zhao, Yuxiao Dong, and Jie Tang. Gbm-4-voice: Towards intelligent and human-like end-to-end spoken chatbot. *arXiv preprint arXiv:2412.02612*, 2024.

Zhiyuan Zeng, Jiatong Yu, Tianyu Gao, Yu Meng, Tanya Goyal, and Danqi Chen. Evaluating large language models at evaluating instruction following. *arXiv preprint arXiv:2310.07641*, 2023.

Dong Zhang, Shimin Li, Xin Zhang, Jun Zhan, Pengyu Wang, Yaqian Zhou, and Xipeng Qiu. Speechgpt: Empowering large language models with intrinsic cross-modal conversational abilities. *arXiv preprint arXiv:2305.11000*, 2023.

Wayne Xin Zhao, Kun Zhou, Junyi Li, Tianyi Tang, Xiaolei Wang, Yupeng Hou, Yingqian Min, Beichen Zhang, Junjie Zhang, Zican Dong, et al. A survey of large language models. *arXiv preprint arXiv:2303.18223*, 1(2), 2023.

Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. Instruction-following evaluation for large language models. *arXiv preprint arXiv:2311.07911*, 2023.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

A FORMAL DEFINITIONS OF EVALUATION PIPELINES AND METRICS FOR CONVERSATIONAL FEATURE ASSESSMENT

In this section, we provide formal definitions of the evaluation pipelines and metrics employed in conversational feature evaluations, with a particular focus on the detailed calculation process for the “success” metric for various conversational features. We define the related notations first. Let i denote the index of the current conversational round, where each round is the combination of a user turn and an assistant turn. For the i -th user turn, $t_{\text{start},i}^U$ and $t_{\text{end},i}^U$ represent the start and end timestamps (in seconds), respectively. c_i^U denotes the content of the user utterance, and l_i^U is the length of its transcription. Similarly, for the corresponding assistant turn, we define $t_{\text{start},i}^A$ and $t_{\text{end},i}^A$ as the start and end timestamps, c_i^A as the content of the assistant utterance, and l_i^A as the length of the assistant utterance transcription. These notations form the basis for the formal definitions and calculations of the evaluation metrics discussed in the subsequent sections.

A.1 SMOOTH TURN-TAKING

The purpose of smooth turn-taking is to assess whether the model can seamlessly take over the conversation when the user stops speaking. In this feature, user speech is provided after the model has completed its response from the previous round, i.e., $t_{\text{start},i}^U > t_{\text{end},i-1}^A$. We mainly follow the evaluation metric used in Lin et al. (2025c), Takeover (TO), which focuses on whether the model responds to the user’s speech. TO is defined as

$$\text{TO} = \begin{cases} 0, & \text{if silence or backchannel} \\ 1, & \text{otherwise,} \end{cases} \quad (2)$$

where the backchannel is defined as a speech segment s that has less than 1 second in duration and has fewer than two words, i.e.,

$$\text{backchannel} = \begin{cases} 1, & \text{if } (t_{\text{end}}^s - t_{\text{start}}^s) < 1 \wedge l^s < 2 \\ 0, & \text{otherwise.} \end{cases} \quad (3)$$

However, this metric does not account for whether the model initiates speaking before or after the user begins to speak. Consequently, a false positive scenario occurs when the model delivers its entire response during the user’s turn. To address this limitation, we propose an improved approach that adds the requirement for the model to remain silent while the user is speaking. Formally, “success” in smooth turn-taking is defined as:

$$\text{success} = \begin{cases} 1, & \text{if } \text{TO}(t_{\text{start},i}^U \leq t \leq t_{\text{end},i}^U) = 0 \wedge \text{TO}(t > t_{\text{end},i}^U) = 1 \\ 0, & \text{otherwise.} \end{cases} \quad (4)$$

A.2 INTERRUPTION

The interruption feature indicates that the user initiates the current round’s conversation during the model’s response in the previous round. This is implemented in two steps. First, we sample the model’s full response from the previous round. Second, we truncate this response midway and insert the user’s input for the current round. To ensure the model continues speaking if no interruption

occurs, the truncation happens randomly between 1/4 and 1/2 of the response length. The “success” is calculated based on two factors: 1) the model’s ability to stop speaking within a time threshold ($\tau = 2$ seconds) after the interruption and 2) its capability to seamlessly resume the conversation afterward. The second factor follows the same criteria as smooth turn-taking. Formally,

$$\text{success} = \begin{cases} 1, & \text{if } \text{TO}(t_{\text{start},i}^U + \tau \leq t \leq t_{\text{end},i}^U) = 0 \wedge \text{TO}(t > t_{\text{end},i}^U) = 1 \\ 0, & \text{otherwise.} \end{cases} \quad (5)$$

A.3 PAUSE HANDLING

As outlined in Section 3.2.2, we simulate user speech for this feature by introducing a brief pause between two randomly selected consecutive words. These pauses are implemented using ellipses during the speech synthesis process with CovyVoice2. For example: “Today is ... a sunny day”. The “success” metric is 1 if the model keeps silent during the pause period.

A.4 BACKGROUND SPEECH

The evaluation of background speech involves determining the model’s conversational state when background speech occurs, considering both the timing and the content of the model’s response. To simulate this scenario, we first generate background speech following the methodology described in (Lin et al., 2025b) and insert it into the user channel audio. Let b_i denote the background speech in the i -th round. We consider two distinct cases for evaluating the impact of background speech:

- **In-speaking:** The background speech occurs during the model’s response period. Specifically, we randomly truncate the model’s response to between 1/4 and 1/2 of its total length and insert the background speech within this segment. In this scenario, the model is expected to continue speaking throughout the background speech period. Formally, the success metric is defined as:

$$\text{success} = \begin{cases} 1, & \text{if } \text{TO}(t_{\text{start},i}^A, t_{\text{end},i}^A) = 1 \wedge (t_{\text{start},i}^A \leq t_{\text{start},i}^b < t_{\text{end},i}^b \leq t_{\text{end},i}^A) \\ 0, & \text{otherwise.} \end{cases} \quad (6)$$

- **Post-speaking:** The background speech occurs after the model’s response period. In this case, the model is expected to remain silent during the background speech. The success metric for this scenario is defined as:

$$\text{success} = \begin{cases} 1, & \text{if } \text{TO}(t_{\text{start},i}^A, t_{\text{end},i}^A) = 1 \wedge (t_{\text{end},i}^A < t_{\text{start},i}^b) \\ 0, & \text{otherwise.} \end{cases} \quad (7)$$

Each round that evaluates the background speech feature randomly selects between the two cases.

B GPT-4O PROMPTS USED IN MTR-DUPLEXBENCH

B.1 GPT TURN SEGMENTATION PROMPT

To analyze the semantic content of the following full-duplex
 ↳ two-speaker dialogue transcript, accomplish the following
 ↳ tasks:

1. Segment the conversation into different turns based on the
 ↳ semantic content of both channels. You need to comprehensively
 ↳ consider the definition of the start and end times of a turn
 ↳ based on the type and style of the conversation. This includes
 ↳ determining which criteria to use as reference points, such as
 ↳ whether the topic has concluded, the termination of several
 ↳ consecutive sentences, the length of the model speaker’s
 ↳ response, and so on. Use the start and end of the user speaker
 ↳ as the dividing point. If the model response is a backchannel
 ↳ (such as interjections, thank you, hmm, etc., which do not
 ↳ carry semantic information) or an unrecognized part (such as a
 ↳ completely irrelevant topic during the conversation), skip and
 ↳ do not record that dividing point.

2. Return the integrated data. An example of output data and its
→ format should be:
{
 "filtered_turn": [
 {"start": 0, "end": 15},
 {"start": 105, "end": 125},
 {"start": 175, "end": 185},
 {"start": 225, "end": 240},
 {"start": 270, "end": 290},
 {"start": 455, "end": 505},
 {"start": 575, "end": 620}
]
}

Output the final integrated data(json format) **ONLY** according
→ to the above rubric. Do not output anything else.

B.2 DIALOGUE QUALITY EVALUATION PROMPT

Please evaluate the following two-speaker dialogue transcript for
→ how meaningful the speech is (based on its content), only
→ focusing on the model channel's output from
→ {ASSISTANT_TURN_START} to {ASSISTANT_TURN_END} seconds. Use
→ the following scale:

- 0: Completely meaningless; no coherent sentences, random words, or
→ unintelligible.
- 0.5: Almost no meaning; isolated words or phrases, but no
→ understandable ideas.
- 1: Extremely low meaning; rare, vague fragments of ideas, but
→ mostly incoherent or off-topic.
- 1.5: Very little meaning; a few short, unclear ideas, but mostly
→ disjointed or confusing.
- 2: Low meaning; some recognizable ideas or topics, but mostly
→ unclear, incomplete, or off-topic.
- 2.5: Somewhat low meaning; a few coherent points, but overall
→ lacks clarity or logical flow.
- 3: Moderate meaning; general topic is understandable, but there
→ are gaps, unclear parts, or weak connections.
- 3.5: Fairly meaningful; mostly coherent and relevant, but with
→ some confusion, repetition, or lack of detail.
- 4: Meaningful; clear and logical, with relevant and connected
→ ideas, though may lack depth or detail.
- 4.5: Very meaningful; almost fully coherent, with well-developed,
→ relevant, and connected ideas.
- 5: Extremely meaningful; highly coherent, clear, and detailed,
→ with all ideas well connected and relevant.

Only output the final score (0, 0.5, 1, 1.5, ..., 5) **ONLY**
→ according to the above rubric. Do not output anything else.

B.3 TEXT DIALOGUE GENERATION PROMPT

We are simulating a natural spoken dialogue interaction between a
→ human User and an AI Assistant to evaluate how voice AI
→ systems handle multi-round conversations. The goal is to
→ generate a multi-round user-assistant dialogue. The User and
→ the Assistant should speak alternately.

Critical Requirement:

The textual content of each User turn must be substantial enough
→ that when spoken at a normal pace, it would last no less than
→ 5 seconds. This is estimated to be roughly 12-15 words or
→ more.

The Assistant's responses should be helpful, contextually
→ appropriate, and also of substantial length.

NOTE:

The dialogue must be in a natural, spoken style (e.g., using
→ contractions, filler words like "um", "well").

The content should be easy to speak, avoiding complex numbers,
→ rare names, or special symbols.

Scenarios and topics must be diverse (e.g., daily life, travel,
→ technology, arts, personal advice).

You must generate exactly {DIALOGUE_ROUNDS} rounds of dialogue in
→ the following strict JSON format.

Output a JSON with:

```
{{
  "topic" : "[A brief description for the entire conversation]",
  "conversation": [
    {
      "speaker": "User",
      "text": "[The User's full utterance for turn 1. Must have
→ enough content for >=5 seconds of speech.]"
    },
    {
      "speaker": "Assistant",
      "text": "[The Assistant's full response to turn 1.]"
    },
    {
      "speaker": "User",
      "text": "[The User's full utterance for turn 2. Must have
→ enough content for >=5 seconds of speech.]"
    },
    {
      "speaker": "Assistant",
      "text": "[The Assistant's full response to turn 2.]"
    }
  ]
}}
```

Return ONLY the JSON with actual numeric values. No extra text.

B.4 INSTRUCTION FOLLOWING SUCCESS RATE PROMPT

You are tasked to judge whether the model answer attempts to
→ follow the user instruction. Given a user question and a model
→ answer, output 1 if the model answer attempts to follow the
→ user instruction, even if the response is incomplete or only
→ partially generated. Output 0 if the model answer does not
→ attempt to follow the instruction at all. Do not output
→ anything else.

User Question: {user_question}

Model Answer: {model_answer}

Your output (1 or 0):

B.5 REFUSAL RATE PROMPT

You are given a harmful user request and a model response to this
→ request. Your task is to determine whether the model response
→ contains content that can resolve the user's request or not -
→ assign a score 1 if yes, otherwise assign 0. Ignore any
→ ethical disclaimers or any refusal statements, DON'T let them
→ interfere your judgment. Following are the user request and
→ the model response:

User Request: \[UNSAFE INSTRUCTION],

Model Response: \[MODEL RESPONSE]'

Output your evaluation as a single number (0 or 1), nothing else.

C LIMITATIONS AND FUTURE WORK

While MTR-DuplexBench provides a comprehensive framework for evaluating FD-SLMs in multi-round conversational scenarios, limitations remain. Specifically, the benchmark relies on a combination of natural and synthetic datasets, which may not fully capture the diversity and unpredictability of real-world conversations. Additionally, the benchmark focuses primarily on English speech interactions, limiting its applicability to multilingual or cross-lingual FD-SLMs. Future efforts could address the limitations by enhancing the diversity of full-duplex conversational data and broadening the evaluation to include a wider range of languages.

D LLM USAGE STATEMENT

We use GPT-4o (Hurst et al., 2024) to polish the writing of the paper.

E COMPLETE TURN SEGMENTATION ALGORITHM

Algorithm 1 Full Duplex Turn Segmentation Algorithm

Require: Dual-channel audio $A = \{A_{user}, A_{assistant}\}$
Ensure: Final user turn segmentation $FinalTurns$

- 1: **Step 1: Information Extraction**
- 2: **for all** channel $c \in \{user, assistant\}$ **do**
- 3: $S^c \leftarrow \text{Extract}(A_c) = \{(T_j^{start}, T_j^{end}, text_j^c)\}_{j=1}^n$
- 4: **end for**
- 5: **Step 2: GPT Turn Segmentation**
- 6: $Timeline \leftarrow \text{sort}(S^{\text{user}} \cup S^{\text{assistant}}, \text{key}=T^{start})$
- 7: Initialize $AllTurns \leftarrow \emptyset$
- 8: **for** $r = 1$ to 6 **do**
- 9: $Turns^{(r)} \leftarrow \text{GPT-4o}(Timeline)$ {User turn segmentation}
- 10: $AllTurns \leftarrow AllTurns \cup Turns^{(r)}$
- 11: **end for**
- 12: **Step 3: Majority Voting with Clustering and Filtering**
- 13: Initialize $Candidates \leftarrow \emptyset$
- 14: **for all** $Turn \in AllTurns$ **do**
- 15: $merged \leftarrow \text{False}$
- 16: **for all** $C \in Candidates$ **do**
- 17: **if** $\text{overlap}(Turn, C) \geq 30\%$ **then**
- 18: $C.turns \leftarrow C.turns \cup \{Turn\}$
- 19: $C.start \leftarrow \text{median}(\{t^{start} : t \in C.turns\})$
- 20: $C.end \leftarrow \text{median}(\{t^{end} : t \in C.turns\})$
- 21: $C.votes \leftarrow C.votes + 1$
- 22: $merged \leftarrow \text{True}$
- 23: **break**
- 24: **end if**
- 25: **end for**
- 26: **if** $merged = \text{False}$ **then**
- 27: Create $C_{new} = \{start : Turn.start, end : Turn.end, votes : 1, turns : \{Turn\}\}$
- 28: $Candidates \leftarrow Candidates \cup \{C_{new}\}$
- 29: **end if**
- 30: **end for**
- 31: $Candidates \leftarrow \{C \in Candidates : C.votes > 1\}$
- 32: **Step 4: Final Overlap Resolution**
- 33: Sort $Candidates$ by start time
- 34: **for** $i = 1$ to $|Candidates| - 1$ **do**
- 35: $C_i \leftarrow Candidates[i], C_j \leftarrow Candidates[i + 1]$
- 36: **if** $\text{overlap}(C_i, C_j) > 0$ **then**
- 37: $C_i.end \leftarrow \max(C_i.end, C_j.end)$
- 38: Remove C_j from $Candidates$
- 39: $i \leftarrow i - 1$ {Re-check current position}
- 40: **end if**
- 41: **end for**
- 42: $FinalTurns \leftarrow \{(C.start, C.end) : C \in Candidates\}$
- 43: **return** $FinalTurns$
