Dream 7B: Diffusion Large Language Models

Jiacheng Ye 1* Zhihui Xie 1* Lin Zheng 1* Jiahui Gao 2* Zirui Wu 1 Xin Jiang 2 Zhenguo Li 2 Lingpeng Kong 1

¹The University of Hong Kong ² Huawei Noah's Ark Lab

🗘 DreamLM/Dream 🔑 Dream-7B

April 2, 2025

Abstract

We introduce Dream 7B, the most powerful open diffusion large language model to date. Unlike autoregressive (AR) models that generate tokens sequentially, Dream 7B employs discrete diffusion modeling to refine sequences in parallel through iterative denoising. Our model consistently outperforms existing diffusion language models on general, mathematical, and coding tasks. Dream 7B demonstrates superior planning abilities and inference flexibility, including arbitrary-order generation, infilling capabilities, and tunable quality-speed trade-offs. These results are achieved through simple yet effective training techniques, including AR-based LLM initialization and context-adaptive token-level noise rescheduling. We release both Dream-Base and Dream-Instruct to facilitate further research in diffusion-based language modeling.




Figure 1: Performance comparison of diffusion and autoregressive language models on various tasks.

1 Introduction

The rapid advancement of large language models (LLMs) has fundamentally transformed artificial intelligence, driving breakthroughs across diverse applications and industries. The current landscape is dominated by autoregressive (AR) models that generate text through sequential left-to-right token prediction, with virtually all leading systems including GPT-4 (OpenAI et al., 2024) and DeepSeek R1 (Guo et al., 2025). While these models have demonstrated remarkable capabilities, a fundamental question emerges: What architectural paradigms might define the next generation of LLMs? This question becomes increasingly important as AR models exhibit inherent limitations in complex reasoning, long-term planning, and maintaining coherence across extended contexts (Bubeck et al., 2023; Dziri et al., 2023; Bachmann and Nagarajan, 2024; Ye et al., 2025a). These limitations are particularly crucial

^{*}Equal Contribution

for emerging applications such as embodied AI, autonomous agents, and long-horizon decision-making systems, where the ability to reason holistically about entire sequences rather than incrementally becomes paramount.

Discrete diffusion models (DMs) have gained attention as a promising alternative for sequence generation since their introduction to the text domain (Austin et al., 2021a; Hoogeboom et al., 2021; Campbell et al., 2022). Rather than building text token by token from left to right, diffusion models begin with completely corrupted sequences and gradually denoise them through multiple refinement steps, enabling bidirectional context integration and more flexible generation patterns. This architectural shift unlocks several theoretical advantages that directly address autoregressive limitations. The parallel nature of diffusion enables richer contextual modeling by incorporating information from all positions simultaneously, potentially leading to more coherent and globally consistent outputs (Li et al., 2022). Furthermore, the iterative refinement process naturally supports controllable generation (Gulrajani and Hashimoto, 2023b; Li et al., 2022) and provides flexible quality-speed trade-offs through adjustable inference steps, offering new dimensions for optimization for test-time scaling (Snell et al., 2024; Muennighoff et al., 2025; Geiping et al., 2025) that complement existing techniques like long-thought chain-of-thought reasoning (Jaech et al., 2024; Guo et al., 2025).

Recent developments have begun to demonstrate the practical viability of scaled diffusion language models. Works such as DiffuLLaMA (Gong et al., 2025), LLaDA (Nie et al., 2025b) have successfully scaled discrete diffusion to billion-parameter regimes. While Mercury Coder (Inception Labs, 2025), as a commercial implementation, has demonstrated remarkable inference efficiency in code generation. This rapid progress, combined with the inherent architectural advantages of diffusion language modeling, positions these models as a promising direction for overcoming the fundamental limitations of autoregressive approaches. However, significant gaps remain in achieving performance parity with state-of-the-art autoregressive models like Qwen2.5 (Qwen et al., 2025) across various general tasks (Clark et al., 2018; Hendrycks et al., 2020).

In this work, we present Dream 7B, a 7-billion parameter diffusion language model that bridges this performance gap while demonstrating unique capabilities inherent to the diffusion paradigm. We introduce a comprehensive training framework that leverages AR-based LLM initialization and context-adaptive noise scheduling to scale diffusion language models. Through extensive evaluation, we establish that diffusion models can match AR-based LLM performance on general language tasks while providing distinct advantages in planning-intensive scenarios and offering unprecedented inference flexibility through arbitrary-order generation and dynamic quality-speed optimization. We release both Dream-Base and Dream-Instruct to facilitate further research in this promising direction.

Takeaways

- We release Dream 7B, which consistently outperforms existing diffusion language models by substantial margins across diverse benchmarks.
- Dream 7B achieves competitive performance with Qwen 2.5 on standard benchmarks (general language understanding, mathematical reasoning, and code generation) while exhibiting superior planning abilities and novel inference flexibility features that naturally emerge from the diffusion modeling paradigm.

2 Related Work

2.1 Diffusion Models for Text

Diffusion models were originally developed for continuous domains like image generation (Song et al., 2021; Ho et al., 2020). Building on their remarkable success, a number of works have extended diffusion techniques to text generation tasks by modeling text in a continuous embedding space, building continuous diffusion language models (Li et al., 2022; Gong et al., 2023b,a; Dieleman et al., 2022). Among these approaches, Lin et al. (2023) demonstrated the feasibility of applying diffusion models within a pre-training and fine-tuning framework on a small-scale transformer.

To fit the discrete nature of text, Austin et al. (2021a); Hoogeboom et al. (2021); Campbell et al. (2022) introduced discrete diffusion, which operates on the discrete vocabulary space, establishing the

foundation for discrete diffusion methods. In this formulation, diffusion forward steps progressively with either [MASK] tokens (leading to an absorbing state) or random tokens (resulting in a uniform state), and the reverse process reconstructs the original text from these noised sequences. Building on this foundation, several studies have improved the training objectives for discrete diffusion (Zheng et al., 2024b; Lou et al., 2024; Shi et al., 2024; Ou et al., 2025; Zhao et al., 2024; Sahoo et al., 2024). Besides, He et al. (2023); Ye et al. (2025c) have shown benefits by initializing discrete diffusion models with pre-trained masked language models (MLMs, e.g., BERT; Devlin et al. 2019). Recent studies have highlighted diffusion language models' advantages for complex reasoning and planning tasks (Ye et al., 2024, 2025a,b). Moreover, combining diffusion and autoregressive methods through block generation has emerged as a promising approach, demonstrating a flexible trade-off between parallelism and sequential coherence (Ye et al., 2024; Arriola et al., 2025).

2.2 Diffusion Large Language Models

Gulrajani and Hashimoto (2023a) analyzed the scaling laws for continuous diffusion language models, highlighting that continuous diffusion models require substantially longer training compared to autoregressive (AR) counterparts for optimal computational efficiency. In the discrete domain, Lou et al. (2024) showed that masked diffusion models (MDMs) could achieve perplexities comparable to or exceeding GPT-2-level AR models. Encouraged by these results, recent efforts have scaled diffusion language models to billions of parameters. Nie et al. (2025a) demonstrated the applicability of 1.1B-scale MDMs in language tasks such as question answering. Instead of training from scratch, Gong et al. (2025) proposed adapting existing AR language models (GPT-2 and LLaMA, from 127M to 7B parameters) into diffusion-based counterparts termed DiffuGPT and DiffuLLaMA. Concurrently, Nie et al. (2025b) presented LLaDA, an 8B-parameter diffusion language model trained from scratch, which achieved performance competitive with LLaMA3-8B (Grattafiori et al., 2024). Furthermore, Mercury Coder (Inception Labs, 2025) has recently shown commercial applicability and efficiency in code generation tasks. Overall, our work builds upon the masked diffusion paradigm and introduces new training techniques to push the performance further, highlighting the potential of diffusion-based models as an alternative to autoregressive LLMs.

3 Preliminary

3.1 Auto-regressive Modeling

Consider a sequence $\mathbf{x} := (\mathbf{x}^1, \dots, \mathbf{x}^N)$ of length N sampled from a data distribution $q(\mathbf{x})$. A fundamental approach in sequence modeling decomposes the joint probability of tokens into a product of conditional probabilities (Jelinek, 1980; Bengio et al., 2000):

$$p_{\theta}(\mathbf{x}) = p_{\theta}(\mathbf{x}^{1}) \underbrace{\prod_{n=2}^{N} p_{\theta}(\mathbf{x}^{n} \mid \mathbf{x}^{1:n-1}),}_{\text{progressive left-context prediction}}$$
(1)

where $\boldsymbol{\theta}$ represents the model parameters and $\boldsymbol{x}^{1:n-1} \coloneqq \boldsymbol{x}^1, \dots, \boldsymbol{x}^{n-1}$ denotes the preceding tokens.

3.2 Discrete Diffusion Modeling

Discrete diffusion models (Sohl-Dickstein et al., 2015; Hoogeboom et al., 2021; Austin et al., 2021a) are a class of latent variable models characterized by a forward noising process and a learned reverse denoising process. Let \mathbf{x}_t denote the noised sequence at timestep t and the [MASK] noise is employed. The forward process $q(\mathbf{x}_{1:T}|\mathbf{x}_0) = \prod_{t=1}^T q(\mathbf{x}_t|\mathbf{x}_{t-1})$ progressively corrupts the original data $\mathbf{x}_0 \coloneqq \mathbf{x}$ into a sequence of increasingly noisy tokens (replaced with [MASK] tokens) $\mathbf{x}_{1:T} \coloneqq \mathbf{x}_1, \dots, \mathbf{x}_T$. The forward process continues until the sequence is fully denoised at t = T. For $t \in (0,T)$, the sequence \mathbf{x}_t is partially noised using a noise schedule α_t (where for each token the probability of remaining unmasked is α_t). The backward process learns to gradually denoise the masked sequence back to the original data distribution by iteratively predicting masked tokens as t moves from T to 0. This denoising process can

be modeled as:

$$p_{\theta}(\mathbf{x}) = \sum_{\mathbf{x}_{1:T} \sim q} p(\mathbf{x}_T) \prod_{t=1}^{T} p_{\theta}(\mathbf{x}_{t-1}|\mathbf{x}_t).$$
progressive full-context prediction (2)

The model parameters $\boldsymbol{\theta}$ can be optimized by minimizing the negative log-likelihood of the clean data \mathbf{x}_0 .

The discrete time formulation $t \in (0,T)$ restricts \mathbf{x}_t to predetermined noise levels, which can introduce bias. To mitigate this limitation and enable flexible sampling across arbitrary noise levels, we adopt continuous-time parameterization where t ranges continuously over [0,1] (Kingma et al., 2021; Campbell et al., 2022; Shi et al., 2024; Ou et al., 2025). This continuous formulation allows the forward process to be expressed as $q(\mathbf{x}_t|\mathbf{x}_s)$ for any $0 \le s < t \le 1$. We employ discrete diffusion with absorbing states and simplify the objective as weighted cross-entropy losses:

$$L(\theta) = -\mathbb{E}_{\mathbf{x}_0 \sim q(\mathbf{x}), t \sim \mathcal{U}(0, 1), \mathbf{x}_t \sim q(\mathbf{x}_t | \mathbf{x}_0)} w(t) \sum_{n=1}^{N} \mathbf{1}_{[\mathbf{x}_t^n = \text{MASK}]} \log p_{\theta}(\mathbf{x}_0^n | \mathbf{x}_t), \tag{3}$$

where the indicator function $\mathbf{1}_{[\mathbf{x}_t^n = \mathsf{MASK}]}$ ensures that the loss is computed only on masked token positions, and $w(t) \in (0,1]$ is a time-dependent reweighting term determined by a transformation of α_t . For instance, when the forward process adopts the noise schedule $\alpha_t = 1 - t$, the corresponding weight becomes $w(t) = \frac{1}{t}$ (Austin et al., 2021a; Zheng et al., 2024b), which assigns greater importance to denoising steps closer to the clean data (i.e., as $t \to 0$). As demonstrated in Shi et al. (2024); Gong et al. (2025), this weighted cross-entropy objective Equation. (3) represents an effective reformulation of the ELBO, which enables optimization of the mask predictor $p_{\theta}(\cdot|\mathbf{x}_t)$ by providing a tractable variational upper bound on the negative log-likelihood.

4 Approach




Figure 2: Comparison of autoregressive modeling and diffusion modeling in Dream. Dream predicts all the masked tokens in a shifted manner, allowing for maximumly architectural alignment and weight initialization with AR models.

4.1 AR-based LLM Initialization

Building on DiffuLLaMA (Gong et al., 2025), we find that leveraging pre-trained weights from existing autoregressive (AR) models provides a non-trivial initialization strategy for diffusion language models. In Dream, we adopt the "Shift Operation" strategy in Gong et al. (2025) to maintain the inherent shift operation characteristic of AR models during the transition to diffusion-based training. Specifically, autoregressive models are trained so that the hidden representation at position i encodes the information necessary to predict the token at position i+1. Rather than disrupting this learned positional relationship, our approach preserves this shift mechanism throughout the diffusion training process. The model continues to utilize hidden state h_i to generate predictions for position i+1, which contrasts with conventional diffusion models that attempt to predict masked tokens at their original positions. This design choice ensures that the diffusion learning process remains aligned with the pretrained representations, preventing the transition from autoregressive to diffusion modeling from disrupting the foundational sequence understanding embedded in the pre-trained weights.




Figure 3: Illustration of the context-adaptive token-level noise rescheduling mechanism. Dream re-decides the noise level for each mask token by measuring its context informationness.

The AR initialization strategy offers computational advantages by building upon established sequence modeling capabilities rather than learning these representations from scratch, as evidenced by our experimental results in Section 5.4. Furthermore, this approach maximizes the utility of existing pretrained AR language models. Once superior AR LLMs become available, our framework enables rapid iteration toward improved diffusion models without requiring costly from-scratch training, effectively leveraging the collective efforts of the research community in autoregressive model development.

4.2 Context-Adaptive Token-Level Noise Rescheduling

Standard diffusion training for text applies uniform sentence-level timesteps, which ignores the varying contextual dependencies of individual tokens. In conventional discrete diffusion training, a single timestep t is sampled to determine the overall noise level for the entire sequence, after which the model performs denoising on all the masked positions uniformly. For instance, when adopting the noise schedule $\alpha_t = 1 - t$, the weighting term w(t) in Equation (3) becomes $\frac{1}{t}$. However, since learning occurs at the token level, the actual noise experienced by each token may deviate from the global timestep t. An example is shown in Figure 3, a shared sentence-level t is assigned to the three mask tokens in the standard discrete diffusion modeling, while the first token should inherently be associated with a lower noise level than subsequent tokens, as it benefits from richer contextual conditioning. This discrepancy leads to suboptimal learning, particularly for tokens with differing degrees of contextual information.

To address this limitation, we move from sequence-level noise scheduling to token-level noise scheduling. We introduce CART (Context-Adaptive noise Rescheduling at Token-level), which measures the contextual informativeness for each token individually and dynamically reassigns appropriate noise levels based on the current context. This approach provides fine-grained, token-specific guidance that better reflects the varying difficulty and contextual dependencies across different positions in the sequence. Specifically, the objective with CART is represented as follows:

$$L(\theta) = -\mathbb{E}_{\mathbf{x}_0 \sim q(\mathbf{x}), t \sim \mathcal{U}(0, 1), \mathbf{x}_t \sim q(\mathbf{x}_t | \mathbf{x}_0)} \sum_{n=1}^{N} \mathbf{1}_{[\mathbf{x}_t^n = \text{MASK}]} w(t, \mathbf{x}_t, n) \log p_{\theta}(\mathbf{x}_0^n | \mathbf{x}_t), \tag{4}$$

where $w(t, \mathbf{x}_t, n)$ is a generalized term of w(t) that can be flexibly designed. In practice, we employ a mixture of geometric distributions to quantify the information contribution of each clean token relative to the noised tokens, which is defined as:

$$w(t, \mathbf{x}_t, n) = \frac{1}{2} \sum_{i=1}^{N} \mathbf{1}_{\left[\mathbf{x}_t^i \neq \text{MASK}\right]} \operatorname{Geo}(p, |n-i| - 1), \tag{5}$$

where $p \in (0, 1]$ controls the sharpness of the geometric distribution. A smaller p causes clean tokens to tend to contribute uniformly to all masked tokens in the sequence, while a larger p forces clean tokens to have a greater influence on the nearby masked tokens.

4.3 Training

Model Architecture Dream models are built upon the Transformer architecture (Vaswani et al., 2017), maintaining full compatibility with existing autoregressive language models while enabling diffusion-based training. Specifically, Dream-7B adopts the same model configuration as Qwen2.5-7B (Qwen et al., 2025).

Pretraining The training objective is to model the data distribution $p_{\theta}(\mathbf{x}_0)$. We estimate Equation (3) via the Monte Carlo method for stochastic gradient descent training. Our training corpus comprises 580 billion tokens spanning text, mathematics, and code domains. The data is sourced from three primary repositories: Dolma v1.7 (Soldaini et al., 2024) for general domain text, OpenCoder (Huang et al., 2025) for programming and code datasets, and DCLM-Baseline (Li et al., 2024) for curated high-quality text and mathematical content. We exclusively utilize open-source datasets to demonstrate the effectiveness of our paradigm and ensure reproducibility.

Supervised Fine-Tuning The SFT training objective is to model the conditional distribution $p_{\theta}(r_0|p_0)$, where p_0 is the prompt and r_0 denotes the response. During fine-tuning, noise is applied only to the response portion of the sequence, keeping the prompt intact to preserve instruction following capabilities. To align Dream with user instructions, we curate a dataset containing 1.8M instruction-response pairs from Tulu 3 (Lambert et al., 2025) and SmolLM 2 (Allal et al., 2025).

5 Experiments

5.1 Setup

Evaluation Tasks We evaluated Dream on a comprehensive suite of benchmarks designed to assess its capabilities across multiple domains. For general language understanding, we employed tasks such as MMLU (Hendrycks et al., 2020), BBH (Suzgun et al., 2022), ARC-E (Clark et al., 2018), ARC-C (Clark et al., 2018), HellaSwag (Zellers et al., 2019), WinoGrande (Sakaguchi et al., 2021), PIQA (Bisk et al., 2020), and RACE (Lai et al., 2017) to test knowledge, reasoning, and commonsense abilities. For mathematical and scientific reasoning, we used GSM8K (Cobbe et al., 2021) and MATH (Hendrycks et al., 2020) for numerical computation and problem-solving, and GPQA (Rein et al., 2023) for scientific understanding. Code generation abilities were evaluated through HumanEval (Chen et al., 2021) and MBPP (Austin et al., 2021b) to measure programming capabilities. The IFEval benchmark specifically measured the model's capacity to adhere to given instructions for instruction following assessment. For planning tasks, we evaluate performance on the Countdown and Sudoku tasks from Ye et al. (2025a), and Trip planning task from Zheng et al. (2024a), which assess planning capabilities with specific objectives.

5.2 Results of Dream-Base

Superior planning performance of diffusion language models over autoregressive models As shown in Table 1, Dream 7B maintains competitive general language capabilities while excelling in complex reasoning scenarios compared to Qwen2.5 7B, demonstrating the superior reasoning and planning abilities of diffusion models. For instance, on general tasks, Dream 7B achieves comparable performance with only modest gaps on MMLU and HellaSwag, while outperforming on reasoning tasks (ARC-E, ARC-C). The most striking advantages emerge in planning tasks, where Dream 7B substantially outperforms Qwen2.5 on Countdown (16.0 vs. 6.2), Sudoku (81.0 vs. 21.0), and Trip planning (17.8 vs. 3.6). Furthermore, we observe that other diffusion models (LLaDA) also consistently outperform Qwen2.5 on these tasks, providing additional evidence for the inherent advantages of diffusion modeling in planning capabilities.

Effectiveness of Dream training approach Compared to the previous state-of-the-art diffusion model (LLaDA 8B, which is trained from scratch), Dream 7B achieves remarkable performance improvements across all evaluation domains while using only 1/4 of the training data (0.6T vs 2.3T tokens). Dream 7B demonstrates significant gains on general tasks, with even more pronounced advantages in reasoning tasks. Notably, Dream 7B achieves substantial improvements on reasoning tasks (e.g., ARC-C improves from 47.5 to 59.8, GSM8K improves from 70.9 to 77.2). Additionally, Dream 7B excels in planning tasks with substantial margins over LLaDA: Countdown improves from 13.2 to 16.0, and Sudoku from 46.0 to 81.0. These results validate the effectiveness of our autoregressive model initialization strategy and context-adaptive noise rescheduling mechanism. Notably, since Dream 7B is initialized from Qwen2.5 weights, we expect that with stronger autoregressive foundation models, our approach will enable the development of even more capable diffusion language models.

Table 1: Comparison of base models on standard evaluation benchmarks. * indicates Dream 7B, LLaDA 8B, Qwen2.5 7B and LLaMA3 8B are evaluated under the same protocol. The best results are bolded and the second best are underlined. Our results are highlighted in blue .

Model	Dream 7B*	LLaDA 8B*	Qwen2.5 $7B^*$	LLAMA3 $8B^*$	Mistral 7B	${\rm DeepSeek}~7{\rm B}$	
Type	Diffusion	Diffusion	AR	AR	AR	AR	
Training Tokens	0.6T	2.3T	18T	15T	-	2T	
General Tasks							
MMLU	69.5 (5)	65.9 (5)	71.9 (5)	63.5 (5)	60.1 (5)	48.2 (5)	
BBH	$\overline{57.9 (3)}$	47.4(3)	63.9 (3)	62.7(3)	-	39.5(3)	
ARC-E	83.9(0)	71.8(0)	77.4(0)	81.1 (0)	80.0 (0)	67.9(0)	
ARC-C	59.8(0)	47.5(0)	51.5(0)	$\overline{53.6 (0)}$	55.5 (0)	48.1(0)	
Hellaswag	73.3(0)	72.7(0)	79.0 (0)	$\overline{78.9 (0)}$	81.3 (0)	75.4(0)	
WinoGrande	$\overline{74.5 (5)}$	73.5(5)	76.4(5)	76.9 (5)	75.3(0)	70.5(0)	
PIQA	75.8(0)	74.8(0)	$\overline{79.8 (0)}$	81.3 (0)	83.0 (0)	79.2(0)	
RACE	44.7(0)	38.7(0)	41.9(0)	39.2(0)	-	46.5(5)	
Mathematics & Science							
GSM8K	77.2(8)	70.9 (8)	78.9 (8)	55.3 (8)	52.1 (8)	17.4 (8)	
MATH	39.6(4)	30.7(4)	41.1 (4)	18.0 (4)	13.1 (4)	6.0(4)	
GPQA	36.6 (5)	30.4(5)	35.5(5)	30.6(5)	-	-	
Code							
HumanEval	57.9 (0)	32.9 (0)	56.7 (0)	35.4 (0)	30.5 (0)	26.2 (0)	
MBPP	<u>56.2</u> (4)	39.0 (4)	63.6(4)	49.2 (4)	47.5 (3)	39.0 (3)	
Planning Tasks							
Countdown	16.0 (8)	13.2 (8)	6.2 (8)	3.7 (8)	-	-	
Sudoku	81.0 (8)	$\overline{46.0 \ (8)}$	21.0 (8)	0.0 (8)	-	-	
Trip planning	17.8 (2)	16.4(2)	3.6 (2)	8.7 (2)	-	-	

5.3 Results of Dream-Instruct

As an early exploration of diffusion LLM post-training, we perform lightweight supervised fine-tuning to align Dream with user instructions. Specifically, we curate 1.8M instruction-response pairs and fine-tune Dream for 3 epochs. The results of Dream-Instruct in Table 2 demonstrate DLLM's potential to match AR-based LLMs in instruction-following tasks, establishing a foundation for future advanced DLLM post-training recipes.

Table 2: Performance comparison after supervised fine-tuning on standard evaluation benchmarks.

Model	Dream 7B	LLaDA 8B	Qwen2.5 7B	LLaMA3 8B
Type	Diffusion	Diffusion	AR	AR
Post-training	SFT	SFT	$_{ m SFT+RL}$	$\operatorname{SFT}+\operatorname{RL}$
Alignment pairs	1.8M	4.5M	$1\mathrm{M}/0.15\mathrm{M}$	-
MMLU	67.0	65.5	76.6	68.4
MMLU-pro	43.3	37	56.3	41.9
GSM8K	81.0	78.6	91.6	78.3
Math	39.2	26.6	75.5	29.6
GPQA	33.0	31.8	36.4	31.9
HumanEval	55.5	47.6	84.8	59.8
MBPP	58.8	34.2	79.2	57.6
IFEval	62.5	59.9	74.7	49.7

5.4 Effect of AR Initialization

To validate the effectiveness of autoregressive (AR) initialization, we conducted preliminary experiments adapting Dream-1B from LLaMA3.2-1B. As demonstrated in Figure 4, the AR initialization strategy proves particularly effective during the early stages of training, providing significant advantages over training from scratch. This observation shows that the existing left-to-right knowledge in AR models provides a strong foundation that accelerates the diffusion model's development of any-order generation capabilities. This acceleration significantly reduces both the number of tokens and computational resources required for pretraining, making our approach highly efficient compared to training diffusion language models from scratch.

Besides, our analysis reveals that the learning rate plays a critical role in preserving the beneficial properties inherited from AR initialization. An excessively high learning rate can rapidly degrade the left-to-right linguistic knowledge embedded in the initial weights, thereby diminishing the advantages of AR initialization. Conversely, an overly conservative learning rate may impede the model's ability to effectively learn the diffusion process. Through systematic hyperparameter tuning, we carefully calibrated the learning rate alongside other training parameters to achieve optimal performance.




Figure 4: Loss comparison of the from-scratch and AR-initialization with LLaMA3.2 1B training on the Dream 1B models with 200B tokens. AR initialization also experiences a high loss at the beginning due to the transition from causal attention to full attention; however, this loss remains lower compared to training from scratch throughout the training.

5.5 Discussion

5.5.1 Analysis of Planning Ability

Ye et al. 2025a,b demonstrated that text diffusion models exhibit superior planning capabilities in small-scale, task-specific contexts. However, it remained unclear whether these advantages extend to general-purpose, scaled diffusion models. In this work, we scale up diffusion language models and systematically evaluate their constraint-based planning abilities using Dream 7B. We evaluated Dream on the Countdown and Sudoku tasks from Ye et al. (2025a). Our experimental comparison included Dream 7B alongside LLaDA 8B, Qwen2.5 7B, and LLaMA3 8B, with the DeepSeek V3-671B (0324) serving as a reference point. All models were evaluated in a few-shot setting without task-specific training.

The results shown in Figure 5 demonstrate that Dream consistently outperforms other similarly-sized baseline models across both tasks. Notably, Dream 7B significantly exceeds the performance of comparably-sized autoregressive models (LLaMA3 8B and Qwen2.5 7B) and, in certain cases (e.g., Countdown3), even surpasses the much larger DeepSeek-V3-671B (0324), despite the latter having




Figure 5: Results on Countdown and Sudoku when varying planning difficulty.

orders of magnitude more parameters. This substantial performance advantage suggests that diffusion language models are inherently more effective at solving problems involving multiple constraints or specific objective optimization. For detailed qualitative examples illustrating the performance differences between Qwen2.5 7B and Dream 7B across various planning scenarios, please refer to Figure 6.

Task	Question (In-context examples are omitted)	Answer from Qwen2.5 7B (AR)	Answer from Dream 7B (Diffusion)
Trip Planning	Here are the cities that have direct flights: Istanbul and Budapest, from Dubrovnik to Istanbul.	Here is the trip plan for visiting the 3 European cities for 12 days: **Day 1-5:** Arriving in Istanbul and visit Istanbul for 5 days. **Day 5:** Fly from Istanbul to Budapest. **Day 5-11:** Visit Budapest for 6 days. **Day 11:** Fly from Budapest to Dubrovnik. **Day 11-12:** Visit Dubrovnik for 3 days.	Here is the trip plan for visiting the 3 European cities for 12 days: **Day 1-3:** Arriving in Dubrovnik and visit Dubrovnik for 3 days. **Day 3-7:** Fly from Dubrovnik to Istanbul. **Day 3-7:** Visit Istanbul for 5 days. **Day 7:** Fly from Istanbul to Budapest. **Day 7-12:** Visit Budapest for 6 days.
Countdown	Given 5 numbers, use +-*/ to operate over the first four numbers to achieve the fifth number. Input: 81,84,82,42,41 Output:	84-81=3,82-42=40,40/3=13.3333333	82-81=1,84-1=83,83-42=41
Sudoku	Fill the position where the values are 0 in a 4x4 grid with digits 1-4 so that each column, each row, and each of the four 2x2 subgrids that compose the grid contains all of the digits from 1 to 4. Input: 4001 3124 1302 0400 Output:	4312 2134 1342 3241	4231 3124 1342 2413

Figure 6: Examples generated by Qwen2.5 7B and Dream 7B.

5.5.2 Quality-Speed Trade-Offs

Diffusion language models provide a unique advantage through their adjustable inference process, where the number of diffusion timesteps can be modified to balance computational speed and output quality. Reducing the number of timesteps speeds up inference but may reduce generation quality, while increasing timesteps improves output quality at the cost of additional computation.

To demonstrate this flexibility, we conduct a systematic quality-speed analysis on the Countdown task, comparing Dream 7B against Qwen2.5 7B across varying timestep configurations, as illustrated in Figure 7. The experimental results demonstrate that Dream's performance exhibits a controllable trade-off between computational efficiency and generation quality through timestep adjustment, providing users with fine-grained control over the inference process. Notably, when diffusion steps are set between 5-20, Dream achieves superior performance in both speed and quality compared to Qwen2.5 7B.

This timestep-based approach introduces an additional dimension for inference-time scaling (Snell et al., 2024; Muennighoff et al., 2025; Geiping et al., 2025), which works alongside existing techniques such as chain-of-thought reasoning used in large language models like OpenAI of (Jaech et al., 2024) and DeepSeek R1 (Guo et al., 2025). This adjustable computation-quality trade-off represents a key advantage that sets diffusion models apart from traditional autoregressive models.




Figure 7: Quality-speed comparison on the Countdown task for Dream 7B and Qwen2.5 7B. By adjusting the diffusion timesteps, the performance of Dream can be flexibly tuned for either speed or quality.

5.5.3 Arbitrary Order Generation

Diffusion models exhibit remarkable inference flexibility, setting them apart from traditional autoregressive (AR) models that typically generate sequences in a fixed left-to-right order. This flexibility stems from their inherent capability to synthesize outputs in arbitrary orders, opening up a wider range of diverse user queries and interaction patterns.

Dream 7B supports completion and infilling tasks naturally, without requiring specialized training. Key examples of this flexibility include:

- Completion: Users can provide an initial piece of text, and the model can seamlessly continue or complete it.
- Infilling: Diffusion models can fill in missing segments within a given text. This can be unconstrained or guided by specific requirements, such as ensuring the generated infill leads to an exact ending sentence.
- Configurable decoding order: Beyond these task-specific flexibilities, users can also exert control over the decoding behavior itself. By adjusting decoding hyperparameters, the generation process can be tailored to mimic the more structured, left-to-right generation characteristic of AR models, or conversely, it can introduce varying degrees of randomness in the decoding order, moving towards a partially or even fully random-order synthesis.

This adaptability in how the output is constructed, not just what is generated, allows diffusion models to cater to different preferences and task requirements, making them versatile tools for a broad spectrum of generation scenarios. We provide dynamic demonstrations of these capabilities at https://hkunlp.github.io/blog/2025/dream/.

6 Conclusion

Dream 7B represents a significant step forward in diffusion-based language modeling, achieving competitive performance with state-of-the-art autoregressive models while providing unique capabilities for flexible text generation. Our experiments reveal that diffusion language models excel particularly in constraint-satisfaction and planning tasks, where their bidirectional nature and iterative refinement process offer clear advantages over traditional left-to-right generation approaches.

The model's ability to perform arbitrary-order generation enables novel applications in completion and infilling tasks, while the adjustable timestep configurations provide users with fine-grained control over the quality-speed trade-off during inference. These capabilities, combined with the demonstrated effectiveness of initializing from pre-trained autoregressive models, establish a practical pathway for developing more flexible and capable language models. Future work will explore advanced post-training recipes, longer context capabilities, and applications to specialized domains requiring enhanced planning and reasoning abilities.

Acknowledgments

We thank Chengwu Cai for his support and helpful discussion. We also acknowledge the open-source community for providing high-quality datasets and evaluation frameworks. This research was supported in part by the joint research scheme of the National Natural Science Foundation of China (NSFC) and the Research Grants Council (RGC) under grant number N HKU714/21.

References

- Loubna Ben Allal, Anton Lozhkov, Elie Bakouch, Gabriel Martín Blázquez, Guilherme Penedo, Lewis Tunstall, Andrés Marafioti, Hynek Kydlíček, Agustín Piqueres Lajarín, Vaibhav Srivastav, Joshua Lochner, Caleb Fahlgren, Xuan-Son Nguyen, Clémentine Fourrier, Ben Burtenshaw, Hugo Larcher, Haojun Zhao, Cyril Zakka, Mathieu Morlon, Colin Raffel, Leandro von Werra, and Thomas Wolf. Smollm2: When smol goes big data-centric training of a small language model, 2025. URL https://arxiv.org/abs/2502.02737.
- Marianne Arriola, Aaron Gokaslan, Justin T. Chiu, Zhihan Yang, Zhixuan Qi, Jiaqi Han, Subham Sekhar Sahoo, and Volodymyr Kuleshov. Block diffusion: Interpolating between autoregressive and diffusion language models, 2025. URL https://arxiv.org/abs/2503.09573.
- Jacob Austin, Daniel D Johnson, Jonathan Ho, Daniel Tarlow, and Rianne Van Den Berg. Structured denoising diffusion models in discrete state-spaces. Advances in neural information processing systems, 34:17981-17993, 2021a.
- Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, et al. Program synthesis with large language models. arXiv preprint arXiv:2108.07732, 2021b.
- Gregor Bachmann and Vaishnavh Nagarajan. The pitfalls of next-token prediction. arXiv preprint arXiv:2403.06963, 2024.
- Yoshua Bengio, Réjean Ducharme, and Pascal Vincent. A neural probabilistic language model. Advances in neural information processing systems, 13, 2000.
- Yonatan Bisk, Rowan Zellers, Jianfeng Gao, Yejin Choi, et al. Piqa: Reasoning about physical commonsense in natural language. In *Proceedings of the AAAI conference on artificial intelligence*, 2020.
- Sébastien Bubeck, Varun Chadrasekaran, Ronen Eldan, Johannes Gehrke, Eric Horvitz, Ece Kamar, Peter Lee, Yin Tat Lee, Yuanzhi Li, Scott Lundberg, et al. Sparks of artificial general intelligence: Early experiments with gpt-4, 2023.

- Andrew Campbell, Joe Benton, Valentin De Bortoli, Thomas Rainforth, George Deligiannidis, and Arnaud Doucet. A continuous time framework for discrete denoising models. *Advances in Neural Information Processing Systems*, 35:28266–28279, 2022.
- Mark Chen, Jerry Tworek, Heewoo Jun, Qiming Yuan, Henrique Ponde De Oliveira Pinto, Jared Kaplan, Harri Edwards, Yuri Burda, Nicholas Joseph, Greg Brockman, et al. Evaluating large language models trained on code. arXiv preprint arXiv:2107.03374, 2021.
- Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. Think you have solved question answering? try arc, the ai2 reasoning challenge. arXiv preprint arXiv:1803.05457, 2018.
- Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. arXiv preprint arXiv:2110.14168, 2021.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proc. of NAACL-HLT*, pages 4171–4186. Association for Computational Linguistics, 2019.
- Sander Dieleman, Laurent Sartran, Arman Roshannai, Nikolay Savinov, Yaroslav Ganin, Pierre H Richemond, Arnaud Doucet, Robin Strudel, Chris Dyer, Conor Durkan, et al. Continuous diffusion for categorical data. arXiv preprint arXiv:2211.15089, 2022.
- Nouha Dziri, Ximing Lu, Melanie Sclar, Xiang Lorraine Li, Liwei Jiang, Bill Yuchen Lin, Sean Welleck, Peter West, Chandra Bhagavatula, Ronan Le Bras, et al. Faith and fate: Limits of transformers on compositionality. *Advances in Neural Information Processing Systems*, 36:70293–70332, 2023.
- Jonas Geiping, Sean McLeish, Neel Jain, John Kirchenbauer, Siddharth Singh, Brian R Bartoldson, Bhavya Kailkhura, Abhinav Bhatele, and Tom Goldstein. Scaling up test-time compute with latent reasoning: A recurrent depth approach. arXiv preprint arXiv:2502.05171, 2025.
- Shansan Gong, Mukai Li, Jiangtao Feng, Zhiyong Wu, and Lingpeng Kong. DiffuSeq-v2: Bridging discrete and continuous text spaces for accelerated Seq2Seq diffusion models. In Houda Bouamor, Juan Pino, and Kalika Bali, editors, Findings of the Association for Computational Linguistics: EMNLP 2023, pages 9868–9875. Association for Computational Linguistics, 2023a.
- Shansan Gong, Mukai Li, Jiangtao Feng, Zhiyong Wu, and Lingpeng Kong. DiffuSeq: Sequence to sequence text generation with diffusion models. In *International Conference on Learning Representations, ICLR*, 2023b.
- Shansan Gong, Shivam Agarwal, Yizhe Zhang, Jiacheng Ye, Lin Zheng, Mukai Li, Chenxin An, Peilin Zhao, Wei Bi, Jiawei Han, Hao Peng, and Lingpeng Kong. Scaling diffusion language models via adaptation from autoregressive models. *International Conference on Learning Representations*, 2025.
- Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, Arun Rao, Aston Zhang, Aurelien Rodriguez, Austen Gregerson, Ava Spataru, Baptiste Roziere, Bethany Biron, Binh Tang, Bobbie Chern, Charlotte Caucheteux, Chaya Nayak, Chloe Bi, Chris Marra, Chris McConnell, Christian Keller, Christophe Touret, Chunyang Wu, Corinne Wong, Cristian Canton Ferrer, Cyrus Nikolaidis, Damien Allonsius, Daniel Song, Danielle Pintz, Danny Livshits, Danny Wyatt, David Esiobu, Dhruv Choudhary, Dhruv Mahajan, Diego Garcia-Olano, Diego Perino, Dieuwke Hupkes, Egor Lakomkin, Ehab AlBadawy, Elina Lobanova, Emily Dinan, Eric Michael Smith, Filip Radenovic, Francisco Guzmán, Frank Zhang, Gabriel Synnaeve, Gabrielle Lee, Georgia Lewis Anderson, Govind Thattai, Graeme Nail, Gregoire Mialon, Guan Pang, Guillem Cucurell, Hailey Nguyen, Hannah Korevaar, Hu Xu, Hugo Touvron, Iliyan Zarov, Imanol Arrieta Ibarra, Isabel Kloumann, Ishan Misra, Ivan Evtimov, Jack Zhang, Jade Copet, Jaewon Lee, Jan Geffert, Jana Vranes, Jason Park, Jay Mahadeokar, Jeet Shah, Jelmer van der Linde, Jennifer Billock, Jenny Hong, Jenya Lee, Jeremy Fu, Jianfeng Chi, Jianyu Huang, Jiawen Liu, Jie Wang,

Jiecao Yu, Joanna Bitton, Joe Spisak, Jongsoo Park, Joseph Rocca, Joshua Johnstun, Joshua Saxe, Junteng Jia, Kalyan Vasuden Alwala, Karthik Prasad, Kartikeya Upasani, Kate Plawiak, Ke Li, Kenneth Heafield, Kevin Stone, Khalid El-Arini, Krithika Iyer, Kshitiz Malik, Kuenley Chiu, Kunal Bhalla, Kushal Lakhotia, Lauren Rantala-Yeary, Laurens van der Maaten, Lawrence Chen, Liang Tan, Liz Jenkins, Louis Martin, Lovish Madaan, Lubo Malo, Lukas Blecher, Lukas Landzaat, Luke de Oliveira, Madeline Muzzi, Mahesh Pasupuleti, Mannat Singh, Manohar Paluri, Marcin Kardas, Maria Tsimpoukelli, Mathew Oldham, Mathieu Rita, Maya Pavlova, Melanie Kambadur, Mike Lewis, Min Si, Mitesh Kumar Singh, Mona Hassan, Naman Goyal, Narjes Torabi, Nikolay Bashlykov, Nikolay Bogoychev, Niladri Chatterji, Ning Zhang, Olivier Duchenne, Onur Çelebi, Patrick Alrassy, Pengchuan Zhang, Pengwei Li, Petar Vasic, Peter Weng, Prajjwal Bhargava, Pratik Dubal, Praveen Krishnan, Punit Singh Koura, Puxin Xu, Qing He, Qingxiao Dong, Ragavan Srinivasan, Raj Ganapathy, Ramon Calderer, Ricardo Silveira Cabral, Robert Stojnic, Roberta Raileanu, Rohan Maheswari, Rohit Girdhar, Rohit Patel, Romain Sauvestre, Ronnie Polidoro, Roshan Sumbaly, Ross Taylor, Ruan Silva, Rui Hou, Rui Wang, Saghar Hosseini, Sahana Chennabasappa, Sanjay Singh, Sean Bell, Seohyun Sonia Kim, Sergey Edunov, Shaoliang Nie, Sharan Narang, Sharath Raparthy, Sheng Shen, Shengye Wan, Shruti Bhosale, Shun Zhang, Simon Vandenhende, Soumya Batra, Spencer Whitman, Sten Sootla, Stephane Collot, Suchin Gururangan, Sydney Borodinsky, Tamar Herman, Tara Fowler, Tarek Sheasha, Thomas Georgiou, Thomas Scialom, Tobias Speckbacher, Todor Mihaylov, Tong Xiao, Ujiwal Karn, Vedanuj Goswami, Vibhor Gupta, Vignesh Ramanathan, Viktor Kerkez, Vincent Gonguet, Virginie Do, Vish Vogeti, Vítor Albiero, Vladan Petrovic, Weiwei Chu, Wenhan Xiong, Wenyin Fu, Whitney Meers, Xavier Martinet, Xiaodong Wang, Xiaofang Wang, Xiaoqing Ellen Tan, Xide Xia, Xinfeng Xie, Xuchao Jia, Xuewei Wang, Yaelle Goldschlag, Yashesh Gaur, Yasmine Babaei, Yi Wen, Yiwen Song, Yuchen Zhang, Yue Li, Yuning Mao, Zacharie Delpierre Coudert, Zheng Yan, Zhengxing Chen, Zoe Papakipos, Aaditya Singh, Aayushi Srivastava, Abha Jain, Adam Kelsey, Adam Shajnfeld, Adithya Gangidi, Adolfo Victoria, Ahuva Goldstand, Ajay Menon, Ajay Sharma, Alex Boesenberg, Alexei Baevski, Allie Feinstein, Amanda Kallet, Amit Sangani, Amos Teo, Anam Yunus, Andrei Lupu, Andres Alvarado, Andrew Caples, Andrew Gu, Andrew Ho, Andrew Poulton, Andrew Ryan, Ankit Ramchandani, Annie Dong, Annie Franco, Anuj Goyal, Aparajita Saraf, Arkabandhu Chowdhury, Ashley Gabriel, Ashwin Bharambe, Assaf Eisenman, Azadeh Yazdan, Beau James, Ben Maurer, Benjamin Leonhardi, Bernie Huang, Beth Loyd, Beto De Paola, Bhargavi Paranjape, Bing Liu, Bo Wu, Boyu Ni, Braden Hancock, Bram Wasti, Brandon Spence, Brani Stojkovic, Brian Gamido, Britt Montalvo, Carl Parker, Carly Burton, Catalina Mejia, Ce Liu, Changhan Wang, Changkyu Kim, Chao Zhou, Chester Hu, Ching-Hsiang Chu, Chris Cai, Chris Tindal, Christoph Feichtenhofer, Cynthia Gao, Damon Civin, Dana Beaty, Daniel Kreymer, Daniel Li, David Adkins, David Xu, Davide Testuggine, Delia David, Devi Parikh, Diana Liskovich, Didem Foss, Dingkang Wang, Duc Le, Dustin Holland, Edward Dowling, Eissa Jamil, Elaine Montgomery, Eleonora Presani, Emily Hahn, Emily Wood, Eric-Tuan Le, Erik Brinkman, Esteban Arcaute, Evan Dunbar, Evan Smothers, Fei Sun, Felix Kreuk, Feng Tian, Filippos Kokkinos, Firat Ozgenel, Francesco Caggioni, Frank Kanayet, Frank Seide, Gabriela Medina Florez, Gabriella Schwarz, Gada Badeer, Georgia Swee, Gil Halpern, Grant Herman, Grigory Sizov, Guangyi, Zhang, Guna Lakshminarayanan, Hakan Inan, Hamid Shojanazeri, Han Zou, Hannah Wang, Hanwen Zha, Haroun Habeeb, Harrison Rudolph, Helen Suk, Henry Aspegren, Hunter Goldman, Hongyuan Zhan, Ibrahim Damlaj, Igor Molybog, Igor Tufanov, Ilias Leontiadis, Irina-Elena Veliche, Itai Gat, Jake Weissman, James Geboski, James Kohli, Janice Lam, Japhet Asher, Jean-Baptiste Gaya, Jeff Marcus, Jeff Tang, Jennifer Chan, Jenny Zhen, Jeremy Reizenstein, Jeremy Teboul, Jessica Zhong, Jian Jin, Jingyi Yang, Joe Cummings, Jon Carvill, Jon Shepard, Jonathan McPhie, Jonathan Torres, Josh Ginsburg, Junjie Wang, Kai Wu, Kam Hou U, Karan Saxena, Kartikay Khandelwal, Katayoun Zand, Kathy Matosich, Kaushik Veeraraghavan, Kelly Michelena, Keqian Li, Kiran Jagadeesh, Kun Huang, Kunal Chawla, Kyle Huang, Lailin Chen, Lakshya Garg, Lavender A, Leandro Silva, Lee Bell, Lei Zhang, Liangpeng Guo, Licheng Yu, Liron Moshkovich, Luca Wehrstedt, Madian Khabsa, Manav Avalani, Manish Bhatt, Martynas Mankus, Matan Hasson, Matthew Lennie, Matthias Reso, Maxim Groshev, Maxim Naumov, Mava Lathi, Meghan Keneally, Miao Liu, Michael L. Seltzer, Michal Valko, Michelle Restrepo, Mihir Patel, Mik Vyatskov, Mikayel Samvelyan, Mike Clark, Mike Macey, Mike Wang, Miquel Jubert Hermoso, Mo Metanat, Mohammad Rastegari, Munish Bansal, Nandhini Santhanam, Natascha Parks, Natasha White, Navyata Bawa, Nayan Singhal, Nick Egebo, Nicolas Usunier, Nikhil Mehta, Nikolay Pavlovich Laptev, Ning Dong, Norman Cheng, Oleg Chernoguz, Olivia Hart, Omkar

Salpekar, Ozlem Kalinli, Parkin Kent, Parth Parekh, Paul Saab, Pavan Balaji, Pedro Rittner, Philip Bontrager, Pierre Roux, Piotr Dollar, Polina Zvyagina, Prashant Ratanchandani, Pritish Yuvraj, Qian Liang, Rachad Alao, Rachel Rodriguez, Rafi Ayub, Raghotham Murthy, Raghu Nayani, Rahul Mitra, Rangaprabhu Parthasarathy, Raymond Li, Rebekkah Hogan, Robin Battey, Rocky Wang, Russ Howes, Ruty Rinott, Sachin Mehta, Sachin Siby, Sai Jayesh Bondu, Samyak Datta, Sara Chugh, Sara Hunt, Sargun Dhillon, Sasha Sidorov, Satadru Pan, Saurabh Mahajan, Saurabh Verma, Seiji Yamamoto, Sharadh Ramaswamy, Shaun Lindsay, Shaun Lindsay, Sheng Feng, Shenghao Lin, Shengxin Cindy Zha, Shishir Patil, Shiva Shankar, Shuqiang Zhang, Shuqiang Zhang, Sinong Wang, Sneha Agarwal, Soji Sajuyigbe, Soumith Chintala, Stephanie Max, Stephen Chen, Steve Kehoe, Steve Satterfield, Sudarshan Govindaprasad, Sumit Gupta, Summer Deng, Sungmin Cho, Sunny Virk, Suraj Subramanian, Sy Choudhury, Sydney Goldman, Tal Remez, Tamar Glaser, Tamara Best, Thilo Koehler, Thomas Robinson, Tianhe Li, Tianjun Zhang, Tim Matthews, Timothy Chou, Tzook Shaked, Varun Vontimitta, Victoria Ajayi, Victoria Montanez, Vijai Mohan, Vinay Satish Kumar, Vishal Mangla, Vlad Ionescu, Vlad Poenaru, Vlad Tiberiu Mihailescu, Vladimir Ivanov, Wei Li, Wenchen Wang, Wenwen Jiang, Wes Bouaziz, Will Constable, Xiaocheng Tang, Xiaojian Wu, Xiaolan Wang, Xilun Wu, Xinbo Gao, Yaniv Kleinman, Yanjun Chen, Ye Hu, Ye Jia, Ye Qi, Yenda Li, Yilin Zhang, Ying Zhang, Yossi Adi, Youngjin Nam, Yu, Wang, Yu Zhao, Yuchen Hao, Yundi Qian, Yunlu Li, Yuzi He, Zach Rait, Zachary DeVito, Zef Rosnbrick, Zhaoduo Wen, Zhenyu Yang, Zhiwei Zhao, and Zhiyu Ma. The llama 3 herd of models, 2024. URL https://arxiv.org/abs/2407.21783.

- Ishaan Gulrajani and Tatsunori Hashimoto. Likelihood-based diffusion language models. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023a.
- Ishaan Gulrajani and Tatsunori B Hashimoto. Likelihood-based diffusion language models. *Advances in Neural Information Processing Systems*, 36:16693–16715, 2023b.
- Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Ruoyu Zhang, Runxin Xu, Qihao Zhu, Shirong Ma, Peiyi Wang, Xiao Bi, et al. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. arXiv preprint arXiv:2501.12948, 2025.
- Zhengfu He, Tianxiang Sun, Qiong Tang, Kuanning Wang, Xuanjing Huang, and Xipeng Qiu. DiffusionBERT: Improving generative masked language models with diffusion models. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki, editors, *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4521–4534, Toronto, Canada, July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.acl-long.248.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. arXiv preprint arXiv:2009.03300, 2020.
- Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising diffusion probabilistic models. In Hugo Larochelle, Marc'Aurelio Ranzato, Raia Hadsell, Maria-Florina Balcan, and Hsuan-Tien Lin, editors, Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual, 2020.
- Emiel Hoogeboom, Didrik Nielsen, Priyank Jaini, Patrick Forré, and Max Welling. Argmax flows and multinomial diffusion: Learning categorical distributions. *Advances in neural information processing systems*, 34:12454–12465, 2021.
- Siming Huang, Tianhao Cheng, J. K. Liu, Jiaran Hao, Liuyihan Song, Yang Xu, J. Yang, Jiaheng Liu, Chenchen Zhang, Linzheng Chai, Ruifeng Yuan, Zhaoxiang Zhang, Jie Fu, Qian Liu, Ge Zhang, Zili Wang, Yuan Qi, Yinghui Xu, and Wei Chu. Opencoder: The open cookbook for top-tier code large language models, 2025. URL https://arxiv.org/abs/2411.04905.
- Inception Labs. Mercury: Ultra-fast language models based on diffusion. https://www.inceptionlabs.ai/introducing-mercury, 2025. Accessed: 2025-06-16.
- Aaron Jaech, Adam Kalai, Adam Lerer, Adam Richardson, Ahmed El-Kishky, Aiden Low, Alec Helyar, Aleksander Madry, Alex Beutel, Alex Carney, et al. Openai of system card. arXiv preprint arXiv:2412.16720, 2024.

- Frederick Jelinek. Interpolated estimation of markov source parameters from sparse data. In *Proc. Workshop on Pattern Recognition in Practice*, 1980, 1980.
- Diederik Kingma, Tim Salimans, Ben Poole, and Jonathan Ho. Variational diffusion models. *Advances in neural information processing systems*, 34:21696–21707, 2021.
- Guokun Lai, Qizhe Xie, Hanxiao Liu, Yiming Yang, and Eduard Hovy. Race: Large-scale reading comprehension dataset from examinations. arXiv preprint arXiv:1704.04683, 2017.
- Nathan Lambert, Jacob Morrison, Valentina Pyatkin, Shengyi Huang, Hamish Ivison, Faeze Brahman, Lester James V. Miranda, Alisa Liu, Nouha Dziri, Shane Lyu, Yuling Gu, Saumya Malik, Victoria Graf, Jena D. Hwang, Jiangjiang Yang, Ronan Le Bras, Oyvind Tafjord, Chris Wilhelm, Luca Soldaini, Noah A. Smith, Yizhong Wang, Pradeep Dasigi, and Hannaneh Hajishirzi. Tulu 3: Pushing frontiers in open language model post-training, 2025. URL https://arxiv.org/abs/2411.15124.
- Jeffrey Li, Alex Fang, Georgios Smyrnis, Maor Ivgi, Matt Jordan, Samir Gadre, Hritik Bansal, Etash Guha, Sedrick Keh, Kushal Arora, Saurabh Garg, Rui Xin, Niklas Muennighoff, Reinhard Heckel, Jean Mercat, Mayee Chen, Suchin Gururangan, Mitchell Wortsman, Alon Albalak, Yonatan Bitton, Marianna Nezhurina, Amro Abbas, Cheng-Yu Hsieh, Dhruba Ghosh, Josh Gardner, Maciej Kilian, Hanlin Zhang, Rulin Shao, Sarah Pratt, Sunny Sanyal, Gabriel Ilharco, Giannis Daras, Kalyani Marathe, Aaron Gokaslan, Jieyu Zhang, Khyathi Chandu, Thao Nguyen, Igor Vasiljevic, Sham Kakade, Shuran Song, Sujay Sanghavi, Fartash Faghri, Sewoong Oh, Luke Zettlemoyer, Kyle Lo, Alaaeldin El-Nouby, Hadi Pouransari, Alexander Toshev, Stephanie Wang, Dirk Groeneveld, Luca Soldaini, Pang Wei Koh, Jenia Jitsev, Thomas Kollar, Alexandros G. Dimakis, Yair Carmon, Achal Dave, Ludwig Schmidt, and Vaishaal Shankar. Datacomp-lm: In search of the next generation of training sets for language models. Advances in neural information processing systems, 2024.
- Xiang Lisa Li, John Thickstun, Ishaan Gulrajani, Percy Liang, and Tatsunori B Hashimoto. Diffusion-lm improves controllable text generation. In *Conference on Neural Information Processing Systems*, NeurIPS, 2022.
- Zhenghao Lin, Yeyun Gong, Yelong Shen, Tong Wu, Zhihao Fan, Chen Lin, Nan Duan, and Weizhu Chen. Text generation with diffusion language models: a pre-training approach with continuous paragraph denoise. In *Proceedings of the 40th International Conference on Machine Learning*, ICML'23. JMLR.org, 2023.
- Aaron Lou, Chenlin Meng, and Stefano Ermon. Discrete diffusion language modeling by estimating the ratios of the data distribution. In *International Conference on Machine Learning*, *ICML*, 2024.
- Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori Hashimoto. s1: Simple test-time scaling. arXiv preprint arXiv:2501.19393, 2025.
- Shen Nie, Fengqi Zhu, Chao Du, Tianyu Pang, Qian Liu, Guangtao Zeng, Min Lin, and Chongxuan Li. Scaling up masked diffusion models on text, 2025a. URL https://arxiv.org/abs/2410.18514.
- Shen Nie, Fengqi Zhu, Zebin You, Xiaolu Zhang, Jingyang Ou, Jun Hu, Jun Zhou, Yankai Lin, Ji-Rong Wen, and Chongxuan Li. Large language diffusion models. arXiv preprint arXiv:2502.09992, 2025b.
- OpenAI, Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, Red Avila, Igor Babuschkin, Suchir Balaji, Valerie Balcom, Paul Baltescu, Haiming Bao, Mohammad Bavarian, Jeff Belgum, Irwan Bello, Jake Berdine, Gabriel Bernadett-Shapiro, Christopher Berner, Lenny Bogdonoff, Oleg Boiko, Madelaine Boyd, Anna-Luisa Brakman, Greg Brockman, Tim Brooks, Miles Brundage, Kevin Button, Trevor Cai, Rosie Campbell, Andrew Cann, Brittany Carey, Chelsea Carlson, Rory Carmichael, Brooke Chan, Che Chang, Fotis Chantzis, Derek Chen, Sully Chen, Ruby Chen, Jason Chen, Mark Chen, Ben Chess, Chester Cho, Casey Chu, Hyung Won Chung, Dave Cummings, Jeremiah Currier, Yunxing Dai, Cory Decareaux, Thomas Degry, Noah Deutsch, Damien Deville, Arka Dhar, David Dohan, Steve Dowling, Sheila Dunning, Adrien Ecoffet, Atty Eleti, Tyna Eloundou, David Farhi, Liam Fedus, Niko Felix, Simón Posada Fishman, Juston Forte, Isabella Fulford, Leo

Gao, Elie Georges, Christian Gibson, Vik Goel, Tarun Gogineni, Gabriel Goh, Rapha Gontijo-Lopes, Jonathan Gordon, Morgan Grafstein, Scott Gray, Ryan Greene, Joshua Gross, Shixiang Shane Gu, Yufei Guo, Chris Hallacy, Jesse Han, Jeff Harris, Yuchen He, Mike Heaton, Johannes Heidecke, Chris Hesse, Alan Hickey, Wade Hickey, Peter Hoeschele, Brandon Houghton, Kenny Hsu, Shengli Hu, Xin Hu, Joost Huizinga, Shantanu Jain, Shawn Jain, Joanne Jang, Angela Jiang, Roger Jiang, Haozhun Jin, Denny Jin, Shino Jomoto, Billie Jonn, Heewoo Jun, Tomer Kaftan, Łukasz Kaiser, Ali Kamali, Ingmar Kanitscheider, Nitish Shirish Keskar, Tabarak Khan, Logan Kilpatrick, Jong Wook Kim, Christina Kim, Yongjik Kim, Jan Hendrik Kirchner, Jamie Kiros, Matt Knight, Daniel Kokotajlo, Łukasz Kondraciuk, Andrew Kondrich, Aris Konstantinidis, Kyle Kosic, Gretchen Krueger, Vishal Kuo, Michael Lampe, Ikai Lan, Teddy Lee, Jan Leike, Jade Leung, Daniel Levy, Chak Ming Li, Rachel Lim, Molly Lin, Stephanie Lin, Mateusz Litwin, Theresa Lopez, Ryan Lowe, Patricia Lue, Anna Makanju, Kim Malfacini, Sam Manning, Todor Markov, Yaniv Markovski, Bianca Martin, Katie Mayer, Andrew Mayne, Bob McGrew, Scott Mayer McKinney, Christine McLeavey, Paul McMillan, Jake McNeil, David Medina, Aalok Mehta, Jacob Menick, Luke Metz, Andrey Mishchenko, Pamela Mishkin, Vinnie Monaco, Evan Morikawa, Daniel Mossing, Tong Mu, Mira Murati, Oleg Murk, David Mély, Ashvin Nair, Reiichiro Nakano, Rajeev Nayak, Arvind Neelakantan, Richard Ngo, Hyeonwoo Noh, Long Ouyang, Cullen O'Keefe, Jakub Pachocki, Alex Paino, Joe Palermo, Ashley Pantuliano, Giambattista Parascandolo, Joel Parish, Emy Parparita, Alex Passos, Mikhail Payloy, Andrew Peng, Adam Perelman, Filipe de Avila Belbute Peres, Michael Petrov, Henrique Ponde de Oliveira Pinto, Michael, Pokorny, Michelle Pokrass, Vitchyr H. Pong, Tolly Powell, Alethea Power, Boris Power, Elizabeth Proehl, Raul Puri, Alec Radford, Jack Rae, Aditya Ramesh, Cameron Raymond, Francis Real, Kendra Rimbach, Carl Ross, Bob Rotsted, Henri Roussez, Nick Ryder, Mario Saltarelli, Ted Sanders, Shibani Santurkar, Girish Sastry, Heather Schmidt, David Schnurr, John Schulman, Daniel Selsam, Kyla Sheppard, Toki Sherbakov, Jessica Shieh, Sarah Shoker, Pranav Shyam, Szymon Sidor, Eric Sigler, Maddie Simens, Jordan Sitkin, Katarina Slama, Ian Sohl, Benjamin Sokolowsky, Yang Song, Natalie Staudacher, Felipe Petroski Such, Natalie Summers, Ilya Sutskever, Jie Tang, Nikolas Tezak, Madeleine B. Thompson, Phil Tillet, Amin Tootoonchian, Elizabeth Tseng, Preston Tuggle, Nick Turley, Jerry Tworek, Juan Felipe Cerón Uribe, Andrea Vallone, Arun Vijayvergiya, Chelsea Voss, Carroll Wainwright, Justin Jay Wang, Alvin Wang, Ben Wang, Jonathan Ward, Jason Wei, CJ Weinmann, Akila Welihinda, Peter Welinder, Jiayi Weng, Lilian Weng, Matt Wiethoff, Dave Willner, Clemens Winter, Samuel Wolrich, Hannah Wong, Lauren Workman, Sherwin Wu, Jeff Wu, Michael Wu, Kai Xiao, Tao Xu, Sarah Yoo, Kevin Yu, Qiming Yuan, Wojciech Zaremba, Rowan Zellers, Chong Zhang, Marvin Zhang, Shengjia Zhao, Tianhao Zheng, Juntang Zhuang, William Zhuk, and Barret Zoph. Gpt-4 technical report, 2024. URL https://arxiv.org/abs/2303.08774.

Jingyang Ou, Shen Nie, Kaiwen Xue, Fengqi Zhu, Jiacheng Sun, Zhenguo Li, and Chongxuan Li. Your absorbing discrete diffusion secretly models the conditional distributions of clean data. *International Conference on Learning Representations*, 2025.

Qwen, :, An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tianyi Tang, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. Qwen2.5 technical report, 2025. URL https://arxiv.org/abs/2412.15115.

David Rein, Betty Li Hou, Asa Cooper Stickland, Jackson Petty, Richard Yuanzhe Pang, Julien Dirani, Julian Michael, and Samuel R Bowman. Gpqa: A graduate-level google-proof q&a benchmark. arXiv preprint arXiv:2311.12022, 2023.

Subham Sekhar Sahoo, Marianne Arriola, Aaron Gokaslan, Edgar Mariano Marroquin, Alexander M Rush, Yair Schiff, Justin T Chiu, and Volodymyr Kuleshov. Simple and effective masked diffusion language models. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024. URL https://openreview.net/forum?id=L4uaAR4ArM.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. Winogrande: An adversarial winograd schema challenge at scale. *Communications of the ACM*, 64(9):99–106, 2021.

- Jiaxin Shi, Kehang Han, Zhe Wang, Arnaud Doucet, and Michalis K. Titsias. Simplified and generalized masked diffusion for discrete data. *Neural Information Processing Systems*, 2024.
- Charlie Snell, Jaehoon Lee, Kelvin Xu, and Aviral Kumar. Scaling llm test-time compute optimally can be more effective than scaling model parameters. arXiv preprint arXiv:2408.03314, 2024.
- Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *International conference on machine learning*, pages 2256–2265. PMLR, 2015.
- Luca Soldaini, Rodney Kinney, Akshita Bhagia, Dustin Schwenk, David Atkinson, Russell Authur, Ben Bogin, Khyathi Chandu, Jennifer Dumas, Yanai Elazar, Valentin Hofmann, Ananya Jha, Sachin Kumar, Li Lucy, Xinxi Lyu, Nathan Lambert, Ian Magnusson, Jacob Morrison, Niklas Muennighoff, Aakanksha Naik, Crystal Nam, Matthew Peters, Abhilasha Ravichander, Kyle Richardson, Zejiang Shen, Emma Strubell, Nishant Subramani, Oyvind Tafjord, Evan Walsh, Luke Zettlemoyer, Noah Smith, Hannaneh Hajishirzi, Iz Beltagy, Dirk Groeneveld, Jesse Dodge, and Kyle Lo. Dolma: an open corpus of three trillion tokens for language model pretraining research. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar, editors, Proceedings of the 62nd Annual Meeting of the Association for Computational Linquistics (Volume 1: Long Papers), August 2024.
- Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. In Proc. of ICLR. OpenReview.net, 2021.
- Mirac Suzgun, Nathan Scales, Nathanael Schärli, Sebastian Gehrmann, Yi Tay, Hyung Won Chung, Aakanksha Chowdhery, Quoc V Le, Ed H Chi, Denny Zhou, et al. Challenging big-bench tasks and whether chain-of-thought can solve them. arXiv preprint arXiv:2210.09261, 2022.
- Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.
- Jiacheng Ye, Shansan Gong, Liheng Chen, Lin Zheng, Jiahui Gao, Han Shi, Chuan Wu, Xin Jiang, Zhenguo Li, Wei Bi, et al. Diffusion of thought: Chain-of-thought reasoning in diffusion language models. *Advances in Neural Information Processing Systems*, 37:105345–105374, 2024.
- Jiacheng Ye, Jiahui Gao, Shansan Gong, Lin Zheng, Xin Jiang, Zhenguo Li, and Lingpeng Kong. Beyond autoregression: Discrete diffusion for complex reasoning and planning. *International Conference on Learning Representations*, 2025a.
- Jiacheng Ye, Zhenyu Wu, Jiahui Gao, Zhiyong Wu, Xin Jiang, Zhenguo Li, and Lingpeng Kong. Implicit search via discrete diffusion: A study on chess. *International Conference on Learning Representations*, 2025b.
- Jiasheng Ye, Zaixiang Zheng, Yu Bao, Lihua Qian, and Quanquan Gu. Diffusion language models can perform many tasks with scaling and instruction-finetuning, 2025c. URL https://arxiv.org/abs/2308.12219.
- Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. Hellaswag: Can a machine really finish your sentence? arXiv preprint arXiv:1905.07830, 2019.
- Lingxiao Zhao, Xueying Ding, Lijun Yu, and Leman Akoglu. Improving and unifying discrete&continuous-time discrete denoising diffusion. arXiv preprint arXiv:2402.03701, 2024.
- Huaixiu Steven Zheng, Swaroop Mishra, Hugh Zhang, Xinyun Chen, Minmin Chen, Azade Nova, Le Hou, Heng-Tze Cheng, Quoc V. Le, Ed H. Chi, and Denny Zhou. Natural plan: Benchmarking llms on natural language planning, 2024a. URL https://arxiv.org/abs/2406.04520.
- Lin Zheng, Jianbo Yuan, Lei Yu, and Lingpeng Kong. A reparameterized discrete diffusion model for text generation. In *Conference on Language Modeling, COLM, October 7-9, 2024, Philadelphia, PA*, 2024b.