#TODO arch\_install: pre svega, mozda namestiti pacman config da bude lep dok se sve skida, ako moze bez sed, bilo bi super

#TODO USER - AFTER INSTALL: \* change ~/.config/git/config

#TODO backup: \* proveriti u virtual machine da li sve radi pre nego sto obrisem trenutni arch sistem \* videti da pre nego sto pacman - S sway, prvo skinem mesa drivere ili one druge, treba videti koji se nude od ta 2 \* mozda staviti da se bluetooth module pali tek kada upalim sway? https://wiki.archlinux.org/index.php/Sway#Manage\_Swayspecific daemons with systemd

#TODO RICE (prio 1): \* swaybar, waybar, \* zscroll, \* luke smith video za temperature, ima jos nesto, ima video na jutubu za zscroll \* workspace-ovi ima na youtube-u i na unixporn ideje, msm da imam jednu dobru u bookmarks

- \* brave working with video playback
- \* rofi, wofi
- \* bluetooth
- \* fade (kao compton)

## rice (prio 2)

- \* all floating shit, dodati i u fedora setup
- \* na sway-u mi se cini da resize nije konstantne brzine nego se menja sa velicinom prozora
- \* aur
- \* dodati padding na alacritty
- \* zsh da ne smara na auto-completion-u, videti da neka smaranja ostanu, npr ona sto retko l

Arch komande se obicno sastoje od prvo jednog velikog slova(e.g., S, R, Q) i mnogo malih slova.

pacman -S, sync(install/update) package

pacman -Syu, synhonize package database and upgrade whole system(recommended) pacman -Sy, syncrhonize package database(not recommended) pacman -Su, upgrade whole system(not recommended)

pacman -Syyu, kad ima 2 y, tera ga da update-uje database iako je keshiran update od malo pre pacman -Sw, skine, ali i ne instalira nego ostavi download file, pa ti sam moras posle instalirati

pacman -Ss, search all packages in title and description

pacman -R, remove package pacman -Rs, remove package and its unused dependencies pacman -Rn, remove package and its system config files

pacman -Rsn, best for removing a package

pacman -Q, prints all installed packages pacman -Qe, prints all explicitly installed packages pacman -Qq, does not print out the version, only the program name (q radi skoro svuda)

```
pacman -Qdt, list of orphans
pacman -Qs, search for locally installed packages
pacman -Si, information for a package
pacman -Qi, information for a locally installed package U file-u /etc/pacman.conf:
```

## Misc options

 $\# Use Syslog\ Color\ Total Download\ Check Space\ Verbose Pkg Lists\ IL ove Candy$