

EDGE²™ TELEMETRY RECEIVER/PROCESSOR

TELEMETRY PROCESSING AT THE EDGE

The Edge² is engineered to provide network telemetry processing at the edge in a portable or rack mountable 2-channel unit. Three Edge² appliances may be rack mounted side-by-side supporting up to 6 channels of RF, BitSync, or Decom processing in a 1U rack space. Each Edge² unit provides LED status indicators for Receiver Status, Bit Sync Status, Frame Sync Status, Time Status, and Ethernet activity.



The Edge² unit when configured with receiver modules provides users with complete single or dual stream RF-to-Ethernet telemetry data processing. Capable of supporting all telemetry frequency bands from 200 MHz to beyond 5.15 GHz, these systems provide complete RF input to TMoIP (IRIG 106 Chapter 10/11 or IRIG 218-20) Ethernet output in a single compact 1U rack mount industrial enclosure.

KEY FEATURES

- IRIG TMoIP Output: IRIG 218-20 or Ch10 (selectable each channel)
- Optional Tri-band receiver supporting RF to TMoIP (Chapter 10/11 & IRIG 218-20)
- Optional high-performance Bit Syncs
- 1 dB Bit Sync Performance
- Up to 50 Mbps bitrate per channel
- 2-channel, 100 Mbps output via the 1GBps port
- Exceeds Class II embedded channel specifications
- Supports jumbo frames up to 9000 MTU
- < 0.5 dB typical noise figure
- Accepts IRIG A, B, and G, and IEEE 1588 PTP time
- Ingests Chapter 4, 7, and 8 formats
- Integrated OMEGA NExT™ real-time data processing, display, data reduction, and data distribution



A Windows Graphical User Interface (GUI) provides the user with control of receiver functions, display of receiver status, and use of integrated IF spectrum and time base displays. The GUI can operate as local control or as remote control over a TCP/IP or UDP network. Full receiver operation, as well as data decommutation, is also integrated within the high-performance OMEGA NExT data processing and display software.